

EOS C80

Digital Cinema Camera

Firmware ver. 1.0.3.1

Safety Instructions

Be sure to read these instructions in order to operate the product safely. Follow these instructions to prevent injury or harm to the operator of the product or others.

WARNING

Denotes the risk of serious injury or death.

2

- Stop using the product in any case of unusual circumstances such as the presence of smoke or a strange smell.
- Do not touch any exposed internal parts.
- Do not get the product wet. Do not insert foreign objects or liquids into the product.
- Do not touch the product connected to a power outlet during lightning storms. This may cause electric shock.
- Do not disassemble or modify the product.
- Do not expose the product to strong shocks or vibration.
- Use only power sources specified in this instruction manual for use with the product.
- Observe the following instructions when using a battery charger or AC adapter.
 - Do not touch the battery charger or AC adapter connected to a power outlet during lightning storms.
 - Do not use the product if the power plug is not fully inserted into the power outlet.
 - Do not unplug the product by pulling the power cord.
 - Do not plug in or unplug the product with wet hands.
 - Do not place heavy objects on the power cord. Do not damage, break or modify the power cord.
 - Do not leave the product connected to a power source for long periods of time.
 - Do not expose the power plug and terminals to dirt or let them come into contact with metallic pins or other metal objects.
 - Do not charge batteries/battery packs at temperatures outside the range of 0 - 40 °C (32 - 104 °F).
- Observe the following instructions when using commercially available batteries or provided battery packs.
 - Do not use leaking batteries/battery packs.
If a battery/battery pack leaks and the material contacts your skin or clothing, flush the exposed area thoroughly with running water. In case of eye contact, flush thoroughly with copious amounts of clean running water and seek immediate medical assistance.
 - Use batteries/battery packs only with their specified product.
 - Do not heat batteries/battery packs or expose them to fire.
 - Do not charge batteries/battery packs using non-authorized battery chargers.
 - Do not expose the terminals to dirt or let them come into contact with metallic pins or other metal objects.
 - Keep batteries out of the reach of children.
 - When disposing of batteries/battery packs, insulate the terminals with tape or other means.
- Do not shoot the sun directly or point a lens or a camera with a lens attached at the sun. Even when the sun does not appear on the screen or is behind the subject, the lens may concentrate the sunlight and cause a malfunction or fire.
- Do not leave a lens or a camera with a lens attached, exposed without the lens cap attached. The lens may concentrate the light and cause fire.
- Do not wrap the product in cloth or other materials when in use or shortly after use when the product is still warm in temperature.
- Do not allow the product to maintain contact with the same area of skin for extended periods of time during use. This may result in low-temperature contact burns, including skin redness and blistering, even if the product does not feel hot. The use of a tripod or similar equipment is recommended when using the product in hot places and for people with circulation problems or less sensitive skin.
- Keep the product out of the reach of young children.
- A strap wrapped around a person's neck may result in strangulation.
- Periodically remove any dust buildup from the power plug and power outlet using a dry cloth.
- Follow any indications to turn off the product in places where its use is forbidden. Not doing so may cause other equipment to malfunction due to the effect of electromagnetic waves and even result in accidents.
- Before installing, be sure the surface is capable of supporting the total weight of the camera and connected devices, and sufficiently reinforce the surface if necessary.

CAUTIONS

Follow the cautions below. Otherwise physical injury or property damage may result.

- Strap is intended for use on the body only. Hanging the strap with any product attached on a hook or other object may damage the product. Also, do not shake the product or expose the product to strong impacts. This may cause injury or damage to the product.
- Do not leave the product in places exposed to extremely high or low temperatures. The product may become extremely hot/cold and cause burns or injury when touched.
- Only mount the product on a tripod that is sufficiently sturdy.
- Do not look at the screen for prolonged periods of time. This may induce symptoms similar to motion sickness. In such a case, stop using the product immediately and rest for a while before resuming use.

Only for European Union and EEA (Norway, Iceland and Liechtenstein) and United Kingdom



These symbols indicate that this product is not to be disposed of with your household waste, according to the WEEE Directive (2012/19/EU), the Battery Regulation ((EU) 2023/1542) and/or national legislation implementing those Directive and Regulation and the UK Waste Electrical and Electronic Equipment Regulations and the UK Batteries and

Accumulators Regulations.

If a chemical symbol is printed beneath the symbol shown above, in accordance with the Battery Regulation and the UK Batteries and Accumulators Regulations, this indicates that a heavy metal (Hg = Mercury, Cd = Cadmium, Pb = Lead) is present in this battery or accumulator at a concentration above an applicable threshold specified in the Battery Regulation and the UK Batteries and Accumulators Regulations.

This product should be handed over to a designated collection point, e.g., on an authorized one-for-one basis when you buy a new similar product or to an authorized collection site for recycling waste electrical and electronic equipment (EEE) and batteries and accumulators. Improper handling of this type of waste could have a possible impact on the environment and human health due to potentially hazardous substances that are generally associated with EEE. Your cooperation in the correct disposal of this product will contribute to the effective usage of natural resources.

For more information about the recycling of this product, please contact your local city office, waste authority, approved scheme or your household waste disposal service or visit www.canon-europe.com/sustainability/approach/.

Table of Contents

Safety Instructions 2

1. Introduction 9

About this Manual 9

Conventions Used in this Manual 9

Supplied Accessories 10

Names of Parts 11

Camera 11

Handle Unit 16

Microphone Holder 16

Workflow Overview: 4K and Higher 17

Color Grading with the ACES Workflow 18

2. Preparations 19

Preparing the Power Supply 19

Using a Battery 19

Using a Power Outlet 21

Using the LCD Screen 23

PIN Code, Date, Time and Language Settings 24

Setting the PIN Code 24

Setting the Date and Time 25

Changing the Language 25

Using the Menus 26

Selecting an Option from the Menu 26

Using the Customized Menus (My Menu) 27

Preparing the Camera 29

Examples of Camera Configurations 29

Preparing the Lens 29

In-Camera Lens Correction 31

Attaching the Handle Unit 32

Attaching the Microphone Holder 33

Checking the Camera's Inclination 33

Attaching an Accessory Compatible with the Multi-Function Shoe 34

Preparing Recording Media 35

Compatible Recording Media 35

Inserting and Removing an SD Card 36

Initializing Cards 37

Setting a Card's Volume Label 37

Switching Between Card Slots 38

Checking the Remaining Recording Time on a Card 38

Recovering Recordings 38

Selecting the Video Recording Method 39

Setting the File Name for Recordings 42

Clips File Names 42

Photo Numbering 43

Using the Fan 44

Adjusting the Black Balance 45

3. Recording 47

Recording Video and Photos 47

Recording 47

Onscreen Displays 49

Reviewing a Recording 55

Adjusting Camera and Recording Settings 56

Performing Basic Settings with Direct Touch Control 56

Direct Setting Mode (FUNC Button) 57

Video Recording Configuration: Video Format, Sensor Mode, System Frequency, Resolution and Frame Rate 59

Selecting the System Frequency 61

Selecting the Sensor Mode 62

Selecting the Main Recording Format 62

Selecting the Resolution of Primary Clips 62

Selecting the Frame Rate 62

Selecting the Bit Rate for Primary Clips 62

Sub Recording Clips 63

Proxy Clips 64

Shutter Speed 66

Recording Under High-Frequency Light Sources 67

Flicker Reduction 67

ISO Speed/Gain 68

Base ISO Speed 68

Manual ISO Speed/Gain Value 69

Automatic ISO Speed/Gain 70

ND Filter 72

Aperture 73

Aperture Settings of the Lens 73

Manual Aperture: Changing the Aperture Value 73

Momentary Automatic Aperture - Push Auto Iris 74

Automatic Aperture 75

Exposure Compensation - AE Shift 75

Light Metering Mode 76

White Balance 77

- White Balance Mode 77
- Custom White Balance 78
- Color Temperature/Preset White Balance 78
- Auto White Balance (AWB) 79

Focus 80

- Focus Mode on the Lens 80
- Manual Focus 80
- One-Shot AF 83
- Continuous AF 83
- Changing the AF Frame Type and Position 85
- Subject Detection Function 86

Image Stabilization 88**Zoom 90**

- Zoom Modes of the Lens 90
- Adjusting the Zoom 90

Onscreen Markers, Zebra Patterns and False Color 91

- Displaying Onscreen Markers 91
- Displaying Zebra Patterns 93
- Displaying False Color 94

Setting the Time Code 95

- Selecting the Time Code Mode 95
- Selecting Drop or Non-Drop Frame 96
- Setting the User Bit 96

Synchronizing with an External Device 98

- Connecting an External Device 98
- Time Code Signal Input 98
- Time Code Signal Output 99

Recording Audio 100

- Audio Format for XF-HEVC S / XF-AVC S Clips 101
- Connecting an External Microphone or External Audio Input Source to the Camera 102
- Selecting the Audio Input Source for Audio Channels 103
- Adjusting the Audio Recording Level 103
- Advanced Audio Input Settings 105
- Multi-Function Shoe Audio Input Settings 106
- Monitoring the Audio with Headphones 106

Colors Bars/Audio Reference Signal 107

- Color Bars 107
- Audio Reference Signal 107

Video Scopes 108

- Displaying a Video Scope 108
- Changing the Waveform Monitor Settings 108
- Changing the Vectorscope Settings 109

Adding Marks to Clips in CAMERA Mode 110

- Adding a Shot Mark while Recording 110
- Adding an  Mark or  Mark to the Last Clip Recorded 110

Using Metadata 111

- Setting a User Memo Created with Canon XF Utility 111
- Using News Metadata 112
- Entering Slate Information About the Recording 113

Special Recording Modes 114

- Slow & Fast Motion Recording 114
- Pre-recording 117
- Continuous Recording 118
- Frame Recording Mode 119
- Interval Recording Mode 119

Using Anamorphic Lenses 121**Web Camera Function 122****Using the RC-V100 Remote Controller 123****4. Customization 125****Assignable Buttons 125**

- Changing the Assigned Function 125

Custom Picture Settings 129

- Selecting Custom Picture Files 129
- Preset Picture Settings 129
- Editing a Custom Picture File's Settings 130
- Look Files 131
- Saving a Custom Picture File 132
- Available Custom Picture Settings 134

Saving and Loading Menu Settings 139

- Saving Menu Settings 139
- Loading Menu Settings 139

5. Playback 141

Playback 141

- Displaying the Index Screen 141
- Playing Back Recordings 142
- Onscreen Displays During Clip Playback 144
- Clip Playback Controls 145
- Adjusting the Volume 146

File Operations 147

- File Menu Operations 147
- Displaying Clip Information 148
- Adding  Marks or  Marks 149
- Deleting  Marks or  Marks 149
- Adding/Deleting Shot Marks 149
- Deleting All the Shot Marks from a Clip 150
- Deleting Recordings 150
- Deleting the User Memo and GPS Information from a Clip 150

6. External Connections 151

Video Output Configuration 151

- Video Output Configuration (Recording/Playback) 151

Connecting to an External Monitor or Recorder 154

- Using the SDI OUT Terminal 154
- Using the HDMI OUT Terminal 155
- RAW Video Output from the HDMI OUT terminal 155
- Selecting the Output Range 156
- Superimposing Onscreen Displays on Video Outputs 157
- Changing the Opacity Level of Onscreen Displays 157

Applying the View Assistance Function to the LCD Screen 158

- Adjusting the Gain Difference When Converting HDR to SDR 159

Audio Output Channels 160

Importing Files to a Computer/Smartphone 161

- Saving Files 161
- Saving XF-HEVC S/XF-AVC S Clips 161
- Saving Audio Files (WAV) 162
- Automatically Transferring Recording Data to an FTP Server 163

7. Network Functions 165

Network functions and connection types 165

- Using a Wi-Fi Network 166
- Using a Wired (Ethernet) Network 167

Configuring Connection Settings 168

- Activating a Network Connection 168
- Adding a New Connection Setting Using the Wizard 169
- Function Settings 169
- Other Connection Methods 174
- Other Network Settings 177
- 802.1X Authentication 177
- Checking and Changing Connection Settings (SET) 178
- Checking and Changing Communication Settings (NW)/Function Settings (MODE) 179

Checking the Network's Status 183

FTP File Transfer 184

- Transferring a Single Clip 184
- Transferring All Clips 184

IP Streaming 185

Browser Remote: Controlling the Camera from a Network Device 187

- Starting Browser Remote 187
- Using Browser Remote 189

Recording Remotely Using an XC Protocol

- Compatible Controller/Application 193
- Recording remotely using the RC-IP100/RC-IP1000 Remote Camera Controller 193
- Recording remotely using the Remote Camera Control Application 193
- Recording remotely using Multi-Camera Control 194

Transferring Recordings to a Smartphone 195

Uploading Recording Data to Frame.io 196

Updating the Firmware Automatically 197

8. Additional Information 199

Menu Options 199

Displaying the Status Screens 213

Recording / Output Signal and Detailed
Settings 214

Sub Recording Clips 214

Troubleshooting 224

List of Messages 230

Access Log 237

Handling Precautions 238

Maintenance/Others 240

Optional Accessories 241

Specifications 243

Compatible Lenses and Functions 249

Reference Tables 251

Approximate Recording Time on a Card 251

Charging Times 251

Appendix: Camera Dimensions 252

Index 255

About this Manual

Thank you for purchasing the Canon EOS C80. Please read this manual carefully before you use the camera and retain it for future reference. Should the camera fail to operate correctly, refer to *Troubleshooting* (📖 224).

Before Using the Camera


- Before making important recordings for the first time, make test recordings using the video configuration(s) you plan to use to check that the camera operates correctly. Should it fail to operate correctly, refer to *Troubleshooting* (📖 224).
- **Copyright notice:** Unauthorized recording of copyrighted materials may infringe on the rights of copyright owners and be contrary to copyright laws.
- **Notes on privacy and publicity rights regarding the use of video:** When using the camera, exercise proper caution in order to protect privacy and avoid any violation of publicity rights.
- **About the LCD screen:** The screen is produced using extremely high-precision manufacturing techniques, with more than 99.99% of the pixels operating to specification. Very rarely, pixels may misfire or light up permanently. This has no effect on the recorded image and does not constitute a malfunction.
- **About the access indicator:** Observe the following precautions while an access indicator (📖 36) is illuminated or flashing in red. Failing to do so may result in permanent data loss.
 - Do not turn off the camera and do not remove the battery or other power source.
 - Do not open the card compartment cover.

Conventions Used in this Manual


- **! IMPORTANT:** Precautions related to the camera's operation.
- **i NOTES:** Additional topics that complement the basic operating procedures.
- **📖:** Reference page number.
- The following terms are used in this manual.
 - "Screen" refers to the LCD monitor's screen.
 - "Battery" refers to a supplied or optional battery pack.
 - "AC adapter" refers to the CA-CP300 B Compact Power Adapter.
 - "SD card" refers to an SD, SDHC or SDXC memory card.
 - "Card" alone, not specified: refers to SD cards.
 - "RAW" refers to the data recorded in Cinema RAW Light.
 - "Multi-Camera Control" refers to Canon Multi-Camera Control.
 - "CAMERA mode": operating mode for making recordings (shooting mode).
 - "MEDIA mode": operating mode for playing back and managing recordings (playback mode).
 - "Access indicator": when not specified, refers collectively to the SD CARD access indicators.
- Unless indicated otherwise, shooting functions are utilized in CAMERA mode.
- Unless indicated otherwise, illustrations in the manual show the Canon EOS C80 camera with a Canon RF24-105mm F4 L IS USM lens attached.
- Photographs in the manual are simulated pictures taken with a still camera.
- Some screenshots have been altered to make them easier to read. Furthermore, screenshots used are from a product in development and may differ slightly from the actual screens due to product enhancement.

Supplied Accessories


The following accessories are supplied with the camera. For accessories sold separately, please refer to *Optional Accessories* (□ 241). Unless indicated otherwise, accessories mentioned in this manual are the ones supplied with the camera.



CA-CP300 B Compact Power Adapter



CG-A20 Battery Charger



BP-A30N Battery Pack
(incl. terminal cover)



Handle Unit




Microphone Holder
(incl. M4 fixation bolts, x2)




Multi-Function Shoe Cover*




Body Cap*



SS-1200 Shoulder Strap



Tape Measure Hook*



Quick Guide

* Comes pre-attached to the camera.


! IMPORTANT

- Do not use the supplied compact power adapter and power cord with other devices as this may cause a malfunction.


Names of Parts

Camera

11



- 1 ND FILTER +/- buttons (72)
- 2 WB (white balance) button (77)/
Assignable button Camera 1 (125)
- 3  (white balance adjustment) button (77)/
Assignable button Camera 2 (125)
- 4 Strap mounts
Pass one end of the SS-1200 Shoulder Strap through the strap mount and adjust the length of the strap.




- 5 Air intake vent (44)
- 6 SDI OUT terminal (154)
- 7 INPUT 1/INPUT 2 terminals (102)
- 8 MIC (microphone) terminal (102)
- 9 USB terminal (122)
- 10  (headphone) terminal (106)
- 11 REMOTE terminal (123)
For connecting the RC-V100 Remote Controller or commercially available remote controllers.
- 12 HDMI OUT terminal (154)
- 13 DISP (display) button (49)/
Assignable button Camera 5 (125)
- 14 ZEBRA button (93)/
Assignable button Camera 6 (125)
- 15 WFM (video scope) button (108)/
Assignable button Camera 4* (125)
- 16 PEAKING button (82)/
Assignable button Camera 3 (125)

* Can be assigned exclusively as a REC button (125)


Removing and attaching the terminal covers

You can remove the covers of the camera's terminals to access them more easily. To remove a terminal's cover, open the cover and gently pull it straight out. To attach back the terminal cover, insert the connecting strip into the opening. If the connecting strip is difficult to grasp, use a pair of tweezers or similar tool.




1 Strap mounts


Insert the end of the SS-1200 Shoulder Strap from the top of the strap mount and pull it from the exhaust ventilation outlet to attach it to the camera.




- 2 Exhaust ventilation outlet (44)
- 3 Assignable button Camera 10 (125)
- 4 Card slots **A** and **B** (36)
- 5 Card compartment cover (36)
- 6 TIME CODE terminal (98)
- 7 Tripod screw holes (1/4"-20, 7.5 mm (0.29 in.) deep)




- 1 REC (start/stop recording) button (47)
- 2 Grip belt
Adjust the grip belt so that you can reach the REC button with your index finger but still have a comfortable but secure grip.



- 3 Front control dial (69, 73)
- 4 RF lens mount index (29)
- 5 Monaural microphone (100)
- 6 Power indicator (green)/Tally lamp (red) (47)
- 7 Lens lock pin
- 8 Lens release button (29)
- 9 Assignable button Camera 11 (125)
The [REC] function can be assigned.
- 10 Lens contacts (29)
- 11 AF LOCK button (85)/
Assignable button Camera 12 (125)



- | | |
|--|---|
| 1 LCD monitor (23) | 8 Audio level dials for CH1 (top) and CH2 (bottom) (104) |
| 2 INPUT 1 (top) / INPUT 2 (bottom) switches (audio source selection, 102) | 9 Audio level switches for CH1 (top) and CH2 (bottom) (103) |
| 3 Joystick (26)
You can push the joystick in 8 directions (up/down, left/right, or diagonally) and press the joystick itself to confirm. | 10 AUDIO STATUS (display the [11] Audio Setup] status screens) button (213) / Assignable button Camera 13 (125) |
| 4 PUSH AUTO IRIS (momentary automatic aperture) button (74)/
Assignable button Camera 7 (125) | 11 Ethernet terminal (167) |
| 5 MAGN. (magnification) button (82)/
INDEX button (142)/
Assignable button Camera 8 (125) | 12 DC IN terminal (21) |
| 6 Rear control dial (69, 74) | 13 Battery compartment (20) |
| 7 FUNC (main functions) button (57)/
Assignable button Camera 9 (125) | 14 BATTERY RELEASE button (20) |
| | 15 CANCEL button (26) |
| | 16 SELECT dial/SET button (26) |
| | 17 MENU button (26) |



- | | |
|--|---|
| <p>1 Accessory mount with socket for 1/4"-20 mounting screws (7.5 mm (0.29 in.) deep) (33)</p> <p>2 Tape measure hook and ϕ focal plane mark
Use the hook to accurately measure the distance from the focal plane.</p> <p>3 POWER switch
🔒: Key lock.
CAMERA: Starts the camera in CAMERA mode.
OFF: Turns off the camera.</p> <p>4 Speaker (146)</p> <p>5 Multi-function shoe (with shoe cover) (34)</p> <p>6 MEDIA button (141)
When the camera is on, press to toggle the camera between CAMERA mode (shooting) and MEDIA mode (playback).</p> | <p>7 SLOT SELECT (card selection) button (38, 142)</p> <p>8 SD CARD access indicator: A/B (36)</p> <p>9 Power cord clamp (unplugging prevention) (22)</p> <p>10 Exhaust ventilation outlet (44)</p> <p>11 Socket for tripod's anti-rotation pin (5.6 mm (0.22 in.) deep)</p> <p>12 DC cable clamp (22)
Used to prevent accidental disconnection.</p> <p>13 Screw holes for 1/4"-20 mounting screws (7.5 mm (0.29 in.) deep)</p> <p>14 Screw hole for 3/8"-16 mounting screws (7.6 mm (0.30 in.) deep)</p> <p>15 Screw holes for tripod reinforcements and accessories with 1/4"-20 mounting screws (7.5 mm (0.29 in.) deep, x2)</p> |
|--|---|

Locking the camera's controls (key lock)

You can set the **POWER** switch to 🔒 (key lock) to lock all the camera's buttons* and switches. This is useful in preventing settings from being changed due to inadvertently pressing one of the buttons. Set the **POWER** switch back to CAMERA to reactivate the controls.


When the camera's controls are locked, you can still operate the camera using an RC-V100 Remote Controller or the Browser Remote application.

* REC buttons are not locked by default but you can choose to lock them too (211).

! IMPORTANT

- Do not use tripods and other accessories with mounting screws exceeding the depth of the screw holes on the camera as this may damage the camera.
- Mounting the camera on a tripod using only one of the 1/4"-20 screw holes for tripod reinforcement may damage the camera.


Handle Unit (32)



- 1 Locking knob
- 2 Cable clamp
- 3 Accessory shoe

- 4 Sockets for the microphone holder (33)

Microphone Holder (33)




- 1 Microphone lock screw
- 2 Microphone holder

- 3 Microphone cable clamp

Workflow Overview: 4K and Higher

The following illustrates the typical workflow for 6K/4K recording with the camera.




- 1 Shoot in 6K/4K mode (📖 59).
- 2 You can record primary clips (6K/4.3K: RAW, 4K: XF-AVC / XF-HEVC S / XF-AVC S) on an SD card in the camera, record 6k data to an external recorder using HDMI RAW, or record 4K data using an external recorder connected to the camera's SDI OUT or HDMI OUT terminal (📖 155).
- 3 While recording primary clips, you can simultaneously record 2K proxy clips on an SD card B.
 - The file names of 2K proxy clips (XF-AVC / XF-HEVC S / XF-AVC S) and 4K clips are linked and identical for the most part (📖 42).
- 4 You can use the 2K proxy clips recorded on the SD card, proxy files generated by Cinema RAW Development or 6k data recorded to an external recorder using HDMI RAW on NLE software to edit the video offline and create an EDL.
- 5 After recording RAW data on an SD card in the camera, develop the clips using the Cinema RAW Development software (📖 162) to generate full-quality data.
 - You can also generate proxy data.
- 6 Perform color grading based on the full-quality data.

Color Grading with the ACES Workflow

You can perform color grading using ACES, the color encoding system defined by the Academy of Motion Picture Arts and Sciences.

18




Color spaces:

- ST2065-1: AP0 primaries, linear floating-point encoding.
- ACESc: AP1 primaries, log floating-point encoding.
- ACEScct: AP1 primaries, log floating-point encoding. Differs from ACESc by adding a 'toe' to the encoding, with a behavior resembling that of the Cineon curve.

Input Transform: Refers to the table used for converting color information of the input device to ST2065-1 color space. It can be downloaded from Canon's website.

Output Transform: Refers to the table used for mapping ST2065-1 color space information to the specific color information scheme used by the display device.

ASC-CDL: Refers to the list that contains color grading adjustment data. This step requires equipment compatible with ASC-CDL.



Preparing the Power Supply

You can power the camera using a battery or a power outlet. Even when a battery is attached, if the camera is connected to a power outlet, it will not draw power from the battery.



Using a Battery

You can power the camera using the included BP-A30N Battery Pack or the optional BP-A60N Battery Pack. Both battery packs are compatible with Intelligent System so you can check the approximate remaining battery usage time (in minutes) on the screen. For more accurate readings, when using a battery for the first time, charge it fully and then use the camera until [Change the battery pack] appears on the screen.

Charging the Battery

Charge battery packs using the CG-A20 Battery Charger and CA-CP300 B Compact Power Adapter. Before charging, remove the terminal cover of the battery pack.

- 1 Connect the AC adapter to the battery charger and plug the power cord into a power outlet.
- 2 Attach the battery to the battery charger.
 - Press lightly and slide the battery in the direction of the arrow until it clicks.
 - The CHARGE indicator starts flashing and also indicates the battery pack's approximate charge. The indicator will stay on when charging has completed.



- approx. 0% to 49%: Flashes once every 2 seconds
- approx. 50% to 74%: Flashes twice every 2 seconds
- approx. 75% to 99%: Flashes 3 times every 2 seconds

- 3 Disconnect the AC adapter from the battery charger and unplug the power cord.
- 4 Remove the battery from the battery charger.

! IMPORTANT


- Do not connect to the battery charger any product that is not expressly recommended for use with this camera.
- When using the battery charger or AC adapter, do not fix it permanently to one place as this may cause a malfunction.
- Even within the operating temperature range of the included CG-A20 Battery Charger or the optional CG-A10 Battery Charger, charging may not be possible depending on the internal temperature of the battery.

NOTES

- To prevent equipment breakdowns and excessive heating, do not connect the battery charger or AC adapter to voltage converters for overseas travels or special power sources such as those on aircraft and ships, DC-AC inverters, etc.
- We recommend charging the battery in temperatures between 10 °C and 30 °C (50 °F and 86 °F). Outside the temperature range of 0 °C to 40 °C (32 °F to 104 °F), charging will not start.
- If there is a malfunction with the battery charger, AC adapter or battery, the charge indicator will go out and charging will stop.
- For handling precautions regarding the battery, refer to *Handling Precautions* (📖 238).
- For approximate charging times / usage times, refer to the *Reference Tables* (📖 251) and *Approximate Continuous Recording Times* (📖 247).
- Charged batteries continue to discharge naturally. Therefore, charge them on the day of use, or the day before, to ensure a full charge.
- We recommend that you prepare batteries to last 2 to 3 times longer than you think you might need.
- Repeatedly charging and completely depleting a battery will eventually shorten its battery life. You can check the battery life on the [🔧 System Setup] status screen (📖 213). Fully charging the battery pack and then depleting it until [Change the battery pack] appears on the screen will give you a more accurate reading.


Attaching the Battery

- 1 Turn off the camera.
- 2 Insert the battery all the way into the compartment as shown in the illustration and press it gently toward the left until it clicks.



Removing the Battery

- 1 Turn off the camera.
- 2 Holding down the BATTERY RELEASE button (①), slide the battery toward the right and then pull it out (②).




Checking the Remaining Battery Charge

You can check the approximate charge level on the battery itself. When the camera is turned on, you can check the approximate remaining battery usage time (in minutes) by looking at any recording/playback screen or the [🔧 System Setup] status screen (📖 213).

Press the CHECK button on the battery. An indicator will light for approximately 3 seconds and show the approximate remaining battery charge.

☀ ○ ○ ○	0-25%
☀ ☀ ○ ○	26-50%
☀ ☀ ☀ ○	51-75%
☀ ☀ ☀ ☀	76-100%



i NOTES

- The remaining battery charge level displayed in minutes on the screen may not match the [🔧 System Setup] status screen or the indicators on the battery pack.


Using a Power Outlet

You can also power the camera directly from a power outlet using the CA-CP300 B Compact Power Adapter (AC adapter). While the camera is powered using a power outlet, you can replace the battery pack even when the camera is turned on.

Connect the power cord to the AC adapter, the AC adapter's DC plug to the DC IN terminal on the camera, and the power plug to a power outlet.


! IMPORTANT

- Make sure to turn off the camera before connecting or disconnecting the AC adapter.
- When using the AC adapter, do not fix it permanently to one place as this may cause a malfunction.
- In order to prevent the camera from powering off due to a power outage or accidental disconnection, it is recommended to attach a battery pack even when recording with the camera connected to the AC adapter.



Preventing the accidental unplugging of the power cord

Pass the power cord through the DC cable clamp (recommended) and/or the clamp at the bottom of the camera as shown in the illustration to prevent the accidental unplugging of the DC plug.



Checking the Voltage Level of the Power Source

The voltage level appears on the screen (📖 49). Select **MENU** > [🔧 System Setup] > [DC IN Warning (V)] to set a power warning level. When the voltage from the DC IN terminal reaches the set value, the onscreen voltage indicator will turn red and a warning will be displayed.


NOTES

- The camera will not start recording if the voltage falls below the selected low-power warning level (📖 211). While shooting, the recording will be interrupted and the camera will turn off if the power voltage falls below the level required for the camera's operation.

Using the LCD Screen

This section explains how to adjust the LCD monitor. You can adjust the direction of the screen as shown below, as well as image settings such as brightness or contrast. Additionally, you can use the touch screen to select the subject or perform a variety of settings using direct touch control (56).

- 1 Open the LCD monitor 180 degrees (①) and adjust to the desired angle (②).
- 2 When the screen is facing the subject (③), you can also place it back in its original position with the screen facing out (④).




i NOTES

- You can adjust the brightness, contrast, color saturation, sharpness and luminance of the LCD screen with the respective settings in the **MENU** > [Monitoring Setup] menu (204). These settings do not affect the recorded video.
- In CAMERA mode, you can use the **MENU** > [Monitoring Setup] > [B&W Image: LCD] setting to change the image on the screen to black and white display. Even when the captured image is displayed in black and white, onscreen displays and icons will be shown in color.
- You can use the **MENU** > [System Setup] > [Touch Screen Response] setting to adjust the LCD monitor's response to touch input.
- When the LCD panel is rotated 180 degrees toward the subject, you can set **MENU** > [Monitoring Setup] > [LCD Mirror Image] to [On] to flip the image horizontally so it shows a mirror image of the subject.
- For details about how to take care of the LCD monitor, refer to *Handling Precautions* (238), *Cleaning* (240).

PIN Code, Date, Time and Language Settings

You will need to set the PIN code, date and time on the camera the first time you power it on, or after the camera's settings have been reset. Refer to *Using the Menus* (📖 26) for instructions on setting operation.

Setting the PIN Code



1 Enter a PIN code (6-digit number).

- The numeric keypad screen is displayed by touching the input area in the center of the screen.
- Touch a key on the screen to select a number, then touch [OK] to confirm the entry.
- You can also use the SELECT dial or the joystick to select a number and press the SET button to enter it.

2 Select [OK].

3 Enter the PIN code again following the on-screen instructions and select [OK].

4 When the confirmation message appears, select [OK].

- You will need to enter the PIN code when starting up the camera.
- By configuring the following settings, you can omit entering the PIN code from next time.
 - Select [Don't require PIN code again] on the PIN code entry screen.
 - Set **MENU** > [🔧 System Setup] > [PIN Code Management] > [PIN Code Request] to [Disable].


! IMPORTANT

- If you forget your PIN code, you will need to reset the device. Please note that all camera settings will be initialized.
- Setting a PIN code does not protect the recorded data stored on the card.
- Canon shall not be liable for the theft of this product or any memory cards.
- If you configure the settings to omit entering the PIN code, please be careful to prevent third parties from accessing the camera's settings and other information.

i NOTES

- Until you enter the PIN code, these connections are not available while the PIN code screen is displayed.
 - USB connection
 - Network connection
- To change the PIN code, go to **MENU** > [🔧 System Setup] > [PIN Code Management] > [PIN Code Change].

Setting the Date and Time



1 Select the desired time zone* using the joystick or the SELECT dial, and confirm by pressing the SET button or the joystick itself.

- The cursor will move to the next field.
- You can also push the joystick left/right to move between the fields.

* The default time zone is [UTC-05:00] (New York) or [UTC+01:00] (Central Europe), depending on the country/region of purchase. Time zones are based on Coordinated Universal Time (UTC).

2 Change the rest of the fields in the same way.

3 Select [Set] and then press SET.

NOTES

- You can display the date/time with the **MENU** > [📺 Monitoring Setup] > [Custom Display 2] or [Custom Display] > [Date/Time] setting.
- With the following settings, you can make changes after the initial setup. You can also change the date format and clock format (12 or 24 hours).
 - **MENU** > [🔧 System Setup] > [Time Zone], [Date/Time] and [Date Format]
- When you do not use the camera for about 3 months, the built-in backup battery may be depleted completely and the date and time setting may be lost. In such case, recharge the built-in backup battery (📖 239) and set the time zone, date and time again.
- Using the GP-E2 GPS Receiver, you can have the camera adjust settings automatically according to the UTC date/time information received from the GPS signal (📖 211).

Changing the Language

The camera's default language is English. You can change it to German, Spanish, French, Italian, Polish, Portuguese, Russian, Ukrainian, Simplified Chinese, Korean or Japanese. Please note that some settings and screens will be displayed in English, regardless of the language setting.


Refer to *Selecting an Option from the Menu* (📖 26) for details on how to navigate the menu to complete this procedure.

1 Select **MENU** > [🔧 System Setup] > [Language 🗣️].

2 Select the desired language and press the MENU button to close the menu.

Using the Menus

Many of the camera's functions can be adjusted using the menu. In CAMERA mode, you can also register frequently used menu settings in a customized menu (My Menu) for easy access. For details about the available menu options and settings, refer to *Menu Options* (📖 199).



Selecting an Option from the Menu

The following is a step-by-step explanation of how to select a typical option from the setup menus. Some menu items may require additional steps. Such operations will be explained in the respective section of the manual. For brevity's sake, references to menu settings throughout the manual will be abbreviated as follows:

MENU > [🔧 System Setup] > [Language 🗣️] > Desired option

1 Press the MENU button.

- The menu opens. The icon displayed in orange is the menu item that was selected the last time the menu was closed (unless the camera was turned off).
- When a menu icon is not selected, first push the joystick up or press the CANCEL button to move the orange selection frame to one of the icons.

2 Push the joystick left/right to select the icon of the desired setup menu.

- You can also use the rear control dial.

3 Press the joystick or the SET button to confirm your selected setup menu.

- The cursor moves to the first item on the first page of the selected setup menu.
- You can also push the joystick down to move the cursor to the list of menu items.
- Going forward, this operation will be referred to as “press SET” in this manual.

4 Select the desired menu item ([Language , in the example) and then press SET.

- Joystick operation:
 - Push the joystick left/right to scroll through the menu pages. Moving left/right from the first/last page will move to the previous/next setup. You can use the front control dial.
 - Push the joystick up/down to move the cursor over the menu items on the page.
- Dial operation:
 - Turning the SELECT dial will scroll through the menu items on the page. Scrolling beyond the first/last menu item in the list will move to the previous/next menu page.
 - Scrolling beyond the first/last page will move to the previous/next setup menu.

5 Push the joystick up/down or turn the SELECT dial to select the desired setting option and then press SET.

- During the selection, the currently selected option is indicated with a  mark. Press SET to confirm your selection and go back to the previous screen.
- When many options are available, a scroll bar will appear on the right. Scroll up or down to see other options.
- Press the CANCEL button or select [] and press SET to return to the previous menu level.

6 Press the MENU button to close the menu.

- Pressing the MENU button at any time closes the menu.

NOTES

- Unavailable items may appear grayed out.
- On some screens, the following icons may be displayed as a guide: , , . They refer, respectively, to pressing the joystick or SET button, the MENU button and the CANCEL button.
- When an RC-V100 Remote Controller is connected to the camera, you can use the remote controller's up/down/left/right/SET buttons in the same way as the camera's joystick. Pressing the SET button is equivalent to pressing the joystick on the camera.
- You can check most of the current settings on the status screens ( 213).
- You can set **MENU** > [ System Setup] > [Ctrl Dial in Menus] to [Disable] to disable the use of the front and rear control dials while browsing the menus. In such case, use the SELECT dial to move between menus.

Using the Customized Menus (My Menu)

In CAMERA mode, you can register up to 6 frequently used menu settings under a My Menu page for easy access. You can save up to 5 separate sets of My Menu settings each with 6 options for different shooting situations. Furthermore, if you set an assignable button to [My Menu] ( 125), you can press the button to access your registered menu settings even faster and more easily.

Adding Menu Settings

1 Select **MENU** > [My Menu] > Desired menu page > [Edit] > [Register].

- A screen will appear where you can select the menu setting you want to add.
- Press the CANCEL button to cancel the operation and return to the regular menu.

2 Select the menu setting you want to add.

3 Select [OK].

- The menu setting you registered will now appear under the currently selected My Menu set.

Rearranging Menu Settings

- 1 Select **MENU** > [★ My Menu] > Desired menu page > [Edit] > [Move].
- 2 Select the menu setting you want to move.
 - The  icon will appear next to the setting you selected to move.
- 3 Move the menu setting to the desired position and press SET.

Removing Menu Settings

- 1 Select **MENU** > [★ My Menu] > Desired menu page > [Edit] > [Delete].
- 2 Select the menu setting you want to remove and then select [OK].

Resetting All the My Menu Sets

Reset all the menu settings registered to the currently selected My Menu set.
Select **MENU** > [★ My Menu] > Desired menu page > [Edit] > [Reset All] and then select [OK].

Renaming My Menu Sets

You can give each of the 5 My Menu sets a more descriptive name to make them easier to identify.
1 Select **MENU** > [★ My Menu] > Desired menu page > [Edit] > [Rename].
2 Enter the desired name (8 characters long) using the keyboard screen (see the following sidebar).

Entering text and numbers

There are two types of screens used to enter text and numbers – the keyboard screen, and the data entry screen. Which screen is used, as well as the available characters will depend on the menu setting.

Keyboard screen

- 1 Touch the character you wish to enter.
 - The characters you entered will appear in the input area at the top of the screen.

Key	Function
	Moves the cursor in the input area.
	Shift key
 / A↔1	Switches between letters, numbers and special characters.
	Space key
	Backspace key




- You can also move the cursor with the SELECT dial or the joystick, and select the desired character by pressing SET.
- 2 After entering the desired text, touch [OK] to confirm.

Data entry screen

Use the SELECT dial or the joystick to select characters.

- 1 Select a character and then press SET to confirm.
 - The cursor will move to the next field.
 - You can also push the joystick left/right to move between the fields.
 - Change the rest of the characters in the same way.
- 2 Select [Set] to confirm the text or value.
 - Press CANCEL to stop entering text.




Preparing the Camera


This section details how to prepare the camera for the first time, including how to mount and remove lenses and the handle unit.

Examples of Camera Configurations


Your camera allows you to build the shooting configuration that best fits your needs and shooting conditions. For details on the optional accessories compatible with this camera, refer to *Optional Accessories* (📖 241) and the **Cinema EOS System Expansion User Guide** (PDF file).



Configuration with microphone holder and handle



Configuration with handle



Minimal configuration

! IMPORTANT

- Be careful not to drop the camera or accessories when attaching, removing or adjusting the various accessories. Use a table or other stable surface to change the camera's configuration.

Preparing the Lens

As much as possible, attach and remove the lens quickly and in a clean environment free of dust. You can also use an EF lens or PL lens by attaching a mount adapter to the RF lens mount. Refer also to the instruction manual of the lens/mount adapter used.

! IMPORTANT


- When attaching/removing a lens, avoid direct sunlight or strong light sources. Also, be careful not to drop the camera or lens.

i NOTES

- **After removing a lens/When a lens is not attached to the camera:**
 - Do not touch the lens's surfaces, the lens mount or any components inside the lens mount area.
 - Place the body cap back on the lens mount and the dust caps on the lens. Clean any dust or dirt from the body cap and dust caps before using them.


Attaching a Lens

- 1 Turn off the camera.
- 2 Remove the body cap from the camera and the dust caps from the lens.
- 3 Attach the lens to the camera and turn the lens in the direction of the arrow until it clicks in place.
 - Align the red mark on the lens with the red lens mount index mark on the camera.



Removing a Lens

- 1 Turn off the camera.
- 2 Hold down the lens release button and turn the lens all the way in the direction of the arrow until it stops.
- 3 Remove the lens.
- 4 Place the body cap back on the lens mount and the dust caps on the lens.



i NOTES

- Turning on the image stabilization function of a lens may reduce the effective usage time of the battery pack. When image stabilization is not necessary, for example if the camera is fixed to a tripod, it is recommended to turn it off.
- Depending on the lens used, you may experience one or more of the following limitations.
 - The lens model name may be shortened when displayed on the screen.
 - You may not be able to focus manually when the focus mode switch of an EF lens is set to AF.
 - You may not be able to use the focus preset function on an EF lens (super telephoto lenses).
 - You may not be able to use the power zoom function on EF lenses with that function.
- This camera's sensor is larger than the sensor size for which RF-S/EF-S lenses are designed (APS-C). When using RF-S/EF-S lenses with this camera, you may notice peripheral illumination fall-off or vignetting (200).
- When using a compatible lens, you can use the **MENU** > [System Setup] > [Retract Lens] setting to retract the lens automatically when the camera's power is turned off with the lens's focus mode switch set to AF.
- When a VR lens is attached, the handle unit, accessories attached to the handle unit or the hand holding the grip may be reflected in the image. Check the image before recording.

Using the EF-EOS R 0.71x Mount Adapter

- You can use the EF-EOS R 0.71x Mount Adapter to attach a compatible EF lens to the camera and shoot video with an angle of view equivalent to full frame (when the sensor mode is [Super 35mm (Cropped)]). Additionally, you can use autofocus, peripheral illumination correction and chromatic aberration correction. For details on compatible lenses, visit your local Canon website.
 - * Setting the camera's sensor mode to [Full Frame] causes vignetting.
- When using the EF-EOS R 0.71x Mount Adapter with some EF lenses, a frame that limits the AF range may be displayed.

Updating the Firmware of a Lens/Mount Adapter/Power Zoom Adapter/Accessory

You can update the firmware of the lens/mount adapter/power zoom adapter/accessory attached to the camera (only in CAMERA mode). For details about firmware updates, visit your local Canon website. The following example explains how to perform a firmware update for lenses.

- 1 Download the lens/mount adapter/power zoom adapter/accessory firmware update file from the Canon website and save it on the root directory of an SD card. Insert the SD card containing the firmware update into the camera's SD card slot B (📖 36).
- 2 Attach the lens/mount adapter/power zoom adapter/accessory you want to update and turn on the camera in CAMERA mode.
 - Attach a lens also when updating the firmware of the mount adapter/power zoom adapter.
- 3 Select **MENU** > [🔧 System Setup] > [Firmware] > [Lens], [Mount Adapter], [Power Zoom Adapter] or [Accessory].
 - The current lens/mount adapter/power zoom adapter/accessory firmware version will appear on the screen.
 - If the menu option is grayed out, the attached lens/mount adapter/power zoom adapter/accessory may not support firmware updates or the SD card used may not contain a valid lens firmware file. Check the lens/mount adapter/power zoom adapter/accessory and SD card and repeat the procedure from the beginning.
- 4 Select [OK].
- 5 Select the lens firmware file (.LFU or .AFU file).
- 6 Select [OK].
 - The firmware will be updated. Once in progress, the lens firmware update cannot be canceled.
- 7 When the confirmation message appears, press SET.

! IMPORTANT

- Be sure to observe the following precautions while the lens firmware is being updated.
 - Do not turn off the camera and do not remove the battery pack or other power source.
 - Do not remove the lens/mount adapter/power zoom adapter/accessory.
 - Do not operate any buttons or controls on the camera.
 - Do not open the card compartment cover and do not remove the SD card.

i NOTES

- The lens firmware cannot be updated while pre-recording is activated.
- Power the camera using an AC adapter or a sufficiently charged battery pack.
- When using an EF extender, remove the extender before performing the procedure.

In-Camera Lens Correction

Depending on the characteristics of the lens used, the corners of an image frame may be darker than the center due to light fall-off (peripheral illumination drop), color shift/color fringing may be visible along high-contrast edges in the image (chromatic aberration), the image produced may not be as sharp at certain apertures (lens diffraction), or the image might appear distorted (distortion aberration). In CAMERA mode, you can apply a correction to compensate as necessary. To apply peripheral illumination or chromatic aberration correction, correction data for the lens used is necessary. Distortion aberration correction is only possible for compatible RF lenses.

- 1 Attach the lens you want to use and turn on the camera in CAMERA mode.

2 Select **MENU** > [Camera Setup] > [Periph. Illum. Corr.], [Chromatic Aberr. Corr.], [Diffraction Correction], or [Distortion Aberr. Corr.].

- If correction data is not available, [Periph. Illum. Corr.] or [Chromatic Aberr. Corr.] will appear grayed out. Visit your local Canon website and check if there is correction data available for the lens you are using. If so, download the necessary update package, update the camera's firmware version and repeat the procedure from the beginning.
- If the appropriate correction data for distortion aberration is not available for the lens attached, [Distortion Aberr. Corr.] will appear grayed out.

3 Select [On].

- The camera will apply the correction for the attached lens to all future recordings.

NOTES


- **About in-camera lens correction data:** The camera contains a register of correction data for compatible lenses that were available at the time the camera went on sale. Correction data for future lenses will be made available as part of the regular updates released for the camera's firmware. For more details, visit your local Canon website.
- **When peripheral illumination/diffraction correction is activated:**
 - Depending on the recording conditions, noise may appear in parts of the image.
 - The level of correction will be lower for lenses that cannot provide distance information.
 - The level of correction will be lower the higher the ISO speed/gain setting used.
 - When using RF-S/EF-S lenses, peripheral illumination fall-off may be more pronounced.
- **Peripheral illumination/chromatic aberration correction cannot be applied in the following cases:**
 - When the appropriate correction data is not available for the lens attached.
 - When using non-Canon lenses. Even if the corresponding menu setting is available (not grayed out), setting it to [Off] is recommended.
- Diffraction correction cannot be applied when the camera cannot obtain the current aperture value of the lens.
- Depending on the shooting settings, peripheral illumination/chromatic aberration/distortion aberration of the shooting lens is corrected and applied during playback.

Attaching the Handle Unit

1 Insert the handle unit's mounting screw into the screw hole of the camera's accessory mount.

2 Tighten the locking knob to firmly secure the handle in place.


- If necessary, use a hex wrench for 0.64 cm, 1/4" screws to tighten the locking knob.



Attaching the Microphone Holder

To the Right Side of the Handle Unit

- 1 Attach the microphone holder to the handle unit.
- 2 Use a commercially available Phillips head (“crosshead”) screwdriver to secure it firmly with the 2 M4 bolts.



Checking the Camera's Inclination

You can display the level of the effective inclination compensation of the camera.

Select **MENU** > [ Monitoring Setup] > [Custom Display 1] > [Level (Numeric)] or [Level (Bar)].

- The following settings are possible if you select [Level (Bar)].
 - [Tilt+Roll]: Displays inclination for both tilt and roll.
 - [Tilt]: Displays the vertical inclination of the optical axis.
 - [Roll]: Displays the amount of rotation around the optical axis.
 - [Off]: Inclination is not displayed.

NOTES


- You can set the level sensitivity and reference angle from **MENU** > [ System Setup] > [Level Sensitivity] or [Level Reference Setting]. The [Level Reference Setting] function uses the angle detected by the camera as reference and displays an angle relative to that reference angle.
- The [Level Reference Setting] function allows you to fine-tune the angle of the level and is enabled only near the following postures.
 - Upright posture, vertical posture (rotation of 90°, -90° in the roll direction)
 - Upside down (rotation of 180° in the roll direction)
 - Lens facing upward (90° in tilt direction)
 - Lens facing downward (-90° in tilt direction)

Attaching an Accessory Compatible with the Multi-Function Shoe

For details on how to attach and use accessories, refer to the instruction manual of the accessory in use.

Remove the multi-function shoe cover (①) and slide the accessory's connecting terminal into the multi-function shoe (②).

- When attaching accessories that communicate through contacts of the multi-function shoe, insert the accessory's mounting foot until it clicks into place, then slide the mounting foot locking lever to secure it.



! IMPORTANT

• Protecting the multi-function shoe:

- After removing accessories from the multi-function shoe, reattach the shoe cap to protect the contacts from dust and water.
 - Blow off any foreign material on the multi-function shoe with a commercially available blower or similar tool.
 - Allow the multi-function shoe to dry before use if it gets wet.
- Using accessories with screws may damage the multi-function shoe.

Preparing Recording Media

The camera records clips, photos and other files on SD cards*. The camera has two card slots, and recording on two cards is possible (📖 39).

Initialize cards (📖 37) when you use them with this camera for the first time.

* The SD card is used also to save/read other files such as custom picture files.

Compatible Recording Media

The following types of memory card can be used with this camera. When recording in RAW format, only SDXC memory cards can be used. For the latest information about recording media tested for use with this camera, visit your local Canon website.

SD cards

SD card type:	 SD cards,  SDHC cards,  SDXC cards
UHS Speed Class*:	U3
Video Speed Class*:	V30, V60, V90

* UHS and Video Speed Class are standards that indicate the minimum guaranteed data transfer rate of SD cards.

Recommended speed class by video configuration

Video configuration			Recommended speed class
Recording mode	Recording format	Resolution	
Slow & fast motion recording	—	—	V90
Other recording modes	RAW ST RAW LT	—	V90
	XF-AVC YCC422 10 bit	4096x2160, 3840x2160	V90
		2048x1080, 1920x1080	V60
	XF-HEVC S YCC422 10 bit	4096x2160, 3840x2160	V60
	XF-HEVC S YCC420 10 bit	4096x2160, 3840x2160	U3, V30
	XF-AVC S YCC422 10 bit	4096x2160, 3840x2160	V90
		2048x1080, 1920x1080	V60
	XF-AVC S YCC420 8 bit	4096x2160, 3840x2160	U3, V30

! IMPORTANT

- After repeatedly recording, deleting and editing clips (if the memory is fragmented), you may notice slower writing speeds to the card and recording may even stop. In such case, save your recordings and initialize the card with the camera. Be sure to initialize cards especially before shooting important scenes.
- If you repeatedly record for short periods of time at a low bit rate, you may not be able to record even if the card has free space.


- **About SDXC cards:** You can use SDXC cards with this camera but these cards are initialized by the camera using the exFAT file system.
 - When using exFAT-formatted cards with other devices (digital recorders, card readers, etc.), make sure that the external device is compatible with exFAT. For more information on compatibility, contact the computer, operating system or card manufacturer.
 - If you use exFAT-formatted cards with a computer OS that is not exFAT-compatible, you may be prompted to format the card. In such case, **cancel the operation to prevent data loss.**

i NOTES

- Proper operation cannot be guaranteed for all cards.
- SDHC cards are formatted using the FAT32 file system so, when recording proxy clips, the video (stream) file in the clip will be split approximately every 4 GB. Playback with the camera will be seamless. SDXC cards use the exFAT file system so the stream file in the clip will not be split.

Inserting and Removing an SD Card

- 1 Wait until the SD CARD access indicator is off or is illuminated in green.
- 2 Open the card compartment cover.
- 3 Insert the card straight, with the label facing the side opposite to the lens, into the SD card slot until it clicks.
 - You can use two cards, one in each card slot.
 - To remove the card, make sure the SD CARD indicator is off and then push the card once to release it. When the card springs out, pull it all the way out.
- 4 Close the card compartment cover.
 - Do not force the cover closed if the card is not correctly inserted.



SD card access indicator

Indicator	Card status
Red	Accessing the card.
Green	Recording/playback is possible and the card is selected for recording/playback.
Off	A card is not inserted or the card slot is not currently selected.

If you set **MENU** > [**F** System Setup] > [Card Access LED] to [Off], the SD card access indicator will not illuminate.

! IMPORTANT

- SD cards have front and back sides that are not interchangeable. Inserting a card facing the wrong direction can cause a malfunction of the camera. Be sure to insert the card as shown in the illustration.

Initializing Cards

Initialize cards when you use them with this camera for the first time. You can also initialize a card to permanently delete all the recordings it contains.

- 1 Select **MENU** > [ Recording/Media Setup] > [Initialize Media].
- 2 Select the desired card.
- 3 Select [OK].
 - The card is initialized and all the data it contains is erased.

IMPORTANT

- SD cards are initialized using the FAT file system, SDHC cards using the FAT32 file system, and SDXC cards using the exFAT file system.
- Initializing a card will permanently erase all data, including photos and protected custom picture files. Lost data cannot be recovered. Make sure you save important recordings in advance.
- Depending on the card, initialization may take up to a few minutes.

NOTES

- If you set an assignable button to [Initialize Media] ( 125), you can press the button to open the [Initialize Media] submenu.

Setting a Card's Volume Label

You can set the volume label for SDXC cards used for recording, in order to make it easier to identify and organize them later.

- 1 Select **MENU** > [ Recording/Media Setup] > [Volume Label] > Desired option.
- 2 Initialize the card ( 37).
- 3 If necessary, set the clip file name's metadata elements ( 42).
- 4 Record clips on the card.
 - The card's volume label changes when the first clip is recorded on a just initialized card.

Options

[Canon]: The card's volume label will be "CANON" regardless of the clip file name settings.

[Canon + Metadata]:

The card's volume label will be "CANON", plus the camera index number and the reel number ( 42).

Switching Between Card Slots


If both slots contain a card, you can switch the card used for recording/playback as necessary.

Press the SLOT SELECT button.

- The access indicator of the selected SD card slot will illuminate in green.

NOTES

- You cannot use the SLOT SELECT button to switch between card slots while recording or playing back.
- You can also perform this function remotely using Browser Remote (📖 190).



Checking the Remaining Recording Time on a Card

The display on the upper left of the screen shows the card icons and the remaining recording time* (in minutes) on each card (📖 51).

On the [📷 Recording/Media Setup] status screen (📖 213), you can check the total space, used space and approximate remaining recording time* of each card. The approximate remaining number of photos (SD card B only) and speed class will be displayed as well.

* Remaining recording times are approximate and calculated based on the current video configuration used.

Recovering Recordings

Some actions, such as suddenly turning off the camera or removing the card while data is being recorded, can cause data errors in the recorded file. You may be able to recover recordings with corrupted data using the following procedure.

- 1 Switch to MEDIA mode and open the index screen with the recordings you wish to recover (📖 141).
- 2 Select the desired recording (with the ? icon).
- 3 Press SET to open the file menu and select [Recover] > [OK].
 - The camera will attempt to recover the corrupted data.

NOTES

- The file may not be recorded if the power is cut or if the SD card is removed immediately after starting recording. In case of recordings with a duration of less than 0.5 seconds, such files may be deleted if file recovery is attempted.
- In some cases, it may not be possible to recover the data. This is more likely when the file system is corrupted or the card is physically damaged.
- Only clips, audio (WAV) and News Metadata files recorded with this camera can be recovered. Photos cannot be recovered.
- In the RAW/XF-HEVC S/XF-AVC S index screen, recovered clips appear with a ► icon instead of the usual thumbnail.

Selecting the Video Recording Method

This camera features various recording modes, as well as video recording methods using two cards. You can also stream the audio/video while recording it on a card (📖 185). Below is an overview. For details, refer to each function's section.

Recording modes

[Recording Mode]	Description	📖
[Normal Recording]	Normal recording. Records a clip in the selected recording format. The most basic video recording method.	47
[Slow & Fast Motion]	Slow & fast motion recording. Records using a frame rate that is different from the playback frame rate (overcrank/undercrank shooting). Audio is not recorded (muted).	114
[S&F Clip / Audio (WAV)]	If [S&F Clip / Audio (WAV)] is selected, audio (WAV) is recorded to the card that is not the video recording destination.	114
[Pre-Recording]	Pre-recording. Records onto a temporary memory (3 seconds) so the clip will contain a few seconds of video and audio recorded before you perform the recording operation.	117
[A Main / B Continuous Rec]	Continuous recording. SD card A is used for normal recording (following REC button record/stop operations), and SD card B is used for continuous recording (uninterrupted recording).	118
[Frame Recording]	Frame recording. A preset number of frames are recorded each time the REC button is pressed, and saved as one clip when frame recording mode ends. Audio is not recorded (muted).	119
[Interval Recording]	Interval recording. Automatically records a pre-defined number of frames at a pre-defined interval. Sound is not recorded in this mode.	119

Second card recording Functions

[2nd Card Rec Functions]	Description	📖
[A Main / B Proxy Rec]	Proxy recording. Simultaneously records a proxy clip (to SD card B, while the main clip is recorded to SD card A) with a smaller file size for offline editing. The proxy clip is recorded with a file name associated with the main clip.	64
[A Main / B Sub Rec]	Sub recording. Simultaneously records a clip to SD card B with a different video configuration from that of the main clip on SD card A.	63
[A Main / B Audio Rec]	The main clip is recorded on card A, and a WAV file* is recorded on card B simultaneously. * Differs from WAV files recorded using slow & fast motion recording.	100
[Relay Recording]	Relay recording. Continues recording on the other card without interruption when the card you are using becomes full. It is available from SD card A to SD card B and vice versa.	—
[Double Slot Recording]	Double slot recording. Records the same clip simultaneously to both cards, which is a convenient way to make a backup copy of your recordings.	—

1 Select the recording mode

- Use direct touch control (📖 56) or in the menu, select **MENU** > [📷 Recording / Media Setup] > [Recording Mode] > Desired option.

2 Select the second card's recording function

- Use direct touch control (📖 56) or in the menu, select **MENU** > [📷 Recording / Media Setup] > [2nd Card Rec Functions] > Desired option.

Available simultaneous recording configurations


		Second card recording function					
		Off	Proxy Recording	Sub Recording	Audio Recording	Relay Recording ²	Double Slot Recording
Recording mode	Normal Recording	●	●	●	●	●	●
	Slow & Fast Motion Recording	●	● ¹	● ¹	—	—	—
	Slow & Fast Motion Recording / Audio (WAV) ⁴	●	—	—	—	—	—
	Pre-recording ²	●	●	●	—	●	●
	Continuous Recording	● ^{2, 3}	—	—	—	—	—
	Frame Recording	●	—	—	—	●	●
	Interval Recording	●	—	—	—	●	●

- Simultaneous recording is available only with normal recording while connected to a network with IP streaming activated.
- ¹ Only when the main recording format is RAW.
- ² Not available when recording in RAW format.
- ³ Not available when recording in XF-AVC format.
- ⁴ Unavailable when the slow & fast motion recording frame rate exceeds 60P.

NOTES

- It is not possible to switch between card slots when proxy recording, sub recording, continuous recording or audio recording is activated.
- If a card becomes full during double slot recording, recording on both cards will stop. On the other hand, if an error occurs with one of the cards, recording will continue on the other card.

Video Recording and Outputs (Diagram)



- ①** Select the main recording format (62, 155)
- ②** Second card recording functions (39)
 - Audio recording, relay recording and double slot recording are also available. Some functions are not available depending on the main recording format and recording mode.
- ③** Custom picture settings (129)
 - You can control various aspects of the image produced using custom picture files.

- ④ For proxy clips: select the proxy recording color conversion (📖 64)
 - Changes the gamma and color space settings.
- ⑤ Apply the view assistance function to the image displayed (📖 158)
 - Changes the gamma and color space settings.

Setting the File Name for Recordings

This section explains how to set the file names for RAW clips, XF-AVC clips, XF-HEVC S clips, XF-AVC S clips and photos.

Clips File Names

The camera allows you to change several settings that determine the clip file name of recorded clips (only in CAMERA mode). For more details on how to enter characters, see *Entering text and numbers* (28).

The basic file name structure is as follows.

A _ 0 0 0 1 C 0 0 1 X yy mm dd _ hh mm ss X X _ C A N O N _ 0 0 1 _ Proxy

1 2 3 4 5 6 7 8 9 10 11

- 1 **Camera index:** Two characters (A to Z, or “_” for the second character) that identify the camera used.
 - 2 **Reel number:** 4 characters (0001 to 9999) that identify the card used. The number is assigned automatically but you can set the initial number. After you insert a new card (just purchased or initialized), the number advances by one when the first recording is made.
 - 3 **Clip number:** 4 characters (C001 to D999). The clip number advances automatically with each clip recorded (switching to D001 after C999), but you can set the initial clip number and select the clip numbering method.
 - 4 **Main codec identifier:** One character that identifies the main codec (X: RAW, A: AVC/H.264, H: HEVC/H.265).
 - 5 **Recording date and time** (set automatically by the camera).
 - 6 **Special recording mode identifier:** Identifies the recording mode (“_” for normal, “C” for the continuous recording clip on SD card B) used by the camera.
 - 7 **Recording time:** Recording hour, minute, and second (set automatically by the camera).
 - 8 **Random component:** 2 characters (numbers 0 to 9 and capital letters A to Z) that change randomly with each clip.
 - 9 **User defined field:** 5 characters (numbers 0 to 9 and capital letters A to Z) for any other identification purposes.
 - 10 **Stream number:** When an SD or SDHC card is used to record clips, a stream number (001 to 999) will be added. The stream number will advance every time the video (stream) file within the clip is split.
 - 11 **Proxy clips only:** The camera will automatically add the suffix “_Proxy” to the file name of proxy clips.
- Apart from component number 11, the file name of the primary clip and the proxy clip will be identical.
 - The file name of double slot recording clips will be the same on both SD cards.
 - Apart from the .WAV extension, the file name of the audio recorded with slow & fast motion clips will be the same as that of the main clip, and will be saved on the "/PRIVATE/AUDIO" folder.

To set the camera index

Select **MENU** > [ Recording/Media Setup] > [Metadata] > [Camera Index] > Desired camera index (28).

To set the clip numbering method

Select **MENU** > [ Recording/Media Setup] > [Metadata] > [Clip Numbering] > [Reset] or [Continuous].

Options

[Reset]: The clip number will restart from 001 every time you insert a new card.

[Continuous]: Clip numbers will start from the initial number set with [Clip Number] (following procedure) and continue across multiple cards.

To set the reel number or initial clip number

- 1 Select **MENU** > [ Recording/Media Setup] > [Metadata] > [Reel Number] or [Clip Number] > [Change].
 - To return to initial settings, select [Reset] instead.
- 2 Enter the reel/clip number using the data entry screen ( 28).

To set the user-defined field


- 1 Select **MENU** > [ Recording/Media Setup] > [Metadata] > [User Defined] > [Change].
 - To return to initial settings, select [Reset] instead.
- 2 Enter the desired text string using the data entry screen ( 28).

Photo Numbering

Photos are automatically assigned consecutive numbers and stored on the SD card in folders. You can select the numbering method to be used.

Photo folder names and file names

Photo number



Select **MENU** > [ Recording/Media Setup] > [Photo Numbering] > Desired option.

Options

- [Reset]: Recording numbers will restart from 100-0001 every time you insert a new card. If a card already contains previous recordings, numbers will continue from the number following that of the last photo on the card.
- [Continuous]: Recording numbers will continue from the number following that of the last photo recorded with the camera. This setting is the most convenient for managing files on a computer. We recommend using the [Continuous] setting.

NOTES

- Each folder can contain up to 500 files. When that number is exceeded, a new folder is created automatically.

Using the Fan

The camera uses a cooling fan to lower the camera's internal temperature. In CAMERA mode, you can change the fan's operation mode and speed. In MEDIA mode, the fan runs at all times but you can select its speed.

Setting the Fan's Operation in CAMERA Mode

1 Select **MENU** > [ System Setup] > [Fan Mode] > Desired option.

If you selected [Always On]

2 Select **MENU** > [ System Setup] > [Fan Speed (Always)] > Desired fan speed.

If you selected [Automatic]

2 Select **MENU** > [ System Setup] > [Fan Speed (STBY)] > Desired fan speed in record standby mode.

3 Select **MENU** > [ System Setup] > [Fan Speed (REC)] > Desired fan speed while recording.

- The [Maximum] option offers the maximum cooling effect but is available only for [Fan Speed (STBY)], as it is noisier.

Options for [Fan Mode]

[Automatic]: The fan runs while the camera is not recording and is automatically turned off while the camera is recording. However, if the internal temperature of the camera is too high ( appears in yellow), the fan will be activated automatically (in that case, **FAN** will appear next to the  icon). When the camera's temperature has decreased sufficiently, the fan will be turned off. Use this setting when you do not want the camera to pick up the fan's operating sound.

[Always On]: The fan runs at all times.

Setting the Fan Speed in MEDIA Mode

1 Select **MENU** > [ System Setup] > [Fan Speed].

2 Select the desired option.



IMPORTANT

- While the fan is running, the exhaust vent will emit warm air.
- Be careful not to obstruct in any way the fan's air vents ( 11, 12, 15).



NOTES

- Depending on the ambient temperature and other shooting conditions, the fan may not turn off even if you set its operating mode to [Automatic].

Adjusting the Black Balance

In CAMERA mode, you can have the camera adjust the black balance automatically when ambient temperature changes considerably or if there is a noticeable change in a true black video signal.

1 Attach the body cap to the lens mount and set the camera to CAMERA mode.

- If a lens was attached, turn off the camera and remove the lens. Place the body cap back on the lens mount and turn on the camera.

2 Select **MENU** > [Camera Setup] > [ABB] > [OK].

- The automatic black balance procedure will start. It may take about 1 minute depending on the frame rate.
- If the sensor is not completely shielded from light, [Error] will appear on the screen. Repeat the procedure from the beginning.

NOTES

Adjusting the black balance is necessary in the following cases:


- When using the camera for the very first time or after a long period of not using it.
- After sudden or extreme changes in ambient temperature.
- After changing the sensor mode.
- After activating or deactivating slow & fast motion recording (including switching to another special recording mode).
- After changing the shooting frame rate, when slow & fast motion recording is activated.
- After resetting the camera's settings.
- During the adjustment of the black balance, you may notice some irregular displays appear on the screen. This is not a malfunction.

Recording Video and Photos

This section explains the basics of recording clips* and photos. For details on recording audio, refer to *Recording Audio* (100).

* "Clip" refers to a single movie unit recorded with a single recording operation. You can also include metadata with the clip.

Recording



* Can be assigned to function as a REC button (125).

1 Set the **POWER** switch to CAMERA.

- The camera turns on in CAMERA mode and enters record standby mode ([STBY]). The power indicator (tally lamp) illuminates in green.
- The access indicators of card slots with a card inserted will illuminate momentarily in red. Then, the access indicators of cards selected for recording will change to green.

2 Press the REC button to begin recording.

- Recording starts. The tally lamp changes from green (power indicator) to red and the recording indicator at the top of the screen changes from [STBY] to [●REC].
- The access indicator of cards used for recording will illuminate in red.
- You can also perform this function remotely using Browser Remote on a connected network device (187) or an XC protocol-compatible device.

3 Press the REC button to stop recording.

- The clip is recorded and the camera enters record standby mode. The tally lamp changes from red to green (power indicator).
- The access indicator of cards selected for recording will change back to green.

! IMPORTANT

- Be sure to save your recordings regularly, especially after making important recordings. Canon shall not be liable for any loss or corruption of data.

i NOTES

- If you record using metadata or News Metadata settings, those settings will be recorded or added to the clip. For more details, refer to *Using Metadata* (111) and *Using News Metadata* (112).
- If the camera switches to the other card while recording video due to the relay recording function (39), the two parts (before/after the switch) will be recorded as separate clips.
- A single clip can be recorded continuously for up to 6 hours. At that point, a new clip will be created automatically and recording will continue on a separate clip (excluding RAW recording, slow & fast motion recording).
- You can use the review function (55) to play back part or all of the last clip recorded without having to switch to MEDIA mode.
- When recording clips on SDHC cards, the video (stream) file in the clip will be split approximately every 4 GB. Playback with the camera will be seamless.
- You can assign the [REC] function to assignable button Camera 4 or Camera 11 and use it to start/stop recording.
- You can set **MENU** > [System Setup] > [Onscreen REC/STBY Button] to [On] to use the onscreen [●REC]/[STBY] touch buttons to stop and start recording respectively.
- When **MENU** > [System Setup] > [Tally Lamp Settings] is set to an option other than [REC], the tally lamp illuminates when PGM tally information is input.

To take photos

While the camera is in record standby mode, you can record photos on SD card B.

- 1 Set an assignable button to [Photo] (125).
- 2 When the camera is in record standby mode, press the assignable button.
 - ▶ **B** appears on the screen and the photo is recorded on SD card B.
 - The SD CARD access indicator will illuminate in red.
 - The size of the recorded photos depends on the video configuration currently in use. For details, refer to *Specifications* (246).


i NOTES

- **Photos cannot be recorded in the following cases**
 - While recording a clip, or when slow & fast motion recording is activated.
 - When pre-recording is activated.
 - While Browser Remote is activated.
 - While color bars are displayed.

Onscreen Displays


Refer to this section for an explanation of the various screen displays that appear in CAMERA mode. You can use the custom display function (204) to turn off individual onscreen displays if they are not required. The menu item that controls each display is given in the following tables (1: indicates a menu item under [Custom Display 1] and 2: indicates a menu item under [Custom Display 2]).

The position of some icons and onscreen displays may change depending on the display level settings, which can be set to level 1, level 2 or level 3. The following screenshot and tables describe the onscreen displays at display level 1 with the [All Displays] setting (53).



AF frames

You can turn AF frames on/off with the **MENU** > [Monitoring Setup] > [Custom Display 1] > [Focus Mode] setting.




Left side of the screen

Icon/Display	Description	Custom Display
, , , , , , frameio , 00 , 00 , Full	Network connection status, functions and upload status (183).	2: [Network Functions]
	Object distance (bar). Only when an RF lens/RF Cinema lens is attached to the camera.	1: [Object Distance (Bar)]
0000 mm	Approximate focal length of the lens.	1: [Focal Length]
000.0 m	Object distance (numeric). Only when an RF lens or certain EF Cinema lenses are attached.	1: [Object Distance (Numeric)]
,	Focus mode (80).	1: [Focus Mode]
	Subject to be detected (86).	
	Detection priority, detection only.	
, , ,	Digital tele-converter (90)	1: [Tele-converter]
RF-S/EF-S , ±0.0 (Lens information)	Lens information. Depending on the lens, the information displayed may differ.	1: [Lens]
	Image stabilization enabled/disabled (88).	1: [Digital IS]
	Lens optical IS (88)	1: [Lens]
(in red) (in yellow)	Lens error warning (226).	
00	Custom picture file selected (129).	1: [Custom Picture]
, , , , , , , , ,	[Gamma/Color Space] setting in the custom picture file (134).	
	Look Files (131).	
	Light metering mode (76).	1: [Light Metering]
	View assistance (158).	1: [View Assist]
	Status of the accessory attached to the multi-function shoe (34). Appears in red in case of a communication error or if the attached accessory is turned off.	2: [Multi-Function Shoe]
	GPS signal: continuously on - satellite signal acquired; flashing - satellite signal not acquired. Displayed only when a GP-E2 GPS Receiver is connected to the camera.	2: [GPS]
	Fan operation: in white – normal (44); in red – fan warning (226).	2: [Temperature/Fan]
(in green) (in yellow) (in red)	Temperature warning (44). When the camera internal temperature rises above a certain level, will appear in yellow. If the temperature rises further, will appear in red.	
	User memo (111).	

Top of the screen

Icon/Display	Description	Custom Display
Recording media status, estimated remaining recording time and recording format		2: [Remaining Rec Time]
000 min	A / B : SD card The card's status is indicated by the icon's color: in green – can record; in yellow – card almost full (5 minutes or less); in red – card almost full (less than 1 minute); in white – reading the card. • The card selected for recording is indicated with a ► mark.	
END	Card is full.	
	No card or cannot record on the card.	
RAW, XF-AVC, XF-HEVC, XF-AVC S, WAV	Video format (62) and audio format (114).	
Recording operation		2: [Recording Mode]
STBY, ● REC	Normal recording: record standby, recording.	
S&F STBY, S&F ● REC	Slow & fast motion recording (114): record standby, recording.	
PRE STBY, PRE ● REC	Pre-recording (117): record standby, recording.	
CONT, ● CONT	Continuous recording (118)	
FRM STBY, FRM ● REC, FRM ● STBY	Frame recording (119): record standby, recording.	
INT STBY, INT ● REC, INT ● WAIT	Interval recording (119): record standby, recording.	
0s / 00m00s	Interval counter (119).	2: [Interval Counter]
REC ➡, STBY ➡ EXT REC ➡, EXT STBY ➡	Recording command (154). "EXT" is displayed when there is no recording media.	2: [Rec Command(EXT REC)]
	Double slot recording (39).	2: [Recording Mode]
00.00P, 00.00i	Frame rate (62). When slow & fast motion recording is activated, the shooting frame rate is also displayed (000/00.00P).	2: [Frame Rate]
Tilt 000.0° Roll 000.0°	Level (numeric) (33)	1: [Level (Numeric)]
	Key lock (15).	1: [Key Lock]
00:00:00.00 / 00:00:00:00 R, P, F, E	Time code (95). Time code status (96).	2: [Time Code]
Power supply level indicator		2: [Remaining Battery]
→ → → → (in red) 000 min	Remaining battery charge of a BP-A30N or BP-A60N Battery Pack and estimated remaining usage time (in minutes). • When is displayed, replace the battery pack with a fully charged one. • Depending on the conditions of use, the actual battery charge level may not be indicated accurately or may not match the levels shown on the [🔧 System Setup] status screen or the indicators on the battery pack.	
DC IN 00.0V	Power supply voltage when using an AC adapter. • When the voltage falls below the selected low-power warning level (211), the voltage will be displayed in red.	

Right side of the screen


Icon/Display	Description	Custom Display
60(24)fps, 60(30)fps	Video output (125).	2: [Output Terminals Status]
[Full], [Super35]	Sensor mode (62).	2: [Sensor Mode]
0000x0000	Resolution (62).	2: [Resolution/Color Sampling]
YCC000 00 bit	Color sampling, bit depth (62).	
▶ B (in green)	Photos can be recorded on the SD card (48).	2: [Photo]
▶ RS (in red)	No SD card or cannot record photos on the SD card.	
[DISP] (in yellow)	Output onscreen displays (157).	2: [OSD Output]
[MAGN] (in yellow) [SET] Change Magn. Ratio	Magnification (82).	1: [Magnification]
[PEAK1], [PEAK2] (in yellow)	Peaking (82).	1: [Peaking]
	Audio level meter (103).	2: [Audio Level Indicator]
[LIM]	Audio limiter (104).	
 00,  OFF	Headphone volume (146).	—
Date/time		2: [Date/Time]
CH0/CH0, CH0+CH0/CH0+CH0	Audio output channels (160).	2: [Monitor Channels]
1/0000.00, 000.00°, 000.00Hz	Shutter speed (66).	1: [Shutter]

Bottom and center of the screen

Icon/Display	Description	Custom Display
 Acc1,  Acc2,  Ttl, 	Wireless microphone	2: [Wireless Mic]
 (horizontal/vertical)	Level (bar) (33).	1: [Level (bar)]
Base 0000	Base ISO (68).	1: [Base ISO]
[SET] Start Tracking [CANCEL] End, [SET] Select Again [CANCEL] End, [CANCEL] Stop Tracking, The lens does not work.	Tracking guide, warning.	
	Direct touch control (56)	—
A_0001C001 to ZZ9999D999	Clip identification. Includes the camera index, reel number and clip number components of the clip file name (42).	2: [Reel/Clip Number]
00 00 00 00	User bit (96).	2: [User Bit]
-  +	Exposure bar (76).	1: [Exposure Bar]
AE ±0.00	AE shift (75).	1: [AE Shift]
 A /  B,  ,  K,  [AWB] 00000K ±00	White balance (77).	1: [White Balance]
ND 00 stops	ND filter (72).	1: [ND Filter]
[A], F00.0 / T00.0, closed	Aperture value (73).	1: [Iris]
[A] ISO 000000, 00.0dB	ISO speed/Gain value (68).	1: [ISO/Gain]

Selecting the Onscreen Display Level

You can press the DISP button to control the amount of information shown over the image. Repeatedly pressing the DISP button will change the display level: Display level 1 → Display level 2 → Display level 3 → Display level 1. In CAMERA mode, you can change the information displayed at each display level in the menu (📖 204).



Example of the
[Main Recording Displays] option

CAMERA mode

Display level ¹	Options	Description
[DISP Level 1]	[All Displays]	All onscreen displays at a larger size.
	[All Displays (Periph. Border)]	All onscreen displays at a smaller size, more appropriate for use with the peripheral border.
[DISP Level 2] ²	[Main Recording Displays]	Only the onscreen displays most relevant for shooting.
	[Only FUNC/MENU]	Only markers, focus frames/tracking frame, and video scopes are displayed. When the FUNC button, MENU button or an assignable button is pressed, the necessary information will be displayed.
[DISP Level 3] ²	[Only REC/STBY]	No onscreen displays except for the recording operation (REC/STBY).
	[No Displays]	No onscreen displays at all.

MEDIA mode

Display level ¹	During clip/photo playback	Index screen/During audio playback
[DISP Level 1]	All onscreen displays.	All onscreen displays.
[DISP Level 2]	No onscreen displays.	
[DISP Level 3]	—	

¹ **MENU** > [📷 Monitoring Setup] > [DISP Level 1], [DISP Level 2] or [DISP Level 3].

² Smaller onscreen displays (same size as when set to [All Displays (Periph. Border)]).

NOTES

- You can change the transparency level of onscreen displays (📖 157).

Peripheral Border Display

You can apply the peripheral border display to all display levels. With the peripheral border display, the camera's image is reduced slightly so the onscreen displays are shown mostly around it and not on top of it, partially hiding it. The peripheral border is linked with the display level. You can select the levels that use the peripheral border with the **MENU** > [⏏ Monitoring Setup] > [Apply Peripheral Border] setting.



Full-screen display



Peripheral border display

NOTES

- When using a display level with the peripheral border display, if you set **MENU** > [⏏ Monitoring Setup] > one of the [OSD Output:] settings to [Off] or [Off (Clean)], the video output from each video terminal will be displayed in full screen.
- When [SDI Output Signal] is set to [4096x2160P/3840x2160P], the peripheral border display is not applied to video output from the SDI OUT terminal.

Displaying the Tally OSD

While recording (REC), the tally OSD (red frame or bar) can be displayed on the screen. Displaying the tally OSD allows you to easily check whether recording is in progress even when viewing the screen from a distance.

- 1 Select **MENU** > [⏏ Monitoring Setup] > one of the [Tally OSD:] settings > [On].
 - Confirm and/or change the screen for tally OSD display and the output destination.
- 2 Select **MENU** > [⏏ Monitoring Setup] > [Tally OSD Settings] > Desired option.

Tally OSD Settings List

[Tally OSD Settings]	Tally Input State	Recording Status (REC)	Tally OSD Lamp Color
[Tally In (PGM/PVW)]	PGM	—	Red
	PVW		Green
	PGM + PVW		Amber
[REC]	—	Recording	Red
	—		
[REC/Tally In (PGM/PVW)]	PGM	Record Standby Mode	Red
	PVW		Green
	PGM + PVW		Amber

- 3 Select **MENU** > [⏏ Monitoring Setup] > [Tally OSD Position] > Desired option.



Frame



Top



Bottom

NOTES

- Recorded video/still images are not affected.


Onscreen Displays in Portrait Mode

When shooting in portrait mode, you can change the orientation of the onscreen displays.

Select **MENU** >  Monitoring Setup > Desired [OSD Orientation:] setting > [ 90 Degrees Left] or [ 90 Degrees Right].

NOTES

- The menu and status screens cannot be rotated.
- Direct touch control (other than recording settings) and the peripheral border display cannot be used when the CAMERA mode screen is rotated.



Reviewing a Recording

If you set an assignable button to [Review Recording] in advance, you can review the last clip (primary clip) recorded on the recording media currently in use even with the camera set to CAMERA mode.

- Set an assignable button to [Review Recording] ( 125).
- Select **MENU** >  System Setup > [Review Recording] > Desired option.
- After you finish recording a clip, press the assignable button.
 - The last clip that was recorded is played back for the selected duration. [▶ REVIEW] appears on the screen.
 - There will be no sound from the built-in speaker but the audio will be output from the  (headphone), HDMI OUT or SDI OUT terminal.
 - You can use the joystick to jump back/forward within the clip. You can also touch or slide the onscreen progress bar to move to a different position in the video ( 145).
 - Press CANCEL or flick down on the screen to stop reviewing the clip.
 - After the clip finishes playing back, or if you stop reviewing the clip, the camera returns to record standby mode.

Options

- [Entire Clip]: Allows you to review the entire clip.
- [Last 4 sec]: Allows you to review just the last 4 seconds of the clip.

NOTES

- If the camera switched cards during a recording, the camera will play back the clip on the card most recently recorded on.
- You cannot review clips when continuous recording is activated.

Adjusting Camera and Recording Settings

Using direct touch control, you can perform a variety of settings (camera, recording, assistance functions, etc.) in CAMERA mode. White balance and exposure related settings can also be modified with the direct setting mode, using the FUNC button.


Performing Basic Settings with Direct Touch Control

With direct touch control you can change commonly used settings such as camera and recording settings and assistance functions. For details about each function, refer to the respective section on the manual.

Available Direct Touch Control Settings

Touch button	Available settings
White balance	White balance mode (custom, preset, color temperature, automatic (AWB)), color correction value.
ND filter	Off, 5 different density settings.
Aperture	Adjustment of the F value/T value.
ISO/Gain	Adjustment of ISO or gain value/adjustment value preset.
Shutter speed	Adjustment of the value in the current shutter speed mode.
 (assistance functions)	Focus guide (on/off), peaking (type), WFM, zebra (type), false color (on/off), markers (on/off), view assistance (on/off).
 (recording settings)	Sensor mode, recording mode, second card recording functions, continuous recording ^{1, 2} , slow & fast shooting frame rate, frame recording frame rate, interval recording frame rate, interval recording time interval, main recording format, CP file selection, main resolution, frame rate, bit rate, B recording format, proxy recording color conversion, B resolution, B bit rate, B frame rate, LCD luminance.

¹ Only when the main recording format is XF-HEVC S / XF-AVC S.
² Only when the [Continuous Recording] setting (118) is changed from [STBY] to [REC].



Turn on/off the Direct Touch Control Interface

Even when the direct touch control interface is displayed, you can still use other functions such as recording, menu settings, direct setting mode or status screens.

- 1 Touch  to open the direct touch control interface.
- 2 Touch  to close the direct touch control interface.

Changing Camera Settings

- 1 Touch the setting you want to adjust, then select the desired value/setting.
 - Once the settings menu is displayed, touch to select the desired value/setting as needed.
 - When the slider appears, drag the slider left/right or touch the ◀/▶ buttons to adjust the desired value.
 - You can also use the SELECT dial or the control dial.
- 2 Touch ↶.



Drag the slider to select the desired value


Using Assistance Functions

- 1 Touch  (assistance functions) and then turn assistance functions on/off, or select the desired assistance function.
- 2 Touch ↶.



Changing Recording Settings


- 1 Touch  (Recording Settings)
 - The recording settings menu will be displayed. There are three pages that can be switched by swiping left and right.
- 2 Select the desired menu setting and then select the desired option.
- 3 Touch ✕.



Direct Setting Mode (FUNC Button)

You can adjust main camera functions—white balance, aperture, ISO speed/gain and shutter speed—using the FUNC button (direct setting mode). This section will explain the basic operation of the direct setting mode. For details about each function, refer to the respective section on the manual.

- 1 Press the FUNC button.
 - The onscreen display of the selected function will be highlighted in orange.
 - Press the FUNC button repeatedly or push the joystick left/right to select a different function (the rear control dial can also be used).
- 2 Push the joystick up/down or turn the SELECT dial to select the desired value or white balance mode.
 - You can also use the front control dial.
- 3 Press SET.
 - The selected value/mode will be set and direct setting mode will end.
 - The onscreen display of the selected function will return to normal.



 NOTES

- The camera will automatically end the direct setting mode in the following cases.
 - If no operation was performed for more than 6 seconds.
 - If the FUNC button is pressed while selecting the shutter speed.
 - If the menu or a status screen was opened.
- If you set an assignable button to [White Balance], [Iris], [ISO/Gain] or [Shutter], you can press the button to enter direct setting mode with the respective function highlighted.

Video Recording Configuration: Video Format, Sensor Mode, System Frequency, Resolution and Frame Rate

When recording media, you can set the video configuration used for primary clips with the following procedures. Select the sensor mode, main recording format (video format, color sampling, bit depth), primary resolution, frame rate and bit rate settings that best match your creative needs. The camera uses a variable bit rate (VBR). Intra-frame options compress the image after analyzing each frame separately and are more appropriate for editing. Long GOP options compress the image after analyzing also changes across a group of pictures and offer better compression (smaller data size). Available options for some settings may change depending on previous selections for other settings. See the following tables for a summary. For details about sub recording clips and audio, refer to *Sub Recording Clips* (63) and *Recording Audio* (100) respectively.

RAW

Sensor mode	Main recording format	Main resolution	Bit depth	System frequency/Frame rate/Bit rate					
				59.94 Hz			50.00 Hz		24.00 Hz
				59.94P	29.97P	23.98P	50.00P	25.00P	24.00P
Full frame	RAW LT	6000x3164	12 bit	—	● 639 Mbps	● 552 Mbps	—	● 576 Mbps	● 553 Mbps
Super 35mm (Cropped)	RAW ST	4368x2304		—	● 563 Mbps	● 451 Mbps	—	● 470 Mbps	● 451 Mbps
	RAW LT			● 678 Mbps	● 366 Mbps	● 293 Mbps	● 611 Mbps	● 306 Mbps	● 293 Mbps

XF-AVC

Main recording format	Main resolution	Bit rate	System frequency/Frame rate							
			59.94 Hz				50.00 Hz			24.00 Hz
			59.94P	59.94i	29.97P	23.98P	50.00P	50.00i	25.00P	24.00P
XF-AVC YCC422 10 bit	4096x2160 3840x2160	600 Mbps Intra-frame	●	—	●	—	—	—	—	—
		500 Mbps Intra-frame	—	—	—	—	●	—	●	—
		480 Mbps Intra-frame	—	—	—	●	—	—	—	●
		450 Mbps Intra-frame	—	—	●	—	—	—	—	—
		375 Mbps Intra-frame	—	—	—	—	—	—	●	—
		360 Mbps Intra-frame	—	—	—	●	—	—	—	●
		300 Mbps Intra-frame	—	—	●	—	—	—	—	—
		250 Mbps Intra-frame	—	—	—	—	—	—	●	—
		240 Mbps Intra-frame	—	—	—	●	—	—	—	●
		250 Mbps Long GOP	●	—	—	—	●	—	—	—
		150 Mbps Long GOP	—	—	●	●	—	—	●	●
	2048x1080	300 Mbps Intra-frame	●	—	—	—	—	—	—	—
		250 Mbps Intra-frame	—	—	—	—	●	—	—	—
		150 Mbps Intra-frame	—	—	●	—	—	—	—	—
		125 Mbps Intra-frame	—	—	—	—	—	—	●	—
		120 Mbps Intra-frame	—	—	—	●	—	—	—	●
		50 Mbps Long GOP	●	—	●	●	●	—	●	●
	1920x1080	300 Mbps Intra-frame	●	—	—	—	—	—	—	—
		250 Mbps Intra-frame	—	—	—	—	●	—	—	—
		150 Mbps Intra-frame	—	●	●	—	—	—	—	—
		125 Mbps Intra-frame	—	—	—	—	—	●	●	—
		120 Mbps Intra-frame	—	—	—	●	—	—	—	●
		50 Mbps Long GOP	●	●	●	●	●	●	●	●
		25 Mbps Long GOP	—	●	—	—	—	●	—	—

XF-HEVC S

Main recording format	Main resolution	Bit rate	System frequency/Frame rate					
			59.94 Hz			50.00 Hz		24.00 Hz
			59.94P	29.97P	23.98P	50.00P	25.00P	24.00P
XF-HEVC S YCC422 10 bit	4096x2160 3840x2160	225 Mbps Long GOP	●	—	—	●	—	—
		135 Mbps Long GOP	—	●	●	—	●	●
	2048x1080 1920x1080	50 Mbps Long GOP	●	●	●	●	●	●
XF-HEVC S YCC420 10 bit	4096x2160 3840x2160	150 Mbps Long GOP	●	—	—	●	—	—
		100 Mbps Long GOP	—	●	●	—	●	●
	2048x1080 1920x1080	35 Mbps Long GOP	●	●	●	●	●	●

XF-AVC S

Main recording format	Main resolution	Bit rate	System frequency/Frame rate					
			59.94 Hz			50.00 Hz		24.00 Hz
			59.94P	29.97P	23.98P	50.00P	25.00P	24.00P
XF-AVC S YCC422 10 bit	4096x2160 3840x2160	600 Mbps Intra-frame	●	●	—	—	—	—
		500 Mbps Intra-frame	—	—	—	●	●	—
		480 Mbps Intra-frame	—	—	●	—	—	●
		450 Mbps Intra-frame	—	●	—	—	—	—
		375 Mbps Intra-frame	—	—	—	—	●	—
		360 Mbps Intra-frame	—	—	●	—	—	●
		300 Mbps Intra-frame	—	●	—	—	—	—
		250 Mbps Intra-frame	—	—	—	—	●	—
		240 Mbps Intra-frame	—	—	●	—	—	●
		250 Mbps Long GOP	●	—	—	●	—	—
		150 Mbps Long GOP	—	●	●	—	●	●
	2048x1080 1920x1080	300 Mbps Intra-frame	●	—	—	—	—	—
		250 Mbps Intra-frame	—	—	—	●	—	—
		150 Mbps Intra-frame	—	●	—	—	—	—
		125 Mbps Intra-frame	—	—	—	—	●	—
		120 Mbps Intra-frame	—	—	●	—	—	●
		50 Mbps Long GOP	●	●	●	●	●	●
XF-AVC S YCC420 8 bit	4096x2160 3840x2160	150 Mbps Long GOP	●	—	—	●	—	—
		100 Mbps Long GOP	—	●	●	—	●	●
	2048x1080 1920x1080	35 Mbps Long GOP	●	●	●	●	●	●

 NOTES

- For details on the signal output from each terminal, refer to *Video Output Configuration* (151).

Selecting the System Frequency

You can change the system frequency also in MEDIA mode if you want to play back clips from a card recorded with a different system frequency setting.

1 Select **MENU** > [ Recording/Media Setup] > [System Frequency].

2 Select the desired option.

- The camera will reset and restart in the selected mode.

Selecting the Sensor Mode

You can change the area of the imaging circle covered by the CMOS sensor to produce the recorded image.

1 Select **MENU** > [ Recording/Media Setup] > [Sensor Mode].

- You can also adjust this setting using direct touch control ( 56).

2 Select the desired option.

Selecting the Main Recording Format

Select the combination of video format, color sampling and bit depth for primary clips.

1 Select **MENU** > [ Recording/Media Setup] > [Main Rec Format].

- You can also adjust this setting using direct touch control ( 56).

2 Select the desired option.

Selecting the Resolution of Primary Clips

1 Select **MENU** > [ Recording/Media Setup] > [Main Resolution].

- You can also adjust this setting using direct touch control ( 56).

2 Select the desired option.

Selecting the Frame Rate

Select the frame rate for the primary clips. This procedure is not necessary when the system frequency is set to 24.00 Hz.

1 Select **MENU** > [ Recording/Media Setup] > [Frame Rate].

- You can also adjust this setting using direct touch control ( 56).

2 Select the desired option.

Selecting the Bit Rate for Primary Clips

Select the bit rate when the primary clip has the following recording format, resolution and frame rates.

Main recording format	Main resolution	Frame rate	Bit rate
XF-AVC YCC422 10bit XF-AVC S YCC422 10bit	4096x2160 Intra-frame 3840x2160 Intra-frame	29.97P	600 Mbps, 450 Mbps, 300 Mbps
		25.00P	500 Mbps, 375 Mbps, 250 Mbps
		24.00P	480 Mbps, 360 Mbps, 240 Mbps
		23.98P	480 Mbps, 360 Mbps, 240 Mbps
XF-AVC YCC422 10bit	1920x1080 Long GOP	59.94i, 50.00i	50 Mbps, 25 Mbps

1 Select **MENU** > [ Recording/Media Setup] > [Bit Rate].

- Operation by direct touch control is also possible ( 56).

2 Select the desired option.

Sub Recording Clips

While recording a primary clip on SD card A, you can simultaneously record the same scene on SD card B. Recording formats that can be used in conjunction are shown below. Refer to *Recording / Output Signal and Detailed Settings* (214) for more details. For more details on audio, see *Recording Audio* (100). When HDMI RAW is set to [On], the primary clip (RAW) will be output from the HDMI OUT terminal and the sub recording clip will be recorded to the card in slot B (155). You can also use direct touch control to perform this function (56).

Primary clip	Sub recording clip				
Main recording format	Recording format / color sampling				
	XF-AVC	XF-HEVC S		XF-AVC S	
	YCC422 10 bit	YCC422 10 bit	YCC420 10 bit	YCC422 10 bit	YCC420 8 bit
RAW ST RAW LT HDMI RAW	●	●	●	●	●
XF-AVC YCC422 10 bit	●	–	–	●	●
XF-HEVC S YCC422 10 bit	–	●	●	–	–
XF-HEVC S YCC420 10 bit	–	–	●	–	–
XF-AVC S YCC422 10 bit	–	–	–	●	●
XF-AVC S YCC420 8 bit	–	–	–	–	●

- 1 Insert an SD card into each card slot (slot A for the main clip, slot B for the sub recording clip).
- 2 Select **MENU** > [Recording/Media Setup] > [2nd Card Rec Functions] > [**A** Main / **B** Sub Rec].
- 3 Select **MENU** > [Recording/Media Setup] > [**B** Rec Format] > Desired option.
- 4 Select **MENU** > [Recording/Media Setup] > [**B** Resolution] > Desired option.
- 5 Select **MENU** > [Recording/Media Setup] > [**B** Rec Frame Rate] > Desired option.
- 6 Select **MENU** > [Recording/Media Setup] > [**B** Bit Rate] > Desired option.
 - Steps 3 to 6 can only be selected with some main recording formats.
- 7 Press the REC button to start recording.
 - Proxy clips will be recorded simultaneously with the primary clips.

NOTES

- If there is no card inserted in the slot used for the primary clip, only the sub recording clip will be recorded.

Proxy Clips

While recording a primary clip on SD card A, you can simultaneously record the same scene as a proxy clip on SD card B. Because proxy clips have smaller files, they are suitable for offline editing. When HDMI RAW is set to [On], the main clip (RAW) will be output from the HDMI OUT terminal, and the proxy clip will be recorded to the card in slot B (📖 155).

You can also use direct touch control to perform this function (📖 56).

Available configurations

Primary clip			Proxy clips								
			Recording format / Resolution / Scanning method / Color sampling / Bit rate								
			XF-AVC			XF-HEVC S			XF-AVC S		
			2048x1080	1920x1080		2048x1080	1920x1080	1280x720	2048x1080	1920x1080	1280x720
			P	P	i	P			P		
Recording format	Resolution	Scanning method	YCC420 8bit			YCC420 10bit		YCC420 8bit	YCC420 8bit		
			35 Mbps			16 Mbps, 9 Mbps		6 Mbps	16 Mbps, 9 Mbps, 6 Mbps		
RAW HDMI RAW	—	—	●	—	—	●	—	—	●	—	—
XF-AVC	4096x2160 2048x1080	P	●	—	—	—	—	—	●	—	—
	3840x2160 1920x1080	P	—	●	—	—	—	—	—	●	●
	1920x1080	i	—	● ¹	● ¹	—	—	—	—	●	●
XF-HEVC S	4096x2160 2048x1080	P	—	—	—	●	—	—	—	—	—
	3840x2160 1920x1080	P	—	—	—	—	●	●	—	—	—
XF-AVC S	4096x2160 2048x1080	P	—	—	—	—	—	—	●	—	—
	3840x2160 1920x1080	P	—	—	—	—	—	—	—	●	●

¹ Cannot be selected if the proxy clip has a larger bit rate than that of the main clip.

- 1 Insert an SD card into each card slot (slot A for the main clip, slot B for the proxy clip).
- 2 Select the main recording format (📖 62).
- 3 Select **MENU** > [🔧 Recording/Media Setup] > [2nd Card Rec Functions] > [**A** Main / **B** Proxy Rec].
- 4 Select **MENU** > [🔧 Recording/Media Setup] > [**B** Rec Format] > Desired option.
- 5 Select **MENU** > [🔧 Recording/Media Setup] > [**B** Resolution] > Desired option.
- 6 Select **MENU** > [🔧 Recording/Media Setup] > [**B** Frame rate] > Desired option.
- 7 Select **MENU** > [🔧 Recording/Media Setup] > [**B** Bit rate] > Desired option.
 - Steps 4 to 7 can only be selected for some primary clip recording formats.

8 Select **MENU** > [Recording/Media Setup] > [Proxy Rec Color Conversion] > Desired option.

- If you select [Conform to Custom Picture], the gamma curve and color space are determined to conform to the gamma curve of Custom Picture. Furthermore, if you select [BT.709 (Canon 709)] or [BT.709 (CMT 709)], they are converted as follows.

Gamma curve of Custom Picture	Gamma curve after conversion		Color space after conversion	
	BT.709 (Canon 709)	BT.709 (CMT 709)	BT.709 (Canon 709)	BT.709 (CMT 709)
BT.709 Standard	BT.709 Standard	BT.709 Standard	BT.709	
BT.709 Wide DR	BT.709 Wide DR	BT.709 Wide DR		
Canon 709	Canon 709	Canon 709		
The gamma curve and color space after applying the Look File and after conversion is [SDR BT.709] or [SDR BT.2020].	SDR	SDR		
Other	Canon 709	CMT 709		

- If you select [BT.709 (Canon 709)] or [BT.709 (CMT 709)], proxy clips are recorded after converting the gamma curve and color space. The value set for **MENU** > [ Monitoring Setup] > [Gain for HDR → SDR Conv.] ( 159) is applied to the proxy clips as well.

9 Press the REC button to start recording.

- Proxy clips will be recorded simultaneously with the primary clips.

NOTES

- If the recording of the primary clip stops during simultaneous recording, recording of the proxy clip will stop as well.
- If there is no card inserted in the slot used for the primary clip, only the proxy clip will be recorded.

Shutter Speed

You can set the shutter speed according to the shooting conditions. For example, you may want to set slower shutter speeds in darker environments. The camera offers the following modes.

You can also perform this function remotely using Browser Remote on a connected network device (📖 187).

[Speed]: Allows you to set the shutter speed (in fractions of a second). You can select the increment to use when adjusting the shutter speed between 1/3-stop and 1/4-stop increments.

[Angle]: You can set the shutter angle to determine the shutter speed.

[Clear Scan]: Set the frequency in order to record CRT computer monitors without displaying black bands or flicker on the screen.

[Slow]: You can set slower shutter speeds to obtain brighter recordings in places with insufficient lighting.

[Off]: The camera uses a standard shutter speed based on the frame rate.

Available shutter speeds
The individual setting options that can be selected will change depending on the frame rate used.

Shutter speed mode		System frequency/Frame rate					
		59.94 Hz			24.00 Hz	50.00 Hz	
		59.94P / 59.94i	29.97P	23.98P	24.00P	50.00P / 50.00i	25.00P
[Speed] ¹	1/3-stop increments	1/1 to 1/2000 (34 setting options in total)					
	1/4-stop increments	1/1 to 1/2000 (47 setting options in total)				1/1 to 1/2000 (45 setting options in total)	
[Angle] ¹		360.00°, 240.00°, 180.00°, 120.00°, 90.00°, 60.00°, 45.00°, 30.00°, 22.50°, 15.00°, 11.25° Also angle values equivalent to the following shutter speeds: 1/120, 1/100, 1/60, 1/50, 1/40, 3/100, 1/30, 1/25.					
[Clear Scan] ¹		23.97 Hz to 1971 Hz Within the above range, the frequency can be set with the minimum available resolution depending on the sensor mode and frame rate.					
[Slow] ²		1/4, 1/8, 1/15, 1/30	1/4, 1/8, 1/15	1/3, 1/6, 1/12		1/3, 1/6, 1/12, 1/25	1/3, 1/6, 1/12
[Off] ¹		1/60	1/30	1/24		1/50	1/25

¹ When slow & fast motion recording is activated, available setting options will vary depending on the selected shooting frame rate.
² Not available when slow & fast motion recording is activated.

- 1 Select **MENU** > [📷 Camera Setup] > [Shutter Mode] > Desired shutter speed mode.
- 2 For [Speed] only: Select **MENU** > [📷 Camera Setup] > [Shutter Increment] > [1/3 stop] or [1/4 stop].
- 3 Adjust the shutter speed, angle value or clear scan frequency using the direct setting mode (📖 57).
 - You can also use direct touch control (📖 56).

Using slow shutter mode

When recording in dark surroundings, you can obtain a brighter picture by using slow shutter mode. You can also use this mode when you wish to add certain effects to your recordings, such as blurring the background during panning shots or recording a moving subject with an afterimage trail.

- Image quality may not be as good as when using faster shutter speeds in brighter surroundings.

-  **NOTES**
- When the shutter speed mode is set to [Slow], bright red, green or blue dots may appear on the screen. In such case, use a faster shutter speed or select a lower ISO speed or gain value (📖 68).
 - When an RC-V100 Remote Controller is connected to the camera, you can change the shutter speed mode with the remote controller's SHUTTER SELECT button and the shutter speed value with the remote controller's SHUTTER ▲/▼ buttons.

Recording Under High-Frequency Light Sources

Flickering may occur when recording video under a rapidly blinking light source. When you execute [Auto Clear Scan Setting], the camera detects the frequency of the light source (in a range of 50.0 Hz to 2011.2 Hz) and shoots at a shutter speed that matches the blinking cycle, reducing flickering.

- 1 Select **MENU** > [📷 Camera Setup] > [Shutter Mode] > [Clear Scan].
- 2 Select **MENU** > [📷 Camera Setup] > [Auto Clear Scan Setting] > [OK].
- 3 Change the shutter speed to the displayed speed.
 - When you select [OK], the shutter speed changes to the displayed speed.

When [No flicker detected.] is displayed, or when the flickering does not disappear even after changing to the displayed shutter speed, perform the following operations:

- Execute [Auto Clear Scan Setting] again.
- Execute [Auto Clear Scan Setting] after changing the camera's orientation by about 90 degrees.
- Adjust manually.
 - Set a control dial / control ring to [Clear Scan (Steps)] or [Shutter] (📖 210).
 - With [Clear Scan (Steps)], you can change the shutter speed to 2, 3, or 4 times, or to 1/2, 1/3, or 1/4 times the frequency set using [Auto Clear Scan Setting].
 - With [Shutter] you can make fine adjustments.

NOTES

- The accuracy of high-frequency flickering detection may be reduced under the following conditions.
 - When there are repetitive patterns (such as grid or stripe patterns).
 - When the subject is in constant movement.
 - In extreme brightness or darkness.
 - When there are multiple light sources in the screen.
 - When the blinking light source is too small.
 - When the subject illumination is low.

Flicker Reduction

You can perform the following procedure to have the camera automatically detect and reduce flicker.

Select **MENU** > [📷 Camera Setup] > [Flicker Reduction] > [Automatic].

NOTES

- When recording under artificial light sources such as fluorescent, mercury or halogen lamps, the screen may flicker depending on the shutter speed. You may be able to avoid flicker by setting the shutter speed mode to [Speed] and the shutter speed to a value matching the frequency of the local electrical system: 1/50* or 1/100 for 50 Hz systems, 1/60 or 1/120 for 60 Hz systems.

* May not be available depending on the frame rate.

Flicker reduction cannot be used in the following cases.

- During slow & fast motion recording when the following shooting frame rates are not used:
 - 59.94 Hz: 30P/60P/120P
 - 50.00 Hz: 25P/50P/100P
- When the system frequency is 24.00 Hz. Or when the frame rate is 23.98P when using a recording mode other than slow & fast motion recording.

ISO Speed/Gain

You may want to adjust the brightness of the image according to the shooting conditions. You can choose between manual and automatic settings. By choosing manual settings you can change the ISO speed or gain value to adjust the sensitivity of the sensor. You can also set the camera's base ISO speed by choosing from four modes.

You can also perform this function remotely using Browser Remote on a connected network device (187).

Available setting values

ISO/Gain ¹	Increment ²	Available setting values
[ISO]	[1 stop]	100 ⁴ , 160 ³ , 200, 400, 640 ³ , 800, 1600, 2500 ³ , 3200, 6400, 12800, 25600, 51200 ⁴ , 102400 ⁴
	[1/3 stop]	100 ⁴ , 125 ⁴ , 160, 200, 250, 320, 400, 500, 640, 800, 1000, 1250, 1600, 2000, 2500, 3200, 4000, 5000, 6400, 8000, 10000, 12800, 16000, 20000, 25600, 32000 ⁴ , 40000 ⁴ , 51200 ⁴ , 64000 ⁴ , 80000 ⁴ , 102400 ⁴
[Gain]	[Normal] (3 dB)	−6dB ⁴ , −3dB ⁴ , −2dB ³ , 0dB to 42dB, 45dB ⁴ to 54dB ⁴
	[Fine] (0.5 dB)	−2dB to 42dB, 42.5dB ⁴ to 54dB ⁴

Available range

Base ISO	ISO/Gain ¹	Increment ²	Available range	
				Extended range ⁴
[Auto Selection]	[ISO]	Any setting	160 to 25600	100 to 102400
	[Gain]	[Normal] (3 dB)	−2dB to 42dB	−6dB to 54dB
		[Fine] (0.5 dB)	−2dB to 42dB	−2dB to 54dB
[Base ISO 160] / [Base ISO 160 (−2dB)] [Base ISO 400] / [Base ISO 400 (6dB)] [Base ISO 800] / [Base ISO 800 (12dB)]	[ISO]	Any setting	160 to 6400	100 to 12800
	[Gain]	[Normal] (3 dB)	−2dB to 30dB	−6dB to 36dB
		[Fine] (0.5 dB)	−2dB to 30dB	−2dB to 36dB
[Base ISO 640] / [Base ISO 640 (−2dB)] [Base ISO 1600] / [Base ISO 1600 (6dB)] [Base ISO 3200] / [Base ISO 3200 (12dB)]	[ISO]	Any setting	640 to 25600	400 to 51200
	[Gain]	[Normal] (3 dB)	−2dB to 30dB	−6dB to 36dB
		[Fine] (0.5 dB)	−2dB to 30dB	−2dB to 36dB
[Base ISO 2500] / [Base ISO 2500 (−2dB)] [Base ISO 6400] / [Base ISO 6400 (6dB)] [Base ISO 12800] / [Base ISO 12800 (12dB)]	[ISO]	Any setting	2500 to 25600	1600 to 102400
	[Gain]	[Normal] (3 dB)	−2dB to 18dB	−6dB to 30dB
		[Fine] (0.5 dB)	−2dB to 18dB	−2dB to 30dB

¹ **MENU** > [Camera Setup] > [ISO/Gain] setting.

² **MENU** > [Camera Setup] > [ISO/Gain Increment] setting.

³ Available only when **MENU** > [Camera Setup] > [ISO/Gain Extended Range] is set to [Off].

⁴ Available only when [ISO/Gain Extended Range] is set to [On].

Base ISO Speed

Set the base ISO speed for the recommended dynamic range. You can achieve low noise even at high ISO/gain levels by switching to one of three settings that suit different lighting conditions (normal lighting, low light, and dark places). Additionally, the [Auto Selection] setting automatically switches between three levels of base ISO according to the ISO/gain value, ensuring an optimal dynamic range and S/N ratio.

Select **MENU** > [Camera Setup] > [Base ISO] > Desired option.

- Available values will depend on the [Gamma/Color Space] setting in the custom picture file and the recording format.

Base ISO settings

Gamma curve	MENU > [Camera Setup] > [ISO/Gain]	
	[ISO]	[Gain]
[Canon Log 2] / [Canon Log 3] (Also applies when the main recording format is RAW)	[Auto Selection], [Base ISO 800], [Base ISO 3200], [Base ISO 12800]	[Auto Selection], [Base ISO 800 (12 dB)], [Base ISO 3200 (12 dB)], [Base ISO 12800 (12 dB)]
[PQ] / [HLG] / [Canon 709] / [BT.709 Wide DR]	[Auto Selection], [Base ISO 400], [Base ISO 1600], [Base ISO 6400]	[Auto Selection], [Base ISO 400 (6 dB)], [Base ISO 1600 (6 dB)], [Base ISO 6400 (6 dB)]
[BT.709 Standard]	[Auto Selection], [Base ISO 160], [Base ISO 640], [Base ISO 2500]	[Auto Selection], [Base ISO 160 (–2 dB)], [Base ISO 640 (–2 dB)], [Base ISO 2500 (–2 dB)]

NOTES

- If you select an ISO/gain value below the base ISO speed, white clipping in the highlights is more likely to occur.
- There is a difference in the amount of noise between each base ISO speed setting. Example: when comparing base ISO 800/ISO 800, base ISO 3200/ISO 3200, and base ISO 12800/ISO 12800, there is a difference in the amount of noise generated in the dark areas.


Manual ISO Speed/Gain Value

- 1 Select **MENU** > [Camera Setup] > [ISO/Gain] > [ISO] or [Gain].
- 2 Select **MENU** > [Camera Setup] > [ISO/Gain Mode] > [Manual].
- 3 Depending on your previous selection, select **MENU** > [Camera Setup] > [ISO/Gain Increment] > Desired option.
- 4 Adjust the ISO speed or gain value using the direct setting mode (57).
 - You can also use direct touch control (56).

Using the Control Dial/Control Ring

You can adjust the ISO speed or gain value using the control dial or the control ring of an RF lens.

- 1 Perform steps 1 to 3 in the *Manual ISO Speed/Gain Value* procedure. (69)
- 2 Select **MENU** > [System Setup] > [Front Control Dial], [Rear Control Dial] or [Control Ring] > [ISO/Gain].
- 3 Turn the control dial or control ring to set the desired ISO speed or gain value.



ISO Speed/Gain Preset


Using direct touch control (56), you can adjust and use up to 3 preset ISO speed/gain values.

Saving a preset value

- 1 Touch  > Current ISO speed/gain value.
- 2 Adjust the value selected and touch [Register].
- 3 Touch the desired position to save the preset value.
 - The current value is saved.

Using a saved preset value

- 1 Touch  > Current ISO speed/gain value.
- 2 Touch the desired preset value (above the slider).
 - The selected preset value is applied.



NOTES

- When high ISO speeds or gain levels are set, the picture may flicker slightly.
- When high ISO speeds or gain levels are set, bright red, green or blue dots may appear on the screen. In such case, use a faster shutter speed ( 66) or select a lower ISO speed or gain value.
- When the ISO speed or gain level is changed, some noise may appear momentarily on the screen. Do not adjust the ISO speed/gain level while recording.
- You can use the **MENU** >  System Setup > [Front Ctrl Dial Dir.], [Rear Ctrl Dial Dir.] or [Control Ring Dir.] setting to change the direction of the adjustment when you turn the control dial or control ring.
- When an RC-V100 Remote Controller is connected to the camera, you can adjust the ISO speed or gain value with the remote controller's ISO/GAIN ▲/▼ buttons.
- If you set an assignable button to [ISO/Gain Mode] ( 125), you can press the button to switch between automatic and manual adjustment.

Automatic ISO Speed/Gain

The sensitivity limit will be set automatically according to the [Gamma/Color Space] setting in the custom picture file.

Gamma curve	Base ISO ¹	Lower sensitivity limit
[Canon Log 3] [Canon Log 2]	[Auto Selection]	ISO 800 (Gain 12 dB)
	[Base ISO 800]	
	[Base ISO 3200]	ISO 3200 (Gain 12 dB)
	[Base ISO 12800]	ISO 12800 (Gain 12 dB)
[BT.709 Wide DR] [PQ] [HLG] [Canon 709]	[Auto Selection]	ISO 400 (Gain 6 dB)
	[Base ISO 400]	
	[Base ISO 1600]	ISO 1600 (Gain 6 dB)
	[Base ISO 6400]	ISO 6400 (Gain 6 dB)
[BT.709 Standard]	[Auto Selection]	ISO 160 (Gain -2 dB)
	[Base ISO 160]	
	[Base ISO 640]	ISO 640 (Gain -2 dB)
	[Base ISO 2500]	ISO 2500 (Gain -2 dB)

¹ When the main recording format is RAW, the available base ISO settings are the same as when the gamma curve component of the [Gamma/Color Space] setting in the custom picture file is set to [Canon Log 2] / [Canon Log 3].

Select **MENU** >  Camera Setup > [ISO/Gain Mode] > [Automatic].

 NOTES

- You can set the responsiveness of the automatic exposure function with the **MENU** > [📷 Camera Setup] > [AE Response] setting*.

* Except when using an incompatible lens (📖 249).

Setting an automatic ISO limit

By setting an ISO limit in automatic mode, you can curb the amount of noise and keep a dark ambient.

Select **MENU** > [📷 Camera Setup] > [Limit for Auto Mode] > Desired option.

ND Filter


Using the ND filter allows you to open up the aperture to obtain a shallower depth of field even when recording in bright surroundings. You can also use the ND filter to avoid the soft focus caused by diffraction when using small apertures. By default, you can select one of 3 density levels. If you enable the extended ND range, you can select one of 5 density levels.

You can also perform this function remotely using Browser Remote on a connected network device (187).

Press the ND FILTER + or – button to select the desired ND filter setting.

ND Filter Range

Displayed units		
Stop	Transmittance	Optical Density
0	1/1	0.0
2	1/4	0.6
4	1/16	1.2
6	1/64	1.8
8	1/256	2.4
10	1/1024	3.0



- Repeatedly pressing ND FILTER + button will change the ND filter setting in the following order (when set to [Stop]): [ND 2 stops] → [ND 4 stops] → [ND 6 stops] → [ND 8 stops]* → [ND 10 stops]* → ND filter off. (The ND FILTER – button cycles through the settings in reverse order.)
- * Only when **MENU** > [Camera Setup] > [Extended ND Range] is set to [On].
- You can also adjust this setting using direct touch control (56).
- For the displayed units ([Camera Setup] > [ND Display Units]), you can choose from [Stop], [Transmittance] or [Optical Density].

NOTES

- You can also press an assignable button set to [ND +] or [ND –] to perform this operation (125).
- Depending on the scene, the color may change slightly when turning the ND filter on/off. Setting a custom white balance (78) may be effective in such case.

About the extended ND range

- When you switch to or from a density level in the extended range, the focus may shift, affecting also the indication on the lens's focus distance scale.
- When you switch to a density level in the extended range, depending on the lens, the camera may not be able to focus at infinity focus.

Changing the ND filter setting using the RC-V100 Remote Controller

- When the remote controller is connected to the camera, you can use the remote controller's ND button in the same way as the camera's ND FILTER + button.
- When using settings up to level 4 (for [ND Display Units] > [Stop]: 2 to 8 stops), the corresponding ND filter indicator (1 to 4, respectively) will illuminate in orange. When the ND filter is set to level 5 (for [ND Display Units] > [Stop]: 10 stops), indicators 1 and 4 will both illuminate.

Aperture

You can affect the brightness of your recordings or change the depth of field by adjusting the aperture. Depending on the lens used, the aperture value displayed may differ (F value or T value) and available aperture values will vary as well (📖 249). You can select the adjustment increment and even use the smallest iris increment allowed by the lens.

You can also perform this function remotely using Browser Remote on a connected network device (📖 187).

Manual aperture: Adjust the aperture value manually.

Automatic aperture: The camera adjusts the aperture automatically.

Push Auto Iris: Momentary automatic aperture. During manual aperture, press the AUTO IRIS button to temporarily adjust the aperture automatically (only while the button is held pressed down).

Aperture Settings of the Lens

To adjust the aperture from the camera, you will need to enable automatic adjustment using the controls on the compatible EF Cinema/Rf (with iris ring) lens. Required settings vary depending on the lens. Refer to the instruction manual of the lens used.

Set the lens or iris ring to automatic aperture.


Manual Aperture: Changing the Aperture Value

- 1 Select **MENU** > [📷 Camera Setup] > [Iris Mode] > [Manual].
 - This setting is available only when a lens compatible with automatic aperture is attached to the camera. For non-compatible lenses, the aperture mode is automatically set to [Manual] and cannot be changed.
- 2 When using a lens equipped with aperture settings, set the lens to automatic aperture mode.
- 3 Select **MENU** > [📷 Camera Setup] > [Iris Increment] > [1/2 Stop] or [1/3 Stop].
 - You can also set **MENU** > [📷 Camera Setup] > [Fine Increment] to [On] to use the smallest iris increment allowed by the lens attached. Nevertheless, the aperture value displayed on the screen will be the closest value in the selected increment scale.
- 4 Adjust the aperture value using direct setting mode (📖 57).
 - You can also use direct touch control (📖 56).

Using the Control Dial/Control Ring

You can also adjust the aperture settings using the control dial (after assigning the [Iris] function) or the control ring of an RF lens/mount adapter.

- 1 Select **MENU** > [🔧 System Setup] > [Front Control Dial], [Rear Control Dial] or [Control Ring] > [Iris].
- 2 Turn the control dial or the control ring of an RF lens to adjust the aperture.



NOTES


- You can use the **MENU** > [🔧 System Setup] > [Front Ctrl Dial Dir.], [Rear Ctrl Dial Dir.] or [Control Ring Dir.] setting to change the direction of the adjustment when you turn the control dial or control ring.
- Closing down the aperture when recording under bright conditions may cause the picture to appear soft or out of focus. The following measures may be effective in avoiding the loss of sharpness due to diffraction.
 - Using a denser ND filter (📖 72).
 - Using a faster shutter speed (📖 66).
 - Applying diffraction correction (📖 31). Results may vary depending on the lens used.
- If you set an assignable button to [Iris +] or [Iris -] (📖 125), you can press the button to respectively open up or close down the aperture.
- When using a lens equipped with aperture settings, you can also adjust the aperture with the iris ring on the lens (📖 73).
- When using a lens with no lens contacts or an incompatible lens (📖 249), you cannot adjust the aperture using the camera. Adjust it using the lens.
- When using a lens that can correct the aperture value according to the position of the zoom, you can use the **MENU** > [📷 Camera Setup] > [Zoom-Iris Correction] setting to activate this correction.
- When an RC-V100 Remote Controller is connected to the camera, you can adjust the aperture with the remote controller's IRIS dial. At default settings, turn the dial right to open up the aperture and left to close the aperture.
- **Using an RF/EF Cinema lens**
 - The aperture value displayed on the screen will be a T value*. The aperture value (T value) displayed on the screen may differ from the indication on the lens's aperture scale.
 - * Updating the firmware is necessary for RF Cinema lenses (📖 31).
 - When the iris is almost fully closed, the aperture value (T value) will appear in gray on the screen.
 - When you change the aperture value from a position of fully open or fully closed iris, multiple adjustment operations may be required until the aperture changes.
- If you use the EF-EOS R 0.71x Mount Adapter to attach an EF lens, the aperture will be approximately one level brighter than the value indicated by the lens.

Momentary Automatic Aperture - Push Auto Iris

During manual aperture, you can press the PUSH AUTO IRIS button to have the camera temporarily take control and adjust the aperture automatically for an optimal exposure.

This function is not available when slow & fast motion recording is activated.

- 1 Select **MENU** > [📷 Camera Setup] > [Iris Mode] > [Manual].
- 2 When using a lens equipped with aperture settings, set the lens to automatic aperture mode (📖 73).
- 3 Press and hold the PUSH AUTO IRIS button.
 - The camera will automatically adjust the aperture to obtain optimal exposure as long as you hold the button pressed down, and **A** will appear on the screen next to the aperture value.
 - When you release the button the aperture value will be set, automatic aperture mode will end and the **A** icon will disappear.



i NOTES

- You can use the **MENU** > [📷 Camera Setup] > [AE Response] setting to change how quickly the aperture changes during automatic aperture mode. This setting has no effect when using an incompatible lens (📖 249).

Automatic Aperture

When a compatible lens is attached to the camera, you can have the camera automatically adjust the aperture. This function is not available when slow & fast motion recording is activated.

- 1 Select **MENU** > [📷 Camera Setup] > [Iris Mode] > [Automatic].
 - The camera will automatically adjust the aperture to obtain optimal exposure. The selected aperture value will appear at the bottom of the screen with an **A** icon next to it.
- 2 When using a lens equipped with aperture settings, set the lens to automatic aperture mode (📖 73).

i NOTES

- If you set an assignable button to [Iris Mode] (📖 125), you can press the button to toggle between the [Automatic] and [Manual] settings.
- The aperture value may change in the following cases.
 - While using the built-in extender or iris compensation function of an EF Cinema lens, when you switch from automatic aperture to manual aperture.
 - When the aperture controls on the lens are switched between automatic/manual mode.
- When using EF Cinema lenses that let you adjust the aperture gain, if the aperture gain is set too high, the aperture adjustment may not be stable ("aperture hunting"), depending on the shooting conditions. In such case, reset the lens's aperture gain to its initial value.

Exposure Compensation - AE Shift

Use AE shift to compensate the exposure that was set using automatic aperture, in order to darken or lighten the image.

You can also perform this function remotely using Browser Remote on a connected network device (📖 187).


- 1 Select **MENU** > [📷 Camera Setup] > [AE Shift].
- 2 Select the desired option.
 - The camera will attempt to adjust the exposure accordingly.
 - You can select one of 17 AE shift levels from -2.0 to +2.0.

NOTES

- If you set an assignable button to [AE Shift +] or [AE Shift -] (📖 125), you can press the button to adjust the AE shift level.

The exposure bar

The ▼ on top of the exposure bar indicates optimal exposure without any shift (AE±0); the scale markings indicate the deviation from optimal exposure in 1/2 EV increments. The indicator inside the exposure bar represents the current exposure. When the difference between current and optimal exposure is larger than ±2 EV, the indicator will flash at the edge of the exposure bar. Optimal exposure will change depending on the light metering mode used.



Light Metering Mode

Select the light metering mode to match the recording conditions. Using the appropriate setting will help achieve a more appropriate exposure level.

1 Select **MENU** > [📷 Camera Setup] > [Light Metering].

2 Select the desired option.

- The icon of the selected mode (📷 or 📷) appears on the screen.

Options

[Backlight]: Suitable when recording backlit scenes.

[Standard]: Averages the light metered from the entire screen, giving more weight to the subject in the center.

[Spotlight]*: Use this option when recording a scene in which only a certain part of the picture is lit, for example, when the subject is lit by a spotlight.

* Cannot be selected when a VR lens is attached.

NOTES

- If [EOS Standard] or [EOS Neutral] is selected for [Select **CP** File], the light metering mode cannot be selected. However, it can be selected if the custom picture file is edited (gamma adjustment, registering a different LUT as a Look File).
- If you set an assignable button to [Backlight] or [Spotlight] (📖 125), you can press the button to toggle between the respective light metering mode and [Standard].
- Adjust the exposure again if you change the metering mode after adjusting the aperture manually.

White Balance

The camera uses an electronic white balance process to calibrate the picture and produce accurate colors under different lighting conditions. The camera offers the following ways to set the white balance.

You can also perform this function remotely using Browser Remote on a connected network device (187).

Custom white balance: You can use a gray card or white object with no pattern to establish the white balance and set it to one of two custom white balance positions, A or B. When recording under fluorescent lights, we recommend setting the custom white balance.

Preset white balance: Set the white balance to (daylight) or (tungsten lamp). You can further adjust the color temperature (K) value and the color compensation (CC) value, which adjusts the color along the green/magenta gradation.

Color temperature: Allows you to set the color temperature between 2,000 K and 15,000 K, and further adjust the color compensation (CC) value.

Auto white balance (AWB): The camera automatically adjusts the white balance to the optimal level.


NOTES

- The [White Balance] setting in the custom picture file (137) takes precedence over the white balance set with these procedures.
- You can use the **MENU** > [Camera Setup] > [Shockless WB] setting to make the transition look smoother when you change the white balance settings.
- When an RC-V100 Remote Controller is connected to the camera, you can adjust the white balance with the remote controller's AWB button, A button, B button, PRESET button and button.
- The color temperatures displayed on the screen are approximate. Use them only as a reference.

White Balance Mode

Select a white balance mode using the direct setting mode (57).

- You can also use direct touch control (56).
- If you set **MENU** > [System Setup] > [Front Control Dial], [Rear Control Dial] or [Control Ring] to [White Balance Mode], you can change the white balance mode using the control dials or control ring of an RF lens.



NOTES

- If you set an assignable button to [AWB], [Set A], [Set B], [Daylight], [Tungsten] or [Kelvin] (125), you can press the button to change the white balance mode temporarily. Press the button again to return to the previous white balance mode.

Custom White Balance

1 Select the A or B icon (📖 77).


- To apply the stored custom white balance setting as is, the rest of the procedure is not necessary. To set a new custom white balance, continue the procedure.

2 Point the camera at a gray card or white object so that it fills the center of screen.

- Use the same lighting conditions you plan to use when recording.

3 Press the button.

- The  A or  B icon will flash quickly.
- Make sure the gray card or white object fills the center of the screen until the procedure is completed.
- Once the icon stops flashing, the procedure is completed. The setting is retained even if you turn off the camera.
- The color temperature and CC value registered by the camera will appear at the bottom of the screen next to the  A or  B icon.



 NOTES

- Readjust the custom white balance if the light source or ND filter setting changes.
- Very rarely and depending on the light source,  may keep flashing (it will change to a slow flashing). In that case, change the subject brightness and adjust the custom white balance again.
- After the camera registers a custom white balance, the color temperature or CC value may appear in gray. This indicates that the value registered exceeds the range of values that can be displayed but the white balance is correctly calibrated and you can continue shooting.

Color Temperature/Preset White Balance

1 Select the or icon (preset white balance), or the icon (color temperature setting) (📖 77).


- To apply the stored preset setting or color temperature as is, the rest of the procedure is not necessary. To adjust the color temperature or CC value, continue the procedure.

2 Press the button.

- The camera will enter the direct setting mode with the color temperature highlighted in orange. To adjust the CC value, push the joystick right.
- You can also adjust the color temperature or CC value using direct touch control (📖 56).

3 Select the desired value.

- The selected color temperature and CC value will be set and will appear on the screen next to the white balance icon.



White balance mode/setting	Adjustment range	
	Color temperature (K)	Color compensation (CC) value
 (daylight)	4,300 K to 8,000 K	-5 to +5
 (tungsten lamp)	2,700 K to 3,700 K	
 (color temperature)	2,000 K to 15,000 K	-20 to +20

NOTES

- You can use the **MENU** > [ Camera Setup] > [C. Temp. Increment] setting to change the units for the color temperature increment to [Mired] (5-mired increments) or [Kelvin] (100-kelvin increments). Even when [Mired] is selected, the color temperature is converted to and displayed in kelvins. Changing this setting may change the white balance setting.
- If you set **MENU** > [ System Setup] > [Front Control Dial], [Rear Control Dial] or [Control Ring] to [White Balance (K)] or [White Balance (CC)], you can adjust the color temperature (K) value and the color compensation (CC) value using the control dials or control ring of an RF lens.

Auto White Balance (AWB)

The camera constantly adjusts the white balance automatically to achieve an appropriate level. The camera will adjust the white balance if the light source changes.

Select the  icon ( 77).

- The color temperature and CC value set automatically by the camera will appear at the bottom of the screen next to the  icon.

NOTES

- Custom white balance may provide better results in the following cases:
 - Changing lighting conditions
 - Close-ups
 - Subjects in a single color (sky, sea or forest)
 - Under mercury lamps and certain types of fluorescent and LED lights
- You can use the **MENU** > [ Camera Setup] > [AWB Response] setting to change how quickly the white balance changes in auto white balance (AWB) mode.
- If you set an assignable button to [AWB Lock] ( 125), you can press the button to lock the current white balance settings set automatically by the camera. To cancel the lock, press the button again (resume auto white balance mode) or select a different white balance setting.

Focus

The camera offers the following ways to focus, depending on the lens used. The camera incorporates Dual Pixel CMOS AF technology for advanced autofocus performance with compatible lenses. Refer to the list of compatible lenses and functions that can be used (📖 249).

You can also adjust the focus remotely using Browser Remote on a connected network device (📖 187). Note that some methods allow you to operate aspects of the focus by touching the LCD screen.

Manual focus (MF): Turn the focus ring on the lens to adjust the focus. The camera offers several focus assistance functions (📖 81) to help you focus more accurately when using the manual focus.

Automatic focus (AF): The focus is adjusted automatically.

- **One-shot AF*:** You will be able to focus manually but still have the option to press an assignable button set to [One-Shot AF] to let the camera focus automatically once on the subject inside the AF frame.
- **Continuous AF*:** The camera automatically keeps the subject inside the AF frame in focus at all times. You can use the AF lock function (📖 85) to change the composition of the picture while keeping the focus on the selected spot.

Functions related to focus adjustment:

- **Subject detection:** Set a subject to be detected in advance to automatically detect the face/head, eyes or body of a person or an animal.
- **Subject tracking:** After you select a subject, the camera keeps focusing it and tracks the subject if it moves.

* Not available when a manual focus lens is attached to the camera.

Focus Mode on the Lens

Use the switch on the lens to select the lens's focus mode (automatic, manual). The name of the controls may differ depending on the lens. Refer to the instruction manual of the lens used.

Set the lens's focus mode to either automatic or manual.

- Either **[AF]** (automatic) or **[MF]** (manual) will appear on the screen.
- When using a lens without a focus mode switch, select **MENU** > [📷 Camera Setup] > [Focus Mode] > [AF] (automatic) or [MF] (manual).

Manual Focus

Focus manually using the focus ring on the lens.

Turn the focus ring to adjust the focus.

NOTES

- With some lenses, you may be able to operate the focus ring even when the focus mode is set to automatic.
- If you operate the zoom after focusing, the focus on the subject may be lost.
- If you focus manually and then leave the camera with the power turned on, the focus on the subject may be lost after a while. This possible slight shift in focus is a result of the internal temperature rising in the camera and lens. Check the focus before resuming shooting.
- When adjusting the focus, be careful not to touch the front of the lens or moving parts on the lens except for the focus ring.
- When an RC-V100 Remote Controller is connected to the camera, you can adjust the focus with the remote controller's FOCUS dial. At default settings, turn the dial right to focus farther and left to focus nearer.

Using the RF lens's focus ring

- You can change the direction of the adjustment when operating the focus ring with the **MENU** > [🔧 System Setup] > [Focus Ring Dir.] setting.
- You can link the amount of focus adjustment when using the focus ring to either the rotation angle or the rotation speed with the **MENU** > [🔧 System Setup] > [Focus Ring Response] setting.
- When the lens is set to autofocus, you can enable/disable manual adjustments with the **MENU** > [🔧 System Setup] > [Focus Ring Operation] setting.


Using the Focus Assistance Functions

In order to focus more accurately, you can use the following focus assistance functions: Dual Pixel Focus Guide, an onscreen guide that shows you if the selected subject is in focus; peaking, which creates a clearer contrast by emphasizing the outlines of the subject; and magnification, which enlarges the image on the screen. You can use peaking and the focus guide or peaking and magnification simultaneously for greater effect.

Focus guide

The focus guide gives you an intuitive visual indication of the current focus distance and the direction and amount of adjustment necessary to bring the selected subject into full focus. When used in combination with subject detection (📖 86), the guide will focus as follows: if set to [People] / [Animals], on the face (or body, if a face cannot be detected) of the subject. If [Eye Detection] is set to [On], the guide will focus on the vicinity of the eyes of the detected person or animal.

- 1 Set the focus mode on the lens to manual (📖 80).
- 2 Using direct touch control (📖 56), you can touch the [Focus Guide] switch to turn on/off the focus guide.
 - Alternatively, you can use the **MENU** > [🔧 Assistance Functions] > [Focus Guide] setting or an assignable button set to [Focus Guide], to display/hide the focus guide.
- 3 Touch the point where you want to focus on the LCD screen to move the focus guide.
 - You can also use the joystick to move the focus guide's frame. Press SET or the CANCEL button to return the focus guide's frame to the center of the screen.
- 4 Adjust the focus manually as necessary.
 - When the focus guide turns green, the subject is correctly focused.



NOTES

- With subjects or in situations where autofocus may not work well (📖 84), the focus guide may not work correctly.
- The focus guide cannot be used in the following cases:
 - While the focus is being adjusted automatically using one-shot AF or continuous AF.
 - When a manual focus lens is attached to the camera, except for compatible RF/EF Cinema lenses (📖 249).


Peaking

The camera offers two peaking levels.

1 Press the PEAKING button.

- The peaking icon (**PEAK1** or **PEAK2**) appears on the left of the screen and outlines (contour lines) in the image that are in focus will be shown highlighted.
- Press the button again to turn off peaking.
- You can use direct touch control (☐ 56) to turn the [Peaking 1]/[Peaking 2] setting on/off.
- Alternatively, you can use one of the **MENU** > [Assistance Functions] > [Peaking:] settings to turn the peaking function on/off separately on the respective terminal/output destination.

2 To change the peaking level, select **MENU** > [Assistance Functions] > [Peaking] > [Peaking 1] or [Peaking 2].




Magnification

1 Press the MAGN. button.

- **MAGN.** appears on the left of the screen and the center of the screen* is magnified 2 times.
- The orange frame displayed on the top right of the screen (magnification frame) shows the approximate part of the image shown magnified.
- Press SET to change the magnification setting in the following order: 2x → 5x → 10x.

2 If necessary, use the joystick to move around the magnification frame and check other parts of the image.

- You can also drag your finger across the LCD screen to move the frame.
- Press the CANCEL button to return the magnification frame to the center position.
- Press the MAGN. button again to cancel the magnification.



* If one of the AF frames or a subject detection frame is displayed on the screen, the area around the active frame will be magnified instead.

NOTES

• About Peaking/Magnification:

- You can use the **MENU** > [Assistance Functions] > [Peaking 1] and [Peaking 2] settings to set the color, gain and frequency of the two peaking levels independently of each other.
- You can use the **MENU** > [Assistance Functions] > [Magn. Output] setting to select where to show the magnified image.
- The assistance functions will not affect your recordings.
- Magnification will be turned off if you change the video configuration (☐ 59), turn **MENU** > [Camera Setup] > [Digital IS] on/off, or if you turn slow & fast motion recording on/off while the magnified image is displayed.
- This function is not applied to the output destination of the HDMI OUT terminal when [HDMI RAW] is set to [On].
- Peaking/magnification are not available while the color bars are displayed.
- When **MENU** > [Assistance Functions] > [B&W during Magn.] is set to [On], the screen is set to black and white during magnification. The assistance functions will not affect your recordings.
- Magnification cannot be displayed under the following conditions.
 - When [Sensor Mode] is set to [Full Frame] or [Super 35mm (Cropped)] and the slow & fast motion recording frame rate exceeds 60P.

- Peaking cannot be displayed under the following conditions.
 - When [OSD Output: SDI] or [OSD Output: HDMI] is set to [Off (Clean)] or [Off].

One-Shot AF

In this focus mode, you will focus manually in most situations but still have the option to have the camera focus automatically only once on the subject inside the AF frame. You can change the type and position of the AF frame.

- 1 Set the focus mode on the lens to automatic (📖 80).
- 2 Assign an assignable button to [One-Shot AF].
- 3 If necessary, change the type and position of the AF frame (📖 85).
- 4 Press and hold the assigned button.
 - As long as the assigned button is held down the camera will focus automatically.
 - When correct focus has been achieved, a green frame is displayed.
 - If [Continuous AF] is disabled and [Subject to detect] is set to [None], the AF frame will disappear when you release the assigned button (after a certain time has passed).

Continuous AF

The camera will focus automatically on a subject inside the area of the selected AF frame position/type (📖 85). For details on compatible lenses, refer to *Compatible Lenses and Functions* (📖 249).

- 1 Set the focus mode on the lens to automatic (📖 80).
- 2 Select **MENU** > [🔧 Camera Setup] > [Continuous AF] > [Enable].
 - A white AF frame will appear on the screen (if the AF frame type is set to an option other than [Whole Area]).
 - When focusing nearer is not possible, the AF frame will turn red.
 - If [Lens action if cannot AF] was set to [Stop], when distance measurement is not possible, the AF operation is stopped, the focus position is fixed and the AF frame becomes yellow.
- 3 If necessary, change the type and position of the AF frame (📖 85).

Subject Tracking Adjustment After Focus

After focusing manually on the desired subject, you can automatically track the subject using the [Track after Focusing] function. When there is no subject in focus, subject tracking is not performed and the AF operation is performed on the automatically detected subject. Available when Continuous AF is enabled.

- 1 Select **MENU** > [🔧 Camera Setup] > [Track after Focusing] > Desired option.
- 2 Turn the focus ring to adjust as needed.

Options for [Track after Focusing]:

[On (tracking frame)]:

An orange frame for trackable subjects is displayed on the screen during focus operation. After the focus operation, the frame changes to a white double frame  (tracking frame) to perform subject tracking.

[On (no tracking frame)]:

No frame for trackable subjects is displayed during focus operation. After the focus operation, a white double frame  (tracking frame) is displayed to perform subject tracking.

[Disable]:

The subject is not tracked.

NOTES


About the autofocus (AF) functions:

- The point where the camera focuses may change slightly depending on shooting conditions, such as subject, brightness and zoom position. Check the focus before resuming shooting.
- Autofocus may take longer in the following cases.
 - With some lenses, the camera may take longer to focus automatically or may not be able to focus correctly. Visit your local Canon website for the latest information.
- You can change the adjustment speed and responsiveness of the autofocus function with the following settings. Visit your local Canon website for the latest information.
 - **MENU** > [CAMERA] Camera Setup] > [AF Speed] to set the AF speed (the speed at which the focus is adjusted) to one of 10 levels.
 - **MENU** > [CAMERA] Camera Setup] > [AF Response] to set the responsiveness of the autofocus function to one of 7 levels.
 - While using continuous AF, you can hold the button assigned to [One-Shot AF] pressed down to temporarily adjust the focus using the maximum AF speed and AF response. This is helpful when you want to focus quickly after focus was lost or to keep a subject in focus while you follow it.
- Continuous AF and one-shot AF will not work in the following cases.
 - When the shooting frame rate in slow & fast motion recording is not set to 24, 25, 30, 48, 50, 60, 100 or 120 (fps).
- Subject tracking after focus operation will not work in the following cases:
 - During slow & fast motion recording when the frame rate is not set to 24, 25, 30, 48, 50, 60, 100 or 120 (fps).
 - When the shutter speed used is slower than 1/30 (59.94 Hz recordings), 1/25 (50.00 Hz recordings) or 1/24 (24.00 Hz recordings or 59.94 Hz recordings with a 23.98P frame rate).
 - When **MENU** > [SYSTEM] System Setup] > [Focus Ring Operation] is set to [Disable During AF].
 - When [Tele-converter] is enabled.
 - AF lock is enabled or the focus mode is set to MF.
 - When there is no subject in focus on the screen.
 - When operating the focus ring with a VR lens or a lens other than an RF lens attached to the camera.
 - When operating the focus from a controller connected to the REMOTE terminal with an attached lens that does not support tracking (📖 249).
 - When operating the focus using Browser Remote or an XC protocol-compatible device.
- **In the following cases, you may not be able to select a subject or track the selected subject after focusing.**
 - When switching between multiple subjects at the same depth.
 - In case of landscapes/distant subjects with a near identical depth.
 - When the subject on the screen appears small.
- Autofocus may not work well on the following subjects or in the following cases. In such case, focus manually.
 - Reflective surfaces
 - Subjects with low contrast or without vertical lines
 - Fast moving subjects
 - When using small apertures.
 - When subjects at different distances appear in the picture.
 - When an ISO speed or gain value in the extended range is selected (📖 68).
 - When the gamma curve component of the [Gamma/Color Space] setting in the custom picture file (📖 134) is set to an option other than [BT.709 Standard].
 - When the main recording format is set to RAW.
 - Through dirty or wet windows
 - Night scenes
 - Subjects with a repetitive pattern

AF Lock

While using continuous AF, you can lock the focus on a certain subject and then move the camera to change the composition.

- 1 While the autofocus is active, press the AF LOCK button.
 - The focus will be locked and **AF** and the AF frame will turn gray. When you are using subject detection, the frame around the main subject will turn gray.
 - The frame displayed on the screen will be the focus guide frame if [Focus Guide] is set to [On].
 - When you use a button assigned to [AF Lock (While Pressed)], the focus will only be locked while the button is held pressed down.
- 2 Press the AF LOCK button again to cancel the AF lock.



NOTES


AF lock will be canceled automatically in the following cases:

- If the camera is turned off or the camera's system frequency is changed.
- If the lens is removed or replaced.
- If **MENU** > [Camera Setup] > [Continuous AF] is changed to [Disable].
- When slow & fast motion recording is activated and the shooting frame rate used is other than 24P, 25P, 30P, 48P, 50P, 60P, 100P or 120P.

Changing the AF Frame Type and Position

You can change the type and position of the AF frame that appears on the screen while using one of the autofocus functions. You can change the position of the AF frame when the frame type is set to an option other than [Whole Area].

Select **MENU** > [Camera Setup] > [AF Frame] > Desired option.



- To move the AF frame (when set to an option other than [Whole Area]), you can touch the desired subject on the LCD monitor or press the joystick (in 8 directions). Press SET or CANCEL to move the AF frame back to the center of the screen.

NOTES

- When [Tele-converter] is enabled, the [Small Zone] frame will be displayed and the position will be [Center Frame]. The size of the AF frame will change depending on the set magnification.

Subject Detection Function

The subject detection function automatically detects the face/head, eyes or body* of a person or animal, according to the menu settings.

You can use subject detection with one of the autofocus functions to let the camera focus on the main subject automatically. You can use the focus guide (📖 81) in combination to help you focus on the main subject manually. You can use the focus guide to adjust the focus on the main subject manually. You can also change the main subject.

* Detected when a person's face/head (after being tracked once) is hidden from view.

- 1 Select **MENU** > [📷 Camera Setup] > [Subject to detect] > [People] or [Animals].
 - [👤] (People) or [🐾] (Animals) appears on the left side of the screen.
- 2 Select **MENU** > [📷 Camera Setup] > [Subj. detect. AF] > [Detect. priority] or [Detect. only].
 - [🔍] (detection priority) or [🔒] (detection only) will appear on the left of the screen.
- 3 Select **MENU** > [📷 Camera Setup] > [Eye Detection] > [On].
- 4 Select **MENU** > [📷 Camera Setup] > [Face Detection AE] > [On].
- 5 Point the camera at the subject.
 - When [Subject to detect] is set to [People], a frame is displayed on all detected people. When set to [Animals], a frame is displayed only the main subject (animals or people). The main subject is determined automatically and is displayed in white when using autofocus, and in gray or yellow* when using manual focus.
 - * When [Continuous AF] is enabled and [Lens action if cannot AF] was set to [Stop].
 - When multiple subjects are detected, ◀ and ▶ are shown on the main subject frame. If [Subject to detect] is set to [People], a gray frame is displayed on subjects other than the main subject. When ◀ and ▶ are shown, pressing the joystick to the left/right switches the main subject to another subject and tracking starts.

Options for [Subj. detect. AF]

[Detect. priority]: When a subject is not being detected, the camera determines the main subject and focuses on it.

[Detect. only]: When a subject is not being detected, the camera locks the focus.

AF operation according to the [Subject to detect] settings is as follows:

- Continuous AF: The camera continuously focuses on the subject it determines to be the main subject.
- One-shot AF: When you press a button assigned to [One-Shot AF], the camera focuses on the subject it determines to be the main subject.

Operation by AF mode

AF mode	Focus operation	Subj. Detect. AF			
		[Detect. Priority]		[Detect. Only]	
		Subject detected	No subject detected	Subject detected	No subject detected
Continuous AF: disabled	Manual focus	Manual focus			
	One-shot AF in operation	Focus on the detected subject	Focus on the subject inside the AF frame	Focus on the detected subject	Focus on the subject inside the AF frame
Continuous AF: enabled	Automatic				Manual focus
	One-shot AF in operation				Focus on the subject inside the AF frame

NOTES

- Typical examples of subjects not correctly detected
 - Faces extremely small, large, dark or bright in relation to the overall picture.
 - Faces that are turned to the side, at a diagonal, partially hidden or upside-down.
 - When the subject is blurred due to weather, the background, etc.
- The subject detection function cannot be used in the following cases.
 - When the shutter speed used is slower than 1/30 (59.94 Hz recordings), 1/25 (50.00 Hz recordings) or 1/24 (24.00 Hz recordings or 59.94 Hz recordings with a 23.98P frame rate), except when slow & fast motion recording mode is activated.
 - When the shooting frame rate for slow & fast motion recording is lower than 24P or higher than 120P.
 - When a manual focus lens is attached to the camera.
 - When [Tele-converter] is enabled.
- Face detection AE cannot be used in the following cases.
 - When shutter speed, ISO speed/gain and aperture are set to manual.
- The camera may mistakenly detect a subject other than the desired subject. In such case, set [Subject to detect] to [None].
- If you set an assignable button to [Subject to detect], [Subj. detect. AF], [Eye Detection] or [Face Detection AE] ( 125), you can press the button to adjust those settings.

Tracking a Specific Subject

You can have the camera track other moving subjects that are not faces and also combine the tracking function with one of the autofocus functions to let the camera focus on the desired subject automatically. To use the tracking function, you will need to set an assignable button to [Tracking] in advance.

1 Set an assignable button to [Tracking] ( 125).

2 Press the assignable button.

- The subject selection mark  will appear on the screen.
- Press the assignable button again or the CANCEL button to end the subject selection mode.

3 Select the subject you want to track.

- Touch the desired subject on the LCD screen.
- You can press the joystick up, down, left, or right to move to the subject you want to track, and then press SET (or press the joystick itself) to start tracking.

4 The  mark changes to a double frame  (tracking frame) and the camera will start tracking the selected subject.

- To stop tracking the selected subject, press CANCEL.

NOTES

- When the AF frame type is set to [Whole Area] or during subject tracking, you can track a subject by touching the subject to be tracked on the LCD monitor. If [Subject to detect] is set to [People] or [Animals], you can switch the main subject by pressing the joystick left or right and start tracking. In this case, no frame will be displayed for subjects other than the main subject (even if set to [People]).
- The camera may start tracking the incorrect subject if there is another subject in the picture with similar color/pattern characteristics. In that case, select the desired subject again.
- Tracking cannot be used in the same cases in which the subject detection function cannot be used.

Image Stabilization

You can use the image stabilizer to compensate for camera shake and achieve steadier shots. The image stabilizer is more effective at wider angles and the effect is reduced the more you approach the telephoto end.

1 Select **MENU** > [Camera Setup] > [Digital IS] > [On].

- When using lenses not compatible with camera-lens communication, perform step 4 to enter the lens's focal length manually.
- Image stabilization is activated and  appears on the left of the screen.
- You can also turn image stabilization on/off using an assignable button set to [Digital IS].

2 Select **MENU** > [Camera Setup] > [Digital IS Mode] > Desired option.

-  (standard) or  (high) will appear on the screen.

3 Select **MENU** > [Camera Setup] > [Motion Vector For Digital IS] > Desired option.

4 For lenses for which the focal length cannot be obtained, select **MENU** > [Camera Setup] > [Lens Focal Length] and enter the lens's focal length using the data entry screen (28).

- The image stabilization is adjusted according to the focal length entered.

5 When using an anamorphic lens, select **MENU** > [Camera Setup] > [Anamorphic Corr.] > Squeeze factor to use to correct the image stabilization.

- If you selected [Lens Squeeze Factor], the anamorphic correction will be applied according to the squeeze factor specified with the **MENU** > [Recording/Media Setup] > [Metadata] > [Lens Squeeze] setting.

Options for [Digital IS Mode]

[Standard]: Compensates for camera shake. The viewing angle is slightly reduced.

[High]: Achieves stronger compensation for camera shake. The viewing angle is further reduced.

Options for [Motion Vector For Digital IS]

[Enable]: Image stabilization using camera shake information and motion vectors. This setting allows for very effective image stabilization.

[Disable]: Image stabilization using only camera shake information.

- When recording a subject (such as a person or an animal) with a large amount movement, enabling this setting may cause the image to shake along with the subject.

NOTES

- [Digital IS Mode] will be [Standard] when all of the following conditions are met:
 - [Sensor Mode] is set to [Full Frame] and [Main Resolution] is set to [4096x2160] or [3840x2160].
 - [Recording Mode] is set to [Slow & Fast Motion] and the recording frame rate is 60P or higher, [Recording Mode] is set to [S&F Clip / Audio (WAV)] and the recording frame rate is 60P, or [Recording Mode] is set to another option and the recording frame rate is 59.94P.
 - [SDI Output Signal] is set to [4096x2160P/3840x2160P].
- If the IS function is turned off on a lens, the camera's image stabilization function is deactivated too and the  icon will flash on the left of the screen. When an RF-S lens is attached, select **MENU** > [Camera Setup] > [Lens Optical IS] > [On] to turn on the image stabilization function of the lens.
- When an assignable button set to [Pause Digital IS] is pressed during camera image stabilization, image stabilization will be temporarily paused ( or  are displayed in gray). Even while the digital IS function is paused, the narrower angle of view is maintained. Pressing the assignable button again will resume image stabilization. Lens image stabilization is not affected. Even during recording, the digital IS function pause/resume can be toggled.
- Depending on the subject and shooting conditions, subject blur may be more prominent (the subject may be momentarily blurred) due to the use of image stabilization.

- Turning off the camera's image stabilization is recommended in the following cases:
 - When using TS-E lenses and fisheye lenses
 - When the camera is expected to be stable, for example when it is mounted on a tripod
- If the degree of camera shake is too high, the image stabilizer may not be able to compensate fully.
- The camera's image stabilizer will not work when using lenses with a focal length exceeding 1000 mm.
- **The camera's image stabilizer will not function in the following cases:**
 - When recording in RAW format
 - When [HDMI RAW] is set to [On].

Zoom

When a lens that supports zoom adjustment is attached, the zoom can be controlled from this camera (📖 249). You can also zoom remotely using Browser Remote on a connected network device (📖 191).

Additionally, you can select the digital tele-converter from the menu and move the focal length to the telephoto range (except when recording in RAW format).

Zoom Modes of the Lens

Use the switch on the lens to select the lens's zoom mode (automatic, manual). The name of the controls may differ depending on the lens. Refer to the instruction manual of the lens/accessory used.

Set the lens's zoom mode to automatic.

- Operating the zoom from the camera is enabled.

Adjusting the Zoom

- 1 Enable automatic zoom mode on the lens.
- 2 Select **MENU** > [📷 Camera Setup] > [Camera Grip Zoom] > [On].
- 3 Select **MENU** > [📷 Camera Setup] > [Camera Grip Zoom Speed] > Desired zoom speed.
 - Zoom speeds are constant; [1] being the slowest and [16] the fastest.
- 4 Use the joystick on the camera grip to zoom.
 - Push the joystick up to zoom in (telephoto) and push it down to zoom out (wide-angle).



NOTES

- When an RC-V100 Remote Controller is connected to the camera and the lens is correctly set, you can zoom with the remote controller's ZOOM dial.
- When using slow zoom speeds, it may take longer for the lens to start moving.

Using the digital tele-converter:

The focal length is multiplied by the selected factor when you select **MENU** > [📷 Camera Setup] > [Tele-converter] > desired option.

Onscreen Markers, Zebra Patterns and False Color

Using onscreen markers allows you to make sure your subject is correctly framed and is within the appropriate safe area. Zebra patterns help you identify areas that are overexposed. The false color overlay allows you to check if the exposure is correct. You can display the assistance overlays independently on the LCD monitor and SDI OUT terminal / HDMI OUT terminal. The assistance overlays will not affect your recordings.

Displaying Onscreen Markers

The camera offers several onscreen markers. You can display multiple onscreen markers simultaneously and select their color individually.

[Center Marker]: Displays a small marker that indicates the center of the screen. You can select the shape of the center marker.


[Horizontal Marker], [Vertical Marker]: Displays a horizontal or vertical line to help you compose level shots.

[Grid Marker]: Displays a grid that allows you to frame your shots correctly (horizontally and vertically).

[Aspect Marker]: Indicates various aspect ratios by displaying border lines or by masking the image outside the selected aspect ratio. The aspect ratio can be set freely by the user.

[Safe Area Marker]: Displays a margin from the edges of the image (using border lines or by masking the image) to indicate the action safe area, text safe area, etc. You can select the core area used as the basis for calculating the safe area and a percentage, relative to the side length.

[User Marker 1], [User Marker 2], [User Marker 3]: Displays up to three rectangular frames whose size and position you can set freely and independently of each other.



1 Select **MENU** > [Assistance Functions] > Desired [Markers:] setting > [On].

- Onscreen markers will be displayed on the corresponding video output.
- You can also use direct touch control (56) to turn the [Markers: LCD] setting on/off.
- If the respective setting is set to [Off], onscreen markers will not be displayed on the corresponding video outputs even if individual markers are configured.

2 Select the marker(s) you wish to display and configure them with the following procedures.

- You can display multiple markers simultaneously.

Center Marker / Horizontal Marker / Vertical Marker / Grid Marker

1 Select **MENU** > [Assistance Functions] > [Center Marker], [Horizontal Marker], [Vertical Marker] or [Grid Marker] > Desired marker color.

- Select [Off] to turn off the marker.

2 For [Center Marker] only: Select **MENU** > [Assistance Functions] > [Center Marker Type] > Desired marker shape.

Aspect Marker

- 1 Select **MENU** > [Assistance Functions] > [Aspect Marker] > Desired marker color or transparency of the masked area.
 - Select [Off] to turn off the marker.
- 2 Select **MENU** > [Assistance Functions] > [Marker Aspect Ratio] > Desired option.
- 3 For [Custom] only: Select **MENU** > [Assistance Functions] > [Marker Custom Asp. Ratio] and enter the aspect ratio using the data entry screen (28).



NOTES

Aspect markers will not be displayed in the following cases.

- When the resolution is set to 3840x2160 or 1920x1080 and the marker aspect ratio is set to [16:9].
- When the resolution is set to 4096x2160 or 2048x1080 and the marker aspect ratio is set to [1.90:1].
- The same applies when the same aspect ratio is set manually using [Custom].

Safe Area Marker

The safe area is displayed using a border line or by masking the image outside the safe area. It can be calculated as a percentage of the width/height.

- 1 Select **MENU** > [Assistance Functions] > [Safe Area Marker] > Desired marker color/mask opacity level.
 - Select [Off] to turn off the marker.
- 2 Only when an aspect marker is already activated: Select **MENU** > [Assistance Functions] > [Basis for Marker Safe Area] > [Whole Picture] or [Selected Aspect Marker].
- 3 Select **MENU** > [Assistance Functions] > [Marker Safe Area %] > Desired percentage.
 - You can select the margin as a percentage of the width/height [(Side Length)].

User Markers

You can set 3 individual user markers ([User Marker 1] to [User Marker 3]) and adjust their color, size and position separately.

- 1 Select **MENU** > [Assistance Functions] > [User Marker 1], [User Marker 2] or [User Marker 3] > Desired marker color.
 - Select [Off] to turn off the marker.
- 2 Select **MENU** > [Assistance Functions] > [User Marker 1 Settings], [User Marker 2 Settings] or [User Marker 3 Settings] > [Size] > [Specification Method] > Desired option.

Options:

[Pixel]: Specify the number of pixels (width and height).

[Ref. Area & Aspect Ratio]: Specify an aspect ratio for the reference area.

[Ref. Area & Magn. Ratio]: Specify a magnification ratio for the selected reference area.

- Select the input value or setting value according to the selected specification method.
- 3 Select **MENU** > [Assistance Functions] > [User Marker 1 Settings], [User Marker 2 Settings] or [User Marker 3 Settings] > [Position] > [Specification Method] > Desired option.

Options:

[Center Coordinates], [Upper-left Coordinates]:

Sets the user marker reference coordinates to the center or the upper-left.

[Centering (User Marker 1)], [Centering (User Marker 2)]:

Aligns the center with that of a user marker. Available options differ depending on the set user marker.

- Select the input value or setting value according to the selected specification method.

When setting a method other than [Reference Area] > [Whole Picture] or a method relative to other markers, such as [Centering (User Marker 1)] to [Centering (User Marker 2)], you can select the following markers for the reference:


- When [User Marker 1] is set: No reference marker can be selected
- When [User Marker 2] is set: [User Marker 1]
- When [User Marker 3] is set: Either [User Marker 1] or [User Marker 2] can be selected

i NOTES

- You can choose the onscreen display level to turn off all other onscreen displays, leaving only the markers (53).
- If you set an assignable button to one of the [Markers:] settings (125), you can press the button to turn the markers on and off on the corresponding video output.
- In MEDIA mode, you can display the same markers as in CAMERA mode by selecting **MENU** > [Assistance Functions] > [Playback Marker Display] > [Enable].

Displaying Zebra Patterns


The camera has a zebra pattern function that shows black and white diagonal stripes over areas that are overexposed. There are two types of zebra patterns and you can display both simultaneously. Zebra 1 lets you identify areas within a certain range ($\pm 5\%$ of a specified level from 5% to 95%) while zebra 2 lets you identify areas that exceed a specified level (from 0% to 100%).



Zebra 1 Zebra 2

1 Press the ZEBRA button to activate the selected zebra pattern on all monitoring devices at once.

- You can also use direct touch control (56) to turn the [Zebra: LCD] setting on/off.
- You can turn the zebra pattern overlay on/off from **MENU** > [Assistance Functions] > [Zebra:] > Desired option.
- Alternatively, you can press an assignable button set to one of the [Zebra:] settings (125), to turn the zebra pattern overlay on and off on the corresponding video output.

**2 Select **MENU** > [Assistance Functions] > [Zebra] > Desired option.****3 Select **MENU** > [Assistance Functions] > [Zebra 1 Level] or [Zebra 2 Level] > Desired option.**

- [Zebra: SDI] cannot be displayed under the following conditions.
 - When [Sensor Mode] is set to [Full Frame] or [Super 35mm (Cropped)], the frame rate exceeds 60P, [SDI Output Signal] is [3840x2160] or higher, and [Peaking: SDI] is set to [On].
 - When [OSD Output: SDI] is set to [Off (Clean)].
- [Zebra: HDMI] cannot be displayed under the following conditions.
 - When [OSD Output: HDMI] is set to [Off].

Displaying False Color

In CAMERA mode, you can display the false color overlay to check the brightness levels as different colors.

94 Select **MENU** > [ Assistance Functions] > Desired [False Color:] setting > [On].

- You can also use direct touch control ( 56) to turn the [False Color: LCD] setting on/off.
- Alternatively, you can press an assignable button ( 125) set to one of the [False Color:] settings to turn the false color overlay on and off on the corresponding output destination.

NOTES

- You can use the **MENU** > [ Assistance Functions] > [False Color Index] setting to check an index (in English only) of the colors used in the false color overlay.

Color	Meaning
Red	White clipping
Yellow	Just below white clipping
Pink	One stop over 18% gray
Green	18% gray (medium gray)
Blue	Just above black clipping
Purple	Black clipping

- Depending on the custom picture file settings, the color displayed might not be that of the correct brightness level.
- [False Color: SDI] cannot be displayed under the following conditions.
 - When [Sensor Mode] is set to [Full Frame] or [Super 35mm (Cropped)], the slow & fast motion recording frame rate exceeds 60P and [SDI Output Signal] is [3840x2160] or higher.
 - When [OSD Output: SDI] is set to [Off (Clean)].
- [False Color: HDMI] cannot be displayed under the following conditions.
 - When [OSD Output: HDMI] is set to [Off].

Setting the Time Code

The camera generates a time code signal and records it with the recorded clips. The time code signal can be output from the TIME CODE terminal, SDI OUT terminal or HDMI OUT terminal. During playback in MEDIA mode, a time code retrieved from the recording media can be output to the SDI OUT terminal.

Depending on the frame rate used, you may be able to select between a drop frame and non-drop frame time code signal (📖 96). The default mode varies depending on the country/region of purchase and, though the time code display style is different for DF and NDF, in this section the NDF display style is used for simplicity's sake.

Selecting the Time Code Mode

You can select the camera's time code mode.

Select **MENU** > [🔧 System Setup] > [Time Code Mode] > Desired option.

Options

- [Preset]: The time code starts from an initial value you can select in advance. The default initial time code is 00:00:00.00 (00:00:00.00 for NDF).
See the following procedures to select the time code running mode and set the initial time code.
- [Regen.]: The camera will read the selected card and the time code will continue from the last time code recorded on the card. The time code runs only while recording so clips recorded consecutively on the same card will have continuous time codes.

Setting the Time Code Running Mode

If you set the time code mode to [Preset], you can select the time code running mode.

Select **MENU** > [🔧 System Setup] > [Time Code Run] > Desired option.

Options

- [Rec Run]: The time code runs only while recording so clips recorded consecutively on the same card will have continuous time codes.
- [Free Run]: The time code starts running the moment you confirm the selection and keeps running regardless of the camera's operation.

Setting the Time Code's Initial Value

If you set the time code mode to [Preset], you can set the initial value of the time code.

- 1 Select **MENU** > [🔧 System Setup] > [Set Time Code] > [Change].
 - The time code setting screen appears with an orange selection frame indicating the hours.
 - To reset the time code to [00:00:00:00], select [Reset] instead. If the running mode is set to [Free Run], the time code will be reset the moment you confirm the selection and keep running continuously from 00:00:00:00.
- 2 Enter the initial time code using the data entry screen (📖 28).
 - If the running mode is set to [Free Run], the time code will start running from the selected time code the moment you confirm the selection.

Selecting Drop or Non-Drop Frame

When the frame rate is set to 59.94P, 59.94i or 29.97P, you can select between a drop frame (DF) or non-drop frame (NDF) time code, depending on how you plan to use your recordings.

With all other frame rates, the time code is set to non-drop frame (NDF) and cannot be changed.

Select **MENU** > [**⚙** System Setup] > [Time Code DF/NDF] > Desired option.

- The time code display will change depending on the setting. When you select [DF], the time code will appear as [00:00:00.00]; when you select [NDF], it will appear as [00:00:00:00].

About the time code display

A letter may appear next to the time code depending on the setting/status. Refer to the following table.

Letter	Description
R	The time code mode is set to [Regen.].
P	The time code mode is set to [Preset] and the running mode is set to [Rec Run].
F	The time code mode is set to [Preset] and the running mode is set to [Free Run].
E	The time code signal is coming from an external source.
No letter	Time code during clip playback.

Setting the User Bit

You can set a user bit composed of the date or the time of recording or an identification code consisting of 8 characters in the hexadecimal system. There are sixteen possible characters: the numbers 0 to 9 and the letters A to F.

The user bit is recorded with clips and can be output from the TIME CODE terminal/SDI OUT terminal/HDMI OUT terminal. It can be used freely to categorize and manage recordings or to keep additional information about them.

1 Select **MENU** > [**⚙** System Setup] > [User Bit Type] > [Setting], [Date] or [Time].

- If you select [Time] or [Date] the rest of the procedure is not necessary.

2 Select [Change].

- To reset the user bit to [00 00 00 00], select [Reset] instead.

3 Enter the user bit using the data entry screen (📖 28).

NOTES

- The frames value of the time code runs from 0 to 23 (frame rate set to 23.98P or 24.00P), from 0 to 24 (frame rate set to 25.00P, 50.00i or 50.00P), or from 0 to 29 (all other frame rates). However, if the frame rate is 23.98P/24.00P and **MENU** > [**⚙** System Setup] > [SDI Output Signal] is set to [1920x1080i(PsF)] or [1280x720P], or if [HDMI Output Signal] is set to [1920x1080i] or [1280x720], the frame count of the time code output to the SDI OUT/HDMI OUT terminal runs from 0 to 29.
- When slow & fast motion recording / frame recording / interval recording is activated, you cannot select the [Free Run] running mode. Conversely, when pre-recording is activated, [Free Run] is set automatically and cannot be changed.
- When slow & fast motion recording / frame recording / interval recording is activated, the time code signal and user bit will not be output from any of the terminals.
- When you mix drop frame and non-drop frame time codes, there might be a discontinuity in the time code at the point where the recording starts.
- When you are using the [Free Run] running mode, the time code will continue running as long as the built-in backup battery has some charge left, even if you disconnect all other power sources.

- If you set an assignable button to [Time Code] (📖 125), you can press the button to open the [🔧 System Setup] menu page with the time code settings.


Synchronizing with an External Device

You can use the camera's TIME CODE terminal to synchronize this camera's time code to an external signal. Using the same external time code signal with multiple cameras allows you to set up a multi-camera recording. You can output the time code signal from the SDI OUT terminal to an editing device (while recording or during playback), so the editor can create video with the same time code.

Connecting an External Device

When synchronizing a time code signal, connect the external device to the TIME CODE terminal on the camera. Be sure to set the TIME CODE terminal to input or output in advance.

Connection diagram



Time Code Signal Input

An external SMPTE-standard LTC timing signal received from the TIME CODE terminal can be recorded as the time code. The user bit of the external timing signal can also be recorded with clips. Before connecting the device, set the TIME CODE terminal to input with the procedure below and make sure the time code running mode is set to [Free Run] (95).

- 1 Select **MENU** > [**⚙** System Setup] > [TC In/Out] > [In].
- 2 To record the external signal's user bit, select also **MENU** > [**⚙** System Setup] > [User Bit Recording Mode] > [External].

i NOTES

- Synchronize the camera's time code with an external time code signal that matches the camera's system frequency. Use a 24-frame time code signal when the frame rate is set to 23.98P or 24.00P, a 25-frame time code signal when it is set to 25.00P, 50.00i or 50.00P and a 30-frame time code signal for other frame rates.
- When a suitable external time code signal is received, the camera's own time code will be synchronized to it and the synchronization will be maintained even if you disconnect the cable from the TIME CODE terminal.
- If the external time code signal is incorrect or there is no input signal, the internal time code set in the camera will be recorded instead.

- When an external time code signal is received, the DF/NDF selection will follow the external time code signal's settings.
- If an external time code signal is input while pre-recording is activated, there might be a discontinuity in the time code of the pre-recorded clip.
- Performing any of the following actions while the cable is not connected will cause the synchronization to be disrupted; the correct time code will be restored once you reconnect the cable.
 - Turning the camera on/off
 - Switching to MEDIA mode
 - Changing the video configuration

Time Code Signal Output

The time code signal output from the TIME CODE terminal will be a SMPTE-standard LTC timing signal. The user bit will also be output.

Select **MENU** > [🔧 System Setup] > [TC In/Out] > [Out].

NOTES

- **About the user bit output:** The user bit set by the user (📖 96) will be output. In MEDIA mode, the user bit is not output from the TIME CODE terminal.
- The time code and user bit will not be output when slow & fast motion recording / frame recording / interval recording is activated.
- With the **MENU** > [🔧 Recording/Media Setup] > [HDMI Time Code] set to [On] you can output the time code signal from the HDMI OUT terminal (📖 155).

Recording Audio

The camera features the following options for audio recording and playback. You can record audio using an external microphone/line-in device (INPUT terminals or MIC terminal), the monaural microphone*, or an accessory compatible with the multi-function shoe.

The audio signal will be output with the video signal from the SDI OUT terminal / HDMI OUT terminal. You can record the audio signal on an external recorder.

* Only for recording voice memos while shooting. Recording voice memos is useful when synchronizing video and audio during editing.

Available audio recording formats

	Video format / audio recording function	Audio format				
		Codec	Sampling frequency	Bit depth	Number of audio channels	Bit rate
Video recording	RAW	Linear PCM	48 kHz	24 bit	4 channels	4.5 Mbps
	XF-AVC	Linear PCM		24 bit	4 channels	4.5 Mbps
	XF-HEVC S ¹ XF-AVC S ¹	Linear PCM		24 bit	4 channels	4.5 Mbps
		AAC		16 bit	2 channels ²	256 Kbps
Audio recording	For slow & fast motion recording	Linear PCM	48 kHz	24 bit	4 channels	4.5 Mbps
	For second card recording functions	Linear PCM	8 kHz	16 bit	1 channel	128 Kbps

¹ Audio for proxy clips is recorded in AAC format.

² CH1 and CH2 audio is recorded.

Audio Settings and Recorded Audio Channels


Menu settings			Recorded audio channels/audio sources			
[Audio Input Selection]*		[CH2 Input]*	CH1	CH2	CH3	CH4
[CH1/CH2]	[CH3/CH4]					
[INPUT Terminals]	[INPUT Terminals]	[INPUT 2]	INPUT 1 terminal	INPUT 2 terminal	INPUT 1 terminal	INPUT 2 terminal
[INPUT Terminals]	[INPUT Terminals]	[INPUT 1]	INPUT 1 terminal	INPUT 1 terminal	INPUT 1 terminal	INPUT 2 terminal
[INPUT Terminals]	[MIC Terminal]	[INPUT 2]	INPUT 1 terminal	INPUT 2 terminal	MIC terminal (L)	MIC terminal (R)
[INPUT Terminals]	[MIC Terminal]	[INPUT 1]	INPUT 1 terminal	INPUT 1 terminal	MIC terminal (L)	MIC terminal (R)
[INPUT Terminals]	[MIC Terminal]	[MIC Terminal]	INPUT 1 terminal	MIC terminal (L+R)	MIC terminal (L)	MIC terminal (R)
[INPUT Terminals]	[Monaural Mic]	[INPUT 2]	INPUT 1 terminal	INPUT 2 terminal	[Monaural Mic]	
[INPUT Terminals]	[Monaural Mic]	[INPUT 1]	INPUT 1 terminal	INPUT 1 terminal		
[INPUT Terminals]	[Monaural Mic]	[Monaural Mic]	INPUT 1 terminal	[Monaural Mic]		
[INPUT Terminals]	[Multi-Function Shoe]	[INPUT 2]	INPUT 1 terminal	INPUT 2 terminal	[Multi-Function Shoe]	
[INPUT Terminals]	[Multi-Function Shoe]	[INPUT 1]	INPUT 1 terminal	INPUT 1 terminal		
[MIC Terminal]	[INPUT Terminals]	—	MIC terminal (L)	MIC terminal (R)	INPUT 1 terminal	INPUT 2 terminal
[MIC Terminal]	[MIC Terminal]	—	MIC terminal (L)	MIC terminal (R)	MIC terminal (L)	MIC terminal (R)
[MIC Terminal]	[Monaural Mic]	—	MIC terminal (L)	MIC terminal (R)	[Monaural Mic]	
[MIC Terminal]	[Multi-Function Shoe]	—	MIC terminal (L)	MIC terminal (R)	[Multi-Function Shoe]	
[Monaural Mic]	[INPUT Terminals]	—	[Monaural Mic]		INPUT 1 terminal	INPUT 2 terminal
[Monaural Mic]	[MIC Terminal]	—			MIC terminal (L)	MIC terminal (R)
[Monaural Mic]	[Monaural Mic]	—			[Monaural Mic]	
[Monaural Mic]	[Multi-Function Shoe]	—			[Multi-Function Shoe]	

Menu settings			Recorded audio channels/audio sources			
[Audio Input Selection]*		[CH2 Input]*	CH1	CH2	CH3	CH4
[CH1/CH2]	[CH3/CH4]					
[Multi-Function Shoe]	[INPUT Terminals]	—	[Multi-Function Shoe]		INPUT 1 terminal	INPUT 2 terminal
[Multi-Function Shoe]	[MIC Terminal]	—			MIC terminal (L)	MIC terminal (R)
[Multi-Function Shoe]	[Monaural Mic]	—			[Monaural Mic]	
[Multi-Function Shoe]	[Multi-Function Shoe]	—			[Multi-Function Shoe]	

* Menu items under the [🔊] Audio Setup] menu.

i NOTES

- You can press the AUDIO STATUS button to display only the [🔊] Audio Setup] status screens. On these status screens you can check the input source selected for each audio channel and other audio-related settings.



Audio Format for XF-HEVC S / XF-AVC S Clips

Select the audio recording format for XF-HEVC S / XF-AVC S clips (primary clips or sub recording clips).



Select **MENU** > [Recording/Media Setup] > [**XF-HEVC S** / **XF-AVC S** Main Audio] or [**B** **XF-HEVC S** / **XF-AVC S** Audio] > Desired option.

Connecting an External Microphone or External Audio Input Source to the Camera

To each of the INPUT terminals you can attach commercially available microphones or analog line in sources with a Mini XLR connector. To the MIC terminal you can attach commercially available condenser microphones/line-in devices (analog) with a $\varnothing$ 3.5 mm stereo mini plug.

Using the supplied microphone holder, you can fix external microphones with a diameter of 19 mm to 20 mm.

- 1 To use a microphone, loosen the microphone lock screw (①), open the microphone holder and insert the microphone (②).
- 2 Tighten the lock screw (③) and put the microphone cable through the cable clamp.
- 3 When using any INPUT terminal, set the corresponding INPUT 1/INPUT 2 (audio source selection) switch to a position other than MIC+48V (④).
- 4 Plug the microphone/external line-in device cable into the desired INPUT terminal or the MIC terminal (⑤).



! IMPORTANT

- Do not connect or disconnect microphones and other audio devices from any INPUT terminal when the corresponding INPUT (audio source selection) switch is set to the MIC+48V position. This may damage the camera and/or device.

Selecting the Input Type for the INPUT 1/INPUT 2 Terminals

Change the position of the corresponding INPUT (audio source selection) switch according to the audio device connected to the INPUT 1/INPUT 2 terminals.

Set the INPUT 1 or INPUT 2 switch to LINE, MIC, or MIC+48V.

- When using the INPUT terminals to record to only one channel, use the INPUT 1 terminal.

IMPORTANT

- When using a microphone that requires phantom power, turn off the camera and set the respective INPUT switch to MIC. After connecting a +48V compatible microphone, switch the INPUT switch to MIC+48V.
- To connect a microphone or other audio device that is not compatible with phantom power to an INPUT terminal, make sure the respective INPUT (audio source selection) switch is set to LINE or MIC. Setting the switch to MIC+48V may damage the audio device.

Selecting the Input Type for the MIC Terminal

Change the setting according to the audio device connected to the MIC terminal.

- 1 Select **MENU** > [] Audio Setup] > [MIC Input]
- 2 Select [MIC (with Power Supply)] or [LINE]
 - Select [MIC (with Power Supply)] to supply plug-in power to the external microphone.

Selecting the Audio Input Source for Audio Channels

You can select the audio input source that will be recorded on CH1/CH2 or CH3/CH4, independently for each pair of audio channels. For details refer to the *Audio Settings and Recorded Audio Channels* table ( 100).

- 1 Select **MENU** > [] Audio Setup] > [Audio Input Selection] > [CH1/CH2].
- 2 Select [INPUT Terminals], [MIC Terminal], [Monaural Mic] or [Multi-Function Shoe].
- 3 Select the audio input for [CH3/CH4], in the same way.
- 4 Press CANCEL to return to the previous screen.

Recording the Same Analog Audio Input to Two Channels

By default, each audio input is recorded to a separate audio channel (INPUT 1 to CH1 and INPUT 2 to CH2). If necessary audio from the INPUT 1 terminal can be recorded on both CH1 and CH2 (CH2 as backup). In that case, you can adjust the audio recording levels of each channel independently of each other.

Select **MENU** > [] Audio Setup] > [CH2 Input] > Desired option.

Options


- [INPUT 2]: Records audio to each channel separately. Audio input into INPUT 1 is recorded to CH1, while audio input into INPUT 2 is recorded to CH2.
- [INPUT 1]: Audio input into INPUT 1 is recorded to both channels. Audio input into INPUT 2 will not be recorded.
- [Monaural Mic] / [MIC Terminal]: Audio input into INPUT 1 is recorded to CH1, while audio input to the built-in microphone and the MIC terminal is recorded to CH2.

Adjusting the Audio Recording Level

You can adjust the audio recording level of the INPUT terminals/ MIC terminal. You can select automatic or manual audio level adjustment, and adjust each audio channel separately or adjust CH1/CH2 or CH3/CH4 together (when the audio level adjustment of the audio channels is linked,  104).

Automatic Audio Level Adjustment for CH1, CH2 or CH1/CH2


Set the audio level switch of the desired channel to A (automatic) to let the camera automatically adjust that channel's audio level.



Manual Audio Level Adjustment for CH1, CH2 or CH1/CH2

You can set the audio level manually from $-\infty$ to +18 dB.

- 1 Set the audio level switch of the desired channel to M (manual).
- 2 Turn the corresponding audio level dial to adjust the audio level.
 - For reference, the 0 corresponds to $-\infty$, 5 corresponds to 0 dB, and 10 corresponds to +18 dB.
 - As a guideline, adjust the audio recording level so that the audio level meter on the screen will go to the right of the -18 dB mark (one mark right of the -20 dB mark) only occasionally.



Using the Menu to Adjust the Audio Level for Each Channel

- 1 Select **MENU** > [F] Audio Setup] > [Audio Rec Level] > Desired option.
 - Use ◀/▶ to choose the desired option.
 - Select [A] (automatic) to adjust the audio level automatically.
 - Select [M] (manual) to manually adjust the audio level using ◀/▶.

Automatic Level Control (ALC): Linking the audio level adjustment of CH1/CH2 or CH3/CH4

- When both CH1 and CH2, or CH3 and CH4, are set to the MIC terminal or INPUT terminals and to the same type of analog audio source (external line input or external microphone), you can use the **MENU** > [F] Audio Setup] > [CH1/CH2 ALC Link] or [CH3/CH4 ALC Link] setting to link the audio level adjustment of both channels.
- When CH1 and CH2 are linked, you can use the CH1 audio level switch and dial to affect both CH1 and CH2. When CH3 and CH4 are linked, you can use the [Audio Rec Level] settings to affect both CH3 and CH4.

Audio peak limiter

- You can set **MENU** > [F] Audio Setup] > [INPUT Limiter] to [On] to activate the audio limiter to limit the amplitude of audio input signals when they start to distort.

NOTES

- We recommend using headphones when adjusting the audio level. If the input level is too high, audio may become distorted even if the audio level indicator shows an appropriate level.

- If you set an assignable button to [Audio Level Indicator] (📖 125), you can press the button to turn the onscreen audio level indicator on and off.
- When the optional the Canon DM-E1D Multi-Function Shoe Directional Stereo Microphone is attached, adjustment with the audio level switch is also possible. In this case, CH1 settings are also applied to CH2.

Advanced Audio Input Settings

You can adjust the audio input settings for the INPUT terminals/MIC terminal. The corresponding menu settings become available only when the respective audio input is active and the following conditions are met:

INPUT terminals: INPUT 1 or INPUT 2 switch is set to MIC or MIC+48V

MIC terminal: [MIC Input] is set to [MIC (with Power Supply)]

Microphone Sensitivity (INPUT Terminals)

You can select the external microphone's sensitivity.

Select **MENU** > [🔊] Audio Setup] > [INPUT 1 Mic Trimming] or [INPUT 2 Mic Trimming] > Desired sensitivity level.

- You can select one of 5 sensitivity levels from -12 dB to +12 dB.

Microphone Attenuator (INPUT Terminals/MIC Terminal)

You can activate the external microphone's attenuator (20 dB).

INPUT Terminals: Select **MENU** > [🔊] Audio Setup] > [INPUT 1 Mic Att.] or [INPUT 2 Mic Att.] > [On].

MIC Terminal: Select **MENU** > [🔊] Audio Setup] > [MIC Att.] > [On].

Low-Cut Filter (INPUT Terminals/MIC Terminal)

You can select the characteristics of the microphone according to the sound to be recorded.

INPUT Terminals: Select **MENU** > [🔊] Audio Setup] > [INPUT 1 Mic Low Cut] or [INPUT 2 Mic Low Cut] > Desired option.

MIC Terminal: Select **MENU** > [🔊] Audio Setup] > [MIC Low Cut] > Desired option.

Options

[Off]: For recording audio under usual conditions.

[LC1]: For recording mainly people's voices.

[LC2]: For reducing the background sound of wind when recording outdoors in windy surroundings (for example, on a beach or close to buildings). Note that when you use this setting some low-frequency sounds may be suppressed along with the sound of wind.

Changing the Reference Level of the External Microphone (INPUT Terminals)

You can select the reference level of each INPUT terminal (-18 dB or -20 dB).

Select **MENU** > [🔊] Audio Setup] > [INPUT Reference Level] > Desired option.

Multi-Function Shoe Audio Input Settings

You can adjust the audio settings for the DM-E1D Directional Stereo Microphone attached to the multi-function shoe. The corresponding adjustment function become available only when the audio input is active. Refer to the DM-E1D instruction manual for more information and details on connections.

Microphone Attenuator (DM-E1D Directional Stereo Microphone)

You can activate the microphone attenuator for a shoe microphone attached to the multi-function shoe (20 dB).

Select **MENU** > [**⏏**] Audio Setup] > [Multi-Function Shoe Input] > [Shoe Mic] > [Shoe Mic Attenuator] > [On].

Low Cut (DM-E1D Directional Stereo Microphone)

You can choose the characteristics of the shoe microphone according to the recorded audio.

Select **MENU** > [**⏏**] Audio Setup] > [Multi-Function Shoe Input] > [Shoe Mic] > [Shoe Mic Low Cut] > Desired option.

Options

[Off]: For recording audio under usual conditions.

[On]: For reducing the background sound of wind when recording outdoors in windy surroundings (for example, on a beach or close to buildings). Note that when you use this setting some low-frequency sounds may be suppressed along with the sound of wind.

Microphone Directionality (DM-E1D Directional Stereo Microphone)

Select **MENU** > [**⏏**] Audio Setup] > [Multi-Function Shoe Input] > [Shoe Mic] > [Shoe Mic Directionality] > Desired option.

Options

[Shotgun (Monaural)]:

Captures clear audio from the front of the microphone.

[90°(Stereo)]: Captures suitable audio from both the front and the sides of the microphone.


[120°(Stereo)]: Captures audio from a wider angle.

Monitoring the Audio with Headphones

Connect headphones with a Ø 3.5 mm stereo mini-plug to the  (headphone) terminal to monitor the recorded audio.

NOTES

- You can adjust the headphone volume with the **MENU** > [**⏏**] Audio Setup] > [Headphone Volume] setting. If you set an assignable button to [Headphones +] or [Headphones -] ( 125), you can press the button to adjust the headphone volume without using the menu.



Colors Bars/Audio Reference Signal

You can have the camera generate color bars and a 1 kHz audio reference signal and output them from the following terminals.

	LCD monitor	SDI OUT terminal	HDMI OUT terminal	🎧 (headphone) terminal
Color bars	●	●	●	–
Audio reference signal	–	●	●	●

Color Bars

The camera offers SMPTE, EBU and ARIB color bars.

- 1 Select **MENU** > [📺 Camera Setup] > [Color Bars] > [On].
 - The selected color bars appear on the screen.
- 2 Select **MENU** > [📺 Camera Setup] > [Color Bar Type] > Desired option.
 - The selected color bars will be recorded when you press the REC button.
 - Turning off the camera or changing the operating mode to MEDIA mode will deactivate the color bars.

NOTES

- If you set an assignable button to [Color Bars] (📖 125), you can press the button to turn the color bars on/off.

Color bars cannot be displayed in the following cases:

- When the gamma curve component of the [Gamma/Color Space] setting in the custom picture is set to an option other than [BT.709 Wide DR], [BT.709 Standard] or [Canon 709].
- When recording in RAW format.
- When [HDMI RAW] is set to [On].

Audio Reference Signal

The camera can record a 1 kHz audio reference signal with the color bars.

Select **MENU** > [🔊 Audio Setup] > [1 kHz Tone] > Desired option.

- You can select one of three audio levels (–12 dB, –18 dB, –20 dB), or [Off] to turn off the signal.
- The reference signal will be output at the selected level when you display the color bars, and will be recorded when you press the REC button.

Video Scopes

The camera can display a simplified waveform monitor or a vectorscope to check your recordings. The selected video scope is displayed on the LCD monitor and can be output to other monitoring devices as well.

Displaying a Video Scope

Choose between a waveform monitor or a vectorscope. You can also change opacity, position and waveform monitor size settings.

1 Select **MENU** > [ Assistance Functions] >


[WFM Function] > [Waveform Monitor] or [Vectorscope].

2 Press the WFM button.

- Alternatively, you can use one of the **MENU** > [ Assistance Functions] > [WFM:] settings to turn the video scope on/off separately on the desired video output.
- By default, the video scope will appear on the right of the screen. Using the **MENU** > [ Assistance Functions] > [Waveform Settings] or [Vectorscope Settings] > [Position] settings, you can select where to display it (left or right side).
- You can also use direct touch control ( 56) to turn on/off the display of video scopes, or to change their position.

3 If needed, select **MENU** > [ Assistance Functions] > [WFM Opacity Level] > Desired option.

- The smaller the percentage the more transparent the onscreen displays.



NOTES

- The waveform monitor will not be affected even if a view assistance function is applied to the image, the range is changed or anamorphic desqueeze is used on the selected video output or screen.
- The video scopes will also be displayed while adjusting a custom picture file's image settings ( 130).

Changing the Waveform Monitor Settings

1 Select **MENU** > [ Assistance Functions] > [Waveform Settings] > [Type] > Desired option.

- If you selected an option other than [Select Line], skip to step 4.

2 Select **MENU** > [ Assistance Functions] > [Waveform Settings] > [Select Line].

3 Enter the Y coordinate of the red horizontal line to display using the data entry screen ( 28).

- The available range of lines that can be selected depends on the vertical component of the resolution used.
For 2160 and over: 0 to maximum value, minus 2 lines (in 2-line increments)
Example: 0 to 2158 (for 2160)
Below 2160: 0 to maximum value, minus 1 line (in 1-line increments)
Example: 0 to 1079 (for 1080)

4 Select **MENU** > [ Assistance Functions] > [Waveform Settings] > [Vertical Scale for HDR] > Desired option.

- Select the Y axis (luminance) scale used when displaying the waveform monitor of an HDR image.

5 If needed, touch the waveform monitor on the screen to change its display size (only for LCD).

- You can also select **MENU** > [ Assistance Functions] > [Waveform Settings] > [Size: LCD] > Desired option.

Options for [Type]

- [Line]: Sets the waveform monitor to line display mode.
- [Line+Spot]: The waveform of the area in the red frame is displayed in red on top of the [Line] mode waveform.
- [Select Line]: The selected horizontal line (in red) will be displayed along with its waveform.
- [RGB]: Shows 3 side-by-side waveforms in an RGB parade.
- [YPbPr]: Shows 3 side-by-side waveforms in a YPbPr parade.

Options for [Vertical Scale for HDR]

- [IRE]: Displays the video scope in IRE units.
- [PQ/HLG]: For HDR-PQ images, displays the video scope in nits (cd/m^2) and the narrow range's (video range) waveform monitor (including when the gamma curve after applying the Look File is set to [PQ]).
For HDR-HLG images, the Y axis shows a relative-index value between 0 and 1000 nits (including when the gamma curve after applying the Look File is set to [HLG]).

i NOTES

- If the waveform monitor is activated and the **MENU** > [CP Custom Picture] > [Edit CP File] > [Knee] > [Point] setting is changed, when you display the waveform monitor, a horizontal line will appear indicating the luminance (Y) level* corresponding to the knee point.
* When a Look File registered to the custom picture file is active, the displayed luminance may not be at the correct level.
- When the waveform monitor's Y axis is set to display in IRE units, a level of 10 bit 64 maps to 0 IRE and 10 bit 940 maps to 100 IRE, regardless of the custom picture settings.

Changing the Vectorscope Settings

- 1 Select **MENU** > [Assistance Functions] > [Vectorscope Settings] > [Type] > Desired option.
- 2 Touch the onscreen vectorscope to switch its magnification rate between [1x] and [2x].
 - You can also select **MENU** > [Assistance Functions] > [Vectorscope Settings] > [Gain] > Desired option.

Options for [Type]

- [Normal]: Displays the usual vectorscope.
- [Spot]: The color signal of the area in the red frame is displayed in red on top of the [Normal] mode waveform.

Adding Marks to Clips in CAMERA Mode

When the recording format is set to XF-AVC, while recording, you can add shot marks (S) to flag an important shot or frame. After recording a clip, you can add an OK mark (OK) or check mark (✓) to help you identify particular clips.

You can add and delete marks also in MEDIA mode (149, 149).

Marks cannot be added to proxy clips.

Adding a Shot Mark while Recording

To add a shot mark to a clip while recording, you must set an assignable button to [Add Shot Mark] in advance.

- 1 Set an assignable button to [Add Shot Mark] (125).
- 2 While you are recording, press the assignable button at the beginning of the shot you wish to mark.
 - [Shot Mark] will appear briefly and the shot mark will be added to the current frame of the clip.

NOTES

- Up to 100 shot marks can be added to a single clip.
- There may be up to a 0.5 second delay from when you press the button to when the camera adds the shot mark.
- When a clip contains a shot mark, S will appear next to the clip's thumbnail in the playback index screen.
- You cannot add a shot mark before pressing the REC button (start/stop recording) when pre-recording is activated, or during interval recording/frame recording.

Adding an OK Mark or ✓ Mark to the Last Clip Recorded

OK marks can be used to protect important clips, as clips with an OK mark cannot be deleted with the camera. To add a mark in CAMERA mode, you must set an assignable button to [Add OK Mark] or [Add ✓ Mark] in advance.

- 1 Set an assignable button to [Add OK Mark] or [Add ✓ Mark] (125).
- 2 After recording a clip, press the assignable button.
 - [OK Mark] or [✓ Mark] will appear briefly and the selected clip mark will be added to the clip.

NOTES

- A clip cannot have both an OK mark and a ✓ mark at the same time.
- When a clip has an OK mark or ✓ mark, the respective icon will appear next to the clip's thumbnail in the playback index screen.

Using Metadata

In CAMERA mode, when the recording format is set to XF-AVC / XF-AVC S / XF-HEVC S, the camera automatically adds metadata to the recorded clips. You can use Canon XF Utility to check and search for specific metadata. You can also create and transfer a user memo remotely using Browser Remote on a connected network device (187).

Metadata components

Metadata	Entering content			Checking content		
	Camera	Canon XF utility	Content Transfer Professional	Camera	Canon XF utility	Content Transfer Professional
User Memo: clip title, creator, location and description.	—	● ¹	—	●	●	—
GPS information: altitude, latitude and longitude.	● ²	● ³	—	●	●	—
Information about the recording: scene and take.	●	—	—	● ⁴	●	—
Information about camera settings: shutter speed, ISO speed/gain value, etc.	— ⁵	—	—	●	●	—
Unique Material Identifiers (UMID): country, organization and user codes based on the SMPTE standard.	● (182)	—	—	● ⁴	—	—
News Metadata (112)	—	—	●	●	—	●

¹ User memo files need to be created using the software and saved on an SD card in advance.

² Only when a GP-E2 GPS Receiver is connected to the camera. While recording, GPS information is recorded automatically by the camera.

³ GPS information can only be added to clips already recorded.

⁴ Only in CAMERA mode.

⁵ Recording data is logged automatically by the camera.

Setting a User Memo Created with Canon XF Utility

Before you can add a user memo, you must first install Canon XF Utility (161). Next, create the user memo and then save it to an SD card. Once you insert the SD card in the camera and select the user memo, it will be added to clips you record.

1 Use Canon XF Utility to save a user memo to an SD card.

- User memo files are saved to the “XMLCMF” folder in the SD card. For details, refer to *Managing User Memo Profiles* in the Canon XF Utility Instruction Manual.

2 Insert the SD card into the camera's SD card slot B.

3 Select **MENU** > [Recording/Media Setup] > [Metadata] > [Add XML File] > [On].

4 Select **MENU** > [Recording/Media Setup] > [Metadata] > [XML File Format] > [User Memo].

5 Select **MENU** > [Recording/Media Setup] > [Metadata] > [User Memo] > Desired user memo file.

- The **MEMO** icon appears on the left of the screen. (only when [ Monitoring Setup] > [Custom Display 2] > [User Memo] is set to [On].)
- Select [Off] to record clips without a user memo.

NOTES

- After you set a user memo, do not remove SD card B while you are recording. If the SD card is removed, the user memo will not be added to the clip.
- You must set the user memo before you start recording for it to be added to the clips. You cannot change the user memo already added to a clip using the camera but you can do so with Canon XF Utility.

Using News Metadata

When recording, you can add News Metadata* to the recorded clips. Using Content Transfer Professional, you can check and edit News Metadata files. The most recently set News Metadata will be prioritized and added. News Metadata cannot be added to clips when the main recording format is RAW. See the following table for details on News Metadata settings.

* Refers to a metadata file compliant with the DPP002 Metadata Exchange for News recommendation ver. 1.1.1.

News Metadata	Entering content		Checking content	
	Camera	Content Transfer Professional	Camera	Content Transfer Professional
Story Title, Description, Keyword (Tags), Category, Contributor, Source/Originator, Copyright Holder, Restrictions.	–	●	●	●
Genre	–	●	–	●
Language	–	–	–	●

NOTES

- News Metadata files with file names that exceed 64 characters (extension included) cannot be used.

Setting News Metadata saved on an SD card

Before setting News Metadata, create a News Metadata file and save it to an SD card. Once you insert the SD card into the camera, select the News Metadata file and start recording. The News Metadata will be added to the recorded clips.

1 Save the News Metadata file to an SD card.

- News Metadata files should be saved in the “/XMLTAG” folder of the SD card.

2 Insert the SD card into the camera’s card slot B.

3 Select **MENU** > [Recording/Media Setup] > [Metadata] > [Add XML File] > [On].

4 Select **MENU** > [Recording/Media Setup] > [Metadata] > [XML File Format] > [News Metadata].

5 Select **MENU** > [Recording/Media Setup] > [Metadata] > [News Metadata] > Desired News Metadata file saved to the SD card.

- The selected News Metadata file will be saved to the camera.

NOTES

- You cannot change the News Metadata already added to a clip using the camera but you can do so using Content Transfer Professional.

Setting News Metadata edited with Content Transfer Professional

Before setting News Metadata, edit the News Metadata file using Content Transfer Professional. Connect the camera to a smartphone using the smartphone application ( 162, 195) to transfer and save News Metadata files from a smartphone to the camera. News Metadata will be added to the recorded clips.

1 Smartphone: edit and save the News Metadata file with Content Transfer Professional.

2 Connect the camera to a smartphone.

3 Operate Content Transfer Professional to load the News Metadata file and transfer it to the camera.

4 Save the News Metadata to the camera.

- News Metadata files transferred from a smartphone will be saved automatically to the camera.
- Automatically, **MENU** > [ Recording/Media Setup] > [Metadata] > [Add XML File] will be set to [On], and [XML File Format] will be set to [News Metadata].
- Only the most recently transferred file can be saved.

Resetting News Metadata

You can reset the News Metadata added to clips.

1 Select **MENU** > [ Recording/Media Setup] > [Metadata] > [News Metadata Reset All].

2 Select [OK].

IMPORTANT

- When the camera is turned off normally, the News Metadata file is saved or a previously saved News Metadata is reset. In the case of a power outage or if the power is not terminated normally the file will not be saved or reset.
- News Metadata saved to the camera will be reset if you select **MENU** > [ System Setup] > [Reset] > [All Settings], or if the camera's firmware is updated.

Entering Slate Information About the Recording

You can enter scene and take information to help identify the recording later on.

1 Select **MENU** > [ Recording/Media Setup] > [Metadata] > [Scene] or [Take] > [Change].

2 Enter the desired text using the keyboard screen ( 28).

- To clear the scene/take information, select [Reset] instead.

Special Recording Modes

The camera features the following special recording modes.

- Slow & fast motion recording (📖 114).
- Pre-recording (📖 117).
- Continuous recording (📖 118).
- Frame recording (📖 119).
- Interval recording (📖 119).

Slow & Fast Motion Recording

The camera can record using a frame rate* (shooting frame rate) that is different from the playback frame rate. Recording a clip with a shooting frame rate higher than the [Frame Rate] setting will result in a slow motion effect during playback. Conversely, a lower shooting frame rate will result in a fast motion effect. Sound is not recorded with the clip, but it can be recorded separately as a WAV file. You can also use direct touch control to perform this function (📖 56).

* Progressive format.

Available shooting frame rates

Frame rate	Available shooting frame rate (fps) during slow & fast motion recording
59.94P	1, 2, 3, 6, 15, 30, 44, 48, 52, 56, 60, 90, 120, 150, 180
29.97P	1, 2, 3, 6, 15, 22, 24, 26, 28, 30, 32, 36, 40, 44, 48, 52, 56, 60, 90, 120, 150, 180
24.00P 23.98P	1, 2, 3, 6, 12, 16, 18, 20, 22, 24, 26, 28, 30, 32, 36, 40, 44, 48, 52, 56, 60, 72, 96, 120, 144, 168, 180
50.00P	1, 5, 15, 25, 34, 38, 42, 46, 50, 54, 58, 60, 75, 100, 120, 125, 150, 175, 180
25.00P	1, 5, 15, 17, 19, 21, 23, 25, 26, 28, 30, 34, 38, 42, 46, 50, 54, 58, 60, 75, 100, 120, 125, 150, 175, 180

Available shooting frame rates (RAW)

Main recording format	Main resolution	Frame rate					
		59.94P	29.97P	23.98P	50.00P	25.00P	24.00P
RAW LT	6000x3164	–	1 to 30	1 to 24	–	1 to 25	1 to 24
RAW ST	4368x2304	–	1 to 30	1 to 30	–	1 to 30	1 to 30
RAW LT		1 to 60	1 to 30	1 to 30	1 to 50	1 to 30	1 to 30

Available shooting frame rates (XF-AVC)

Main recording format	Main resolution	Frame rate	Bit rate	Shooting frame rate during slow & fast motion recording
XF-AVC YCC422 10 bit	4096x2160 Intra-frame 3840x2160 Intra-frame	59.94P	600 Mbps	1 to 60
		50.00P	500 Mbps	1 to 60
		29.97P	600 Mbps, 450 Mbps	1 to 30
		29.97P	300 Mbps	1 to 60
		25.00P	500 Mbps, 375 Mbps	1 to 30
		25.00P	250 Mbps	1 to 60
		24.00P, 23.98P	480 Mbps, 360 Mbps	1 to 30
		24.00P, 23.98P	240 Mbps	1 to 60
	4096x2160 Long GOP 3840x2160 Long GOP	59.94P, 50.00P	250 Mbps	1 to 120
		29.97P	150 Mbps	1 to 120
		25.00P, 24.00P, 23.98P	150 Mbps	1 to 100
		25.00P	135 Mbps	120
		24.00P, 23.98P	130 Mbps	120
	2048x1080 Intra-frame 1920x1080 Intra-frame	59.94P	300 Mbps	1 to 120
		50.00P	250 Mbps	1 to 120
		29.97P	150 Mbps	1 to 120
		25.00P	125 Mbps	1 to 120
		24.00P, 23.98P	120 Mbps	1 to 120
	2048x1080 Long GOP 1920x1080 Long GOP	59.94P, 50.00P, 29.97P, 25.00P, 24.00P, 23.98P	50 Mbps	1 to 180 ¹

¹ Up to 120 when the sensor mode is [Super 35mm (Cropped)].

Available shooting frame rates (XF-HEVC S)

Main recording format	Main resolution	Frame rate				
		59.94P	29.97P	23.98P / 24.00P	50.00P	25.00P
XF-HEVC S YCC422 10 bit	4096x2160 Long GOP 3840x2160 Long GOP	1 to 120	1 to 120	1 to 120 ¹	1 to 120	1 to 120
XF-HEVC S YCC420 10 bit	2048x1080 Long GOP 1920x1080 Long GOP	1 to 180 ²	1 to 180 ²	1 to 180 ²	1 to 180 ²	1 to 180 ²

¹ For XF-HEVC S YCC422 10 bit recording at 135 Mbps, the bit rate is 130 Mbps only for 120P.

² Up to 120 when the sensor mode is [Super 35mm (Cropped)].

Available shooting frame rates (XF-AVC S)

Main recording format	Main resolution	Frame rate	Bit rate	Shooting frame rate during slow & fast motion recording
XF-AVC S YCC422 10 bit	4096x2160 Intra-frame 3840x2160 Intra-frame	59.94P	600 Mbps	1 to 60
		50.00P	500 Mbps	1 to 60
		29.97P	600 Mbps, 450 Mbps	1 to 30
		29.97P	300 Mbps	1 to 60
		25.00P	500 Mbps, 375 Mbps	1 to 30
		25.00P	250 Mbps	1 to 60
		24.00P, 23.98P	480 Mbps, 360 Mbps	1 to 30
		24.00P, 23.98P	240 Mbps	1 to 60
	4096x2160 Long GOP 3840x2160 Long GOP	59.94P, 50.00P	250 Mbps	1 to 120
		29.97P	150 Mbps	1 to 120
		25.00P, 24.00P, 23.98P	150 Mbps	1 to 100
		25.00P	135 Mbps	120
		24.00P, 23.98P	130 Mbps	120
	2048x1080 Intra-frame 1920x1080 Intra-frame	59.94P	300 Mbps	1 to 120
		50.00P	250 Mbps	1 to 120
		29.97P	150 Mbps	1 to 120
		25.00P	125 Mbps	1 to 120
		24.00P, 23.98P	120 Mbps	1 to 120
	2048x1080 Long GOP 1920x1080 Long GOP	59.94P, 50.00P, 29.97P, 25.00P, 24.00P, 23.98P	50 Mbps	1 to 180 ¹
XF-AVC S YCC420 8 bit	4096x2160 Long GOP 3840x2160 Long GOP	59.94P, 50.00P, 29.97P, 25.00P, 24.00P, 23.98P	—	1 to 120
	2048x1080 Long GOP 1920x1080 Long GOP		—	1 to 180 ¹

¹ Up to 120 when the sensor mode is [Super 35mm (Cropped)].

Available shooting frame rates (Proxy clip recording: XF-AVC / XF-HEVC S / XF-AVC S)

Proxy clip resolution	Frame rate				
	59.94P	29.97P	23.98P / 24.00P	50.00P	25.00P
2048x1080	1 to 60	1 to 30	1 to 30	1 to 50	1 to 30

1 To record audio, insert an SD card into the card slot where video is not being recorded.

2 Select **MENU** > [ Recording/Media Setup] > [Recording Mode] > [Slow & Fast Motion] or [S&F Clip/Audio (WAV)].

- Slow & fast motion recording is activated. [S&F STBY] appears on the screen and the shooting frame rate appears next to the frame rate setting (the playback frame rate).

3 Select **MENU** > [ Recording/Media Setup] > [Slow & Fast Frame Rate] > Desired frame rate.

4 Press the REC button to begin recording.

- The tally lamp changes from green (power indicator) to red.
- [S&F STBY] changes to [S&F  REC] while recording.

5 Press the REC button again to stop recording.

- The clip is recorded on the selected SD card.
- When [S&F Clip/Audio (WAV)] is selected, audio in WAV format will be recorded on the SD card where video is not being recorded.
- The tally lamp changes from red to green (power indicator) and the onscreen display changes back to [S&F STBY].

6 Select **MENU** > [Recording/Media Setup] > [Recording Mode] > [Normal Recording] to turn off slow & fast motion recording.

NOTES

- When [Sensor Mode] is set to [Super 35mm (Cropped)] and the frame rate is 120P, the viewing angle is slightly narrow regardless of the [Main Rec Format] and [Main Resolution] settings.
- When the slow & fast motion recording frame rate exceeds 60P, the following functions cannot be used.
 - Second card recording functions (proxy clips and sub recording clips).
 - CV protocol.
- When [S&F Clip / Audio (WAV)] is selected, slow & fast motion recording frame rates exceeding 60P cannot be set.
- The maximum recording time of a single clip is the equivalent of approximately 6 hours of playback time.
- The shooting frame rate cannot be changed while recording.
- If you change the system frequency, slow & fast motion recording will be canceled and the shooting frame rate will be reset to its default value.
- **About the time code when slow & fast motion recording is activated:**
 - The time code mode can be set to [Regen.], or to [Preset] with [Rec Run] running mode.
 - If the time code running mode was set to [Free Run], the time code running mode will be changed automatically to [Rec Run] when slow & fast motion recording is activated.
 - When the special recording mode is turned off, the time code running mode will return to its previous setting.
 - The time code signal will not be output from any terminal.
- **Recording Audio (WAV)**
 - Audio is recorded with the following settings: 48 kHz, 24 bit, 4 channels.
 - If video cannot be recorded due to a card problem, audio will also not be recorded.
 - However, video will be recorded even if audio cannot be recorded due to a card problem.
 - Audio will not be recorded if there is an existing WAV file with the same file name.
 - Audio recording will stop automatically after reaching 60 minutes (video recording will continue).
 - A maximum of 999 WAV files can be recorded.

Pre-recording

When pre-recording is activated, the camera starts recording continuously onto a temporary memory (approx. 3 seconds) so when you press the REC button, the clip will contain also a few seconds of video and audio recorded before you pressed the button. Pre-recording is not available when the main recording format is set to RAW.

You can also use direct touch control to perform this function ( 56).

1 Select **MENU** > [Recording/Media Setup] > [Recording Mode] > [Pre-Recording].

- [PRE STBY] appears on the screen.

2 Press the REC button to begin recording.

- The tally lamp changes from green (power indicator) to red.
- [PRE STBY] changes to [PRE  REC] while recording.

3 Press the REC button again to stop recording.

- The clip is recorded. The recorded clip will include a few seconds of video and audio recorded before the REC button was pressed.
- The tally lamp changes from red to green (power indicator) and the onscreen display changes back to [PRE STBY].

4 Select **MENU** > [Recording/Media Setup] > [Recording Mode] > [Normal Recording] to stop pre-recording.

NOTES

- Pre-recording will be canceled if the recording mode is changed.
- **About the time code when pre-recording is activated:**
 - The time code of the clip will start a few seconds before the REC button was pressed.
 - The time code will be recorded with the running mode set to [Free Run].
 - If the time code mode was set to [Regen.], or to [Preset] with [Rec Run] running mode, the time code running mode will be changed automatically to [Free Run] when pre-recording is activated.
 - When the special recording mode is turned off, the time code running mode will return to its previous setting.

Continuous Recording

Audio and video are recorded on both cards in this mode, normal recording on SD card A, and continuous recording on SD card B. This function can be used when the main recording format is set to XF-HEVC S / XF-AVC S. Audio will be recorded in linear PCM format.

With the exception of step 5, you can also use direct touch control to perform this function ( 56).

1 Insert an SD card into each card slot (slot A for normal recording, slot B for continuous recording).

2 Select **MENU** > [Recording/Media Setup] > [Recording Mode] > [**A** Main / **B** Continuous Rec].

- The continuous recording mode is activated and [CONT] appears on the screen next to the SD card B indicator.

3 Select **MENU** > [Recording/Media Setup] > [Continuous Recording] > [REC].

- The tally lamp changes from green (power indicator) to red and continuous recording starts on SD card B. The onscreen display changes to [● CONT].

4 Press the REC button to start recording.

- Normal recording on SD card A starts.
- If you press the button before step 3, recording will start on both cards.

5 Select **MENU** > [Recording/Media Setup] > [Continuous Recording] > [STBY].

- The tally lamp changes from red to green (power indicator) and recording stops on both cards. The onscreen display changes to [CONT].

6 Select **MENU** > [Recording/Media Setup] > [Recording Mode] > [Normal Recording] to turn off continuous recording.

NOTES

- When continuous recording is activated, if recording on SD card B (continuous recording) is not available, normal recording on SD card A will not be possible either.
- Continuous recording will continue even if SD card A becomes full.
- If [Continuous Recording] is set to [STBY] and the main recording format is changed to an option other than XF-HEVC S / XF-AVC S, continuous recording will be canceled.

Frame Recording Mode

Set the number of frames in advance. We recommend operating the camera remotely or stabilizing the camera, for example, on a tripod. Sound is not recorded in this mode.

You can also use direct touch control to perform this function (📖 56).

- 1 Select > [📷 Recording/Media Setup] > [Recording Mode] > [Frame Recording].
 - [FRM STBY] appears on the screen (with [FRM] flashing).
- 2 Select > [📷 Recording/Media Setup] > [Frame Rec: Frame Rate] (📖 202) > Desired option.
- 3 Press the REC button to begin recording.
 - The tally lamp changes from green (power indicator) to red.
 - [FRM STBY] changes to [FRM ● REC] while recording.
 - The camera automatically records the specified number of frames.
- 4 Repeat until you finish recording.
- 5 Select > [📷 Recording/Media Setup] > [Recording Mode] > [Normal Recording] to stop frame recording.
 - Frame recording mode ends and all of the recorded frames are joined together into one clip.
 - The tally lamp changes from red to green (power indicator) and [STBY] appears on the screen.

NOTES

- Frame recording cannot be used when the frame rate is set to 59.94i or 50.00i. When in use, frame recording will end if the frame rate is set to 59.94i or 50.00i.
- The number of frames recorded cannot be changed while recording.
- The same image as the last frame when frame recording was stopped may be recorded and added to the end of the clip.
- **About the time code when frame recording is activated:**
 - The time code mode can be set to [Regen.], or to [Preset] with [Rec Run] running mode. The time code advances by the number of frames recorded every time.
 - If the time code running mode was set to [Free Run] or the camera was synchronized to an external time code signal, the time code running mode will be changed automatically to [Rec Run] when frame recording is activated.
 - When the special recording mode is deactivated, the time code will return to its previous setting.
 - The time code will not be output from any terminal.

Interval Recording Mode

Set the interval and number of frames in advance. Sound is not recorded in this mode.

You can also use direct touch control to perform this function (📖 56).

- 1 Select > [📷 Recording/Media Setup] > [Recording Mode] > [Interval Recording].
 - [INT STBY] appears at the top of the screen (with [INT] flashing).
- 2 Select > [📷 Recording/Media Setup] > [Interval Rec: Time Interval] (📖 202) > Desired option.
- 3 Select > [📷 Recording/Media Setup] > [Interval Rec: Frame Rate] (📖 202) > Desired option.

4 Press the REC button to begin recording.

- The tally lamp changes from green (power indicator) to red.
- [INT STBY] changes to [INT ● REC] while recording.
- The camera automatically records the set number of frames at the specified interval.

5 Press the REC button again to stop recording.

- The tally lamp changes from red to green (power indicator) and [INT STBY] appears at the top of the screen (with [INT] flashing).

6 Select > [Recording/Media Setup] > [Recording Mode] > [Normal Recording] to stop interval recording.

 NOTES

- Interval recording cannot be used when the frame rate is set to 59.94i or 50.00i. When in use, interval recording will end if the frame rate is set to 59.94i or 50.00i.
- The interval and the number of frames recorded cannot be changed while recording.
- The same image as the last frame when interval recording was stopped may be recorded and added to the end of the clip.
- **About the time code when interval recording is activated:**
 - The time code mode can be set to [Regen.], or to [Preset] with [Rec Run] running mode. The time code advances by the number of frames recorded every time.
 - If the time code running mode was set to [Free Run] or the camera was synchronized to an external time code signal, the time code running mode will be changed automatically to [Rec Run] when interval recording is activated.
 - When the special recording mode is deactivated, the time code will return to its previous setting.
 - The time code will not be output from any terminal.

Using Anamorphic Lenses

You can attach an anamorphic lens to the camera and set the anamorphic desqueeze ratio used to display the image from the camera on monitoring devices while shooting or during playback.

- 1 Select **MENU** > [ Monitoring Setup] > Desired [Anamorphic:] setting > [On].
- 2 Select **MENU** > [ Monitoring Setup] > [Anamorphic Desqueeze] > Desired option.
- 3 If necessary, select **MENU** > [ Monitoring Setup] > [Desqueeze for S&F] > [Reduced Display].
 - When slow & fast motion recording is activated, the desqueezed image can only be displayed windowboxed ([Reduced Display]).

Options

[Lens Squeeze Factor]:

The desqueeze factor is linked to the **MENU** > [ Recording/Media Setup] > [Metadata] > [Lens Squeeze] setting.

- [x2.0]: Stretches the video horizontally by a factor of 2.
 [x1.8]: Stretches the video horizontally by a factor of 1.8.
 [x1.3]: Stretches the video horizontally by a factor of 1.3.




NOTES

- You can record the lens's squeeze factor in the clip's metadata with the **MENU** > [ Recording/Media Setup] > [Metadata] > [Lens Squeeze] setting.
- If [Anamorphic: HDMI] is set to [On] when the HDMI OUT terminal's resolution is set to [4096x2160 / 3840x2160] and the frame rate is set to 59.94P or 50.00P, the video output from the HDMI OUT terminal will be a 1920x1080 image.
- If [Anamorphic: SDI] is set to [On], 4K output (4096x2160 / 3840x2160) at 59.94P / 50.00P to the SDI OUT terminal is converted to 2K output (2048x1080 / 1920x1080).
- The image displayed during photo playback and the camera's live view image in the Browser Remote application will not be desqueezed.

Web Camera Function

You can connect the camera to a computer using an interface cable, and use the camera as a web camera (with compatible software). Only video can be recorded while using this function. For more details about supported operative systems or software tested for use with the camera, visit your local Canon website. For more details, refer to the computer's instruction manual.

When connecting the camera to a computer, use a Canon cable.



Video output configuration

Main resolution	Video format	Resolution	Frame rate
3840x2160, 1920x1080	Motion JPEG	1024x576	30 fps (maximum)
6000x3164, 4368x2304, 4096x2160, 2048x1080		1088x576	

- 1 Select **MENU** > [🔧 System Setup] > [USB Mode] > [Video Output (UVC)].
- 2 Connect the camera to a computer.
- 3 Open the desired compatible software on the computer.
- 4 When the connection ends, disconnect the interface cable from the camera.


NOTES

- This function cannot be used simultaneously with IP streaming, the Browser Remote function ( 187), XC protocol ( 193) or while shooting photos.

Using the RC-V100 Remote Controller

You can connect the RC-V100 Remote Controller to the camera in order to control the camera (including advanced recording functions) from a distance. The remote controller lets you turn the camera on, navigate the menus and remotely control the aperture and shutter speed, change picture-related settings like the knee and sharpness, and more.

For details on how to connect and use the remote controller, refer to its instruction manual.



1 Turn off the camera and connect the RC-V100 Remote Controller to the camera.

2 Turn on the camera in CAMERA mode.

3 Select **MENU** > [🔧 System Setup] > [REMOTE Term.] > [RC-V100 (REMOTE A)].

Options

[RC-V100 (REMOTE A)]:

Select this option to use the RC-V100 connected to the camera with the RC-V100's remote cable.

[Standard]:


Select this option to use commercially available remote controls.

NOTES

- The AUTO KNEE button and AF button will have no effect on the camera.
- The AUTO IRIS button on the remote controller can operate the camera only when a lens compatible with auto iris (📖 249) is attached to the camera.
- The ZOOM dial on the remote controller can operate the lens only when a compatible lens (📖 249) is attached to the camera.

Assignable Buttons

The camera offers a number of assignable buttons to which you can assign various function. Assign often-used functions to the buttons you find most convenient to personalize the camera to your needs and preferences. You can find 13 assignable buttons on the camera's body, and 4 assignable buttons on the RC-V100 Remote Controller, RC-IP100/RC-IP1000 Remote Camera Controller, Remote Camera Control Application, and Multi-Camera Control. In most cases, the names of the buttons printed on the camera and accessories also indicate their default settings.



Changing the Assigned Function

Functions can be set separately in CAMERA mode and MEDIA mode.

- 1 Press the MENU button and, while holding it pressed down, press the assignable button whose function you wish to change.
 - A list of available functions appears.
 - You can also select the appropriate menu setting from the various pages of the **MENU** > [🔍 Assignable Buttons] menu.
- 2 Select the desired function.
 - The selected function will be assigned to the selected button.
- 3 If you selected [User Setting], select the menu setting you want to register.
 - The selected menu setting will be assigned to the selected button. User-selected settings will be indicated with a **MENU** icon in the [🔍 Assignable Buttons] menu.
- 4 Press the assignable button to use the assigned function as described in the following table.

NOTES

- You can check the [Assignnable Buttons] status screens (213) to see what functions are currently assigned to each button.
- You can reset only the functions assigned to the assignable buttons, without affecting other camera settings, with the **MENU** > [System Setup] > [Reset] > [Assignnable Buttons] function. All the assignable buttons will return to their default function.
- When you select **MENU** > [Assignnable Buttons] > [Link to Camera] > [Enable], the functions assigned to assignable buttons 1–4 on the camera can also be assigned to assignable buttons 1–4 of the RC-V100, RC-IP100/RC-IP1000, Remote Camera Control Application, and Multi-Camera Control.

Assignnable functions

Functions whose names include a video output destination (LCD, terminal name) affect only the specified video output, while [All] indicates the function affects all video outputs.

Function name	Description	CAMERA mode	MEDIA mode	
[One-Shot AF] ¹	The camera focuses automatically one time only (one-shot AF function).	●	–	83
[AF Lock]	Turns the AF lock function on/off.	●	–	85
[AF Lock (While Pressed)] ^{1, 2}	Activates the AF lock function while the button is held pressed down.			
[AF Frame]	Toggles the type of the AF frame.	●	–	85
[Focus Mode]	Toggles the focus mode between AF (autofocus) and MF (manual focus).	●	–	80
[Face Detection AE]	Turns face detection AE on/off	●	–	86
[Subj. detect. AF]	Toggles the [Subj. detect. AF] setting between [Detect. priority] and [Detect. only].	●	–	86
[Subject to detect]	Switches the subject to be detected.	●	–	86
[Eye Detection]	Turns eye detection on/off.	●	–	–
[Tracking]	Enters/cancels tracking standby mode.	●	–	87
[Focus Guide]	Turns the focus guide on/off.	●	–	81
[Peaking: All], [Peaking: LCD], [Peaking: SDI], [Peaking: HDMI]	Turns peaking on/off.	●	–	82
[Magnification], [Magn.: LCD], [Magn.: SDI], [Magn.: HDMI]	Turns magnification on/off.	●	–	82
[Tele-converter]	Cycles through the digital tele-converter options in the following order: x1.5 → x2.0 → x2.5 → x3.0 → Off.	●	–	90
[Push Auto Iris] ¹	The camera automatically adjusts the aperture only while the button is held pressed down.	●	–	74
[Iris Mode]	Switches the aperture adjustment mode between automatic and manual.	●	–	73
[Iris +], [Iris –]	Opens up/closes the aperture, respectively.	●	–	
[ND +], [ND –]	Cycles through ND filter settings in increasing (higher density) or decreasing (lower density) order, respectively.	●	–	72
[Auto Clear Scan Setting]	Displays the [Auto Clear Scan Setting] screen	●	–	67
[Base ISO]	Switches between base ISO speed settings.	●	–	68
[ISO/Gain Mode]	Changes the ISO speed/Gain adjustment mode.	●	–	68
[AE Shift +], [AE Shift –]	Compensates the exposure making the image brighter/darker, respectively.	●	–	75
[Backlight], [Spotlight]	Toggles the light metering mode between [Standard] and [Backlight]/[Spotlight], respectively.	●	–	76

Function name	Description	CAMERA mode	MEDIA mode	
[Zebra: All], [Zebra: LCD], [Zebra: SDI], [Zebra: HDMI]	Turns zebra patterns on/off.	●	—	93
[WFM: All], [WFM: LCD], [WFM: SDI], [WFM: HDMI]	Turns the selected video scope on/off.	●	●	108
[View Assist: All], [View Assist: LCD], [View Assist: SDI], [View Assist: HDMI]	Turns view assistance on/off.	●	—	159
[False Color: All], [False Color: LCD], [False Color: SDI], [False Color: HDMI]	Turns the false color overlay on/off.	●	—	94
[False Color Index]	Displays/hides the false color index screen.			
[White Balance]	Enters the direct setting mode with the white balance mode highlighted and ready to be adjusted.	●	—	77
[Set White Balance]	Starts the white balance calibration for a custom white balance setting.	●	—	78
[AWB Lock] ¹	While using auto white balance (AWB), locks the current white balance settings.	●	—	79
[ AWB], [ Set A], [ Set B], [ Daylight], [ Tungsten], [ Kelvin]	Changes the white balance mode/setting to the respective option.	●	—	77
[Lens Optical IS]	Turn lens optical IS on/off.	●	—	—
[Digital IS]	Turns the digital image stabilizer (digital IS) on/off.	●	—	88
[Pause Digital IS] ¹	Pauses/resumes the digital IS function. Switching is possible while recording. The angle of view is maintained even when the digital IS function is temporarily paused.	●	—	88
[LCD Setup]	Opens the [ Monitoring Setup] menu page with the settings for adjusting the LCD screen.	●	●	204
[OSD Output: SDI], [OSD Output: HDMI]	Turns the camera's onscreen displays on/off.	●	●	157
[OSD Opacity: All], [OSD Opacity: LCD], [OSD Opacity: SDI], [OSD Opacity: HDMI]	Changes the transparency level of onscreen displays.	●	●	157
[DISP]	Changes the onscreen display level.	●	●	53
[OSD Orientation: LCD]	Changes the onscreen display direction in the following order: standard, 90 degrees rotation, 270 degrees rotation.	●	—	55
[Markers: All], [Markers: LCD], [Markers: SDI], [Markers: HDMI]	Turns onscreen markers on/off.	●	●	91
[Color Bars]	Turns color bars on/off.	●	—	107
[IP Streaming]	Turns the IP streaming function on/off.	●	—	185
[Photo] ¹	Records a photo.	●	—	48
[Review Recording] ¹	Plays back the last clip recorded in CAMERA mode.	●	—	55
[Time Code]	Opens the [ System Setup] menu page with the time code settings.	●	—	95

Function name	Description	CAMERA mode	MEDIA mode	
[Add Shot Mark] ¹	Adds a shot mark to the clip.	●	●	110, 149, 149
[Add  Mark], [Add  Mark]	Adds an  or  mark to the clip.	●	●	
[Headphones +], [Headphones -]	Increases/reduces the headphone volume, respectively.	●	●	146
[Monitor Channels]	Switches the audio channels output from the  (headphone) terminal and the built-in speaker.	●	●	160
[Audio Level Indicator]	Turns the audio level meter on/off.	●	●	103
[FUNC]	Enters the direct setting mode.	●	—	57
[Slow & Fast Motion]	Turns slow & fast motion recording on/off.	●	—	114
[Slow & Fast Frame Rate]	When slow & fast motion recording is activated, highlights the shooting frame rate in order to adjust it.			
[Output: 60 ⇄ 60 (24) fps] ^{1, 3, 4} , [Output: 60 ⇄ 60 (30) fps] ^{1, 3, 4}	When the frame rate is 59.94P or 59.94i, toggles the frame rate of video output terminals and the LCD screen between said frame rates and 24 fps or 30 fps, respectively.	●	—	—
[Iris]	Enters the direct setting mode with the aperture value highlighted and ready to be adjusted.	●	—	73
[Shutter]	Enters the direct setting mode with the shutter speed highlighted and ready to be adjusted.	●	—	66
[ISO/Gain]	Enters the direct setting mode with the ISO speed or gain value highlighted and ready to be adjusted.	●	—	69
[Status] ¹	Displays the status screens.	●	●	213
[Audio Status]	Displays the [] Audio Setup] status screens. You can press SET to open the [] Audio Setup] menu.	●	●	213
[MENU]	Displays the menu.	●	●	—
[Custom Picture]	Opens the [] Custom Picture] menu.	●	—	129
[My Menu]	Opens the [] My Menu] customized menu.	●	—	27
[Initialize Media]	Opens the [Initialize Media] submenu.	●	●	37
[Play/Pause]	Pauses and resumes the playback.	—	●	142
[INDEX/Cancel Resume]	Returns to the index screen. The next time the clip is selected, playback will start from the beginning.	—	●	142
[INDEX]	Returns to the index screen. The next time the clip is selected, playback will start from the frame where it stopped.			
[Slot Selection]	Switches between card slots.	●	●	38
[Select File]	File selection.	—	●	—
[Refine]	Switches [Refine] (refining clip selection) on/off.	—	●	—
[REC]	Functions as the REC button. Can only be assigned to assignable button Camera 4 and 11.	●	—	47
[CAMERA ⇄ MEDIA] ^{2, 5}	Switches between CAMERA mode and MEDIA mode.	●	●	—
[ MENU] User Setting] ¹	Customizable slot. Assign to the button any menu setting you would like to register.	●	●	—

¹ Function can be used only by assigning it to a button.

² Cannot be used with XC Protocol.

³ Not available when slow & fast motion recording is activated.

⁴ Cannot be used when [HDMI RAW] is set to [On].

⁵ Cannot be set with Browser Remote/XC Protocol. Even when [Link to Camera] is set to [Enable], operation from Browser Remote or XC protocol is not possible.

Custom Picture Settings

The camera lets you change many settings (📖 134) that control various aspects of the image produced. As a set, all these settings are treated as a single custom picture file. After adjusting the desired settings to your preference, you can save up to 20 custom picture files (in the camera or on an SD card), and load them later to apply exactly the same settings (📖 132). You can also save the custom picture file as part of the metadata recorded with clips (📖 134). Custom picture settings do not affect the recording or output of RAW clips.

Selecting Custom Picture Files

In CAMERA mode, select a custom picture file to apply its settings to your recordings or to edit, rename, protect, or transfer it.

1 Select **MENU** > [📷 Custom Picture] > [Select 📷 File].

- The custom picture file selection screen is displayed.
- Select one of the custom picture files saved in the camera (C1 to C20). To use the settings of a custom picture file saved on an SD card, copy the file to the camera in advance (📖 133).
- You can also use direct touch control's 📷 recording settings (📖 56).

2 Select the desired file.

- When you close the menu, the selected custom picture file's settings will be applied.

Preset Picture Settings

The following settings are saved to custom picture files C1 to C20 as preset custom picture settings. Custom picture files C1 to C9 are protected by default and need to be unprotected before they can be edited.

Preset custom picture file	[Gamma/Color Space]*	[Color Matrix]	[Look File]	Characteristics
C1: [Canon 709]	[Canon 709 / BT.709]	[Neutral]	—	These settings produce a look appropriate also for use without post processing, featuring high contrast while ensuring a wide dynamic range optimized for playback on BT.709 compliant monitors.
C2: [Canon Log 2]	[Canon Log 2 / C.Gamut]		—	These settings use Canon Log 2 gamma and require post-production processing. They achieve superior gradation in the shadows (dark areas of the image).
C3: [Canon Log 3]	[Canon Log 3 / C.Gamut]		—	These settings use Canon Log 3 gamma and require post-production processing. They keep the [Canon Log] gamma characteristics while expanding its dynamic range.
C4: [BT.709 Wide DR]	[BT.709 Wide DR / BT.709]		—	These settings produce a wide dynamic range and are appropriate for playback on BT.709 compliant monitors.
C5: [BT.709 Standard]	[BT.709 Standard / BT.709]	[Video]	—	These settings are appropriate for playback on BT.709 compliant monitors, and use a gamma curve that meets ITU-R BT.709 standards.

Preset custom picture file	[Gamma/Color Space]*	[Color Matrix]	[Look File]	Characteristics
C6: [PQ]	[PQ / BT.2020]	[Neutral]	–	These settings use a high dynamic range gamma curve compliant with the PQ standard defined by ITU-R BT.2100**.
C7: [HLG]	[HLG / BT.2020]		–	These settings use a high dynamic range gamma curve compliant with the HLG standard defined by ITU-R BT.2100**.
C8: [EOS Standard]	[BT.709 Wide DR / BT.709]		On	Reproduces the image quality and look of an EOS interchangeable lens DSLR camera with its picture style set to [Standard].
C9: [EOS Neutral]	[BT.709 Wide DR / BT.709]		On	Reproduces the image quality and look of an EOS interchangeable lens DSLR camera with its picture style set to [Neutral].
C10: [User10] to C20: [User20]	[Canon 709 / BT.709]		–	These settings produce a look appropriate also for use without post processing, featuring high contrast while ensuring a wide dynamic range optimized for playback on BT.709 compliant monitors.

* This setting is found under **MENU** > [CP Custom Picture] > [Edit CP File].

** ITU-R BT.2100 is a standard for a bit depth of 10 or 12 bits. When the video configuration is set to one of the 8 bit options, the gamma curve is approximately equivalent to this standard.



NOTES

About the logarithmic gamma curves (Canon Log settings)

- These gamma curves require post-production processing. They were designed to make the most of the imaging sensor characteristics in order to obtain impressive levels of dynamic range.
- In CAMERA mode, you can apply a view assistance function to the LCD screen's image to use gamma curve settings more suitable for viewing on a monitor screen.
- There are also other LUTs available that can be applied for processing in post-production. For the latest information on available LUTs, please visit your local Canon website.

About changing custom picture related settings using the RC-V100 Remote Controller

- When an RC-V100 Remote Controller is connected to the camera, you can press the remote controller's CUSTOM PICT. button to open the [CP Custom Picture] menu.
- If a protected custom picture file is selected on the camera, custom picture related settings cannot be changed using the remote controller.
- Adjusting custom picture related settings using the remote controller will change the settings registered under the currently selected custom picture file. If you want to keep an important custom picture file, copy it in advance to an SD card or select in advance a custom picture file you do not mind changing.

Editing a Custom Picture File's Settings

In CAMERA mode, adjust the image quality to your preference and save the settings as part of a custom picture file.

1 Select a custom picture file (📖 129).

2 Select **MENU** > [CP Custom Picture] > [Edit CP File].

- Select an unprotected custom picture file.

3 Select a setting you wish to change and select the desired option.

- Refer to *Available Custom Picture Settings* (📖 134) for details on the various settings.
- Repeat step 3 for other settings as necessary.
- When you close the menu, the new custom picture settings will be applied.

Renaming Custom Picture Files

- 1 Select a custom picture file (📖 129).
- 2 Select **MENU** > [**CP** Custom Picture] > [Edit **CP** File] > [Rename] > [Input].
 - Enter the desired file name (16 characters long) (📖 28).

Protecting Custom Picture Files

Protecting a custom picture file prevents its settings from being accidentally changed.

- 1 Select a custom picture file (📖 129).
- 2 Select **MENU** > [**CP** Custom Picture] > [Edit **CP** File] > [Protect] > [Protect].
 -  will appear next to the file name.
 - To remove the protection, select [Unprotect] instead.

Resetting Custom Picture Files

- 1 Select a custom picture file (📖 129).
- 2 Select **MENU** > [**CP** Custom Picture] > [Edit **CP** File] > [Reset].
- 3 Select a preset custom picture setting and then select [OK].
 - The custom picture file will be reset to the selected values.

Look Files

You can register LUT files created with Blackmagic Design's DaVinci Resolve as Look Files in the custom picture file. Using a Look File allows you to adjust the video quality of the recorded video. These adjustments apply also to proxy clips, photos, and screen/output terminals.

- 1 Insert the SD card with the desired Look File (.cube format, located in the root directory of the SD card) into the camera's SD card slot B.
- 2 Select a custom picture file. (📖 129)
- 3 Select **MENU** > [**CP** Custom Picture] > [Edit **CP** File] > [Gamma/Color Space] > Desired option.
- 4 Select **MENU** > [**CP** Custom Picture] > [Edit **CP** File] > [Look File Setup] > [Register].
 - The Look Files in the SD card will be displayed.
- 5 Select the desired Look File.
- 6 Select the [Gamma/Color Space] setting to use after the Look File is applied.
- 7 Select [OK] twice.
 - The selected Look File will be loaded and registered to the custom picture file.
 - The image quality adjustments set in the Look File will be applied, and **LOOK** will appear on the screen.
 - When disabling the image quality adjustments set in the Look File, select **MENU** > [**CP** Custom Picture] > [Edit **CP** File] > [Look File] > [Off].

NOTES

About Look files

- The camera supports LUT files (3D LUT/.cube format) in 17 grid or 33 grid format created with Blackmagic Design's DaVinci Resolve.
- LUT files with input ranges outside the 0 to 1 range in the header ("LUT_3D_INPUT_RANGE") are not supported.
- LUT files which include values outside of the 0 to 1 range in the data area are not supported.
- LUT files 2 MB and larger, as well as files with a name containing over 65 characters are not supported.
- Only the following characters can be used in the file name:
Numbers 0 to 9, upper/lower case letters a to z, underscore (_), hyphen (-), period (.) and a single byte space.
- Save a Look File to the root directory of the SD card.
- If the correct input/output gamma curve and color space conversion are not selected, video will not be output correctly.
- A Look File cannot be used if the [Gamma/Color Space], [HLG Color], [White Level 100%], or [Over 100%] settings are changed after registering it.
- When the gamma curve component of the [Gamma/Color Space] setting in the custom picture is set to either [BT.709 Standard] or [BT.709 Wide DR], super-white (video signal above 100%) and super-black (video signal below 0%) levels of brightness will be clipped. When the video signal contains super-white brightness levels, select **MENU** > [**CP** Custom Picture] > [Edit **CP** File] > [Other Functions] > [Over 100%] > [Press] and then activate the Look File to apply it to a signal compressed to 100%.
- When playing RAW clips, the Look File registered when the clip was recorded will only be applied to the thumbnail and not the clip itself.

Deleting a Look File

You can delete Look Files registered in custom picture files.

- 1 Select a custom picture file ( 129).
- 2 Select **MENU** > [**CP** Custom Picture] > [Edit **CP** File] > [Look File Setup] > [Delete] > [OK].
 - The Look File will be deleted and the image quality adjustments will be reversed to the original settings of the selected custom picture file.

Saving a Custom Picture File

Copying Custom Picture Files

You can copy custom picture files between the camera and SD card. Insert in advance into the camera the card where you want to save your custom picture files or the card that contains the custom picture file you want to load.

Copying a File from the Camera to an SD Card

- 1 Select a custom picture file ( 129).
- 2 Select **MENU** > [**CP** Custom Picture] > [Save **CP** File] > [Copy to SD Card B].
- 3 Select the destination file on the card and then select [OK].
 - Select an existing custom picture file to overwrite it or [New File] to save the settings as a new custom picture file on the card.
- 4 When the confirmation message appears, press SET.

 NOTES

- Custom picture files are exclusively compatible for use only with the same camera model.

Replacing a File in the Camera with a File on an SD Card

- 1 Select the custom picture file that you wish to replace ( 129).
- 2 Select **MENU** > [ Custom Picture] > [Save  File] > [Load from SD Card B].
- 3 Select the file with the settings that you want to replicate and then select [OK].
 - The file in the camera will be overwritten by the one on the card.
- 4 When the confirmation message appears, press SET.



Embedding the Custom Picture File in Clips (CAMERA Mode)


When you record after having set custom picture settings, you can have the custom picture file embedded in the metadata and saved along with the clips. When displaying the information screen in MEDIA mode, you can check the custom picture settings used at the time of recording.


Select **MENU** > [ Recording/Media Setup] > [Metadata] > [Add  File] > [On].

Available Custom Picture Settings

Menu items	Options / Additional information
[Gamma/Color Space]	[Canon Log 2 / C.Gamut], [Canon Log 3 / C.Gamut], [Canon Log 3 / BT.2020], [Canon Log 3 / BT.709], [Canon 709 / BT.709], [BT.709 Wide DR / BT.709], [BT.709 Standard / BT.709], [PQ / BT.2020], [HLG / BT.2020] Combination of gamma curve and color space settings that affects the overall look and color space of the image. Gamma curve [Canon Log 2]: Logarithmic gamma curve that obtains a richer color gradation in the dark areas of the image. Requires image processing in post-production. [Canon Log 3]: Logarithmic gamma curve that keeps the characteristics of the [Canon Log] setting while expanding its dynamic range. Requires image processing in post-production. [PQ]: HDR (high dynamic range) gamma curve compliant with the PQ standard defined by ITU-R BT.2100.* [HLG]: HDR (high dynamic range) gamma curve compliant with the HLG standard defined by ITU-R BT.2100.* [BT.709 Wide DR]: Gamma curve with a very wide dynamic range. Optimized for playback on BT.709 compliant monitors. Equivalent to the [Wide DR] setting in previous camera models. [BT.709 Standard]: Gamma curve that meets ITU-R BT.709 standards, for playback on BT.709 compliant monitors. Equivalent to the [Normal 3] setting in previous camera models. [Canon 709]: Gamma curve appropriate also for use without post processing, featuring high contrast while ensuring a wide dynamic range. Use this when outputting to a BT.709 compliant monitor. * ITU-R BT.2100 is a standard for a bit depth of 10 or 12 bits. When the video configuration is set to one of the 8 bit options, the gamma curve is approximately equivalent to this standard. Color space [C.Gamut]: Color space developed by Canon based on the specific characteristics of the camera's imaging sensor. It covers a wider color gamut than that of BT.2020. Use this setting with workflows that require ACES2065-1 color space. [BT.2020]: Color space that meets ITU-R BT.2020 standards, which defines parameters for ultra-high-definition television (4K/8K). [BT.709]: Standard color space that is compatible with sRGB specifications.
[Color Matrix]	[Neutral], [Production Camera], [Video] The color matrix affects the overall color tonality of the image. [Neutral]: Reproduces neutral colors. [Production Camera]: Reproduces colors more suitable for motion picture production. [Video]: Reproduces colors with a contrast suitable for TV broadcasting.
[Look File]	[On], [Off] Image quality adjustments set in the Look File will be applied.
[Look File Setup]	
[Register]	Registers a Look File to a custom picture file.
[Delete]	Deletes a Look File registered to a custom picture file.



Menu items	Options / Additional information
[HLG Color]	[BT.2100], [Vivid] Changes the quality of color reproduction when using the hybrid log gamma (HLG). This setting is only available when [Gamma/Color Space] is set to [HLG / BT.2020]. [BT.2100]: Color reproduction according to ITU-R BT.2100 specifications. [Vivid]: More saturated color reproduction according to the 'Traditional Colour' approach in ITU-R BT.2390.
[Black]	
[Master Pedestal]	–50 to +50 (±0) Increases or decreases the black level. Higher settings will make dark areas brighter but decrease contrast. This setting is not available when the gamma curve component of the [Gamma/Color Space] setting is set to one of the [Canon Log 2] or [Canon Log 3] options.
[Master Black Red], [Master Black Green], [Master Black Blue]	–50 to +50 (±0) These settings correct the color cast in blacks. These settings are not available when the gamma curve component of the [Gamma/Color Space] setting is set to one of the [Canon Log 2] or [Canon Log 3] options.
[Black Gamma]	
[Level]	–50 to +50 (±0)
[Range], [Point]	–20 to +50 (±0)
	These settings control the lower part of the gamma curve (dark areas of the image). These settings are only available when the gamma curve component of the [Gamma/Color Space] setting is set to one of the [BT.709 Standard] options. [Level]: Raises or lowers the lower part of the gamma curve. [Range]: Selects the adjustment range from the selected [Point]. [Point]: Determines the shape of the lower part of the gamma curve.
[Low Key Saturation]	
[Activate]	[On], [Off] Set this setting to [On] to enable the adjustment of color saturation in dark areas with the [Level] setting.
[Level]	–50 to +50 (±0) Specifies how saturated colors are in dark areas.
[Knee]	
[Activate]	[On], [Off] Set this setting to [On] to enable the adjustment of the knee point with the following settings. These settings are only available when the gamma curve component of the [Gamma/Color Space] setting is set to one of the [BT.709 Standard] options.
[White Level 100%]	[On] , [Off]
[Slope]	–35 to +50 (---)
[Point]	50% to 100% (85%)

Menu items	Options / Additional information
[Saturation] –10 to +10 (±0) 	These settings control the upper part of the gamma curve (highlights of the image). By compressing the highlights, you can prevent parts of the image from being overexposed. [White Level 100%]: Adjusts automatically to keep output at 100% even if [Point] is changed. [Slope]: Determines the slope of the gamma curve above the knee point (can only be adjusted if [White Level 100%] is set to [Off]). [Point]: Sets the knee point of the gamma curve. When [White Level 100%] is set to [Off], it is adjusted within a range of 50% to 109%. [Saturation]: Adjusts the color saturation in the highlights.
[Sharpness]	
[Level]	–10 to +50 (±0) Sets the sharpness level of the video output signal and the recorded signal.
[Detail Frequency]	–8 to +8 (±0) Sets the center frequency of horizontal sharpness. Setting higher values increases the frequency, which, in turn, increases the sharpness.
[Coring Level]	–30 to +50 (±0) Sets the level of correction of artifacts caused by high sharpness levels (coring). Higher values prevent sharpness from being applied to minute details, resulting in less noise.
[Limit]	–50 to +50 (±0) Restricts how much sharpness is applied.
[Noise Reduction]	
[Automatic]	[On], [Off] Adaptively changes the noise reduction effect.
[Spatial Filter]	[Off], 1 to 12 Reduces noise by applying a soft focus-like effect on the entire picture. When set to a value other than [Off], afterimages are not produced but the whole image will have a softer look.
[Frame Correlation]	[Off], 1 to 3 Reduces noise elements by comparing the current image to the previous one (field). When set to a value other than [Off], the perceived resolution will not be affected but an afterimage may appear for moving subjects.
[Skin Detail]	
[Effect Level]	[Off], [Low], [Middle], [High]
[Hue]	–16 to +16 (±0)
[Chroma], [Area], [Y Level]	0 to 31 (16)
	The camera applies a softening filter to areas in the picture with skin tones to give a more pleasant appearance. By changing these settings, you can determine what areas will be detected as skin tones. A zebra pattern will appear on the screen or video output terminal over areas of the image that are detected as having skin tones. [Effect Level]: Adjusts the level of the filter. [Hue]: Adjusts the hue for detection of skin tones. [Chroma]: Adjusts the color saturation for detection of skin tones. [Area]: Adjusts the color range for detection of skin tones. [Y Level]: Adjusts the brightness for detection of skin tones.

Menu items	Options / Additional information
[Color Matrix Tuning]	
[Gain]	–50 to +50 (±0)
[Phase]	–18 to +18 (±0)
	These settings adjust the color intensity ([Gain]) and color phase ([Phase]) of the color matrix, affecting the color tones of the whole image.
[R-G], [R-B], [G-R], [G-B], [B-R], [B-G]	–50 to +50 (±0)
	Each matrix changes the tint of the picture along the color gradations detailed below, affecting the color tones of the whole image. [R-G]: cyan/green and red/magenta; [R-B]: cyan/blue and red/yellow; [G-R]: magenta/red and green/cyan; [G-B]: magenta/blue and green/yellow; [B-R]: yellow/red and blue/cyan; [B-G]: yellow/green and blue/magenta.
[White Balance]	
[R Gain], [G Gain], [B Gain]	–50 to +50 (±0)
	These settings adjust the amount of white balance throughout the whole image by changing the intensity of red tones ([R Gain]), green tones ([G Gain]), and blue tones ([B Gain]).
[Color Correction]	
[Select Area]	[Off] , [Area A], [Area B], [Area A&B]
	The camera detects areas with certain color characteristics (color phase, chroma, area and Y level) and corrects them when recording. You can set the color correction for up to two different areas (A and B) and apply the color correction to either one ([Area A] or [Area B]) or both of them ([Area A&B]). While color correction is activated, parts of the image that are not detected as having the characteristics specified for area A or B will appear colorless on the screen or the image output from the output terminals (except when adjusting the [Revision Level]/[Revision Phase] settings).
[Area A Setting Phase], [Area B Setting Phase]	0 to 31 (0)
	These settings determine the color phase of the area to be corrected (A or B, respectively).
[Area A Setting Chroma], [Area B Setting Chroma], [Area A Setting Area], [Area B Setting Area], [Area A Setting Y Level], [Area B Setting Y Level]	0 to 31 (16)
	These settings determine the following color characteristics of the area to be corrected (A or B, respectively). [Area A Setting Chroma], [Area B Setting Chroma]: Color saturation. [Area A Setting Area], [Area B Setting Area]: Color range. [Area A Setting Y Level], [Area B Setting Y Level]: Brightness.
[Area A Revision Level], [Area B Revision Level]	–50 to +50 (±0)
	These settings adjust the amount of correction applied to the color saturation in the corrected area (A or B, respectively).
[Area A Revision Phase], [Area B Revision Phase]	–18 to +18 (±0)
	These settings adjust the amount of correction applied to the color phase in the corrected area (A or B, respectively).
[Other Functions]	
[Over 100%]	[Through] , [Press], [Clip]
	Determines how the camera handles video signals exceeding 100%. This setting is not available when the gamma curve component of the [Gamma/Color Space] setting is set to one of the [Canon Log 2], [Canon Log 3], [PQ], [HLG] or [Canon 709] options. [Through]: Leave the signal unchanged. [Press]: Compress a signal of up to 108% down to 100% levels. [Clip]: Clip the signal at 100%.

NOTES

- Depending on other menu settings, you may not be able to obtain the desired image effect even after changing the custom picture settings.

- When an RC-V100 Remote Controller is connected to the camera, the following custom picture settings can be changed using the buttons and dials on the remote controller.
 - [Black] > [Master Pedestal], [Master Black Red], [Master Black Blue]
 - [Black Gamma] > [Level]
 - [Knee] > [Slope], [Point] (only when [Knee] > [Activate] is set to [On])
 - [Sharpness] > [Level]
 - [White Balance] > [R Gain], [B Gain]

Saving and Loading Menu Settings

After you adjust settings in the various menus, you can save those settings in the camera or on SD card B. You can load those settings at a later date or on another camera of the same model so that you can use that camera in the same way.

Saving Menu Settings

- 1 Select **MENU** > [🔧 System Setup] > [Transfer Menu/📁] > [Save].
- 2 Select [To Camera] or [To SD Card B] and then select [OK].
 - The camera's menu settings will be saved to the selected destination. If menu settings were previously saved, the old file will be overwritten by the current menu settings.

Loading Menu Settings

- 1 Select **MENU** > [🔧 System Setup] > [Transfer Menu/📁] > [Load].
- 2 Select [From Camera] or [From SD Card B] and then select [OK].
 - The camera's menu settings will be replaced by the settings in the previously saved file. Then, the screen will turn black momentarily and the camera will restart.

NOTES

- The following menu settings are not saved with this operation.
 - **MENU** > [📷 Camera Setup] > [ABB], [Color Bars]
 - **MENU** > [📁 Recording/Media Setup] > [Metadata] > [News Metadata], [User Memo]
 - **MENU** > [📷 Assistance Functions] > [Magnification], [Magn. Output], [False Color Index]
 - **MENU** > [📷 Assistance Functions] > [Waveform Settings] > [Size: LCD]
 - **MENU** > [🌐 Network Settings] > [Advanced Settings] > [FTP Transfer Settings]
 - **MENU** > [🔧 System Setup] > [Level Reference Setting]
- When menu settings are loaded with this operation, even protected custom picture files in the camera will be replaced.

Playback

This section explains how to play back clips, photos and WAV audio with the camera. For details on playing back recordings using an external monitor, refer to *Connecting to an External Monitor or Recorder* (154).

Displaying the Index Screen

Press the MEDIA button (15)

- The camera is set to MEDIA mode and the clip thumbnails will appear in the index screen.
- Use the joystick or the SELECT dial to move the orange selection frame.
- Flick up/down on the screen or turn the front control dial to move to the next/previous page.




- | | |
|--|---|
| 1 Key lock (15) | 13 Power supply level (51) |
| 2 Shot mark (149) | 14 Clip number / Total number of clips |
| 3 mark / mark (149) | 15 Recording date (month and day only) and time |
| 4 Orange selection frame | 16 Clip's start time code |
| 5 Proxy clip (64) | 17 Clip duration |
| 6 Clip identification (camera index, reel number, clip number and clip/audio file name) (42) | 18 Custom picture file embedded (134) |
| 7 Recording date and time | 19 Special recording mode (114) |
| 8 Network status / functions (183) | 20 Color sampling and resolution, audio recording format |
| 9 Recording media A / B | <ul style="list-style-type: none"> • For RAW clips, RAW mode (ST/LT) and resolution are displayed. |
| 10 File selection (143) | 21 Frame rate (62) |
| 11 Index screen currently displayed (142) | <ul style="list-style-type: none"> • For slow & fast motion recording clips, the recording/playback frame rate is displayed. |
| 12 Clip thumbnail | |

NOTES

- If the card contains XF-AVC clips recorded at a system frequency other than the one currently used by the camera, you will not be able to play back the clips and the clip thumbnails will not appear in the index screen. To play back such clips, change the camera's system frequency ( 61) to match the recordings on the card.

Switching Card Slots


If both card slots contain a card, press the SLOT SELECT button to play back recordings from the other card. You can also switch card slots by touching the orange dot next to the card currently selected.



Switching Index Screens

The clip index screen that appears when you switch to MEDIA mode depends on the current recording settings.

- 1 Press the INDEX button.
 - The index screen selection menu appears.
- 2 Select the desired index screen.
 - The selected index screen appears.
 - Select [Cancel] to return to the previous index screen.



Options

[RAW Index]: Clips in RAW format.

[XF-AVC Index]: Clips in XF-AVC format.

[XF-HEVC S / XF-AVC S Index]:
Clips in XF-HEVC S / XF-AVC S format.

[Photo index]: Photos recorded on the card.


[WAV Index]: Audio files (WAV format).

Playing Back Recordings

After selecting the desired index screen, play back the desired clips, photos or audio files. You can use the touch screen or assignable buttons to play back the recordings.

Touch the thumbnail of the recording you want to play back.

- Playback will start.
- You can also move the orange selection frame using the joystick or the SELECT dial, and then press and hold the SET button (for approximately 1 second) to start playback.
- Touch the screen or press the joystick to pause/resume playback.
- Press the INDEX button or flick the screen down to stop the playback and return to the index screen.



- While browsing photos, press the joystick left/right to move to the previous/next photo.

Custom picture settings of RAW clips during playback

RAW clips are played back using the following custom picture settings.

- [Gamma/Color Space]: Same setting used for recording
- [Color Matrix]: [Neutral]
- Contour lines are de-emphasized in a way similar to setting [Sharpness] > [Level] to -10.
- Other settings are set to [Off].

Lens Correction of RAW clips during playback

- Depending on the shooting settings, peripheral illumination/chromatic aberration/distortion aberration of the shooting lens is corrected and applied during playback.

NOTES

- The following image files may not be displayed correctly.
 - Images not recorded with this camera.
 - Images edited on a computer.
 - Images whose file names have been changed.


Refining Clip Selection for Playback

Play back only the selected clips in succession.

- 1 Touch  on the index screen.
 - The file selection screen is displayed.
 - Touch  to return to the index screen.
- 2 Touch a thumbnail to select a clip, then touch .
 - The Refine screen is displayed.
 - Touch  to return to the file selection screen, or  to return to the index screen.
- 3 Touch the desired thumbnail on the Refine screen.
 - Subsequent operations are the same as for *Playing Back Recordings*.
 - Once playback ends, the screen returns to the Refine screen.




File selection screen example



Refine screen example

Onscreen Displays During Clip Playback

144



- | | |
|--|---|
| 1 Fan operation (44) and temperature warning (226) | 8 Frame rate ² (62) |
| 2 Output onscreen displays (157) | 9 Custom picture file embedded ³ (134) |
| 3 Playback button ▶ | 10 ☐ mark ³ / ☒ mark ³ / Proxy clip (149, 64) |
| Advance 10 seconds ⏭ | 11 Time code (95) |
| Go back 10 seconds ⏮ | 12 Video format (62) |
| 4 Recording date and time ¹ | 13 Color sampling and bit depth (62) |
| 5 Frame reverse button ◀▶ | 14 Resolution (62) |
| Frame advance button ▶▶ | 15 Headphone volume (146) |
| 6 Base ISO | 16 Audio level meter ⁴ |
| 7 Playback operation | 17 Aperture value ⁵ (73) |
| ▶ PLAY Playback | 18 ISO speed/Gain ⁵ (68) |
| ⏸ PAUSE Playback pause | 19 Progress bar |
| 10 sec ▶▶ Advance 10 seconds | 20 Shutter speed ⁵ (66) |
| ◀◀ 10 sec Go back 10 seconds | 21 User bit (96) |
| ◀▶/▶▶ Frame reverse/Frame advance | 22 Audio output channels (160) |
| F FWD x5 Fast forward (speed: x5) | |
| F FWD x15 Fast forward (speed: x15) | |
| F FWD x60 Fast forward (speed: x60) | |
| F REV x5 Rewind (speed: x5) | |
| F REV x15 Rewind (speed: x15) | |
| F REV x60 Rewind (speed: x60) | |

¹ Only when [Monitoring Setup] > [Custom Display] > [Date/Time] is set to [On].

² For clips recorded using slow & fast motion recording, the shooting frame rate and playback frame rate will both be displayed.

³ XF-AVC clips only.

⁴ Only when [Monitoring Setup] > [Custom Display] > [Audio Level Indicator] is set to [On].


⁵ Only when [Monitoring Setup] > [Custom Display] > [Camera Data] is set to [On].

NOTES

- You can press the DISP button repeatedly to change the level of onscreen displays (53).

Audio (WAV) playback screen

See *Onscreen Displays During Clip Playback* (144) for the description of onscreen displays that are common on all playback screens.



- 1 Audio file name
- 2 Sampling frequency and bit depth
- 3 Audio level meter

Clip Playback Controls

The following playback types are available using the joystick and the touch screen. You can also change the position in the video using the progress bar.

Playback type	Operation
Fast playback ¹	During playback, push the joystick up or down. Repeat to increase the playback speed to approximately 5x → 15x → 60x the normal speed ² .
Advance 10 seconds	During playback, touch the right side of the screen twice. During playback pause, touch ⏸ on the right side of the screen.
Go back 10 seconds	During playback, touch the left side of the screen twice. During playback pause, touch ⏮ on the left side of the screen.
Frame advance/reverse	During playback pause, push the joystick up or down, or touch ◀▶ / ▶▶
Skip to the beginning of the next clip	During playback, push the joystick right, or flick the screen to the left.
Skip to the beginning of the current clip	During playback, push the joystick left.
Skip to the previous clip	During playback, push the joystick left twice, or flick the screen to the right.
Change the playback/playback pause position in the video	During playback/playback pause, touch or slide the progress bar.

¹ You may notice some anomalies (blocky video artifacts, banding, etc.) in the playback picture.

² The speed indicated on the screen is approximate.

NOTES


- There is no audio during any of the playback types listed in the previous table.
- You can press the ▶/■ button during fast playback to return to playback at normal speed.

Adjusting the Volume

You can use headphones or the built-in speaker to listen to the audio during normal playback. When you connect headphones to the  (headphone) terminal, the speaker will be muted. The audio signal will also be output from the SDI OUT terminal / HDMI OUT terminal.

1 Select **MENU** > [] Audio Setup] > [Headphone Volume] or [Speaker Volume].

2 Select the desired level.



NOTES

- For details on changing the audio channel, refer to *Audio Output* ( 160).
- If you set an assignable button to [Headphones +] or [Headphones -] ( 125), you can press the button to adjust the headphone volume without using the menu.

File Operations

You can perform various operations on the file selected in the index screen using the file menu. Available options will depend on the type of recording selected.

File Menu Operations

1 Select the desired recording.

2 Press SET.

- The file menu will be displayed. Available functions will differ depending on the recording.
- You can also touch the screen for approximately 1 second to display the file menu.

3 Select a menu item.

File menu options

Menu item	Description	Index screen				
		[RAW]	[XF-AVC]	[XF-HEVC S / XF-AVC S]	[Photos]	[WAV]
[Cancel]	Closes the menu.	●	●	●	●	●
[Play]	Starts playback.	●	●	●	●	●
[Display Clip Info]	Displays the information screen (148).	●	●	●	—	—
[Add  Mark] or [Delete  Mark] ^{1,2}	Adds or deletes an  mark (149, 149).	—	●	—	—	—
[Add  Mark] or [Delete  Mark] ^{1,2}	Adds or deletes a  mark (149, 149).	—	●	—	—	—
[Del. All Shot Marks] ¹	Deletes all the shot marks (150).	—	●	—	—	—
[Recover]	Recovers a recording.	●	●	●	—	●
[Delete]	Deletes a recording (150).	●	●	●	●	●
[Delete User Memo]	Deletes the user memo and GPS information of a clip (150).	—	●	●	—	—
[FTP Transfer]	Transfers a clip using the FTP protocol (184).	—	●	●	—	—
[Frame.io Upload]	Adds clip to the Frame.io upload queue.	—	● ³	● ³	—	● ³
[Stop]	Ends photo playback.	—	—	—	●	—
[Select]	Displays the file selection screen on the index screen. Alternatively, selects a file on the file selection screen.	●	●	●	—	—
[Deselect]	Clears selection for a file.	●	●	●	—	—
[Deselect All]	Clears selection for all files and returns to the index screen.	●	●	●	—	—
[Refine]	Displays the Refine screen.	●	●	●	—	—
[Reselect]	Returns from the Refine screen to the selection screen.	●	●	●	—	—
[End Refining]	Returns from the Refine screen to the index screen.	●	●	●	—	—

¹ Excluding proxy clips.

² If the clip already contains an  or  mark, the option to delete the mark will appear in the menu.

³ Only card slot B proxy clips and audio recordings (second card recording functions).

Displaying Clip Information

1 Select the desired clip in the clip index screen.

2 On the file menu, select [Display Clip Info].

- The [Clip Info] screen will appear.
- Push the joystick left/right or touch  on the screen to move to the previous/next clip. Press the CANCEL button to return to the index screen.



- | | |
|--|--|
| 1 Thumbnail of the selected clip | 11 Custom picture file embedded (📖 134) |
| 2 Clip geotagged with GPS information | 12 Proxy clip (📖 64) |
| 3 Thumbnail of the previous clip | 13 Color sampling and bit depth (📖 62) |
| 4 Thumbnail of the next clip | <ul style="list-style-type: none"> • For RAW clips, RAW mode (ST/LT) and bit depth are displayed. |
| 5 Special recording mode (📖 114) | 14 Lens model name |
| 6 Recording date and time | 15 Clip's start time code |
| 7 Clip file name (📖 42) | 16 Clip's end time code |
| 8 Compression, bit rate and resolution (📖 59) | 17 Clip duration |
| 9 Frame rate ¹ (📖 62) | |
| 10 Shot mark (📖 149) and  mark /  mark (📖 149) | |

¹ For clips recorded using slow & fast motion recording, the shooting frame rate and playback frame rate will both be displayed.

Displaying Additional Information (User Memo/News Metadata)

From the [Clip Info] screen, you can push the joystick up or down, or touch / on the screen to display user memo or News Metadata details. To return to the [Clip Info] screen, push the joystick in the direction displayed to the left of [Clip Info] at the bottom of the screen (/) or touch [Clip Info] at the top of the screen.

Displaying Custom Picture Settings

If a custom picture file was embedded with the clip, you can push the joystick up or down, or touch / on the screen to display the custom picture settings used. To return to the [Clip Info] screen, push the joystick in the direction displayed to the left of [Clip Info] at the bottom of the screen (/) or touch [Clip Info] at the top of the screen.

Adding OK Marks or ✓ Marks

You can add an OK mark (OK) or check mark (✓) to XF-AVC clips to help you identify particular clips. Since clips with an OK mark cannot be deleted with the camera, you can use this mark also to protect important clips.

Adding an OK Mark or ✓ Mark During Playback

You can add an OK mark or ✓ mark to a clip during playback or playback pause.

- 1 Set an assignable button to [Add OK Mark] or [Add ✓ Mark] (125).
- 2 During playback/playback pause of an XF-AVC clip, press the assignable button to add the clip mark.
 - [OK Mark] or [✓ Mark] will appear briefly and the selected clip mark will be added to the clip.
 - Playback will be paused.

Adding an OK Mark or ✓ Mark from the Index Screen

- 1 Select the desired clip from the XF-AVC index screen.
- 2 Press SET (file menu) and select [Add OK Mark] or [Add ✓ Mark] > [OK].
 - The selected clip mark is added to the clip.

NOTES

- A clip cannot have both an OK mark and ✓ mark at the same time. When you add a ✓ mark to a clip with an OK mark, the OK mark will be deleted. Similarly, when you add an OK mark to a clip with a ✓ mark, the ✓ mark will be deleted.

Deleting OK Marks or ✓ Marks

You can delete an OK mark or ✓ mark added to an XF-AVC clip.

- 1 Select the desired clip from the XF-AVC index screen.
- 2 Press SET (file menu) and select [Delete OK Mark] or [Delete ✓ Mark] > [OK].
 - The selected mark is deleted.

Adding/Deleting Shot Marks

During the playback of a clip recorded in XF-AVC format, you can add shot marks (S) to particular frames in the clip that you want to single out. You can also delete all shot marks at once.

Adding Shot Marks during Playback

- 1 Set an assignable button to [Add Shot Mark] (125).
- 2 During playback/playback pause of an XF-AVC clip, press the assignable button at the point in the clip where you want to add the shot mark.
 - [Shot Mark] will appear briefly and the shot mark will be added to the current frame of the clip.
 - Playback will be paused.

Deleting All the Shot Marks from a Clip

- 1 Select the desired XF-AVC clip in the index screen.
- 2 Press SET (file menu) and select [Del. All Shot Marks] > [OK].
 - All shot marks in the selected clip are deleted.

Deleting Recordings

You can delete clips, photos and audio files (WAV). To delete clips with an **OK** mark, you need to delete the **OK** mark beforehand (📖 149).

- 1 Select the desired file in the index screen.
 - Photos are selectable on the playback screen.
- 2 Press SET (file menu) and select [Delete] > [OK].
 - The file is deleted.
 - The operation cannot be canceled.



IMPORTANT

- **Be careful when deleting recordings. Once deleted, they cannot be recovered.**

Deleting the User Memo and GPS Information from a Clip

- 1 Select the desired clip in the index screen.
- 2 Press SET (file menu) and select [Delete User Memo] > [OK].
 - The user memo and GPS information that were recorded in the selected clip's metadata are deleted.

Video Output Configuration

The video signal output from the SDI OUT terminal / HDMI OUT terminal, depends on the clip's video configuration and on various menu settings.

Video Output Configuration (Recording/Playback)

Video configuration			MENU > [🔧 System Setup]		SDI OUT terminal		HDMI OUT terminal	
Recording format	Resolution	Frame rate	[SDI Output Signal]	[HDMI Output Signal]	Output format ¹	Output frame rate ²	Output format ¹	Output frame rate ²
RAW	4368x2304	59.94P, 50.00P	4096x2160P / 3840x2160P	4096x2160P / 3840x2160P	4096x2160	Same as shooting frame rate	4096x2160	Same as shooting frame rate
			2048x1080P / 1920x1080P	1920x1080P	2048x1080		1920x1080	
			1920x1080P		1920x1080			
			1920x1080i(PsF)	1920x1080i	1920x1080	59.94i, 50.00i	1920x1080	59.94i, 50.00i
			1280x720P	1280x720P	1280x720	Same as shooting frame rate	1280x720	Same as shooting frame rate
	6000x3164 4368x2304	29.97P, 25.00P, 24.00P, 23.98P	4096x2160P / 3840x2160P	4096x2160P / 3840x2160P	4096x2160	Same as shooting frame rate	4096x2160	Same as shooting frame rate
			2048x1080P / 1920x1080P	1920x1080P	2048x1080		1920x1080	
			1920x1080P		1920x1080			
			1920x1080i(PsF)	1920x1080i	1920x1080	29.97PsF(59.94i), 25.00PsF(50.00i), 60.00i, 59.94i	1920x1080	59.94i, 50.00i, 60.00i, 59.94i
			1280x720P	1280x720P	1280x720	59.94P, 50.00P, 60.00P, 59.94P	1280x720	59.94P, 50.00P, 60.00P, 59.94P

Video configuration			MENU > [F] System Setup]		SDI OUT terminal		HDMI OUT terminal		
Recording format	Resolution	Frame rate	[SDI Output Signal]	[HDMI Output Signal]	Output format ¹	Output frame rate ²	Output format ¹	Output frame rate ²	
XF-AVC XF-HEVC S XF-AVC S	4096x2160 3840x2160	59.94P, 50.00P	4096x2160P / 3840x2160P	4096x2160P / 3840x2160P	4096x2160 / 3840x2160	Same as shooting frame rate	4096x2160 / 3840x2160	Same as shooting frame rate	
			2048x1080P / 1920x1080P	1920x1080P	2048x1080 / 1920x1080		1920x1080		
			1920x1080P		1920x1080				
			1920x1080i(PsF)	1920x1080i	1920x1080	59.94i, 50.00i	1920x1080	59.94i, 50.00i	
			1280x720P	1280x720P	1280x720	Same as shooting frame rate	1280x720	Same as shooting frame rate	
	2048x1080 1920x1080		2048x1080P / 1920x1080P ³	1920x1080P ⁴	2048x1080 / 1920x1080	Same as shooting frame rate	1920x1080	Same as shooting frame rate	
			1920x1080P		1920x1080				
			1920x1080i(PsF)	1920x1080i	1920x1080	59.94i, 50.00i	1920x1080	59.94i, 50.00i	
			1280x720P	1280x720P	1280x720	Same as shooting frame rate	1280x720	Same as shooting frame rate	
	1280x720		1280x720P ³	1280x720P ⁴	1280x720	Same as shooting frame rate	1280x720	Same as shooting frame rate	
	4096x2160 3840x2160 2048x1080 1920x1080 1280x720	29.97P, 25.00P, 24.00P, 23.98P	4096x2160P / 3840x2160P	4096x2160P / 3840x2160P	4096x2160 / 3840x2160	Same as shooting frame rate	4096x2160 / 3840x2160	Same as shooting frame rate	
			2048x1080P / 1920x1080P	1920x1080P	2048x1080 / 1920x1080		1920x1080		
			1920x1080P		1920x1080				
			1920x1080i(PsF)	1920x1080i	1920x1080	29.97PsF(59.94i), 25.00PsF(50.00i), 60.00i, 59.94i	1920x1080	59.94i, 50.00i, 60.00i, 59.94i	
			1280x720P	1280x720P	1280x720	59.94P, 50.00P, 60.00P, 59.94P	1280x720	59.94P, 50.00P, 60.00P, 59.94P	
			2048x1080 1920x1080	2048x1080P / 1920x1080P ³	1920x1080P ⁴	2048x1080 / 1920x1080	Same as shooting frame rate	1920x1080	Same as shooting frame rate
				1920x1080P		1920x1080			
				1920x1080i(PsF)	1920x1080i	1920x1080	29.97PsF(59.94i), 25.00PsF(50.00i), 60.00i, 59.94i	1920x1080	59.94i, 50.00i, 60.00i, 59.94i
				1280x720P	1280x720P	1280x720	59.94P, 50.00P, 60.00P, 59.94P	1280x720	59.94P, 50.00P, 60.00P, 59.94P
			1280x720	1280x720P ³	1280x720P ⁴	1280x720	59.94P, 50.00P, 60.00P, 59.94P	1280x720	59.94P, 50.00P, 60.00P, 59.94P
	1920x1080	59.94i, 50.00i	1920x1080i(PsF) ³	1920x1080i ⁴	1920x1080	Same as shooting frame rate	1920x1080	Same as shooting frame rate	
			1280x720P	1280x720P	1280x720	59.94P, 50.00P	1280x720	59.94P, 50.00P	


¹ Color sampling will be YCC422 10 bit. The video signal's effective bit depth will be output.

- ² During slow & fast motion recording, the output frame rate will change depending on the output format of the terminal.
- When the resolution is [1920x1080i(PsF)]/[1920x1080i], it will be changed as follows: 59.94P / 29.97P / 23.98P → 59.94i, 50.00P / 25.00P → 50.00i, 24.00P → 60.00i.
 - When the resolution is a option other than the above, it will be changed as follows: 59.94P / 29.97P / 23.98P → 59.94P, 50.00P / 25.00P → 50.00P, 24.00P → 60.00P.
- ³ During playback (MEDIA mode), [4096x2160P/3840x2160P], [2048 x1080P/1920x1080P], [1920x1080P] and [1920x1080i(PsF)] can also be selected. Available options depend on the setting values.
- ⁴ During playback (MEDIA mode), [4096x2160P/3840x2160P], [1920x1080P] and [1920x1080i] can also be selected. Available options depend on the setting values.

Connecting to an External Monitor or Recorder

When you connect the camera to an external device, be it a monitor (to monitor the recording or for playback) or an external video recorder (for recording), adjust the required settings in the menu. For details about output signals, refer to *Video Output Configuration* (📖 151).

Connection diagram



NOTES

- Powering the camera from a power outlet using an AC adapter is recommended.
- If you set **MENU** > [🔧 Recording/Media Setup] > [Rec Command(EXT REC)] to [On] and connect the camera to another device using the SDI OUT or HDMI OUT terminal, you can control the recording operation on the other device in conjunction with the camera's recording operation (REC button). However, this function cannot be used during slow & fast motion recording, frame recording, interval recording or continuous recording.
When connecting to the HDMI OUT terminal, select [HDMI Time Code] > [On].

Using the SDI OUT Terminal

The digital signal that is output from the SDI OUT terminal includes the video signal, audio signal, time code signal, recording command signal, metadata and clip file name information. You can connect an external video recorder to the SDI OUT terminal to record 4K or 2K video. For details about configuring and using external recorders, refer to the instruction manual of the external device used.

- 1 Select **MENU** > [🔧 System Setup] > [SDI Output] > [On].
- 2 Select **MENU** > [🔧 System Setup] > [SDI Output Signal] > Desired option.

NOTES

- You can select a video output signal compliant with Level A of the SMPTE ST 425-1 standard.
- Depending on the external recorder, you may not be able to record at the desired video configuration.
- After you connect the camera to the external recorder, make a test recording first to check that audio and video are recorded correctly on the external recorder.

Using the HDMI OUT Terminal

The digital signal that is output from the HDMI OUT terminal includes the video signal and audio signal. You can output also the time code signal, recording command and various assistance displays (onscreen displays, markers, etc.) in order to check them also on an external monitor.

- 1 Connect the HDMI cable to the HDMI OUT terminal.
- 2 Select **MENU** > [🔧 System Setup] > [HDMI Output Signal] > Desired option.
- 3 To output the time code signal, select **MENU** > [⚙️ Recording/Media Setup] > [HDMI Time Code] > [On].

NOTES

- You can set **MENU** > [🔧 System Setup] > [Linked to HDMI Monitor] to [On] to automatically change the HDMI OUT terminal's output resolution according to the capabilities of the connected monitor. When this setting is set to [Off], the output resolution is set according to the menu settings and if the connected monitor is not compatible with the signal output from the camera, HDMI output will stop.
- The HDMI OUT terminal is for output only. Do not connect the camera to another device's output terminal using the HDMI OUT terminal as this will cause a malfunction.
- Correct operation cannot be guaranteed when connecting the camera to DVI monitors.
- Video may not be output correctly depending on the connected external monitor/recorder or the HDMI cable used. In such case, use another terminal.

RAW Video Output from the HDMI OUT terminal

You can output video in RAW format from the HDMI OUT terminal and perform 6K recording with a compatible recorder. During video output, you can also record video to card B simultaneously.

- 1 Select **MENU** > [⚙️ Recording/Media Setup] > [Sensor Mode] > [Full Frame].
- 2 Select **MENU** > [⚙️ Recording/Media Setup] > [System Frequency] > [59.94Hz] or [50.00Hz].
- 3 Select **MENU** > [⚙️ Recording/Media Setup] > [Frame Rate] > [59.94P] or [50.00P].
 - Change the main recording format to a format that allows you to select [Frame Rate] > [59.94P] or [50.00P].
- 4 Select **MENU** > [⚙️ Recording/Media Setup] > [HDMI RAW] > [On].
- 5 When recording to card B, select **MENU** > [⚙️ Recording/Media Setup] > [2nd Card Rec Functions] > an option other than [Off].

Video Output Configuration

Main recording video configuration			HDMI OUT terminal	
Main recording format	Main resolution*	Frame rate	Resolution	Frame rate
HDMI RAW	6000x3164	59.94P	4096x2160	59.94P
		50.00P		50.00P

* Bit depth will be 10 bit.

NOTES

- **MENU** > [⚙️ Recording/Media Setup] > [Recording Mode] is set to [Normal Recording].
- Image will not be displayed correctly when connected to a device that is not compatible with the camera's HDMI RAW output function.

When set to HDMI RAW, The following settings are not applied to video output from the HDMI OUT terminal:

- Any of the **MENU** > [Monitoring Setup] > [B&W Image:], [Anamorphic:], [OSD Output:], [OSD Orientation:], [View Assist:] options.
- Any of the **MENU** > [Assistance Functions] > [Peaking:], [False Color:], [Zebra:], [WFM:] or [Markers:] options.

When set to HDMI RAW, the following settings cannot be used:

- **MENU** > [Assistance Functions] > [Magn. Output] > [HDMI].
- **MENU** > [System Setup] > [HDMI Output Signal] and [Linked to HDMI Monitor].
- [Output: 60↔60(24)fps] and [Output: 60↔60(30)fps] (assignable functions).

Selecting the Output Range

You can select the output range of video signals (when using log gamma or PQ/HLG HDR) output from the SDI OUT terminal / HDMI OUT terminal to determine how the image levels are mapped to code values. Moreover, you can select the setting independently for Canon Log output and for HDR output.

Applied output range settings

Custom picture file			Applied range settings
[Gamma]	[Look File]	[Gamma/Color Space] after the Look File is applied	MENU > [Monitoring Setup] > [Range]
[Canon Log 2] [Canon Log 3]	[Off] [On]	— [Conform to Custom Picture]	[During Canon Log Output]
[PQ] [HLG]	[Off] [On]	— [Conform to Custom Picture]	
[BT.709 Wide DR] [BT.709 Standard] [Canon 709]	[Off] [On]	— [Conform to Custom Picture]	— (Fixed narrow range)
—	[On]	[SDR BT.709]	
		[SDR BT.2020]	
		[HDR PQ(BT.2100)]	
		[HDR HLG(BT.2100)]	[During HDR Output]

1 Select **MENU** > [Monitoring Setup] > Desired [Range] option.

2 Select [During Canon Log Output] or [During HDR Output] > Desired option.

Options (SDI OUT terminal)

[Full Range]: The signal output will use full range coding.

[Narrow Range]:
The signal output will use narrow range (video range) coding.

Options (HDMI OUT terminal)

[Full Range Priority]:
The signal output will use full range coding whenever possible but will change the range automatically according to the capabilities of the connected monitor.

[Narrow Range]:
The signal output will use narrow range (video range) coding.

NOTES

- During playback, the applied range is determined according to the gamma used at the time of recording.
- When [View Assist:] ( 159) are set to [On], output range settings are disabled.

Superimposing Onscreen Displays on Video Outputs

You can output the camera's onscreen displays along with the video output from the SDI OUT terminal / HDMI OUT terminal to check the onscreen displays on an external monitor. You can also adjust the opacity level of superimposed onscreen displays. This setting will not affect your recordings.

Select **MENU** > [ Monitoring Setup] > [OSD Output: SDI] or [OSD Output: HDMI] > [On].

- **DISP**  appears on the right of the screen (In CAMERA mode, only if **MENU** > [ Monitoring Setup] > [Custom Display 2] > [OSD Output] is set to [On]).

NOTES

- Assistance functions will not be superimposed when the [OSD Output:] options are set to [Off (Clean)] or [Off], with the following exceptions.
 - Magnification
 - Range display when [Custom Picture] > [Skin Detail] or [Color Correction] is set
- When only peaking/zebra pattern/false color is superimposed, set the desired [OSD Output:] option to [On] and set the onscreen display level to [DISP Level 3].
- If you set an assignable button to one of the [OSD Output:] options, you can press the button to turn the camera's onscreen displays on and off.

Changing the Opacity Level of Onscreen Displays

You can make onscreen displays more visible or less conspicuous by changing their opacity level. You can select to which screens to apply the opacity levels. This function allows you to reduce screen glare when recording in dark places.

- 1 To change the visibility of onscreen displays on individual video outputs, select **MENU** > [ Monitoring Setup] > Desired [OSD Opacity:] setting > [On].
- 2 Select **MENU** > [ Monitoring Setup] > [OSD Opacity Level] > Desired option.
 - The smaller the percentage the more transparent the onscreen displays.
- 3 Select **MENU** > [ Monitoring Setup] > [OSD Opacity: Appl. Screens] > [All] or [Only Rec/Playback Screens].
 - You can apply the selected opacity level to all onscreen displays (including menus, etc.) or only to onscreen displays on the shooting and playback screens.

NOTES

- If you set an assignable button to one of the [OSD Opacity:] settings, you can press the button to change the opacity level of onscreen displays on the corresponding video outputs.

Applying the View Assistance Function to the LCD Screen

When a special gamma curve/color space is selected in the custom picture file, you can easily convert the image output by enabling the View Assistance function, resulting in a gamma curve/color space optimal for viewing on BT.709 compliant monitors.

List of view assistance

View assistance	Gamma curve	Color space	Description
[CMT 709]	CMT 709	BT.709	Converts the gamma curve/color space of the image output, resulting in a standard gamma curve/color space. It produces a look suitable for a cinema production, keeping a wide dynamic range without clipping when log recording.
[Canon 709]	Canon 709	BT.709	These settings produce a look appropriate also for use without post processing, featuring high contrast while ensuring a wide dynamic range optimized for playback on BT.709 compliant monitors.
[HDR Assist. (400%)] ¹	Original gamma curve	BT.709	LUT for viewing HDR (high dynamic range) images. The view assistance follows the ITU-R BT.2100 transfer function to convert a brightness range of 1600% or 400% respectively into a linear brightness scale.
[HDR Assist. (1600%)] ¹			

¹ Only **MENU** > [Monitoring Setup] > [View Assist: LCD] can be selected.

Available view assistance options

Availability and whether or not the View Assistance function can be applied depend on the [Gamma/Color Space] and [Look File] settings in the custom picture file (129). If these settings are changed, View Assistance will be turned off.

Custom picture file		Available View Assistance options			
[Look File]	[Gamma/Color Space] after the Look File is applied	[CMT 709]	[Canon 709]	[HDR Assist. (400%)]	[HDR Assist. (1600%)]
[Off]	—	See the following table (A).			
	[Conform to Custom Picture]				
[On]	[SDR BT.709]	—	—	—	—
	[SDR BT.2020]	—	—	—	—
	[HDR PQ(BT.2100)]	●	●	●	●
	[HDR HLG(BT.2100)]	●	●	●	—

Available view assistance options (A)

Custom picture file	Available View Assistance options			
[Gamma/Color Space]	[CMT 709]	[Canon 709]	[HDR Assist. (400%)]	[HDR Assist. (1600%)]
[Canon Log 2 / C.Gamut]	●	●	●	●
[Canon Log 3 / C.Gamut]	●	●	●	●
[Canon Log 3 / BT.2020]	●	●	●	●
[Canon Log 3 / BT.709]	●	●	—	—
[PQ / BT.2020]	●	●	●	●
[HLG / BT.2020]	●	●	●	—
[Canon 709 / BT.709] [BT.709 Wide DR / BT.709] [BT.709 Standard / BT.709]	—	—	—	—

Applying the View Assistance Function

- 1 Select **MENU** > [📺] Monitoring Setup > desired [View Assist:] setting > [On].
 - The view assistance function is applied and the gamma curve and color space of the displayed image will change.
 - The signal output will use narrow range (video range) coding.
- 2 Select **MENU** > [📺] Monitoring Setup > desired [Select View Assist:] option > desired setting.

NOTES

- The colors modified by using this function are an approximation.
- If you enable **MENU** > [🔧] Assistance Functions > one of the [False Color:] settings, the effect of the view assistance is temporarily removed.

Adjusting the Gain Difference When Converting HDR to SDR

You can adjust the SDR gain difference relative to HDR within a range of ± 7.5 dB (in 0.5 dB increments) in the following cases:

- When the main clip is set to HDR* and a view assistance function that changes the color space to CMT 709 / Canon 709 is applied to the output.
- When the main clip is set to HDR* and [Proxy Rec Color Conversion] is set to [BT.709 (Canon 709)] / [BT.709 (CMT 709)].

* When the [Gamma/Color Space] setting in the custom picture file is set to [PQ / BT.2020] or [HLG / BT.2020], or when the [Gamma/Color space] setting after applying a Look File is set to [HDR PQ (BT.2100)] or [HDR HLG (BT.2100)].

Select **MENU** > [📺] Monitoring Setup > [Gain for HDR→SDR Conv.] > Desired option.

Audio Output Channels

The camera can output audio from the SDI OUT terminal, HDMI OUT terminal,  (headphone) terminal or speaker. When recording or playing back clips recorded with 4-channel audio, you can select which audio channels are output from the HDMI OUT terminal and headphones.

Audio output configuration

Recorded audio configuration		Audio output during recording/playback		
Audio format	Audio bit depth	SDI OUT terminal	HDMI OUT terminal	 (headphone) terminal
4-channel linear PCM	24 bit	4-channel linear PCM 24 bit	2-channel linear PCM 16 bit	2 channels
2-channel AAC	16 bit			

To select the audio channels for headphone output

Select **MENU** > [] Audio Setup] > [Monitor Channels] > Desired audio output option (L/R).

- Options like [CH1+2] indicate that two audio channels (CH1 and CH2 in this example) are mixed and output from the same side.

To select the audio channels for HDMI output

Select **MENU** > [] Audio Setup] > [HDMI OUT Channels] > [CH1/CH2] or [CH3/CH4].

Importing Files to a Computer/Smartphone

Canon offers software applications as free downloads that allow you to save on a computer/smartphone clips recorded with the camera, develop RAW clips, and more.

Saving Files

Use Canon XF Utility to save and organize XF-AVC clips and other recorded files on a computer. You can use the Canon XF plugins to easily use XF-AVC clips directly from Avid non-linear editing (NLE) software. The software and plugins are available as free downloads from your local Canon website. Check the download page for the system requirements and latest information.

You will find detailed instructions about installing and uninstalling the software in the "Read This First" file (Install-XF Utility.pdf) included in the compressed file you will download from the website. For details about using the software, refer to the instruction manual (PDF file) that is installed with the software.

Canon XF Utility (for Windows/macOS): Software application that allows you to save clips on a computer, check, play back and organize clips and grab still frames from clips.

Canon XF Plugin for Avid Media Access (for Windows/macOS): Plugin that allows you to easily import clips from a card or a local folder in the computer to the compatible version of Avid Media Composer (an NLE application compatible with Avid Media Access), directly from within the application.

Saving XF-HEVC S/XF-AVC S Clips

Make sure to save XF-HEVC S/XF-AVC S clips recorded with this camera to a computer. To do so, you will need a card reader connected to a computer or a computer with a card slot. For details on transferring files from the card, refer to the computer's instruction manual or OS's help modules.

Under certain circumstances, clips may be split and recorded as separate files. Using MP4 Join Tool you can join the split XF-HEVC S/XF-AVC S clips and save them as a single seamless clip.

Transferring Files to a Computer

- 1 Insert the card with the desired clips into the card slot of the computer or card reader connected to the computer.
- 2 Follow the OS's onscreen instructions.
- 3 Copy the clips on the card to the computer.
 - XF-HEVC S/XF-AVC S clips are located in folders named "XFVC/REEL_XXXX" and photos are located in folders named "DCIM/XXX_mmdd", where XXX is the folder number and mmdd stands for the recording date.

Joining Clips Split by the Camera

Use MP4 Join Tool to join XF-HEVC S/XF-AVC S clips split by the camera in the following cases.

- When the camera switches to the other card while recording video due to the relay recording function (📖 39).
- The video (stream) file in the clip will be split approximately every 4 GB.

MP4 Join Tool is available as a free download (for Windows or macOS) from your local Canon website. Check the download page for the system requirements and latest information.

You will find detailed instructions about installing and uninstalling the software in the "Read This First" file (Install-MP4 Join Tool.pdf) included in the compressed file you download. For details about using the software, refer to the instruction manual (PDF file) that is installed with the software.

Saving Audio Files (WAV)

Audio files in WAV format can be saved to a computer in the same way as XF-HEVC S / XF-AVC S files. Copy the desired audio files (located in the “/PRIVATE/AUDIO” folder of the SD card) to the computer.

Developing RAW Clips

Use Cinema RAW Development to develop RAW clips shot/recorded with the camera. After you develop the clips and export them to a full-quality standard file type such as DPX, they will be ready for color grading. Alternatively, you can use the Canon RAW Plugin to easily use RAW clips unaltered (in RAW format) directly from major non-linear editing (NLE) applications. The software and plugin are available as free downloads from your local Canon website. Check the download page for the system requirements and the latest information. You will find detailed instructions about installing and uninstalling the software in the “Read This First” file (Install-Cinema RAW Development.pdf) included in the compressed file you will download from the website. For details about using the software, refer to the instruction manual (PDF file) that is installed with the software.

Cinema RAW Development (for Windows/macOS): Software application that allows you to develop, play back and export RAW clips.


Canon RAW Plugin for Avid Media Access (for Windows/macOS): Plugin that allows you to easily import RAW clips to the compatible version of Avid Media Composer (an NLE application compatible with Avid Media Access), directly from within the application.

Canon RAW Plugin for Final Cut Pro (macOS): Plugin that allows you to easily import RAW clips to Apple’s Final Cut Pro, directly from the application.

Saving Recordings to a Smartphone

You can save XF-HEVC S / XF-AVC S clips recorded with the camera, as well as WAV audio, photos and News Metadata files to a smartphone. Content Transfer Professional is needed for this operation. You can connect a smartphone to the camera using a compatible USB cable* or the network functions (📖 195).

* For details on compatible USB cables, visit your local Canon website.



- 1 Select **MENU** > [🔧 System Setup] > [USB Mode] > Desired option.
For iOS devices: select [Canon App(s) for iPhone].
For Android devices: select [Canon App(s)/GP-E2].
- 2 Connect the smartphone to the camera using a compatible USB cable.
- 3 Open the application on the smartphone.
- 4 Use the application to save the files.
- 5 When the connection ends, disconnect the USB cable from the camera.

Automatically Transferring Recording Data to an FTP Server

You can use Content Transfer Professional to automatically transfer XF-HEVC S clips, XF-AVC S clips, WAV audio, photos and News Metadata to an FTP server. Install Content Transfer Professional on your smartphone in advance (📖 195).

1 Connect the smartphone to the camera.

When using a USB cable, perform steps 1 to 3 of *Saving Recordings to a Smartphone* (📖 162).

When using network functions, perform steps 2 to 6 of *Transferring Recordings to a Smartphone* (📖 195).

2 Smartphone: specify the destination FTP server on Content Transfer Professional, and start the [Transfer by camera operation] function.

3 Press REC to start recording.

- Recorded clips are automatically transferred.

4 End the connection.

Network functions and connection types

To be able to use the following network functions you will need to connect to a Wi-Fi network, or use the  (Ethernet) terminal on the camera to connect to a wired (Ethernet) network.

Network functions and connection types

Network function	Description	Wired network (Ethernet)	Wi-Fi		
			Infrastructure ¹	Camera Access Point ²	
FTP File Transfer	Transfer clips recorded with the camera to another device connected to the network using the FTP protocol.	●	●	●	184
IP Streaming	Stream the camera's live video and audio over IP to a compatible IP video decoder connected to the network.	●	●	—	185
Browser Remote	Control the camera remotely from the Web browser of a connected device.	●	●	●	187
Canon App (Content Transfer Professional)	Transfer clips/audio recorded with the camera to a smartphone, or apply News Metadata created/edited with Content Transfer Professional to the camera.	—	●	—	195
XC Protocol	Control the camera remotely using a controller or application compatible with the XC Protocol via an IP connection.	●	●	●	193
CV Protocol	Output metadata information (from the Ethernet terminal) necessary for virtual production in real time on a PC application.	● ³	—	—	173
Frame.io ⁴	Upload recording data from the camera using Adobe's Frame.io Camera to Cloud function.	●	●	—	196

¹ Connection to a Wi-Fi network via an external access point (wireless router, etc.)

² Direct connection to one Wi-Fi-enabled device where the camera serves as the Wi-Fi access point.

³ IPv4 only.

⁴ Cannot be used outside the service area of Frame.io.

Security

When connecting the camera to a network, make sure to use a secure network environment.

It is recommended to use the camera with the default settings.

When connecting the camera to a network, there is a risk of unauthorized access from unintended third parties or cyber-attacks. If access from an external network is not required, physically and/or virtually block access so that only specified devices can access the network. Additionally, Wi-Fi (wireless LAN) may be intercepted by malicious third parties, posing a risk of eavesdropping on communication content.

If access to an external network is required, it is important to implement a secure method of communication, such as using a VPN (Virtual Private Network) that can block access from the outside. Use Wi-Fi in a secure environment. AES encryption is recommended.

In particular, the following functions do not support protocol encryption for communication with the camera; therefore, use these functions in a secure network environment.

- Canon App (Content Transfer Professional)
- CV Protocol

! IMPORTANT

- Canon shall not be liable for any direct or indirect damages caused by network security issues.
- The camera cannot be directly connected to the communication lines (including public wireless LAN) of telecommunications carriers (mobile communications companies, fixed-line communications companies, Internet providers, etc.). When connecting the camera to the Internet, be sure to connect via a router or similar device.

Before using the network functions


- The instructions in this chapter assume you already have a correctly configured and working network and correctly configured network device(s). If necessary, refer to the documentation provided with the network devices you plan to use.
- Configuring the network settings requires adequate knowledge about configuring and using wired (Ethernet) and/or wireless (Wi-Fi) networks. Canon cannot provide support regarding network configurations.

! IMPORTANT

- In case it is necessary to set a password for network connections or function settings, make sure to set a secure password that is long enough to be hard to guess, including a combination of characters and symbols. Use caution not to lose the password.

i NOTES

- Do not open the card compartment cover while using network functions.
- Do not place cables connected to the camera's SDI OUT terminal or HDMI OUT terminal, INPUT terminals, MIC terminal or USB terminal near the built-in wireless antenna. Doing so may negatively affect the wireless communication or the audio recorded.



Using a Wi-Fi Network

Wi-Fi Connection Types

You can connect the camera in Infrastructure mode, using an access point (wireless router etc.), or in Camera Access Point mode, directly to a network device. The type of connection you can use, depends on the network function you wish to use (165).

For an Infrastructure connection, the camera offers 4 ways to configure an access point and the method you use will depend on the type and specifications of the access point and network you plan to use.

Camera Access Point: When shooting in a location where there are no access points available, the camera can serve as a wireless access point*. Wi-Fi enabled devices will be able to connect to the camera directly.

* Limited only to the connection between the camera and supported Wi-Fi enabled devices. The functionality is not the same as that of commercially available access points.

Infrastructure connection:

WPS (button): If your wireless router supports Wi-Fi Protected Setup (WPS), setup will be easy and require minimal configuring and no passwords. To check if your wireless router has a WPS button and for details about how to activate the Wi-Fi protected setup, refer to the instruction manual of your wireless router.



WPS (PIN code): Even if your wireless router does not have a dedicated WPS button, it may support WPS using a PIN code instead. For setup using a PIN code, you will need to know in advance how to activate the wireless router's WPS function. For details refer to the instruction manual of your wireless router.

Searching for Access Points: If your access point does not support the WPS function or you cannot activate it, you can have the camera search for access points in the area.


Entering the SSID and authentication method: Manually enter the SSID and other information about the access point.

! IMPORTANT

- Depending on the country/region of use, some restrictions on outdoor use or Camera Access Point connections may apply when using the IEEE 802.11b/g/a/n/ac wireless standard. Check in advance the applicable areas of use and restrictions.

Using a Wired (Ethernet) Network

Connect a commercially available Ethernet cable to the camera's  (Ethernet) terminal to use a wired network. Use Category 5e, shielded twisted pair (STP) Ethernet cables compatible with Gigabit Ethernet (1000BASE-T) and with good shielding capability. For more details about Ethernet cables, refer to the manufacturer's instruction manual.


Connecting

Configuring Connection Settings

To connect to a network you will need to define in advance a connection setting (SET), which is a combination of one or two communication settings (networks, NW) and one or two network function settings (MODE). You can save in the camera up to 25 individual communication settings and function settings, and up to 20 combinations of connection settings (SET1 to SET20).

To configure a connection setting for the first time, you will follow the setup wizard (169). Using the wizard, you can set up only one network and one function per connection setting. After having configured multiple connection settings, you can change them (for example to add a secondary network or second function) and you can create new ones combining existing communication and function settings (178).

If you configure a connection setting with both the [IP Streaming] and [Browser Remote] network functions, you will be able to use both functions simultaneously.



Activating a Network Connection

Activate the desired network connection to use network functions or to configure the connection setting online.

- 1 Select **MENU** > [Network Settings] > [Network] > [Enable].
- 2 When using connection settings that you saved previously, select **MENU** > [Network Settings] > [Connect] > Desired connection setting ([SET1] to [SET20]) > [OK].
 - To end the network connection, set [Connect] to [Disconnect] instead.

Adding a New Connection Setting Using the Wizard

You can use the wizard to set up a new connection setting. This section uses a connection to a Wi-Fi network using the WPS push button method as an example. Refer to the instruction manual of the access point for details about the location and operation of the WPS button.

- 1 Enable the network functions (📖 168).
- 2 Select **MENU** > [ Network Settings] > [New Conn. Setting (Wizard)] > Desired network function > [OK].
- 3 Select [Create New Comm. Setting].
 - Once you have added multiple communication settings, you can select [Select Existing Setting] to reuse the settings for a network that you saved previously.
- 4 Select [Wi-Fi ].
 - To configure a wired (Ethernet) network (📖 174).
- 5 Select [Connect with WPS] > [WPS (Push Button)].
 - To use a different configuration method, complete the corresponding procedure.
 Camera Access Point (📖 174)
 WPS using a PIN code (📖 175)
 Detected access points (📖 175)
 SSID/authentication mode input (📖 175)
 Manual setup without connecting to the network (📖 176)
- 6 Press and hold the WPS button on the wireless router and then, on the camera, select [OK].
- 7 To configure the IPv4 settings automatically and not use IPv6 settings, select [Automatic Setting] > [Disable].
 - To configure IPv4 settings manually (📖 176).
 - To use the default IPv6 settings, select [Enable] instead. After completing the wizard, change the IPv6 settings as necessary (📖 180).
- 8 Select [OK] to continue to configure the function settings.
 - The communication settings are saved to an [NW] file.
 - Continue with one the following procedures to configure the selected function's settings.
 FTP transfer (📖 169), IP streaming (📖 170), Browser Remote (📖 172), Canon App (📖 172),
 XC Protocol (📖 173), CV Protocol (📖 173), Frame.io (📖 173)

NOTES

- The [WPS (Push Button)] method may not work correctly depending on the devices used or the surrounding conditions. In such case try using [WPS (PIN Code)] (📖 175) or selecting one of the detected networks (📖 175).

Function Settings

FTP Transfer

This section continues the connection settings wizard (📖 169). In the function settings you will configure the FTP server settings and other settings related to the handling of folders and files. If necessary, consult the network administrator in charge of the FTP server.

- 1 Select [Create New Func. Setting].
 - Once you have added multiple function settings, you can select [Select Existing Setting] to reuse the settings for an FTP server that you saved previously.
- 2 Select the desired transfer mode.

3 Configure the destination FTP server. Select [Server] and [Port No.] > [OK].

- Enter the FTP server's IP address or host name using the keyboard screen. Enter the port number using the data entry screen (📖 28).
- Usually, the port number used is 21 (FTP or FTPS transfers) or 22 (SFTP transfers).
- Depending on the FTP mode selected in step 2, perform either step 4 or steps 4-5 and then continue to step 6.

SFTP transfers

4 Enter the user name and password for the SSH protocol's authentication. Select [User Name] and [Password] > [OK].

- Enter the desired user name and password using the keyboard screen (📖 28).

FTP/FTPS transfers

4 Select [Enable] to use passive mode or [Disable] to use active mode.

- In most cases, select [Disable].

5 Enter the user name and password for the FTP server. Select [User Name] and [Password] > [OK].

- Enter the desired user name and password using the keyboard screen (📖 28).

All transfer modes

6 Select the destination folder on the server.

7 Select [OK]

- The function settings are saved to a [MODE] file.

8 Select the connection setting (SET1 to SET20) where to save the settings and then select [OK].

- The camera will connect to the network and will be ready to use the FTP transfer function (📖 184).

Options for [FTP Mode]

[FTP]: Transfer method where the data is not encrypted.

[FTPS]: Secure transfer method using a root certificate (📖 177).

[SFTP]: Secure transfer method using an SSH secure channel.

Options for [Destination Folder]

[Root Directory]:

Files are saved on the root directory of the destination FTP server.

[Select Folder]: Enter the desired path using the keyboard screen (📖 28). If the folder does not exist on the destination FTP server, it will be created automatically.

IP Streaming

This section continues the connection settings wizard (📖 169). In the function settings you will configure the streaming video bit rate and resolution, the protocol used and the receiver's settings. For details refer to the instruction manual of the decoder device or software you will use.

1 Select [Create New Func. Setting].

- Once you have added multiple function settings, you can select [Select Existing Setting] to reuse IP streaming settings that you saved previously.

2 Select the desired protocol.

- Depending on the selected protocol, perform steps 3 to 6 if necessary and then continue to step 7.

[RTP+FEC] streaming

- 3 Configure the receiver's settings. Select [Destination Server] and [Dest. Port No.] > [OK].
 - Enter the receiver's IP address using the keyboard screen. Enter the port number using the data entry screen (☐ 28).
 - Using the default port number is recommended.
- 4 Configure the settings used to send FEC packets. Select [FEC Port No.] and [FEC Interval] > [OK].
 - Enter the port number using the data entry screen (☐ 28).
 - Using the default settings is recommended.
 - Proceed to step 7.

[RTSP+RTP] streaming

- 3 Configure the receiver's settings. Select [Destination Server] and [Dest. Port No.] > [OK].
 - Enter the receiver's IP address using the keyboard screen. Enter the port number using the data entry screen (☐ 28).
 - Using the default port number is recommended.
- 4 Enter the user name and password of the RTSP client. Select [RTSP: User Name] and [RTSP: Password] > [OK].
 - Enter the desired user name and password using the keyboard screen (☐ 28).
 - Proceed to step 7.

SRT

- 3 Select the connection mode.
 - Caller: Connect to a decoder or a computer from the camera.
 - Listener: Listens for connections from the decoder or computer.
- 4 When [Caller] is selected, enter [Destination Server], [Dest. Port No.] and [Stream ID], then select [OK].
 - Using the default port number is recommended.
- 5 When [Listener] is selected, enter [Listening Port No.] then select [OK].
 - Enter the port number of the decoder or computer.
- 6 Select [Encryption Settings], enter [Passphrase] and [Latency], and then select [OK].

All streaming protocols

- 7 Select the video streaming configuration.
- 8 Select the audio channels.
- 9 Depending on the resolution and frame rate, a screen may prompt you to change other settings. Change the settings as necessary.
- 10 Select [OK].
 - The function settings are saved to a [MODE] file.
- 11 Select the connection setting (SET1 to SET20) where to save the settings.
- 12 Select [OK].
 - The camera will connect to the network and will be ready to start streaming.
- 13 Connect the decoder to the network and complete any necessary configurations on the receiving side so the decoder is ready to receive video over IP.
 - To start streaming, refer to *IP Streaming* (☐ 185).

Options for [Protocol]

- [UDP]: This protocol prioritizes transfer speeds but does not guarantee the reliability/integrity of the data. Lost or delayed IP packets are ignored.

- [RTP]: Standard protocol for video/audio broadcasts over the Internet. Lost or delayed IP packets are ignored.
- [RTP+FEC]: This setting uses the RTP protocol and adds a layer of FEC error correction so the receiving side* can recover lost or delayed IP packets.
- [RTSP+RTP]: This setting uses the RTSP (real time streaming) protocol to control the streaming server (camera) in real time and the RTP protocol for the broadcast over IP. With the RTSP protocol, the receiver can control when to start and stop the broadcast.
- [SRT]: A protocol for high-speed transmission that suppresses the occurrence of lost/delayed packets. Transmitted data can be encrypted.

* A decoder compatible with FEC error correction is required.

Browser Remote

This section continues the connection settings wizard (📖 169). A user name and password are required to log in to the Browser Remote application. In the function settings you will configure up to three different users for single-user or two-user operation.

- 1 Select [Create New Func. Setting].
 - Once you have added multiple function settings, you can select [Select Existing Setting] to reuse Browser Remote settings that you saved previously.
- 2 Enter the user names and passwords as necessary.
- 3 Select [OK] twice.
 - The function settings are saved to a [MODE] file.
- 4 Select the connection setting (SET1 to SET20) where to save the settings and then select [OK].
 - The camera will connect to the network and will be ready to accept commands from the Browser Remote application (📖 187).

Canon App (Connecting to a Smartphone)

This section details the necessary settings to connect the camera to a smartphone through a network. Be sure to connect both the smartphone and the camera to the same network in advance.

A Content Transfer Professional is necessary to connect the camera to a smartphone. For details on downloading the necessary Content Transfer Professional, refer to *Transferring Recordings to a Smartphone* (📖 195). For more details, refer to the smartphone's instruction manual.

- 1 Select [Create New Func. Setting].
 - Once you have added multiple function settings, you can select [Select Existing Setting] to reuse Canon App settings that you saved previously.
- 2 Select [OK].
- 3 As indicated on the screen, open the application on the smartphone.
- 4 Select the camera using the Content Transfer Professional.
 - If the camera and the smartphone are connected to the same network, the camera will be detected automatically.
- 5 Select [OK].
 - The connection will be completed.
 - The function settings are saved to a [MODE] file.
- 6 Select the connection setting (SET1 to SET20) where to save the settings.
- 7 Select [OK].
 - The connection will be completed and the camera will be ready to operate with the connected smartphone (📖 195).

XC Protocol

Set a user name and password to connect to an XC Protocol compatible device connected to a network.

- 1 Select [Create New Func. Setting].
- 2 Set the authentication method used by the XC Protocol (HTTP/HTTPS) server.
 - After selecting [Basic Authentication] or [Digest Authentication], set the user name and password.
 User name: 5 to 15 alphanumeric characters or symbols.
 Password: 8 to 32 alphanumeric characters or symbols (use at least 2 types from each).
- 3 Select [OK].
 - The function settings are saved to a [MODE] file.
- 4 Select the connection setting (SET1 to SET20) where to save the settings.
- 5 When the confirmation message appears, press SET.
 - The camera will connect to the network and will be ready to accept commands from the remote controller/application (📖 193).

CV Protocol

Configure the camera to output metadata information necessary for virtual production in real time on a PC application. Ethernet IPv4 only.

- 1 Select [Create New Func. Setting].
- 2 Enter [Destination Server] and [Dest. Port No.] as the destination settings and select [OK].
 - Enter the address for the communication method (Unicast/Multicast*/Broadcast) used by the destination server.
 * Transmission is possible only within the same network segment.
 - Using the default port number is recommended.
- 3 Select the connection setting (SET1 to SET20) where to save the settings.
- 4 When the confirmation message appears, press SET.
 - Use the Canon Live Link Plugin for Unreal Engine to send metadata information to applications used for virtual production. For details about using and downloading Live Link Plugin for Unreal Engine refer to the Canon website.

NOTES

- When the set slow & fast motion recording frame rate exceeds 60P, [CV Protocol] cannot be used at the same time.

Frame.io

Set up a connection between the camera and Frame.io.

- 1 Select [Create New Func. Setting].
 - If there is a previously registered function setting related to Frame.io, you can select it from [Select Existing Setting].
- 2 Select the pairing destination.

[Keep Current Pairing]: Maintains the pairing status with the camera.

[Create New Pairing]: Creates a new pairing with Frame.io. If you want to re-pair when the camera is already paired, select [OK].
- 3 Select [OK].
 - The pairing code is displayed.
 - If [Keep Current Pairing] is selected, proceed to step 6.
- 4 From Frame.io: Access Frame.io and enter the pairing code.
 - The camera is paired with Frame.io.

- 5 Select [OK].
- 6 Select [Auto Upload File Formats].
 - [XF-AVC Proxy]: Proxy clips in XF-AVC format.
 - [XF-HEVC S/XF-AVC S Proxy]: Proxy clips in XF-HEVC S/XF-AVC S format.
 - [Audio Proxy]: Audio recording files (second card recording functions).
- 7 Select [OK].
 - The function settings are saved to a [MODE] file.
- 8 Select the connection setting (SET1 to SET20) where to save the settings, then select [OK].
 - The connection is completed. Refer to *Uploading Recording Data to Frame.io* (📖 196) for operation details.

Other Connection Methods

This section explains how to configure communication settings using methods other than the WPS push button.

Ethernet Settings

- 1 In the [Network Type] screen, select [Ethernet .
- 2 Make sure the Ethernet cable is correctly connected (📖 167) and select [Setup with Network Connection].
 - Select [Setup without Network Connection] to only configure the settings, without connecting to the network.
- 3 Set the IP address (📖 176).
- 4 Select [OK] to continue to configure the function settings.
 - The communication settings are saved to an [NW] file.
 - Continue with one the following procedures to configure the selected function's settings (📖 169).

Camera Access Point

Connect a network device with the camera's access point. Two configuration methods are available: easy connection and manual connection.

- 1 In the [Select a network] screen, select [Camera Access Point Mode].
- 2 Select the configuration method.
 - Depending on the selected method, perform either step 3 or steps 3-7 and then continue to step 8.

[Easy Connection]

- 3 The camera will assign the network name (SSID) and password automatically. Review the settings for the camera's Wi-Fi access point and select [OK].
 - These settings are necessary to connect a network device to the camera.

[Manual Connection]

- 3 Enter the SSID (network name) for the Camera Access Point and then select [OK].
 - Enter the desired network name using the keyboard screen (📖 28).
- 4 Select the Wi-Fi channel.
 - Select [Automatic Setting] to have the camera select the channel automatically, or select [Manual Setting] > Desired channel.
- 5 Select the encryption settings.
 - Select [AES] to use AES encryption, or [Disable] to use no encryption.
 - If you selected [Disable], skip to step 7.

6 Enter the password for the Camera Access Point and then select [OK].

- Enter the desired password using the keyboard screen (📖 28).

7 Set the IP address (📖 176).

Both configuration methods

8 Select [OK] to continue to configure the function settings.

- The communication settings are saved to an [NW] file.
- Continue with one the following procedures to configure the selected function's settings (📖 169).

9 Before you can save the connection setting, connect the network device to the camera.

- Activate the device's Wi-Fi function, select the camera's SSID (network name) from the list and enter the password to connect to the camera.

WPS using a PIN Code

Connect to an access point using a PIN code. For most wireless routers, you must use a Web browser to access the setup screen. For details on how to set up the access point, refer to the access point's user manual.

1 In the [Select a network] screen, select [Connect with WPS] > [WPS (PIN Code)].

- The camera will generate and display an 8-digit PIN code.

2 Enter the PIN code into the wireless router's WPS (PIN code) setup screen and then, on the camera, select [OK].

3 Set the IP address (📖 176).

4 Select [OK] to continue to configure the function settings.

- The communication settings are saved to an [NW] file.
- Continue with one the following procedures to configure the selected function's settings (📖 169).

Detected Access Points

The camera will automatically detect access points in the vicinity. After you select the desired access point, you only need to enter the selected network's password to connect the camera. Be sure to activate tethering in advance when using a smartphone as an access point. For details about the access point's network name (SSID) and password refer to the wireless router's instruction manual or consult the network administrator in charge of the access point.

1 In the [Select a network] screen, scroll through the list of detected networks and select the desired network.

- If the access point is encrypted, enter the password of the access point using the keyboard screen (📖 28).

2 Set the IP address (📖 176).

3 Select [OK] to continue to configure the function settings.

- The communication settings are saved to an [NW] file.
- Continue with one the following procedures to configure the selected function's settings (📖 169).

SSID/Authentication Mode Input

You can connect to a specific access point by manually entering its details. For details about the access point's network name (SSID) and password refer to the wireless router's instruction manual or consult the network administrator in charge of the access point.

1 In the [Select a network] screen, select [Enter SSID/Authentication Method].

2 Enter the SSID (network name) of the desired network and then select [OK].

- Enter the desired network name using the keyboard screen (📖 28).

3 Select the network's authentication method.

- If you select [Open System], select [Disable] (no encryption) and skip to step 6, or select [WEP] and continue the procedure.
- If you select [Shared Key] or [Open System] > [WEP], select the key index.
- If you select [WPA/WPA2/WPA3-Personal], proceed to step 4.
- If you select [WPA/WPA2/WPA3-Enterprise], proceed to step 5.

4 Enter the password of the desired network and then select [OK].

- Enter the desired password using the keyboard screen (📖 28).

5 Set the IP address (📖 176).

6 Select [OK] to continue to configure the function settings.

- The communication settings are saved to an [NW] file.
- Continue with one the following procedures to configure the selected function's settings (📖 169).

Offline Configuration without Connecting to a Network

1 In the [Select a network] screen, select [Configure Offline].

2 Select the network type.

- If you select [Infrastructure], continue with the procedure to enter the SSID and authentication mode, from step 2 (📖 175).
- If you select [Camera Access Point Mode], continue from that procedure, from step 2 (📖 174).

Configuring the Camera's IP Address

This section explains how to configure the IP address. Available settings will change depending on the network function selected.

1 Select the method used to configure IPv4 settings, [Automatic Setting] or [Manual Setting].

- When using the wizard to add a new connection setting, make the selection in the [IP Address Settings (IPv4)] screen.
- If you select [Automatic Setting], skip to step 4.

[Manual Setting]

2 Select [IP Address] and [Subnet Mask] and enter the desired addresses using the data entry screen (📖 28).

- To use a default gateway, select [Use Gateway] > [Enable] and then select [Gateway] and enter the address.
- To use a DNS address, select [Use DNS Address] > [Manual Setting] and enter the address.

3 Select [OK].

Both methods

4 Select whether to use TCP/IPv6 settings or not.

- To use IPv4 settings, select [Disable].
- To configure IPv6 settings (📖 180).

Other Network Settings

Reading/Deleting a Root Certificate for FTP Transfer

When you use the [FTPS] transfer mode, you will need to read onto the camera the same root certificate saved on the FTP server. You can also check the content of a previously loaded root certificate or delete it.

- 1 Set the camera to MEDIA mode.
- 2 Save the desired root certificate file onto the root directory of a card and insert it into card slot B.
- 3 Select **MENU** > [ Network Settings] > [Advanced Settings] > [FTP Transfer Settings] > [Read Root Certificate] > [OK].
 - The root certificate file is read from the card.
 - After reading a root certificate file, you can select [Root Certificate Details] to check the certificate's issuer and expiration date, or select [Delete Root Certificate] to delete the root certificate in the camera.

NOTES

- Only one root certificate, with one of the following file names, can be read by the camera: "ROOT.CER", "ROOT.CRT" and "ROOT.PEM".
- If you transfer files using FTPS transfer with a self-signed certificate, you may not be able to trust the destination server.

802.1X Authentication

The camera is compatible with the following protocols.

EAP-TLS: X.509 supported

EAP-TTLS, PEAP: MS-CHAP v.2 supported

Select **MENU** > [ Network Settings] > [Advanced Settings] > [802.1X Authentication] > [Setup Wizard].

- Follow the wizard to complete the authentication settings.
When you select the [EAP-TLS] protocol, the root certificate (8021X_R.CER), client certificate (8021X_C.CER) and private key (8021X_C.KEY) will be read from the card.
When you select the [EAP-TTLS] or [PEAP] protocol, select [User Name] and [Password] and enter the information using the keyboard screen ( 28). Then, read the root certificate from the card. Each must be saved directly in the card's root directory.
- After reading the authentication files, select [Check Settings] to check their content. Select [Delete Settings] to delete the authentication files in the camera.

Reading/Deleting a Root Certificate for Frame.io Upload

This section describes how to read a root certificate onto the camera when using Frame.io.

- 1 Save the desired root certificate file onto the root directory of a card and insert it into card slot B.
- 2 Select **MENU** > [ Network Settings] > [Frame.io] > [Root Certificate].
- 3 Select [Read Root certificate], then select [OK].
 - The root certificate file is read from the card.
 - After reading a root certificate file, you can select [Root Certificate Details] to check the certificate's issuer and expiration date, or select [Delete Root Certificate] to delete the root certificate in the camera.

NOTES

- Only one root certificate, with one of the following file names, can be read by the camera: "FRAMEIO.CER", "FRAMEIO.CRT" and "FRAMEIO.PEM".

Giving a Nickname to the Camera

You can give the camera a nickname that is used on network connections and network devices to make it easier to identify.

Select **MENU** > [ Network Settings] > [Nickname].

- Enter the desired nickname using the keyboard screen ( 28).

Checking and Changing Connection Settings (SET)

You can check and, if necessary, change the settings of connection settings (SET) registered in the camera. In addition to deleting and renaming connection settings, you can also add to a connection setting a secondary network or second function.

Checking the Content of a Connection Setting

Select **MENU** > [ Network Settings] > [Connection Setting] > Desired connection setting ([SET1] to [SET20]) > [Check Settings].

- The detailed content of the connection setting is displayed.
- Push the joystick left/right or turn the SELECT dial to review all the settings and press the CANCEL button to return to the menu.

Changing Settings using the Wizard

- 1 Select **MENU** > [ Network Settings] > [Connection Setting] > Desired connection setting ([SET1] to [SET20]) > [Change with Wizard].
- 2 Select the desired network function and then follow the wizard as described in the previous procedure (from step 3,  169) and make any changes as necessary.

Changing Connection Settings using Existing Settings

You can use previously registered communication settings ([NW] files) or function settings ([MODE] files) to easily replace the content of a connection setting or to add a second network or network function in addition to those registered using the wizard.

- 1 Select **MENU** > [ Network Settings] > [Connection Setting] > Desired connection setting ([SET1] to [SET20]) > [Select Existing Setting].

To add/replace a communication or function setting

- 2 Select the setting you want to change > [Select Existing Setting] > Desired NW or MODE file.
 - In the list of communication settings and function settings registered in the camera, only those that can be selected will be displayed in white and others will be grayed out.
- 3 Select [Set].
 - If necessary, select [Check Comm. Settings] or [Check Function Settings] to check the content of the selected file before making the change.

To delete a communication or function setting

2 Select the setting you want to remove > [Clear Selected] > [OK].

NOTES

- A connection setting can have two communication settings (primary/secondary network) and up to two function settings (only for [IP Streaming] and [Browser Remote]).
- If both communication settings are deleted, the connection setting itself will be reset and will appear as [Unspecified].

Renaming Connection Settings

You can rename connection setting (SET) files to make them easier to identify from the list.

Select **MENU** >  Network Settings] > [Connection Setting] > Desired connection setting ([SET1] to [SET20]) > [Settings Name].

- Enter the desired name (up to 12 characters) using the keyboard screen ( 28).

Deleting Connection Settings

Select **MENU** >  Network Settings] > [Connection Setting] > Desired connection setting ([SET1] to [SET20]) > [Delete Settings] > [OK].

- The connection setting will be deleted.

NOTES

- Even if you delete a connection setting, the individual communication/function settings stored in it are not deleted. You can reuse these settings to configure other connection settings.

Checking and Changing Communication Settings (NW)/Function Settings (MODE)

You can check the content of communication settings ([NW] files) and function settings ([MODE] files) saved in the camera and change or delete them as necessary.

Checking the Content of a Communication Setting/Function Setting

- 1 Select **MENU** >  Network Settings] > [Advanced Settings] > [Communication Settings] or [Function Settings].
- 2 Select the desired communication setting ([NW1] to [NW25]) or function setting ([MODE1] to [MODE25]).
- 3 Select [Check Settings].
 - The detailed content of the selected setting is displayed.
 - Push the joystick left/right or turn the SELECT dial to review all the settings and press the CANCEL button to return to the menu.

Changing/Deleting Communication Settings/Function Settings

- 1 Select **MENU** >  Network Settings] > [Advanced Settings] > [Communication Settings] or [Function Settings].
- 2 Select the desired communication setting ([NW1] to [NW25]) or function setting ([MODE1] to [MODE25]).
- 3 Select [Change Settings] and change the various settings as necessary.
 - If in step 2 you selected an [Unspecified] settings file, the only option available is [Create New with Wizard] ( 169).
 - Select [Delete Settings] > [OK] to delete the communication setting/function setting.

Configuring TCP/IPv6 Settings

If in the wizard you selected [Enable] to use IPv6 settings, change the settings as necessary after completing the wizard.

- 1 After step 3 in the previous procedure, select [TCP/IPv6] > [TCP/IPv6 Settings] > [Enable].
 - This step is not necessary if you selected [Enable] when you used the wizard to add a new connection setting.
 - Continue the procedure to change the default IPv6 settings.
- 2 To configure the IPv6 settings manually, select [Manual Setting] > [Enable].
 - [DNS Server] changes to [Manual Setting].
- 3 Select [DNS Server] > Desired option.
 - If you selected [Disable] in step 2, you can set [DNS Server] to [Auto Assign].
 - When not using a DNS server, select [Disable].
- 4 If you set [DNS Server] to [Manual Setting] in step 3, configure the [DNS Address].
 - Enter the IP address using the data entry screen (📖 28).

When [Manual Setting] is set to [Enable]

- 5 Select [Manual Address] (manually entered IPv6 address), [Prefix Length] (bits available for the network address) and [Gateway] (gateway's IP address) and enter the necessary information.
 - Enter the IP addresses and prefix length using the data entry screen (📖 28).

Individual settings available for manual change (communication settings)

Menu item	Setting options and additional information
[Wi-Fi]	
[SSID]	–
[Advanced Settings]	[Authentication Method], [Password]
[TCP/IPv4]	
[IP Address Settings]*	[Automatic Setting], [Manual Setting]
[DNS Server]	[Disable], [Auto Assign], [Manual Setting]
[DNS Address]*, [IP Address]*, [Subnet Mask]*, [Gateway]*	
[TCP/IPv6]	
[TCP/IPv6 Settings]*	[Disable], [Enable]
[Manual Setting]	[Disable], [Enable]
[DNS Server]	[Disable], [Auto Assign], [Manual Setting]
[DNS Address], [Manual Address], [Prefix Length], [Gateway]	Enter the desired address using the data entry screen (📖 28).

Individual settings available for manual change (function settings)

Menu item	Setting options and additional information
[FTP Transfer]	
[Destination Server]	
[Server]*, [Port No.]*	
[User Name/Password]	
[User Name]*, [Password]*	
[Destination Folder]*	
[Dest. Folder Structure]	[Default], [Camera]
[Overwrite Files]	[Skip], [Save As (New Name)], [Overwrite] Determines how to deal with files to be transferred when files with the same name already exists in the destination folder. [Skip]: The file will not be transferred. [Save As (New Name)]: The file will be transferred and “_1” will be added to the end of the file name. [Overwrite]: The file will be transferred, overwriting any file with the same name on the FTP server.
[Passive Mode]*	[Disable], [Enable]
[New Folder by Date]	[Enable], [Disable]
[IP Streaming]	
[Protocol]*	[UDP], [RTP], [RTP+FEC], [RTSP+RTP], [SRT]
[Destination Server]*, [Dest. Port No.]*, [FEC Port No.]*	
[FEC Interval]	10 to 100 (intervals of 5)
[RTSP: User Name]*, [RTSP: Password]*	
[SRT: Connection Mode]	[Caller], [Listener]
[SRT: Stream ID]	
[SRT: Listening Port No.]	
[SRT: Encryption Settings]	[Disable], [AES-128], [AES-192], [AES-256]
[SRT: Passphrase]	
[SRT: Latency]	
[Video Output Conf.]*	[9Mbps/1920x1080 59.94P], [4Mbps/1920x1080 59.94P], [9Mbps/1920x1080 50.00P], [4Mbps/1920x1080 50.00P], [9Mbps/1920x1080 59.94i], [4Mbps/1920x1080 59.94i], [9Mbps/1920x1080 50.00i], [4Mbps/1920x1080 50.00i]
[Audio Out Channels]*	[CH1/CH2], [CH3/CH4]
[CV Protocol]	
[Destination Server]	
[Dest. Port No.]	

* Change these settings as explained in the wizard (169).

Changing Browser Remote Settings

1 Select **MENU** >  Network Settings] > [Advanced Settings] > [Browser Remote Settings].

2 Change the various settings as necessary.

- You can select [Port No. (HTTP)] or [Port No. (HTTPS)] to change the port numbers used for each connection. Using the default port numbers (HTTP: 80, HTTPS: 443) is recommended.
- To use an HTTPS connection, select [HTTPS] > [Enable].

To use a secure HTTPS connection, use a Camera Access Point connection setting and connect the network device to the camera using a normal HTTP connection ( 187) and download the necessary certificate from the Browser Remote's settings tab ( 192). After you import the certificate you downloaded to your Web browser, you will be able to use a secure HTTPS connection.

To change XC Protocol settings


1 Select **MENU** >  Network Settings] > [Advanced Settings] > [XC Protocol Settings].

2 Change the various settings as necessary.

- You can select [Port No. (HTTP)] or [Port No. (HTTPS)] to change the port numbers used for each connection. Using the default port numbers (HTTP: 80, HTTPS: 443) is recommended.
- When [HTTPS] > [Enable] is selected, you will be able to access XC Protocol-compatible devices connected to the network via HTTPS communication. To use HTTPS communication, first select [Save HTTPS Self-signed Cert] to save the self-signed certificate to the SD card in slot B. Next, import the saved self-signed certificate into the XC Protocol-compatible device to enable HTTPS communication.

Checking the Network's Status

Unless you selected to configure a connection setting offline (without connecting to the network), immediately after configuring a new connection setting, the camera will connect to the network automatically and the selected function settings will be activated. The icons displayed on the screen will indicate the type of network selected and the connection status. When you disable the network functions or disconnect from the network, the icons will disappear.



Network connection icons

- Wi-Fi (Infrastructure):
In yellow – the camera is connecting to or disconnecting from the network. In white – the network function can be used.
- Wi-Fi (Camera Access Point):
In yellow – starting the camera's access point. In white – the camera's access point is ready. Connect the Wi-Fi enabled device to the camera.
- Ethernet:
In yellow – the camera is connecting to or disconnecting from the network. In white – the network function can be used.

Network function icons

- FTP: FTP file transfer (📖 184)
- IP: IP streaming (📖 185)
- CV Protocol: CV protocol (📖 173)
- frame.io: Frame.io (📖 196)

Frame.io upload status icons

00, 00, **Full**: Uploading, upload paused, upload requests are full.

FTP File Transfer

In MEDIA mode, you can transfer clips from the camera to another device connected to the network, using the FTP protocol.

The following explanations assume that the FTP server is on, ready and correctly configured.

Transferring a Single Clip

- 1 Connect the camera to the desired network and activate the network functions (📖 168).
 - Select a connection setting with the [FTP Transfer] function setting.
- 2 Select the desired clip in the [XF-AVC] or [XF-HEVC S / XF-AVC S] index screen (📖 141).
- 3 Press SET to open the file menu and select [FTP Transfer] > [OK].
 - The camera will connect to the FTP server and the file will be transferred.
 - Select [Cancel] to interrupt the file transfer in progress.

Transferring All Clips

- 1 Connect the camera to the desired network and activate the network functions (📖 168).
 - Select a connection setting with the [FTP Transfer] function setting.
- 2 Open the [XF-AVC] or [XF-HEVC S / XF-AVC S] index screen (📖 141).
- 3 Select **MENU** > [📶 Network Settings] > [FTP Transfer All Clips] > [OK].
 - The camera will connect to the FTP server and all the files will be transferred.
 - Select [Cancel] to interrupt the file transfer in progress.



IMPORTANT

- Observe the following precautions when transferring files. Failing to do so may interrupt the transfer and incomplete files may remain at the transfer destination.
 - Do not open the card compartment cover.
 - Do not remove the power source or turn off the camera.
- If incomplete files remain at the transfer destination, check the content and make sure they are safe to delete before deleting them.



NOTES

- Depending on the access point's settings and capabilities, it may take some time to transfer files.

IP Streaming

In CAMERA mode, you can stream the camera's live video and audio over IP to a compatible IP video decoder* connected to the network. You can use IP streaming for live broadcasts or to send video reports from a location with poor network connectivity.

* This can be a dedicated video transfer device or decoder software on a computer. For details about compatible decoders, please visit your local Canon website.

Configuration of video streamed over IP

Main recording video configuration			Streamed video configuration				
Video format	Main resolution	Frame rate	Video			Audio	
			Bit rate	Resolution	Frame rate	Audio format	Bit rate
XF-AVC, XF-AVC S	3840x2160, 1920x1080	59.94P	4 Mbps, 9 Mbps	1920x1080	59.94P, 59.94i	MPEG-2 AAC 2 channels*	256 Kbps
		59.94i			59.94i		
		50.00P			50.00P, 50.00i		
		50.00i			50.00i		

* When the audio of the primary clip uses 4 channels, you can select which channels to stream over IP.

1 On the receiver's side: Connect the decoder to the network and complete any necessary configurations so it is ready to receive video over IP.

- For details refer to the instruction manual of the decoder device or software you will use.

2 On the camera: Connect the camera to the desired network and activate the network functions (168).

- Select a connection setting with the [IP Streaming] function setting.

3 Select **MENU** > [Network Settings] > [Activate IP Streaming] > [Enable].

- The camera will start streaming video over the selected network.
- You can press the REC button to simultaneously record the same image in the camera.

4 On the receiver's side: Connect to the camera.

When the streaming protocol is [RTSP+RTP], access the following URL and log in using the RTSP user name and password (170).

rtsp://xxx.xxx.xxx.xxx/stream

Camera's IP address

When the streaming protocol is [SRT] and the connection mode is [Listener], access the following URL.

srt://xxx.xxx.xxx.xxx/xxx...

Camera's IP address

Listener port number

- If the data to be transmitted is encrypted, enter the SRT passphrase.

5 On the camera: To end the streaming, select **MENU** > [Network Settings] > [Activate IP Streaming] > [Disable].

! IMPORTANT

- Streamed data is not encrypted.

i NOTES

- Except when the streaming protocol is RTSP or SRT, once IP streaming is activated, the camera will continue to broadcast video and audio data over the network, regardless of the status of the receiver. Be careful to set up the correct IP address and test in advance that the receiving decoder can indeed receive the signals.

- Depending on the network used and the connection conditions, you may experience lost or delayed IP packets.
- After streaming continuously for 24 hours, the camera will stop the IP streaming momentarily and then restart it automatically.
- When using IP streaming together with the Browser Remote function, you may experience stuttering issues in the streamed video or audio. When the two functions are used simultaneously, it is recommended not to log out from/reconnect to Browser Remote.
- Opening the card compartment cover and removing a card while IP streaming is activated may cause brief stops in the streamed video and audio.
- **IP streaming cannot be used in the following cases:**
 - When the main recording format is set to one of the [XF-HEVC S] or [RAW] options.
 - When using a recording mode other than [Normal Recording].
 - When [2nd Card Rec Functions] is set to an option other than [Off].
 - When using the camera as a web camera.

Browser Remote: Controlling the Camera from a Network Device

In CAMERA mode, you can operate the camera remotely using Browser Remote, an application that can be accessed on a connected network device. Using Browser Remote you can check the camera's live image and control various recording settings*. You can also check other important indications, such as remaining recording time on the card, remaining battery charge/power source details, time code, etc.

* White balance, ISO speed/gain, shutter speed, ND filter, aperture, focus and zoom.

Starting Browser Remote

After connecting the camera to the network In CAMERA mode, you can start the Browser Remote application on the Web browser* of any network device** connected to the same network.

* A Web browser that supports JavaScript and is enabled to accept cookies is required.

** For details about compatible devices, operating systems, Web browsers, etc., please visit your local Canon website.

Preparations on the Camera

- 1 Connect the camera to the desired network and activate the network functions (📖 168).
 - Select a connection setting with the [Browser Remote] function setting.
- 2 Check the Browser Remote's URL in the [🔌 Network Settings] status screen (📖 213).
 - When using IPv6 settings, check the camera's IP address instead (📖 213).
 - Write down the URL or IP address if necessary.

On the Network Device


- 1 Connect the network device to the camera or to the same access point as the camera.
- 2 Start the Web browser on the network device.
- 3 Enter Browser Remote's URL.
 - Enter the URL / IP address you checked previously into the Web browser's address bar as follows.

`http://xxx.xxx.xxx.xxx:nnn`

 Camera's IP address Port No. (can be omitted when using the default port no.)


- To use an HTTPS connection, enter "https:" instead of "http:".
- When using IPv6 settings, enter the camera's IPv6 IP address instead.

- 4 Enter the user name and password.
 - Be sure to log in with the user name and password of one of the users that were set on the camera (📖 172). If necessary, consult the administrator who configured the camera's settings.
 - The Browser Remote screen will appear. The screen displayed may be different depending on the user information used to log in.



Example of the login screen. The screen may differ depending on the Web browser and version used.

- 5 To change the application's language, select [⋮] > [Language 🗨] > Desired language.
 - Most buttons and controls emulate physical controls on the camera and are labeled in English only, regardless of the language selected.
 - Note that not all the languages supported by the camera are supported by the Browser Remote application.
- 6 Use the Browser Remote controls to operate the camera.
 - Descriptions of the controls are given in the following pages.



7 When you have finished using Browser Remote, select [⋮] > [Log Out] on the Browser Remote screen to end the application.

 NOTES


- Depending on the network used and the connection performance, you may notice delays in the refreshing of the live view image and other settings. If the delay is too long, changing the resolution of the live view image is recommended ( 192).
- If Browser Remote is set to a language other than the language set on the network device, the application may not be displayed correctly.

Using Browser Remote

NOTES

- Browser Remote does not support multi-touch gestures.

The Main Remote Operation Screen



- 1 Network connection indicator**
While Browser Remote is correctly connected to the camera, the dots will keep turning on and off in a loop.
- 2 Live view screen**
Shows the camera's live view image.
- 3 Double slot recording**
- 4 Recording operation** ( 51) and recording command ( 202) (same as on the camera)
- 5 Time code** (same as on the camera)
- 6 Add a shot mark**
- 7 Add a  mark**
- 8 Add an  mark**
- 9 Camera's nickname** ( 178) and lens model name
- 10 [LIVE VIEW] button**
Touch the button to display the camera's live view image on the Browser Remote screen.
- 11 [Touch Focus] button**
Touch the button to unlock (enable) the touch focus mode.
- 12 IP streaming**
Available only when using a connection setting with both the [Browser Remote] and [IP Streaming] function settings.

13 [REC] button

Touch the button to start recording. The recording operation indicator changes to [●REC] and the center of the button turns red.

The time code will advance while recording.

Touch the button again to stop recording. The recording operation indicator changes back to [STBY].

14 Card selection and approximate remaining recording time

15 [SLOT SELECT] button


Touch to select the other card when both card slots contain a card.

16 Assignable buttons

17 Assignable functions check

18 Remaining battery charge

The menu is displayed in detail as follows when Full Controls is selected.
If needed, use the [Full Ctrl] switch.



19 Manual zoom slider

Touch to adjust the zoom.

20 Manual focus controls

When [Focus] is active, touch [◀◀◀], [◀◀] or [◀] to focus closer or [▶], [▶▶] or [▶▶▶] to focus farther. There are three levels of adjustment - [◀]/[▶] is the smallest and [◀◀◀]/[▶▶▶] the largest. Keep touching the button (long press) for a continuous operation.

21 Continuous AF

22 AF frame

23 AF response

24 One-shot AF

25 Subject to detect

26 Tracking

27 Eye detection

28 ND filter

29 Aperture value

30 Iris increment

31 Push auto iris

32 Base ISO

33 ISO speed/gain value

34 ISO/Gain increment

35 Shutter mode

36 Shutter increment

37 AE response

38 Face detection AE

39 White balance method selection

When the white balance mode is set to [AWB], touch [AWB Lock] to lock the current white balance settings. Touch again to resume the automatic white balance (AWB). When the white balance mode is set to [A] or [B], touch [A/B] to register a custom white balance.

40 Custom picture file

41 Full Ctrl (full controls) switch

42 Key lock button

Touch the icon to lock the Browser Remote screens in order to prevent settings from being changed inadvertently. Controls on the camera are not locked.

43 Browser Remote settings (192)

44 Function shortcut button

Displays the various adjustable functions. Touch the function you wish to adjust.


- 45 [Focus Guide] switch

Touch to display the focus guide (81).
- 46 Lens action if AF is not possible
- 47 AF speed
- 48 AF lock
- 49 Subject detection AF
- 50 Cancel tracking
- 51 Extended ND range
- 52 Fine increment
- 53 ISO speed/gain extended range
- 54 AE shift
- 55 Color temperature, Color compensation

: Browser Remote Settings Tab

- 1 Language selection

Touch to select the display language for some screens and messages.
- 2 Display style
- Touch to select the background color of the Browser Remote screens.
- 3 Secured connection
- Touch to download the certificate required to use a secure HTTPS connection.
- 4 Live view resolution
- Select [Large] (higher resolution) or [Small] (lower resolution) depending on the quality of the connection.
- 5 Log out
- Touch to log out from the Browser Remote application.



Recording Remotely Using an XC Protocol Compatible Controller/Application

Set the IP address of the camera on the optional XC Protocol compatible RC-IP100/RC-IP1000 Remote Camera Controller or Remote Camera Control Application¹ to control the camera remotely. You can also control the camera remotely using Multi-Camera Control² on a smartphone connected to the same network as the camera.

¹ Available from your local Canon website.

² Available from the App Store.

1 In CAMERA mode, activate the network functions (📖 168)

- Select a connection setting with the [XC Protocol] function setting.

Recording remotely using the RC-IP100/RC-IP1000 Remote Camera Controller

You can remotely control camera settings like the aperture and shutter speed, or change picture related settings like the knee and sharpness. For more details on the connection, settings and the RC-IP100/RC-IP1000 refer to the RC-IP100/RC-IP1000 instruction manual.

NOTES

- The zoom can only be operated when a compatible lens (📖 249) is attached to the camera.
- [PRESET] focus and zoom settings can only be used when a compatible RF lens / EF Cinema lens is attached to the camera (CN-E70-200mm T4.4 L IS KAS S, CN-E18-80mm T4.4 L IS KAS S or RF24-105mm F2.8 L IS USM Z).
- Even if the camera's controls are locked (key lock), you can use the RC-IP100/RC-IP1000 to operate the camera (📖 15).

NOTES

- **About changing custom picture related settings**
 - If a protected custom picture file is selected on the camera, custom picture related settings cannot be changed using the remote camera controller or Remote Camera Control Application.
 - Adjusting custom picture related settings using the remote camera controller or Remote Camera Control Application will change the settings registered under the currently selected custom picture file. If you want to keep an important custom picture file, backup it or select in advance a custom picture file you do not mind changing.

Recording remotely using the Remote Camera Control Application

During recording, you can check the angle of view using Live View and adjust various picture related settings. For details about connection/setup and the Remote Camera Control Application, refer to the Remote Camera Control Application manual.

NOTES

- Even when camera operation is disabled by key lock, operation is possible using the Remote Camera Control Application (📖 15).
- When adjusting custom picture related settings, refer to *About changing custom picture related settings* (📖 193).

Recording remotely using Multi-Camera Control

You can use a smartphone connected to the same network as the camera to remotely operate the camera and record video. During recording, you can check the angle of view using Live View and adjust various picture related settings.

1 Install Multi-Camera Control on your smartphone.

- Download and install Multi-Camera Control from the App Store.
- There is no need to repeat this step after the first time.

2 Connect the smartphone to the same network (access point) as the camera.

- For details, refer to the smartphone's instruction manual.

3 Activate the desired network connection (📖 168).

- Select a connection setting with the [XC Protocol] function setting.

4 Open Multi-Camera Control on the smartphone.

5 Operate the smartphone to connect to the camera.

6 Operate Multi-Camera Control on the smartphone to record remotely.

7 When you finish the procedure, set **MENU** > [📶 Network Settings] > [Network] to [Disable].

- You can also set **MENU** > [📶 Network Settings] > [Connect] to [Disconnect].



NOTES

- Even when camera operation is disabled by key lock, operation is possible using the Multi-Camera Control (📖 15).

Transferring Recordings to a Smartphone

You can transfer and save clips (XF-HEVC S, XF-AVC S), audio (WAV), photos (JPEG) and News Metadata files to a smartphone (connected to the same network as the camera) (📖 162).

1 Install Content Transfer Professional on your smartphone.

- Download and install the Content Transfer Professional from the App Store or Google Play.
- There is no need to repeat this step after the first time.

2 Connect the smartphone to the same network (access point) as the camera.

- Be sure to activate tethering in advance when using a smartphone as an access point.
- For details, refer to the smartphone's instruction manual.

3 Activate the desired network connection (📖 168).

- Select a connection setting with the [Canon App] function setting. However, since the Canon application settings are saved for each smartphone, reconfiguration is required when using a different smartphone.

4 As indicated on the screen, open the application on the smartphone.

5 Operate the smartphone to connect to the camera.

6 Select [OK].

7 Using the Content Transfer Professional, transfer recordings from the camera.

8 When you finish the procedure, set **MENU** > [📶 Network Settings] > [Network] to [Disable].

- You can also set **MENU** > [📶 Network Settings] > [Connect] to [Disconnect].
- When you end the connection from the smartphone, **MENU** > [📶 Network Settings] > [Network] will be set to [Disable].

NOTES

- Use a supported USB cable* or the network functions to connect the camera to a smartphone. When connecting using a USB cable, refer to *Saving Recordings to a Smartphone* (📖 162).

Uploading Recording Data to Frame.io

Once paired with the camera, you can use Adobe's Frame.io Camera to Cloud function to upload proxy clips (XF-AVC, XF-HEVC S, XF-AVC S) and WAV audio (second card recording functions) recorded on the card in slot B.

Automatic upload

- 1 Activate the network functions ( 168).
 - Select a connection setting with the [Frame.io] function setting.
- 2 Select **MENU** > [ Network Settings] > [Frame.io] > [Auto Upload On Recording] > [On], then start recording.
 - The data is added to the upload queue and uploaded to Frame.io sequentially.

Manual upload

- 1 Switch to MEDIA mode.
- 2 Activate the network functions ( 168).
 - Select a connection setting with the [Frame.io] function setting.
- 3 Select the recording data to be uploaded from the slot B [XF-AVC], [XF-HEVC S/XF-AVC S] or [WAV] index screen.
- 4 Select the clip menu > [Frame.io Upload] > [OK].
 - The data is added to the upload queue and uploaded to Frame.io sequentially.



NOTES

- You can check the upload status from **MENU** > [ Network Settings] > [Frame.io] > [Upload Status/Del. Request]. If you want to delete a request, select the clip and select SET > [OK].
- Select **MENU** > [ Network Settings] > [Frame.io] > [Delete All Requests] > [OK] to clear all upload requests.
- Select **MENU** > [ Network Settings] > [Frame.io] > [Pause Uploading] > [Enable] to pause the upload.
- During recording, uploads to Frame.io are paused.

Updating the Firmware Automatically

If the server has the latest firmware when the camera is connected to a network using a function setting other than the CV protocol, an asterisk will be shown on  on the menu. In this case, you can update the camera's firmware using the following procedure.

- 1 Insert an SD card into the camera's SD card slot B ( 36).
- 2 Select **MENU** > [ System Settings] > [Firmware] > [Download Latest Firmware] > [OK].
- 3 Read the End User License Agreement (EULA) carefully and agree to it.
 - The latest firmware is downloaded to the SD card.
- 4 After downloading is complete, select [OK] twice.
 - The firmware update starts and cannot be aborted.
- 5 When the update is complete, select [OK].
 - The camera's settings are reset and the PIN code setting screen appears.

IMPORTANT

- Make sure that you observe the following during firmware update:
 - Do not turn off power. Do not remove the battery or power supply.
 - Do not perform any other button operation.
 - Do not open the memory card cover and remove the SD card.

NOTES

- Connect the AC adapter or attach a fully charged battery to the camera.

Menu Options

For details about how to select an item, refer to *Using the Menus* (📖 26). For details about each function, see the reference page or the explanation accompanying the menu entry. Setting options in boldface indicate default values.

Depending on the camera's operating mode and the settings, some menu items may not be available. Such menu items do not appear or appear grayed out in menu screens.

To skip directly to the page of a specific menu:

[📷 Camera Setup] menu	📖 199	[🛠 Assistance Functions] menu	📖 206
[🖼 Custom Picture] menu	📖 201	[🌐 Network Settings] menu	📖 208
[📹 Recording/Media Setup] menu	📖 201	[🔗 Assignable Buttons] menu	📖 209
[🔊 Audio Setup] menu	📖 203	[⚙ System Setup] menu	📖 210
[📺 Monitoring Setup] menu	📖 204	[★ My Menu] customized menu	📖 212

[📷 Camera Setup] menu (CAMERA mode only)

Menu item	Setting options and additional information
[Iris Mode]	[Automatic], [Manual] (📖 73) This setting is available only when a compatible lens (📖 249) is attached to the camera.
[Iris Increment]	[1/2 stop], [1/3 stop] (📖 73)
[Fine Increment]	[On], [Off]
[Zoom-Iris Correction]	[On] , [Off] If you are using a compatible lens, when this setting is set to [On], the camera will adjust as needed to keep the selected aperture value while zooming. Because of this adjustment, the brightness of the image might flicker slightly or you may hear the operation sound. When the setting is set to [Off], there will be no flickering or operation sounds but the aperture value will gradually increase (the picture will get darker) as you zoom.
[ND Display Units]	[Stop] , [Transmittance], [Optical Density] (📖 72)
[Extended ND Range]	[On], [Off] (📖 72)
[Shutter Mode]	[Speed], [Angle] , [Clear Scan], [Slow], [Off] (📖 66)
[Shutter Increment]	[1/3 stop], [1/4 stop]
[Auto Clear Scan Setting]	– (📖 67)
[Flicker Reduction]	[Automatic], [Off] (📖 67)
[Base ISO]	Available settings differ depending on the [Gamma/Color Space] component in the custom picture file and the recording format settings. (📖 68)
[ISO/Gain]	[ISO] , [Gain] (📖 68)
[ISO/Gain Mode]	[Automatic], [Manual] (📖 70)
[ISO/Gain Extended Range]	[On], [Off] (📖 68)
[ISO/Gain Increment]	[ISO]: [1 stop], [1/3 stop] (📖 68) [Gain]: [Normal] , [Fine]
[Limit for Auto Mode]	Available values differ depending on the main recording format, gamma curve in the custom picture file, ISO/gain extended range and base ISO settings. (📖 70)
[Light Metering]	[Backlight], [Standard] , [Spotlight] (📖 76)
[AE Shift]	–2.0 to +2.0 in 0.25 point intervals (±0) (📖 75)

Menu item	Setting options and additional information	
[AE Response]	[High], [Normal] , [Low] Determines how quickly the exposure (aperture, shutter speed and gain) changes when using the automatic adjustment mode.	(74)
[Shockless WB]	[On], [Off]	(77)
[AWB Response]	[High], [Normal] , [Low]	(79)
[C. Temp. Increment]	[Mired] , [Kelvin]	(77)
[Continuous AF]	[Disable], [Enable]	(80)
[Lens action if cannot AF]	[Continue focus search] , [Stop]	(83)
[Track after Focusing]	[On (tracking frame)], [On (no tracking frame)], [Disable]	(83)
[AF Frame]	[Small Zone], [Zone], [Large Zone: Vertical], [Large Zone: Horizontal], [Whole Area]	(85)
[AF Speed]	+1 to +10 (7)	(84)
[AF Response]	−3 to +3 (0)	
[Focus Mode]	[AF] , [MF]	(80)
[Subject to detect]	[People] , [Animals], [None]	(86)
[Subj. detect. AF]	[Detect. priority] , [Detect. only]	(86)
[Eye Detection]	[On] , [Off]	(86)
[Face Detection AE]	[On], [Off]	(126)
[Camera Grip Zoom]	[On], [Off]	(90)
[Camera Grip Zoom Speed]	1 to 16 (8)	
[Tele-converter]	[x3.0], [x2.5], [x2.0], [x1.5], [Off]	
[ABB]	—	(45)
[Color Bars]	[On], [Off]	(107)
[Color Bar Type]	[SMPTE] , [EBU]* , [ARIB]	
[Periph. Illum. Corr.], [Chromatic Aberr. Corr.], [Diffraction Correction], [Distortion Aberr. Corr.]	[On], [Off]	(31)
[RF-S/EF-S Lens]	[On], [Off] If peripheral brightness fall-off or vignetting occurs when using an EF-S lens, you can set [RF-S/EF-S Lens] to [On] to slightly crop the imaging area. The image is enlarged digitally by a factor of about 1.09x (when the resolution is 4096x2160 or 2048x1080), or 1.04x (when the resolution is 3840x2160 or 1920x1080), affecting image quality. Available only when the main recording format is set to an option other than RAW, the sensor mode is set to an option other than [Full Frame], and the digital tele-converter is disabled. In most cases, leaving the [Off] option is recommended.	(29)
[Lens Optical IS]	[On] , [Off] When an RF-S lens is attached, set this setting to [On] to compensate for camera shake using optical image stabilization.	(88)
[Digital IS]	[On], [Off]	(88)
[Digital IS Mode]	[High], [Standard]	(88)
[Motion Vector For Digital IS]	[Enable], [Disable]	(88)
[Lens Focal Length]	1 to 1000 (50)	(88)
[Anamorphic Corr.]	[Lens Squeeze Factor], [x2.0], [x1.8], [x1.3], [Off]	

* The default value depends on the country/region of purchase.

[Custom Picture] menu (CAMERA mode only)

Menu item	Setting options and additional information
[Select  File]	[C1:Canon 709] , [C2:Canon Log 2], [C3:Canon Log 3], [C4:BT.709 Wide DR], [C5:BT.709 Standard], [C6:PQ], [C7: HLG], [C8:EOS Standard], [C9:EOS Neutral], [C10: User10] to [C20: User20] (129)
[Edit  File]	
[Rename]	— (131)
[Protect]	[Unprotect], [Protect]
[Reset]	[Canon 709] , [Canon Log 2], [Canon Log 3], [BT.709 Wide DR], [BT.709 Standard], [PQ], [HLG], [EOS Standard], [EOS Neutral], [User (Canon 709)]
Detailed custom picture settings	Refer to the tables in the <i>Available Custom Picture Settings</i> section. (134)
[Save  File]	(132)
[Copy to SD Card B], [Load from SD Card B]	—

[Recording/Media Setup] menu

Menu item	Setting options and additional information
[Initialize Media]	[SD Card A], [SD Card B] (37)
[Sensor Mode]	[Full Frame] , [Super 35mm (Cropped)] (62)
[System Frequency]	[59.94 Hz] , [50.00 Hz] ¹ , [24.00 Hz] (61)
[Main Rec Format]	[RAW ST], [RAW LT], [XF-AVC YCC422 10 bit] , [XF-HEVC S YCC422 10 bit], [XF-HEVC S YCC420 10 bit], [XF-AVC S YCC422 10 bit], [XF-AVC S YCC420 8 bit] (62) Available options vary depending on the sensor mode.
[Main Resolution]	[RAW]: [6000x3164], [4368x2304] [XF-AVC]: [4096x2160 Intra-frame], [4096x2160 Long GOP], [3840x2160 Intra-frame], [3840x2160 Long GOP] , [2048x1080 Intra-frame], [2048x1080 Long GOP], [1920x1080 Intra-frame], [1920x1080 Long GOP] [XF-HEVC S]: [4096x2160], [3840x2160] , [2048x1080], [1920x1080] [XF-AVC S]: [XF-AVC S YCC422 10 bit]: [4096x2160 Intra-frame], [4096x2160 Long GOP], [3840x2160 Intra-frame], [3840x2160 Long GOP] , [2048x1080 Intra-frame], [2048x1080 Long GOP], [1920x1080 Intra-frame], [1920x1080 Long GOP] [XF-AVC S YCC420 8 bit]: [4096x2160], [3840x2160] , [2048x1080], [1920x1080] Available options vary depending on the sensor mode and frame rate. (62)
[Frame Rate]	When [System Frequency] is set to [59.94 Hz]: [59.94i]*, [59.94P] ¹ , [29.97P], [23.98P] When [System Frequency] is set to [50.00 Hz]: [50.00i]*, [50.00P] ¹ , [25.00P] When [System Frequency] is set to [24.00 Hz]: [24.00P] * XF-AVC clips only. Not available when slow & fast motion recording, frame recording or interval recording is activated. (62) Available options vary depending on the sensor mode and main recording format/main resolution.

Menu item	Setting options and additional information	
[Bit Rate]		(62)
	Available options vary depending on the main recording format, main resolution and frame rate.	
[XF-HEVC] / [XF-AVC] Main Audio]	[AAC 16 bit 2CH] , [LPCM 24 bit 4CH]	(101)
[Recording Mode]	[Normal Recording] , [Slow & Fast Motion], [S&F Clip / Audio (WAV)], [Pre-Recording], [A Main / B Continuous Rec], [Frame Recording], [Interval Recording]	(39, 114)
[Slow & Fast Frame Rate]		(114)
	Available options and default value vary depending on other settings. See the tables on the reference page.	
[Continuous Recording]	[REC], [STBY]	(118)
[Frame Rec: Frame Rate]	[1] , [3], [6], [9]	(119)
[Interval Rec: Time Interval]	[1 sec] , [2 sec], [3 sec], [5 sec], [10 sec], [15 sec], [30 sec], [1 min], [2 min], [3 min], [5 min], [10 min]	(119)
[Interval Rec: Frame Rate]	[1] , [3], [6], [9]	
[2nd Card Rec Functions]	[Off] , [A Main / B Proxy Rec], [A Main / B Sub Rec], [A Main / B Audio Rec], [Relay Recording], [Double Slot Recording], [A ---(HDMI Main) / B Proxy Rec]*, [A ---(HDMI Main) / B Sub Rec]* * Only available when [HDMI RAW] is set to [On].	(39)
[B Rec Format]	[XF-AVC YCC422 10 bit] , [XF-AVC YCC420 8 bit], [XF-HEVC S YCC422 10 bit], [XF-HEVC S YCC420 10 bit], [XF-AVC S YCC422 10 bit], [XF-AVC S YCC420 8 bit]	(63) (64)
	Available options vary depending on the main recording format.	
[B Resolution]	Available options vary depending on the main recording's settings.	(63)
[B Frame Rate]	[Same as Main Recording] , [59.94i], [59.94P], [50.00i], [50.00P]	(63)
[B Bit Rate]	Available options vary depending on the [B Resolution] and [B Frame Rate] settings.	(63)
[B XF-HEVC] / [XF-AVC] Audio]	[AAC 16 bit 2CH] , [LPCM 24 bit 4CH]	(101)
[Proxy Rec Color Conversion]	[Conform to Custom Picture] , [BT.709 (Canon 709)], [BT.709 (CMT 709)]	(64)
[Metadata]		
[Camera Index]	[A_] to [ZZ]	(42)
[Reel Number]	[0001] to [9999]	
[Clip Number]	[001] to [999]	
[User Defined]	User defined string up to 5 characters ([CANON])	(43)
[Scene], [Take]	Scene description up to 16 characters / Take description up to 8 characters	(113)
[Lens Squeeze]	[x2.0], [x1.8], [x1.3], [Off]	(121)
[Add XML File]	[On] , [Off]	(111)
[XML File Format]	[News Metadata] , [User Memo]	(112)
[News Metadata]	[Off] , list of available News Metadata files	(112)
[News Metadata Reset All]	–	(113)
[User Memo]	[Off] , list of available user memo files	(111)
[Country Code], [Organization], [User Code]	Identifiers up to 4 characters ([00_] default for [Organization] only) [Country Code]: This identifier is the country code defined by ISO-3166-1 and is to be entered starting from the left. [Organization]: This identifier represents the organization that owns or operates the camera and can be obtained by registering with the SMPTE Registration Authority. If the organization is not registered, enter [0000]. [User Code]: This identifier designates the user. Leave this blank if [Organization] is set to [0000].	
[Add CP File]	[On] , [Off]	(134)
[Clip Numbering]	[Reset], [Continuous]	(42)
[HDMI RAW]	[On], [Off]	(155)
[Rec Command(EXT REC)]	[On], [Off]	(154)

Menu item	Setting options and additional information
[HDMI Time Code]	[On], [Off] (154)
[Photo Numbering]	[Reset], [Continuous] (43)
[Volume Label]	[Canon], [Canon + Metadata] (37)

¹ The default value depends on the country/region of purchase.

[🔊] Audio Setup] menu

Menu item	Setting options and additional information
[Audio Input Selection]	
[CH1/CH2], [CH3/CH4]	[INPUT Terminals] , [MIC Terminal], [Monaural Mic], [Multi-Function Shoe] (103)
[CH2 Input]	[INPUT 2] , [INPUT 1], [Monaural Mic], [MIC Terminal] (103)
[CH1/CH2 ALC Link], [CH3/CH4 ALC Link]	[Linked], [Separated] (104)
[Audio Rec Level]	[A] (Automatic), [M] (Manual) 0 to 100 (50) (104)
[INPUT 1 Mic Trimming], [INPUT 2 Mic Trimming]	[+12 dB], [+6 dB], [0 dB] , [−6 dB], [−12 dB] (105)
[INPUT 1 Mic Att.], [INPUT 2 Mic Att.]	[On], [Off] (105)
[INPUT 1 Mic Low Cut], [INPUT 2 Mic Low Cut]	[Off] , [LC1], [LC2] (105)
[INPUT Reference Level]	[−18 dB] , [−20 dB] (105)
[INPUT Limiter]	[On], [Off] (104)
[MIC Att.]	[On], [Off] (105)
[MIC Low Cut]	[Off] , [LC1], [LC2] (105)
[MIC Input]	[MIC (with Power Supply)] , [LINE] (103)
[Multi-Function Shoe Input]	(100)
[Shoe Mic]	
[Shoe Mic Attenuator]	[On], [Off]
[Shoe Mic Low Cut]	[On], [Off]
[Shoe Mic Directionality]	[Shotgun (Monaural)], [90° (Stereo)] , [120° (Stereo)]
[Wireless Mic]	
[Audio Rec Level]	[A] (Automatic), [M] (Manual) 0 to 100 (50)
[🔊1 Wind Filter], [🔊2 Wind Filter]	[On], [Off]
[🔊1 Attenuator], [🔊2 Attenuator]	[On], [Off]
[Wireless Mic Mixing]	[Enable] , [Disable]
[MUTE button]	[Enable], [Disable]
[Movie recording button]	[Enable], [Disable]
[Tally Lamp]	[On] , [Off]
[Display Wireless Mic Status]	—
[1 kHz Tone]	[−12 dB], [−18 dB], [−20 dB], [Off] (107)

Menu item	Setting options and additional information
[Headphone Volume]	[Off], 1 to 15 (8) (146)
[Speaker Volume]	[Off], 1 to 15 (8)
[Monitor Channels]	[CH1/CH2] , [CH1/CH1], [CH2/CH2], [CH1+2/CH1+2], [CH3/CH4], [CH3/CH3], [CH4/CH4], [CH3+4/CH3+4], [CH1/CH3], [CH2/CH4], [CH1+3/CH2+4] (160)
[HDMI OUT Channels]	[CH1/CH2] , [CH3/CH4]
[Level Meter Display Color]	[Color] , [White]

[Monitoring Setup] menu

Menu item	Setting options and additional information
[LCD Brightness], [LCD Contrast]	–50 to 50 (±0) (23)
[LCD Color]	–20 to 20 (±0)
[LCD Sharpness]	1 to 4 (2)
[LCD Luminance]	[–2], [–1], [Normal] , [+1] to [+6]
[LCD Mirror Image]	[On], [Off]
[Anamorphic: LCD], [Anamorphic: SDI], [Anamorphic: HDMI]	[On], [Off] (121)
[Anamorphic Desqueeze]	[Lens Squeeze Factor] , [x2.0], [x1.8], [x1.3]
[Desqueeze for S&F]	[Reduced Display], [Off]
[B&W Image: LCD], [B&W Image: SDI], [B&W Image: HDMI]	[On], [Off] (23)
[OSD Output: SDI]	[On], [Off (Clean)] (157)
[OSD Output: HDMI]	[On] , [Off] (157)
[Tally OSD: LCD], [Tally OSD: SDI], [Tally OSD: HDMI]	[On] , [Off] (54)
[Tally OSD Settings]	[REC/Tally In (PGM/PVW)], [REC], [Tally In (PGM/PVW)]
[Tally OSD Position]	[Frame] , [Top], [Bottom]
[DISP Level 1]	[All Displays] , [All Displays (Periph. Border)] (53)
[DISP Level 2]	[Main Recording Displays] , [Only FUNC/MENU]
[DISP Level 3]	[Only REC/STBY] , [No Displays]
[Apply Peripheral Border]	[DISP Level 1/2/3], [DISP Level 1/2], [DISP Level 1], [DISP Level 2] , [DISP Level 3], [Off] (54)
[Custom Display 1]	(49)
[Light Metering], [Custom Picture], [Focal Length], [ND Filter], [Focus Mode], [Key Lock], [White Balance], [AE Shift], [Iris], [ISO/Gain], [Shutter], [Base ISO], [Peaking], [Tele-converter], [Digital IS], [Magnification], [View Assist], [Lens]	[On] , [Off]
[Object Distance (Numeric)], [Object Distance (Bar)]	[Always On], [Only in MF Mode], [Off]
[Level (Numeric)]	[On], [Off]

Menu item	Setting options and additional information
[Level (Bar)]	[Tilt+Roll], [Roll], [Tilt], [Off]
[Exposure Bar]	[On] , [Disable During AE], [Off]
[Custom Display 2]	(144)
[Remaining Battery], [Remaining Rec Time]	[Only Warnings], [Normal] , [Off]
[Recording Mode], [Interval Counter], [Time Code], [Reel/Clip Number]	[On] , [Off]
[Photo]	[Only Warnings], [Normal] , [Off]
[Temperature/Fan], [Sensor Mode], [Resolution/Color Sampling], [Frame Rate], [Output Terminals Status], [OSD Output]*, [Rec Command(EXT REC)], [User Memo]*, [User Bit]*, [Monitor Channels]*, [Audio Level Indicator], [Multi-Function Shoe]	[On] , [Off] [On], [Normal]: Show the icon/onscreen display always or whenever the necessary conditions are triggered. [Only Warnings]: Show the icon/onscreen display only when a critical level is reached. • The default setting for items marked with an asterisk (*) is [Off].
[Wireless Mic]	[Only Warnings], [Normal] , [Off]
[Network Functions], [GPS]	[On] , [Off]
[Date/Time]	[Date/Time], [Time], [Date], [Off]
[Custom Display]	(144)
	These settings are available only in MEDIA mode and determine whether the following onscreen displays will appear on the playback image.
[Audio Level Indicator]	[On] , [Off]
[Date/Time], [Camera Data]	[On], [Off] [Audio Level Indicator]: The audio level meter (clips only). [Date/Time]: The date and time when the clip/photo was recorded. [Camera Data]: The aperture value, shutter speed and ISO speed/gain value used to record the clip (clips only).
[Displayed Units]	[Meters] , [Feet] ¹ Changes the distance units used in camera displays between meters and feet.
[OSD Opacity: LCD], [OSD Opacity: SDI], [OSD Opacity: HDMI]	[On], [Off] (157)
[OSD Opacity Level]	[75%] , [62.5%], [50%], [37.5%], [25%]
[OSD Opacity: Appl. Screens]	[All] , [Only Rec/Playback Screens]
[OSD Orientation: LCD]	[0 Degrees] , [90 Degrees Left], [90 Degrees Right] (55)
[OSD Orientation: SDI], [OSD Orientation: HDMI]	[Linked to LCD] , [90 Degrees Left], [90 Degrees Right]
[View Assist: LCD]	[On], [Off] (158)
[Select View Assist: LCD]	[CMT 709] , [Canon 709], [HDR Assist. (1600%)], [HDR Assist. (400%)]
[View Assist: SDI], [View Assist: HDMI]	[On], [Off] (159)
[Select View Assist: SDI], [Select View Assist: HDMI]	[CMT 709] , [Canon 709] (158)
[Gain for HDR→SDR Conv.]	−7.5 dB to +7.5 dB in 0.5 dB intervals (−3.0 dB) (159)
[Range: SDI]	(156)

Menu item	Setting options and additional information
[During Canon Log Output]	[Full Range] , [Narrow Range]
[During HDR Output]	[Full Range], [Narrow Range]
[Range: HDMI]	(81 156)
[During Canon Log Output]	[Full Range Priority] , [Narrow Range]
[During HDR Output]	[Full Range Priority], [Narrow Range]

¹ The default value depends on the country/region of purchase.

[Assistance Functions] menu

Menu item	Setting options and additional information
[Focus Guide]	[On], [Off] (81)
[Peaking: LCD], [Peaking: SDI], [Peaking: HDMI]	[On], [Off] (82)
[Peaking]	[Peaking 1] , [Peaking 2]
[Peaking 1]	
[Color]	[White] , [Red], [Yellow], [Blue]
[Gain]	[Off], 1 to 15 (8)
[Frequency]	1 to 4 (2)
[Peaking 2]	
[Color]	[White], [Red] , [Yellow], [Blue]
[Gain]	[Off], 1 to 15 (15)
[Frequency]	1 to 4 (1)
[Magnification]	[On], [Off] (82)
[Magn. Output]	[LCD] , [SDI], [HDMI]
[B&W during Magn.]	[On], [Off] (82)
[False Color: LCD], [False Color: SDI], [False Color: HDMI]	[On], [Off] (94)
[False Color Index]	–
[Zebra: LCD], [Zebra: SDI], [Zebra: HDMI]	[On], [Off] (93)
[Zebra]	[Zebra 1] , [Zebra 2], [Zebra 1+2]
[Zebra 1 Level]	[5 ±5%] to [95 ±5%] in 5 percentage point intervals ([70 ±5%])
[Zebra 2 Level]	0% to 100% in 5 percentage point intervals ([100%])
[WFM: LCD], [WFM: SDI], [WFM: HDMI]	[On], [Off] (108)
[WFM Opacity Level]	[Linked to OSD Opacity] , [100%], [80%], [60%], [40%], [20%] Select the WFM opacity level. If set to [Linked to OSD Opacity], it will be linked to the [OSD Opacity Level] setting.
[WFM Function]	[Waveform Monitor] , [Vectorscope]

Menu item	Setting options and additional information	
[Waveform Settings]		(108)
[Size: LCD]	[Normal] , [2x] Changes the size of the waveform displayed on the screen.	
[Position]	[Right] , [Left]	
[Type]	[Line] , [Line+Spot], [Select Line], [RGB], [YPbPr]	
[Vertical Scale for HDR]	[IRE] , [PQ/HLG]	
[Select Line]	2160 or higher: 0 to maximum value –2 lines (2-line increments) Example: 0 to 2158 (for 2160) (1080) Below 2160: 0 to maximum value –1 line (1-line increments) Example: 0 to 1079 (for 1080) (540) Available options depend on the resolution and operating mode (CAMERA/MEDIA mode).	
[Vectorscope Settings]		(109)
[Position]	[Right] , [Left]	
[Type]	[Normal] , [Spot]	
[Gain]	[1x] , [2x]	
[Markers: LCD], [Markers: SDI], [Markers: HDMI]	[On] , [Off]	(91)
[Playback Marker Display]	[Enable] , [Disable]	(91)
[Center Marker]	[Yellow], [Blue], [Green], [Red], [Black], [Gray], [White], [Off]	(91)
[Center Marker Type]	[Cross 1] , [Cross 2], [Dot 1], [Dot 2]	
[Horizontal Marker], [Vertical Marker], [Grid Marker]	[Yellow], [Blue], [Green], [Red], [Black], [Gray], [White], [Off]	
[Aspect Marker]	[Yellow], [Blue], [Green], [Red], [Black], [Gray], [White], [Mask 100%], [Mask 75%], [Mask 50%], [Mask 25%], [Off]	(92)
[Marker Aspect Ratio]	[4:3], [13:9], [14:9], [16:9], [1.375:1], [1.66:1], [1.75:1], [1.85:1], [1.90:1], [2.35:1], [2.39:1] , [9:16], [4:5], [2:1], [1:1], [Custom]	
[Marker Custom Asp. Ratio]	0.01:0.01 to 9.99:9.99 (1.00:1.00)	
[Safe Area Marker]	[Yellow], [Blue], [Green], [Red], [Black], [Gray], [White], [Mask 100%], [Mask 75%], [Mask 50%], [Mask 25%], [Off]	(92)
[Basis for Marker Safe Area]	[Whole Picture] , [Selected Aspect Marker]	
[Marker Safe Area %]	[80% (Side Length)], [88% (Side Length)], [90% (Side Length)], [93% (Side Length)], [95% (Side Length)]	
[User Marker 1], [User Marker 2], [User Marker 3]	[Yellow], [Blue], [Green], [Red], [Black], [Gray], [White], [Off]	(92)

Menu item	Setting options and additional information
[User Marker 1 Settings], [User Marker 2 Settings], [User Marker 3 Settings]	(📖 92)
[Size]	
[Specification Method]	[Pixel] , [Ref. Area & Aspect Ratio], [Ref. Area & Magn. Ratio]
[Pixel]	[Width]: 2 to 2048 (only even numbers) (1000) [Height]: 2 to 1080 (only even numbers) (1000)
[Reference Area]	[Whole Picture] , [User Marker 1], [User Marker 2] Available options differ depending on the settings for [User Marker 1 Settings] to [User Marker 3 Settings].
[Marker Aspect Ratio]	[4:3], [13:9], [14:9], [16:9], [1.375:1], [1.66:1], [1.75:1], [1.85:1], [1.90:1], [2.35:1], [2.39:1] , [9:16], [4:5], [2:1], [1:1], [Custom]
[Marker Custom Asp. Ratio]	[Available Range]: 0.01:0.01 to 9.99:9.99 (1.00:1.00)
[Magnification Ratio]	[Available Range]: 50 to 150% (95%)
[Position]	
[Specification Method]	[Center Coordinates] , [Upper-left Coordinates], [Centering (User Marker 1)], [Centering (User Marker 2)] Available options differ depending on the settings for [User Marker 1 Settings] to [User Marker 3 Settings].
[Center Coordinates]	[Horizontal]: -1024 to 1024 (0) [Vertical]: -540 to 540 (0)
[Upper-left Coordinates]	[Horizontal]: 0 to 2048 (0) [Vertical]: 0 to 1080 (0)

[📶 Network Settings] menu

Menu item	Setting options and additional information
[Network]	[Enable], [Disable] (📖 168)
[Connect]	[Disconnect] , [SET1] to [SET20]
[Connection Setting]	[SET1] to [SET20] (📖 178)
[Create New with Wizard]	—
[Create with Existing Setting]	—
[Check Settings]	—
[Change with Wizard]	—
[Select Existing Setting]	—
[Settings Name]	File name up to 12 characters
[Delete Settings]	—
[New Conn. Setting (Wizard)]	[FTP Transfer], [IP Streaming], [Browser Remote], [Canon App], [XC Protocol], [CV Protocol], [Frame.io] (📖 169)
[Activate IP Streaming]	[Enable], [Disable] (📖 185)

Menu item	Setting options and additional information	
[Frame.io]		(196)
[Pair]	–	
[Unpair]	–	
[Pairing Information]	–	
[Upload Status/Del. Request]	–	
[Delete All Requests]	–	
[Pause Uploading]	[Disable] , [Enable]	
[Auto Upload On Recording]	[On] , [Off]	
[Auto Upload File Formats]	[XF-AVC Proxy], [XF-HEVC S / XF-AVC S Proxy], [Audio Proxy]	
[Root Certificate]	[Read Root Certificate], [Root Certificate Details], [Delete Root Certificate]	
[FTP Transfer All Clips]	In MEDIA mode only.	(184)
[IPv4 address name]	Displays the current IPv4 address information.	
[View Error Info]	Displays the latest network related error message.	
[Advanced Settings]		(179)
[Communication Settings]	[NW1] to [NW25]	
[Function Settings]	[MODE1] to [MODE25]	
[Browser Remote Settings]	[User Name/Password], [Port No. (HTTP)], [Port No. (HTTPS)], [HTTPS]	(182)
[FTP Transfer Settings]	[Read Root Certificate], [Root Certificate Details], [Delete Root Certificate]	(177)
[XC Protocol Settings]	[Authentication Method], [User Name/Password], [Port No. (HTTP)], [Port No. (HTTPS)], [HTTPS], [Save HTTPS Self-signed Cert]	(173)
[802.1X Authentication]	[Setup Wizard], [Check Settings], [Delete Settings]	(177)
[Nickname]	User defined string up to 16 characters ([C80])	(178)

[Assignable Buttons] menu

Following are the default settings for each assignable button. For a complete list of the functions that can be assigned, refer to the detailed table (126).

Menu item	Setting options and additional information	
[Camera]	1: [White Balance] , 2: [Set White Balance] , 3: [Peaking: All] , 4: [WFM: All] , 5: [DISP] , 6: [Zebra: All] , 7: [Push Auto Iris] , 8: [Magnification] , 9: [FUNC] , 10: [(NONE)] , 11: [(NONE)] , 12: [AF Lock] , 13: [Audio Status]	
[Browser Remote/XC Prot.]		
[Link to Camera]	[Enable], [Disable]	
	1: [Magnification] , 2: [Peaking: All] , 3: [Zebra: All] , 4: [WFM: All]	
[REMOTE A]		(125)
[Link to Camera]	[Enable], [Disable]	
	1: [Magnification] , 2: [Peaking: All] , 3: [Zebra: All] , 4: [WFM: All]	

[🔧 System Setup] menu

Menu item	Setting options and additional information
[Reset]	[All Settings], [Assignable Buttons], [Level] These settings reset the following camera settings to default values/settings. [All Settings]: All the camera's settings except for the hour meter. [Assignable Buttons]: Only the assignable buttons. [Level]: The level reference angle settings.
[Transfer Menu/CP]	(📖 139)
[Save]	[To Camera], [To SD Card B]
[Load]	[From Camera], [From SD Card B]
[Time Zone]	List of world time zones. [UTC-05:00 New York] or [UTC+01:00 Central Europe] ¹ (📖 25)
[Date/Time]	—
[Date Format]	[YMD], [YMD/24H], [MDY] , [MDY/24H], [DMY] , [DMY/24H] ¹
[Language 🗣️]	[Deutsch], [English] , [Español], [Français], [Italiano], [Polski], [Português], [Русский], [Українська], [简体中文], [한국어], [日本語] (📖 25)
[REMOTE Term.]	[RC-V100 (REMOTE A)], [Standard] (📖 123)
[SDI Output]	[On] , [Off] (📖 154)
[SDI Output Signal]	[4096x2160P/3840x2160P], [2048x1080P/1920x1080P] , [1920x1080P], [1920x1080i(PsF)], [1280x720P] (📖 154)
[HDMI Output Signal]	[4096x2160P/3840x2160P] , [1920x1080P], [1920x1080i], [1280x720P] (📖 155)
[Linked to HDMI Monitor]	[On] , [Off]
[Time Code Mode]	[Preset] , [Regen.] (📖 95)
[Time Code Run]	[Rec Run] , [Free Run]
[Time Code DF/NDF]	[DF] , [NDF] (📖 96)
[Set Time Code]	59.94 Hz: [00:00:00.00] to [23:59:59.29] 50.00 Hz: [23:59:59.24] 24.00 Hz: [23:59:59.23] (📖 95)
[TC In/Out]	[In] , [Out] (📖 98, 99)
[User Bit Recording Mode]	[Internal] , [External] (📖 98)
[User Bit Type]	[Setting] , [Time], [Date] (📖 96)
[Front Control Dial], [Rear Control Dial], [Control Ring]	[Iris] , [Shutter], [Clear Scan (Steps)], [ISO/Gain], [White Balance Mode], [White Balance (K)], [White Balance (CC)], [Select Subject], [Off] (📖 69, 74, 78, 86) Determines the function assigned to the respective control dial/control ring. The [Select Subject] setting allows you to switch the main subject/eye used for subject detection/eye detection. • The default function for the rear control dial and control ring is [Off].
[Front Ctrl Dial Dir.], [Rear Ctrl Dial Dir.], [Control Ring Dir.], [SELECT Dial Dir.]	[Reverse], [Normal] Changes the direction of the adjustment when operating the front/rear control dial, the control ring on the lens/adaptor or the SELECT dial, respectively.
[Ctrl Dial in Menus]	[Disable], [Enable] (📖 26) Enables or disables the use of the front and rear control dials to navigate the setup menus, direct touch control, direct setting mode and status screens.
[Focus Ring Operation]	[Enable During AF] , [Disable During AF]
[Focus Ring Direction]	[Reverse], [Normal] Changes the direction of the adjustment when operating the focus ring on an RF lens.
[Focus Ring Response]	[Varies with Rotation Speed], [Linked to Rotation Degree]

Menu item	Setting options and additional information
[Focus/Control Ring]	[Focus Ring], [Control Ring] Selects the function assigned to the RF-S lens focus/control ring. When set to [Control Ring], focus is set to AF*. * When the focus is in the Center Focus Macro range (using a lens equipped with the Center Focus Macro function), focus is not set to AF even if set to [Control Ring] and focus operations from other devices will not be possible. To leave the Center Focus Macro range, select [Focus Ring] and operate the ring to focus at infinity focus.
[Key Lock]	[All Buttons], [All Except REC Button] (15)
[REC Button]	[Disable], [Enable] (47)
	Enables or disables the use of the REC buttons.
[Assign. Button 4 as REC]	[On], [Off] (125)
	When this setting is set to [On], assignable button 4's function changes to [REC].
[Assign. Button 11 as REC]	[On], [Off] (125)
	When this setting is set to [On], assignable button 11's function changes to [REC].
[Onscreen REC/STBY Button]	[On], [Off] (47)
	When this setting is set to [On], the recording operation indicator (REC/STBY) on the CAMERA mode screen becomes an onscreen button you can touch to start/stop recording.
[Touch Screen Response]	[Normal] , [Low] (23)
[Review Recording]	[Entire Clip] , [Last 4 sec] (55)
[Tally Lamp]	[On] , [Off]
	When this setting is set to [On], the tally lamp illuminates/flashes according to the camera and tally input status.
[Tally Lamp Settings]	[Power/Media/Tally In (PGM)] , [REC/Tally In (PGM)], [REC], [Tally In (PGM)] (48)
	When this setting is set to [Power/Media/Tally In (PGM)], the tally lamp illuminates/flashes according to battery and recording warnings and the SD card recording status.
[Card Access LED]	[On] , [Off] (36)
	When this setting is set to [On], the card access indicator illuminates when the camera is accessing the card.
[ (Ethernet) LED]	[On] , [Off]
	When this setting is set to [On], the  (Ethernet) indicator illuminates/flashes when the camera is accessing a wired network.
[USB Mode]	[Video Output (UVC)], [Canon App(s) for iPhone], [Canon App(s)/GP-E2] (162)
	Select [Canon App(s)/GP-E2] when connecting the GP-E2 GPS Receiver to the camera using an optional interface cable.
[GPS Auto Time] ²	[On], [Off]
	When this setting is set to [On], the camera automatically adjust its date and time settings according to the information received from the GPS signal. - While the automatic date/time adjustment is activated, the MENU > [ System Setup] > [Date/Time] setting will not be available. - The time will not be updated while recording video.
[Fan Mode]	[Automatic], [Always On] (44)
[Fan Speed (STBY)]	[Maximum], [High], [Middle], [Low]
[Fan Speed (REC)], [Fan Speed (Always)], [Fan Speed]	[High], [Middle], [Low]
[Level Sensitivity]	[x16], [x8], [x4], [x2], [Standard] (33)
[Level Reference Setting]	[Cancel] , [OK] (33)
[DC IN Warning (V)]	11.5 V to 15.0 V in 0.1 V intervals (13.0 V) (22)

Menu Options

Menu item	Setting options and additional information
[Retract Lens]	[On], [Off] When a compatible lens (📖 250) is attached to the camera and the focus mode switch on the lens is set to AF, if this setting is set to [On], the lens will retract fully when the camera is turned off. When this setting is set to [On], turning off the camera will move the focus position. To prevent this, set this setting to [Off]. Note that there is no guarantee that the focus position will not move, so checking the focus position is recommended when turning on the camera.
[Reset Hour Meter]	The camera has two “hour meters” – the first keeps track of total operation time and the second keeps track of operation time since the last time the second hour meter was reset with this function.
[Certification Information]	This displays select certification information that apply to this camera.
[Firmware]	
[Camera], [Lens], [Mount Adapter], [Power Zoom Adapter], [Accessory]	Check/update the firmware version of the camera, lens (📖 31), mount adapter, power zoom adapter or accessory.
[Download Latest Firmware]	Download the latest firmware and update the camera. (📖 197)
[PIN Code Management]	(📖 24)
[PIN Code Request]	[Disable], [Enable]
[PIN Code Change]	–
[Access Log Display]	– (📖 237)

¹ The default value depends on the country/region of purchase.

² Only when the GP-E2 GPS Receiver is connected to the camera.

[★ My Menu] menu (CAMERA mode only)

Menu item	Setting options and additional information
[CAMERA-1: Edit] to [CAMERA-5: Edit]	[Register], [Move], [Delete], [Reset All], [Rename] (📖 27)

Displaying the Status Screens

You can use the status screens to check the camera's various settings. You can also output the status screens to an external monitor. Portions of the status screens will be displayed in English regardless of the language selected.

- 1 Set an assignable button to [Status] (📖 125).
- 2 Press the assignable button to open the status screens.
 - The status screen most recently displayed will appear unless you turned off the camera or changed the operating mode.
 - You can also press the AUDIO STATUS button to open directly only the [🔊 Audio Setup] status screen.
- 3 Scroll through the status screens to check the desired settings.
 - Bring the cursor to a page number and push the joystick left/right to move between the status screens.
 - You can also use front/rear control dials and the SELECT dial to navigate the status screens in the same way as the setup menus.
- 4 Press the assignable button again or select [✕ CLOSE] to close the status screens.
 - You can also press the MENU button to close the status screens and open the menu instead.

Recording / Output Signal and Detailed Settings

Sub Recording Clips (63)

Main clip: RAW

Sub recording clip: XF-AVC, XF-HEVC S

Primary clip				Sub recording clip configuration ¹		
Main recording format	Main resolution	Frame rate	Bit rate	Sub recording format and resolution/bit rate		
				XF-AVC YCC422 10 bit	XF-HEVC S YCC422 10 bit	XF-HEVC S YCC420 10 bit
RAW LT	4368x2304	59.94P	678 Mbps	4096x2160 / 600 Mbps Intra-frame 4096x2160 / 250 Mbps Long GOP 2048x1080 / 300 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 225 Mbps Long GOP 2048x1080 / 50 Mbps Long GOP	4096x2160 / 150 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
		50.00P	611 Mbps	4096x2160 / 500 Mbps Intra-frame 4096x2160 / 250 Mbps Long GOP 2048x1080 / 250 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 225 Mbps Long GOP 2048x1080 / 50 Mbps Long GOP	4096x2160 / 150 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
HDMI RAW	6000x3164	59.94P	—	4096x2160 / 600 Mbps Intra-frame 4096x2160 / 250 Mbps Long GOP 2048x1080 / 300 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 225 Mbps Long GOP 2048x1080 / 50 Mbps Long GOP	4096x2160 / 150 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
		50.00P	—	4096x2160 / 500 Mbps Intra-frame 4096x2160 / 250 Mbps Long GOP 2048x1080 / 250 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 225 Mbps Long GOP 2048x1080 / 50 Mbps Long GOP	4096x2160 / 150 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
RAW ST, RAW LT	6000x3164, 4368x2304	29.97P	639 Mbps, 563 Mbps, 366 Mbps	4096x2160 / 600 Mbps Intra-frame 4096x2160 / 450 Mbps Intra-frame 4096x2160 / 300 Mbps Intra-frame 4096x2160 / 150 Mbps Long GOP 2048x1080 / 150 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 135 Mbps Long GOP 2048x1080 / 50 Mbps Long GOP	4096x2160 / 100 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
		25.00P	576 Mbps, 470 Mbps, 306 Mbps	4096x2160 / 500 Mbps Intra-frame 4096x2160 / 375 Mbps Intra-frame 4096x2160 / 250 Mbps Intra-frame 4096x2160 / 150 Mbps Long GOP 2048x1080 / 125 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 135 Mbps Long GOP 2048x1080 / 50 Mbps Long GOP	4096x2160 / 100 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
		24.00P	553 Mbps, 541 Mbps, 293 Mbps	4096x2160 / 480 Mbps Intra-frame 4096x2160 / 360 Mbps Intra-frame 4096x2160 / 240 Mbps Intra-frame 4096x2160 / 150 Mbps Long GOP 2048x1080 / 120 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 135 Mbps Long GOP 2048x1080 / 50 Mbps Long GOP	4096x2160 / 100 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
		23.98P	552 Mbps, 541 Mbps, 293 Mbps	4096x2160 / 480 Mbps Intra-frame 4096x2160 / 360 Mbps Intra-frame 4096x2160 / 240 Mbps Intra-frame 4096x2160 / 150 Mbps Long GOP 2048x1080 / 120 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 135 Mbps Long GOP 2048x1080 / 50 Mbps Long GOP	4096x2160 / 100 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP

¹ In most cases, the frame rate is the same as in the primary clip.

Sub recording clip: XF-AVC S

Primary clip				Sub recording clip configuration ¹	
Main recording format	Main resolution	Frame rate	Bit rate	Sub recording format and resolution/bit rate	
				XF-AVC S YCC422 10 bit	XF-AVC S YCC420 8 bit
RAW LT	4368x2304	59.94P	678 Mbps	4096x2160 / 600 Mbps Intra-frame 4096x2160 / 250 Mbps Long GOP 2048x1080 / 300 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 150 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
		50.00P	611 Mbps	4096x2160 / 500 Mbps Intra-frame 4096x2160 / 250 Mbps Long GOP 2048x1080 / 250 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 150 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
HDMI RAW	6000x3164	59.94P	—	4096x2160 / 600 Mbps Intra-frame 4096x2160 / 250 Mbps Long GOP 2048x1080 / 300 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 150 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
		50.00P	—	4096x2160 / 500 Mbps Intra-frame 4096x2160 / 250 Mbps Long GOP 2048x1080 / 250 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 150 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
RAW ST, RAW LT	6000x3164, 4368x2304	29.97P	639 Mbps, 563 Mbps, 366 Mbps	4096x2160 / 600 Mbps Intra-frame 4096x2160 / 450 Mbps Intra-frame 4096x2160 / 300 Mbps Intra-frame 4096x2160 / 150 Mbps Long GOP 2048x1080 / 150 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 100 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
		25.00P	576 Mbps, 470 Mbps, 306 Mbps	4096x2160 / 500 Mbps Intra-frame 4096x2160 / 375 Mbps Intra-frame 4096x2160 / 250 Mbps Intra-frame 4096x2160 / 150 Mbps Long GOP 2048x1080 / 125 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 100 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
		24.00P	553 Mbps, 541 Mbps, 293 Mbps	4096x2160 / 480 Mbps Intra-frame 4096x2160 / 360 Mbps Intra-frame 4096x2160 / 240 Mbps Intra-frame 4096x2160 / 150 Mbps Long GOP 2048x1080 / 120 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 100 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
		23.98P	552 Mbps, 541 Mbps, 293 Mbps	4096x2160 / 480 Mbps Intra-frame 4096x2160 / 360 Mbps Intra-frame 4096x2160 / 240 Mbps Intra-frame 4096x2160 / 150 Mbps Long GOP 2048x1080 / 120 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 100 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP

¹ In most cases, the frame rate is the same as in the primary clip.

Main clip: XF-AVC

Sub recording clip: XF-AVC

216

Primary clip					Sub recording clip configuration ¹
Main recording format	Main resolution		Frame rate	Bit rate	Sub recording format and resolution/bit rate
					XF-AVC YCC422 10 bit
XF-AVC YCC422 10 bit	4096x2160	Intra-frame	59.94P, 50.00P	600 Mbps, 500 Mbps	2048x1080 / 300 Mbps, 250 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP
		Long GOP		250 Mbps	2048x1080 / 50 Mbps Long GOP
		Intra-frame	29.97P, 25.00P, 24.00P, 23.98P	600 Mbps, 500 Mbps, 480 Mbps, 480 Mbps	4096x2160 / 150 Mbps Long GOP 2048x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP
		Intra-frame		450 Mbps, 375 Mbps, 360 Mbps, 360 Mbps	4096x2160 / 150 Mbps Long GOP 2048x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP
		Intra-frame		300 Mbps, 250 Mbps, 240 Mbps, 240 Mbps	4096x2160 / 150 Mbps Long GOP 2048x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP
		Long GOP		150 Mbps	2048x1080 / 50 Mbps Long GOP
	3840x2160	Intra-frame	59.94P, 50.00P	600 Mbps, 500 Mbps	1920x1080 / 300 Mbps, 250 Mbps Intra-frame 1920x1080 / 50 Mbps Long GOP The following are 59.94i / 50.00i: 1920x1080 / 150 Mbps, 125 Mbps Intra-frame 1920x1080 / 50 Mbps Long GOP 1920x1080 / 25 Mbps Long GOP
		Long GOP		250 Mbps	1920x1080 / 50 Mbps Long GOP The following are 59.94i / 50.00i: 1920x1080 / 50 Mbps Long GOP 1920x1080 / 25 Mbps Long GOP
		Intra-frame	29.97P, 25.00P, 24.00P, 23.98P	600 Mbps, 500 Mbps, 480 Mbps, 480 Mbps	3840x2160 / 150 Mbps Long GOP 1920x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 1920x1080 / 50 Mbps Long GOP
		Intra-frame		450 Mbps, 375 Mbps, 360 Mbps, 360 Mbps	3840x2160 / 150 Mbps Long GOP 1920x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 1920x1080 / 50 Mbps Long GOP
		Intra-frame		300 Mbps, 250 Mbps, 240 Mbps, 240 Mbps	3840x2160 / 150 Mbps Long GOP 1920x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 1920x1080 / 50 Mbps Long GOP
		Long GOP		150 Mbps	1920x1080 / 50 Mbps Long GOP

Primary clip					Sub recording clip configuration ¹
Main recording format	Main resolution		Frame rate	Bit rate	Sub recording format and resolution/bit rate
					XF-AVC YCC422 10 bit
XF-AVC YCC422 10 bit	2048x1080	Intra-frame	59.94P, 50.00P	300 Mbps, 250 Mbps	2048x1080 / 50 Mbps Long GOP
		Long GOP		50 Mbps	—
		Intra-frame	29.97P, 25.00P, 24.00P, 23.98P	150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps	2048x1080 / 50 Mbps Long GOP
		Long GOP		50 Mbps	—
	1920x1080	Intra-frame	59.94P, 50.00P	300 Mbps, 250 Mbps	1920x1080 / 50 Mbps Long GOP
		Long GOP		50 Mbps	—
		Intra-frame	29.97P, 25.00P, 24.00P, 23.98P	150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps	1920x1080 / 50 Mbps Long GOP
		Long GOP		50 Mbps	—
		Intra-frame	59.94i, 50.00i	150 Mbps, 125 Mbps	1920x1080 / 50 Mbps Long GOP 1920x1080 / 25 Mbps Long GOP
		Long GOP		50 Mbps	—
		Long GOP		25 Mbps	—
		Long GOP		25 Mbps	—

¹ In most cases, the frame rate is the same as in the primary clip.

Sub recording clip: XF-AVC S

Primary clip				Sub recording clip configuration ¹		
Main recording format	Main resolution		Frame rate	Bit rate	Sub recording format and resolution/bit rate	
					XF-AVC S YCC422 10 bit	XF-AVC S YCC420 8 bit
XF-AVC YCC422 10 bit	4096x2160	Intra-frame	59.94P, 50.00P	600 Mbps, 500 Mbps	2048x1080 / 300 Mbps, 250 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	2048x1080 / 35 Mbps Long GOP
		Long GOP		250 Mbps	2048x1080 / 50 Mbps Long GOP	2048x1080 / 35 Mbps Long GOP
		Intra-frame	29.97P, 25.00P, 24.00P, 23.98P	600 Mbps, 500 Mbps, 480 Mbps, 480 Mbps	4096x2160 / 600 Mbps, 500 Mbps, 480 Mbps, 480 Mbps Intra-frame 450 Mbps, 375 Mbps, 360 Mbps, 360 Mbps Intra-frame 300 Mbps, 250 Mbps, 240 Mbps, 240 Mbps Intra-frame 4096x2160 / 150 Mbps Long GOP 2048x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 100 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
		Intra-frame		450 Mbps, 375 Mbps, 360 Mbps, 360 Mbps	4096x2160 / 450 Mbps, 375 Mbps, 360 Mbps, 360 Mbps Intra-frame 300 Mbps, 250 Mbps, 240 Mbps, 240 Mbps Intra-frame 4096x2160 / 150 Mbps Long GOP 2048x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 100 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
		Intra-frame		300 Mbps, 250 Mbps, 240 Mbps, 240 Mbps	4096x2160 / 300 Mbps, 250 Mbps, 240 Mbps, 240 Mbps Intra-frame 4096x2160 / 150 Mbps Long GOP 2048x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 100 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
		Long GOP		150 Mbps	4096x2160 / 150 Mbps Long GOP 2048x1080 / 50 Mbps Long GOP	4096x2160 / 100 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
		Intra-frame		300 Mbps, 250 Mbps, 240 Mbps, 240 Mbps	4096x2160 / 300 Mbps, 250 Mbps, 240 Mbps, 240 Mbps Intra-frame 4096x2160 / 150 Mbps Long GOP 2048x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 100 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP

Primary clip				Sub recording clip configuration ¹		
Main recording format	Main resolution		Frame rate	Bit rate	Sub recording format and resolution/bit rate	
					XF-AVC S YCC422 10 bit	XF-AVC S YCC420 8 bit
XF-AVC YCC422 10 bit	3840x2160	Intra-frame	59.94P, 50.00P	600 Mbps, 500 Mbps	1920x1080 / 300 Mbps, 250 Mbps Intra-frame 1920x1080 / 50 Mbps Long GOP	1920x1080 / 35 Mbps Long GOP
		Long GOP		250 Mbps	1920x1080 / 50 Mbps Long GOP	1920x1080 / 35 Mbps Long GOP
		Intra-frame	29.97P, 25.00P, 24.00P, 23.98P	600 Mbps, 500 Mbps, 480 Mbps, 480 Mbps	3840x2160 / 600 Mbps, 500 Mbps, 480 Mbps Intra-frame 450 Mbps, 375 Mbps, 360 Mbps, 360 Mbps Intra-frame 300 Mbps, 250 Mbps, 240 Mbps, 240 Mbps Intra-frame 3840x2160 / 150 Mbps Long GOP 1920x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 1920x1080 / 50 Mbps Long GOP	3840x2160 / 100 Mbps Long GOP 1920x1080 / 35 Mbps Long GOP
		Intra-frame		450 Mbps, 375 Mbps, 360 Mbps, 360 Mbps	3840x2160 / 450 Mbps, 375 Mbps, 360 Mbps, 360 Mbps Intra-frame 300 Mbps, 250 Mbps, 240 Mbps, 240 Mbps Intra-frame 3840x2160 / 150 Mbps Long GOP 1920x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 1920x1080 / 50 Mbps Long GOP	3840x2160 / 100 Mbps Long GOP 1920x1080 / 35 Mbps Long GOP
		Intra-frame		300 Mbps, 250 Mbps, 240 Mbps, 240 Mbps	3840x2160 / 300 Mbps, 250 Mbps, 240 Mbps, 240 Mbps Intra-frame 3840x2160 / 150 Mbps Long GOP 1920x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 1920x1080 / 50 Mbps Long GOP	3840x2160 / 100 Mbps Long GOP 1920x1080 / 35 Mbps Long GOP
		Long GOP		150 Mbps	3840x2160 / 150 Mbps Long GOP 1920x1080 / 50 Mbps Long GOP	3840x2160 / 100 Mbps Long GOP 1920x1080 / 35 Mbps Long GOP
	2048x1080	Intra-frame	59.94P, 50.00P	300 Mbps, 250 Mbps	2048x1080 / 300 Mbps, 250 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	2048x1080 / 35 Mbps Long GOP
		Long GOP		50 Mbps	2048x1080 / 50 Mbps Long GOP	2048x1080 / 35 Mbps Long GOP
		Intra-frame	29.97P, 25.00P, 24.00P, 23.98P	150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps	2048x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	2048x1080 / 35 Mbps Long GOP
		Long GOP		50 Mbps	2048x1080 / 50 Mbps Long GOP	2048x1080 / 35 Mbps Long GOP

Primary clip				Sub recording clip configuration ¹		
Main recording format	Main resolution		Frame rate	Bit rate	Sub recording format and resolution/bit rate	
					XF-AVC S YCC422 10 bit	XF-AVC S YCC420 8 bit
XF-AVC YCC422 10 bit	1920x1080	Intra-frame	59.94P, 50.00P	300 Mbps, 250 Mbps	1920x1080 / 300 Mbps, 250 Mbps Intra-frame 1920x1080 / 50 Mbps Long GOP	1920x1080 / 35 Mbps Long GOP
		Long GOP		50 Mbps	1920x1080 / 50 Mbps Long GOP	1920x1080 / 35 Mbps Long GOP
		Intra-frame	29.97P, 25.00P, 24.00P, 23.98P	150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps	1920x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 1920x1080 / 50 Mbps Long GOP	1920x1080 / 35 Mbps Long GOP
		Long GOP		50 Mbps	1920x1080 / 50 Mbps Long GOP	1920x1080 / 35 Mbps Long GOP
		Intra-frame	59.94i, 50.00i	150 Mbps, 125 Mbps	—	—
		Long GOP		50 Mbps	—	—
		Long GOP		25 Mbps	—	—

¹ In most cases, the frame rate is the same as in the primary clip.

Main clip: XF-HEVC S

Primary clip					Sub recording clip configuration ¹	
Main recording format	Main resolution		Frame rate	Bit rate	Sub recording format and resolution/bit rate	
					XF-HEVC S YCC422 10 bit	XF-HEVC S YCC420 10 bit
XF-HEVC S YCC422 10 bit	4096x2160	Long GOP	59.94P, 50.00P	225 Mbps	2048x1080 / 50 Mbps Long GOP	2048x1080 / 35 Mbps Long GOP
		Long GOP	29.97P, 25.00P, 24.00P, 23.98P	135 Mbps	2048x1080 / 50 Mbps Long GOP	4096x2160 / 100 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
	3840x2160	Long GOP	59.94P, 50.00P	225 Mbps	1920x1080 / 50 Mbps Long GOP	1920x1080 / 35 Mbps Long GOP
		Long GOP	29.97P, 25.00P, 24.00P, 23.98P	135 Mbps	1920x1080 / 50 Mbps Long GOP	3840x2160 / 100 Mbps Long GOP 1920x1080 / 35 Mbps Long GOP
	2048x1080	Long GOP	59.94P, 50.00P	50 Mbps	—	2048x1080 / 35 Mbps Long GOP
		Long GOP	29.97P, 25.00P, 24.00P, 23.98P	50 Mbps	—	2048x1080 / 35 Mbps Long GOP
	1920x1080	Long GOP	59.94P, 50.00P	50 Mbps	—	1920x1080 / 35 Mbps Long GOP
		Long GOP	29.97P, 25.00P, 24.00P, 23.98P	50 Mbps	—	1920x1080 / 35 Mbps Long GOP
XF-HEVC S YCC420 10 bit	4096x2160	Long GOP	59.94P, 50.00P	150 Mbps	—	2048x1080 / 35 Mbps Long GOP
		Long GOP	29.97P, 25.00P, 24.00P, 23.98P	100 Mbps	—	2048x1080 / 35 Mbps Long GOP
	3840x2160	Long GOP	59.94P, 50.00P	150 Mbps	—	1920x1080 / 35 Mbps Long GOP
		Long GOP	29.97P, 25.00P, 24.00P, 23.98P	100 Mbps	—	1920x1080 / 35 Mbps Long GOP
	2048x1080	Long GOP	59.94P, 50.00P	35 Mbps	—	—
		Long GOP	29.97P, 25.00P, 24.00P, 23.98P	35 Mbps	—	—
	1920x1080	Long GOP	59.94P, 50.00P	35 Mbps	—	—
		Long GOP	29.97P, 25.00P, 24.00P, 23.98P	35 Mbps	—	—

¹ In most cases, the frame rate is the same as in the primary clip.

Main clip: XF-AVC S

Primary clip					Sub recording clip configuration ¹	
Main recording format	Main resolution		Frame rate	Bit rate	Sub recording format and resolution/bit rate	
					XF-AVC S YCC422 10 bit	XF-AVC S YCC420 8 bit
XF-AVC S YCC422 10 bit	4096x 2160	Intra-frame	59.94P, 50.00P	600 Mbps, 500 Mbps	2048x1080 / 300 Mbps, 250 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	2048x1080 / 35 Mbps Long GOP
		Long GOP		250 Mbps	2048x1080 / 50 Mbps Long GOP	2048x1080 / 35 Mbps Long GOP
		Intra-frame	29.97P, 25.00P, 24.00P, 23.98P	600 Mbps, 500 Mbps, 480 Mbps, 480 Mbps	4096x2160 / 150 Mbps Long GOP 2048x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 100 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
		Intra-frame		450 Mbps, 375 Mbps, 360 Mbps, 360 Mbps	4096x2160 / 150 Mbps Long GOP 2048x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 100 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
		Intra-frame		300 Mbps, 250 Mbps, 240 Mbps, 240 Mbps	4096x2160 / 150 Mbps Long GOP 2048x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 2048x1080 / 50 Mbps Long GOP	4096x2160 / 100 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
		Long GOP		150 Mbps	2048x1080 / 50 Mbps Long GOP	4096x2160 / 100 Mbps Long GOP 2048x1080 / 35 Mbps Long GOP
	3840x 2160	Intra-frame	59.94P, 50.00P	600 Mbps, 500 Mbps	1920x1080 / 300 Mbps, 250 Mbps Intra-frame 1920x1080 / 50 Mbps Long GOP	1920x1080 / 35 Mbps Long GOP
		Long GOP		250 Mbps	1920x1080 / 50 Mbps Long GOP	1920x1080 / 35 Mbps Long GOP
		Intra-frame	29.97P, 25.00P, 24.00P, 23.98P	600 Mbps, 500 Mbps, 480 Mbps, 480 Mbps	3840x2160 / 150 Mbps Long GOP 1920x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 1920x1080 / 50 Mbps Long GOP	3840x2160 / 100 Mbps Long GOP 1920x1080 / 35 Mbps Long GOP
		Intra-frame		450 Mbps, 375 Mbps, 360 Mbps, 360 Mbps	3840x2160 / 150 Mbps Long GOP 1920x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 1920x1080 / 50 Mbps Long GOP	3840x2160 / 100 Mbps Long GOP 1920x1080 / 35 Mbps Long GOP
		Intra-frame		300 Mbps, 250 Mbps, 240 Mbps, 240 Mbps	3840x2160 / 150 Mbps Long GOP 1920x1080 / 150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps Intra-frame 1920x1080 / 50 Mbps Long GOP	3840x2160 / 100 Mbps Long GOP 1920x1080 / 35 Mbps Long GOP
		Long GOP		150 Mbps	1920x1080 / 50 Mbps Long GOP	3840x2160 / 100 Mbps Long GOP 1920x1080 / 35 Mbps Long GOP

Main recording format	Primary clip				Sub recording clip configuration ¹	
	Main resolution		Frame rate	Bit rate	Sub recording format and resolution/bit rate	
					XF-AVC S YCC422 10 bit	XF-AVC S YCC420 8 bit
XF-AVC S YCC422 10 bit	2048x1080	Intra-frame	59.94P, 50.00P	300 Mbps, 250 Mbps	2048x1080 / 50 Mbps Long GOP	2048x1080 / 35 Mbps Long GOP
		Long GOP		50 Mbps	—	2048x1080 / 35 Mbps Long GOP
		Intra-frame	29.97P, 25.00P, 24.00P, 23.98P	150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps	2048x1080 / 50 Mbps Long GOP	2048x1080 / 35 Mbps Long GOP
		Long GOP		50 Mbps	—	2048x1080 / 35 Mbps Long GOP
	1920x1080	Intra-frame	59.94P, 50.00P	300 Mbps, 250 Mbps	1920x1080 / 50 Mbps Long GOP	1920x1080 / 35 Mbps Long GOP
		Long GOP		50 Mbps	—	1920x1080 / 35 Mbps Long GOP
		Intra-frame	29.97P, 25.00P, 24.00P, 23.98P	150 Mbps, 125 Mbps, 120 Mbps, 120 Mbps	1920x1080 / 50 Mbps Long GOP	1920x1080 / 35 Mbps Long GOP
		Long GOP		50 Mbps	—	1920x1080 / 35 Mbps Long GOP
XF-AVC S YCC420 8 bit	4096x2160	Long GOP	59.94P, 50.00P	150 Mbps	—	2048x1080 / 35 Mbps Long GOP
		Long GOP	29.97P, 25.00P, 24.00P, 23.98P	100 Mbps	—	2048x1080 / 35 Mbps Long GOP
	3840x2160	Long GOP	59.94P, 50.00P	150 Mbps	—	1920x1080 / 35 Mbps Long GOP
		Long GOP	29.97P, 25.00P, 24.00P, 23.98P	100 Mbps	—	1920x1080 / 35 Mbps Long GOP
	2048x1080	Long GOP	59.94P, 50.00P	35 Mbps	—	—
		Long GOP	29.97P, 25.00P, 24.00P, 23.98P	35 Mbps	—	—
	1920x1080	Long GOP	59.94P, 50.00P	35 Mbps	—	—
		Long GOP	29.97P, 25.00P, 24.00P, 23.98P	35 Mbps	—	—

¹ In most cases, the frame rate is the same as in the primary clip.

Troubleshooting

If you have a problem with your camera, refer to this section. Consult your dealer or a Canon Service Center if the problem persists.

Power source

The camera will not turn on or it turns off by itself.

- The battery pack is depleted. Replace or charge the battery pack.
- Remove the battery pack and reattach it correctly.

Shortly after turning it on, the camera turns off on its own.

- You are using a battery pack that is not compatible for use with this camera. Use a recommended battery pack (□ 241).

Cannot charge the battery pack.

- The temperature of the battery pack is outside the charging range. If the battery pack's temperature is below 0 °C (32 °F), warm it before charging it; if it is above 40 °C (104 °F), let the battery pack cool down before charging it.
- Charge the battery pack in temperatures between 0 °C and 40 °C (32 °F and 104 °F).
- The battery pack is faulty. Replace the battery pack.

The battery pack is depleted extremely quickly even at normal temperatures.

- Check the [☞ System Setup] status screen (□ 213) to check if the battery pack has reached the end of its battery life. If so, buy a new battery pack.

Recording

The camera's controls are not responsive/disabled.

- When the **POWER** switch is set to **⏻**, all buttons (or all buttons with the exception of some REC buttons) are locked and cannot be operated. Set the **POWER** switch to CAMERA. You can change which controls are locked with the **MENU** > [☞ System Setup] > [Key Lock] setting.

Performing a recording operation (pressing a button/touching the onscreen button) will not start recording.

- The card is full or it already contains the maximum number of clips (999 clips). Delete some clips (□ 150) or save your recordings and initialize the card (□ 37) to free some space. Alternatively, replace the card.
- The REC button was pressed while all the camera's controls were locked (key lock, □ 15). Unlock the controls or set **MENU** > [☞ System Setup] > [Key Lock] to [All Except REC Button].
- The REC button that was used may be disabled. Change the **MENU** > [☞ System Setup] > [REC Button], [Assign. Button 4 as REC], [Assign. Button 11 as REC] and [Onscreen REC/STBY Button] settings to enable the use of the desired button or onscreen button.
- Power supply to the camera has reached the level set for the power level warning (□ 211). Check the power source.
- The camera cannot record while the [Color Correction] settings in the custom picture file (□ 137) are being adjusted (except for the [Revision Level]/[Revision Phase] settings).

The point when the recording operation was performed does not match the beginning/end of the recording.

- There may be a slight interval between pressing the REC button (or touching the onscreen button) and the actual start/end of recording. This is not a malfunction.

The camera will not focus.

- The camera may not be able to focus on certain subjects using autofocus. Focus manually (□ 80).
- When [Continuous AF] is enabled and [Lens action if cannot AF] is set to [Stop], start focusing manually until the AF frame changes from yellow to white.
- The lens is dirty. Clean the lens with a soft lens-cleaning cloth.

When a subject flits across in front of the lens, the image appears slightly bent.

- This is a phenomenon typical of CMOS image sensors. When a subject crosses very quickly in front of the camera, the image may seem slightly warped. This is not a malfunction.

Bright red, green or blue dots appear on the screen.

- Try adjusting the black balance (□ 45). The camera's CMOS sensor is a delicate piece of precision engineering. Direct exposure of the sensor to ion rays or other types of cosmic radiation may affect it and this may rarely appear as bright colored dots on the screen. This is the nature of CMOS image sensors and does not represent a malfunction.
- The effects of the damage may be more noticeable when the camera is used in places subject to high temperatures, when a high ISO speed or gain level is used and when slow shutter speeds are used.

Abnormal images appear on the screen and the camera cannot record properly.

- While recording using an almost empty battery pack together with an AC adapter, the AC adapter was inadvertently disconnected or the power supply was suddenly interrupted. Reconnect the AC adapter and turn the camera off and then on again or replace the battery pack with a fully charged one.

Changing between recording (●REC) and record standby (STBY) takes longer than usual.

- When the card contains a large number of clips, some operations may take longer than usual. Save your recordings and initialize the card (□ 37). Alternatively, replace the card.

Clips or photos cannot be recorded properly.

- This may occur as clips and photos are recorded/deleted over time. Save your recordings and initialize the card (□ 37).

After using the camera for a long time, it becomes hot.

- The camera may become hot after using it continuously for long periods of time; this is not a malfunction. If the camera becomes unusually hot or it becomes hot after using it only for a short while, it may indicate a problem with the camera. Consult a Canon Service Center.

Playback

Cannot delete clips/photos

- XF-AVC clips with an **OK** mark cannot be deleted with the camera. Remove the **OK** mark (□ 149).
- The LOCK switch on the SD card is set to prevent accidental erasure. Change the position of the LOCK switch.
- Photos that were protected using other devices cannot be deleted with this camera.

Deleting clips takes longer than usual.

- When the card contains a large number of clips, some operations may take longer than usual. Save your recordings and initialize the card (□ 37).

Indicators and Onscreen Displays

appears in red on the screen.

- Battery pack is depleted. Replace or charge the battery pack.

appears on the screen.

- The camera cannot communicate with the battery pack attached so the remaining battery time cannot be displayed.

The power indicator/tally lamp does not illuminate.

- Set **MENU** > [ System Setup] > [Tally Lamp] to [On].

The power indicator/tally lamp flashes quickly. (4 flashes per second)

- The battery pack is depleted. Replace or charge the battery pack.
- There is not enough available space on the cards. Delete recordings (□ 150) to free some space or replace the card.
- A system error has occurred. Turn the camera off and then on again. If this does not solve the problem, consult a Canon Service Center.

The power indicator/tally lamp flashes slowly. (1 flash per second)

- The combined available space on the cards is low. Delete recordings (□ 150) to free some space or replace the card.

appears in red on the screen.

- An SD card error occurred. Remove and reinsert the SD card. If the display does not change back to normal, save your recordings and initialize the SD card (□ 37).

A / **B** appears in red on the screen followed by [END].

- The indicated card is full. Delete recordings (□ 150) to free some space or replace the card.

Even after stopping recording, the access indicator stays illuminated in red.

- The clip is being recorded on the card. This is not a malfunction.

TEMP appears in yellow on the screen.

- The camera's internal temperature has reached a predetermined level. You can continue using the camera.

TEMP appears in red on the screen.

- The camera's internal temperature has risen further while **TEMP** appeared in yellow on the screen. Turn off the camera and wait until the temperature has decreased.

FAN appears in red on the screen.

- The cooling fan may not be working properly. The camera will automatically turn off after a few minutes. Consult a Canon Service Center.

LENS appears on the screen.

- The camera and lens cannot communicate normally. Clean the lens's contacts and reattach the lens.

The aperture value (T or F value) appears in gray on the screen.

- When using a compatible EF Cinema lens (□ 249), the aperture value will appear in gray when the camera detects that the aperture may be close to fully closed. As you continue to close down the aperture further, the display will change to [closed].

The ND filter indicator appears in red or as [- -] on the screen, and the ND filter indicators on the RC-V100 Remote Controller are flashing.

- The ND filter mechanism may not be working properly. Consult a Canon Service Center.

Picture and Sound

There is no picture from an external monitor.

- Make sure the cable connecting the camera to the monitor is correctly connected on both sides.
- Check that the correct video input is selected on the external monitor.

There is no picture or sound from an external monitor/recorder connected to the HDMI OUT terminal

- Disconnect the HDMI cable and then restore the connection or turn the camera off and then on again.
- Check that the settings of the external monitor/recorder match the configuration of the output signal selected on the camera (□ 151).
- Replace the HDMI cable.

An assistance display (peaking/zebra pattern/video scope/onscreen markers/false color/magnification/B&W image/tally OSD/anamorphic desqueeze/view assistance) does not appear or is not applied on the screen.

- These assistance displays have separate settings that allow you to turn the display on/off on individual monitoring devices/video outputs. Check the settings to see that the desired function is enabled on the desired monitor/video output.
- Onscreen displays output has not been enabled. Activate the output of the camera's onscreen displays (□ 157).

Screen displays turn on and off repeatedly.

- The battery pack is depleted. Replace or charge the battery pack.
- Remove the battery pack and reattach it correctly.

Abnormal characters appear on the screen and the camera does not operate properly.

- Remove all the cards and disconnect the power source. After a moment, reconnect the power and reinsert the cards. If the problem still persists, use the **MENU** > [🔧 System Setup] > [Reset] > [All Settings] function. This resets all the camera's settings to default values, except for the hour meter.

Video noise appears on screen.

- Keep a distance between the camera and devices that emit strong electromagnetic fields such as near powerful magnets and motors, MRI machines or high-voltage power lines.

Horizontal bands appear on the screen.

- This is a phenomenon typical of CMOS image sensors when recording under some types of lighting. This is not a malfunction. You may be able to reduce the symptoms by setting the shutter speed mode to [Speed] and the shutter speed to a value matching the frequency of the local electrical system: 1/50* or 1/100 for 50 Hz systems, 1/60 or 1/120 for 60 Hz systems.

*May not be available depending on the frame rate.

Audio is not recorded.

- The audio input source is not correctly selected (☞ 102) or a microphone is not connected to the selected terminal.
- When using the INPUT 1/INPUT 2 terminals, make sure you are using a mini XLR connector. When using the MIC terminal, make sure you are using a condenser microphone with a Ø 3.5 mm stereo mini plug.
- The external microphone is not turned on or its battery is depleted.
- The external microphone connected to the INPUT 1/INPUT 2 terminal requires phantom power. Set the corresponding INPUT 1/INPUT 2 audio source selection switch to MIC+48V (☞ 102).
- The external microphone connected to the MIC terminal requires plug-in power but **MENU** > [🎵] Audio Setup] > [MIC Input] is set to an option other than [MIC (with Power Supply)].
- To record audio for slow & fast motion clips, set the recording mode to [S&F Clip / Audio (WAV)] (☞ 39).

Sound is distorted or is recorded at lower levels.

- This may happen when the appropriate audio level is not set correctly. Adjust the audio recording level manually (☞ 104). You can also activate the microphone attenuator (☞ 105) to reduce the audio level.
- The audio source selected for the INPUT terminal or MIC terminal is incorrect. When using an external microphone, set the INPUT switch to MIC or set **MENU** > [🎵] Audio Setup] > [MIC Input] to [MIC (with Power Supply)]. When using an analog audio device set the INPUT switch or the [MIC Input] setting to [LINE].
- The audio level is adjusted manually and the recording level is set too low. Check the audio level meter on the screen and adjust the audio level correctly (☞ 103).

Cards and Accessories

Cannot insert the card.

- The card you are trying to insert is not facing the correct direction. Turn it over and insert it.

Cannot record on the SD card.

- A compatible card must be used (☞ 35).
- Initialize the card (☞ 37) when you use it with the camera for the first time.
- The card is full or it already contains the maximum number of clips (999 clips). Delete recordings (☞ 150) to free some space or replace the card.
- The clip number has reached its maximum value. Save your recordings and initialize the card (☞ 37) or delete all the clips (☞ 150).
- The LOCK switch on the SD card is set to prevent accidental erasure. Change the position of the LOCK switch.
- The folder and file numbers for photos have reached their maximum value. Set **MENU** > [📷 Recording/Media Setup] > [Photo Numbering] to [Reset] and insert a new card.

Recording to and playing back from a card is slow.

- This may occur as recordings are made and deleted repeatedly over time. Save your recordings and initialize the card (☞ 37).

The RC-V100 Remote Controller or commercially available remote control does not work.

- Make sure that **MENU** > [🔧 System Setup] > [REMOTE Term.] is set to [RC-V100 (REMOTE A)] when using the RC-V100 Remote Controller or to [Standard] when using a commercially available remote control (☞ 123).
- Turn off the camera, reconnect the remote controller and then turn the camera back on again.
- When the currently selected custom picture file is protected, detailed custom picture settings cannot be adjusted using the RC-V100. Unprotect the file (☞ 131).

Connections with External Devices

Video noise appears on a nearby TV screen.

- When using the camera in a room where a TV is located, keep a distance between the AC adapter and the power or antenna cables of the TV.

Network Functions

Check This First

- Are the camera, computer or other network devices all turned on?
- Is the camera properly powered on and ready for use? Is the PIN code correctly configured and entered if required?
- Is the network working and correctly configured?
- Are all network devices correctly connected to the same network as the camera?
- When using a Wi-Fi network, are there any obstructions between the camera and the access point or between the network device used and the access point?

Cannot connect with an access point.

- Check that the settings on the network device the camera is trying to connect with are correct.
- The wireless signal is not strong enough or there are other devices in the vicinity interfering with the wireless signal. Refer to *Precautions Regarding Wi-Fi Networks* (□ 229).

Cannot establish a Camera Access Point connection with a network device.

- When you reset all the camera settings, all network settings are lost as well. Configure the network settings again (□ 174).
- The wireless signal is not strong enough or there are other devices in the vicinity interfering with the wireless signal. Refer to *Precautions Regarding Wi-Fi Networks* (□ 229).
- If you cannot connect to the camera from a mobile device, change the [Network] setting to [Disable] and then change it back to [Enable].

Cannot transfer clips

- Canceling data transfer or opening the card compartment cover may cause an unexpected error due to inconsistency with the connection destination. Reconnect the AC adapter or reattach the battery and turn the camera off and then back on.
- Clips that have not been recovered cannot be transferred. Recover clips in advance (□ 38).

Cannot connect with a wired (Ethernet) network.

- Use a category 5e or better shielded twisted pair (STP) Ethernet cable.
- Try replacing the Ethernet cable.
- When you reset all the camera settings, all network settings are lost as well.
- Check that the network device to which the camera is connected is on and functioning properly. To use 1000BASE-T connection speeds, make sure to use network devices compatible with Gigabit Ethernet (1000BASE-T).

The (Ethernet) indicator is illuminated or flashing in red or is turned off.

- The Ethernet cable was disconnected or the camera cannot connect to the network device. Check the cable connection and the network device.

The Browser Remote application will not start on the Web browser.

- Make sure to use a connection setting with the [Browser Remote] function setting.
- The URL entered into the Web browser's address bar is incorrect. Select **MENU** > [ Network Settings] > [Connection Setting] > Connection setting in use > [Check Settings] and check the camera's IP address. Use this IP address as the URL (□ 187).

The Browser Remote screen is not displayed correctly on the Web browser.

- The device, operating system or Web browser used may not be supported. For the latest information about supported systems, visit your local Canon website.
- Enable JavaScript and cookies in your Web browser's settings. For details, refer to the help modules or online documentation of the Web browser used.

Cannot start IP streaming.

- Make sure IP streaming was activated on the camera (□ 185).
- If the IP streaming protocol is set to an option other than [RTSP+RTP], make sure the [Destination Server] is set correctly (□ 170).
- IP streaming cannot be used in the following cases. Check the settings.
 - When the main recording format is set to [RAW].
 - When the system frequency is set to 24.00 Hz.
 - When the recording mode is set to an option other than normal recording.
 - When [2nd Card Rec Functions] is set to an option other than [Off].

Cannot connect the optional XC Protocol compatible RC-IP100/RC-IP1000 Remote Camera Controller, Remote Camera Control Application or Multi-Camera Control.

- Make sure to use a connection setting with the [XC Protocol] function setting.
- Check that the settings on the optional RC-IP100/RC-IP1000, Remote Camera Control Application or Multi-Camera Control that the camera is trying to connect with are correct.

Precautions Regarding Wi-Fi Networks

When using a Wi-Fi network, try the following corrective actions if the transmission rate drops, the connection is lost, or other problems occur.

Positioning a network device (access point, mobile device, etc.)

- When using a Wi-Fi network indoors, place the network device in the same room as the camera.
- Place the network device in an open, unobstructed location, where people or objects do not come between it and the camera.
- Place the network device as close as possible to the camera. Change the position, height or facing of the network device, as necessary.

About camera installation and setup when using the 2.4 GHz band.

The following operations may improve the communication status.

- Do not install the handle unit so as not to block the signal.
- When using Browser Remote, set the Browser Remote [Live view resolution] to [Small] (□ 192).

Nearby electronic devices

- If the transmission rate over a Wi-Fi network drops because of interference from the following electronic devices, switching to the 5 GHz band or to a different channel may solve the problem.
- Wi-Fi networks using the IEEE 802.11b/g/n protocol operate in the 2.4 GHz band. For this reason, the transmission rate may drop if there are nearby microwave ovens, cordless telephones, wireless microphones and Bluetooth or similar devices operating on the same frequency band.

Using multiple cameras/Wi-Fi adapters/access points

- Check that there are no IP address conflicts among the devices connected to the same network.
- If multiple cameras are connected to a single access point, connection speeds may be reduced.
- To reduce radio wave interference when there are multiple access points using IEEE 802.11b/g or IEEE 802.11n (in the 2.4 GHz band), leave a gap of four channels between each wireless access point. For example, use channels 1, 6, and 11, channels 2, 7, and 12, or channels 3, 8, and 13.

If you can use IEEE 802.11a/n/ac (in the 5 GHz band), switch to IEEE 802.11a/n/ac and specify a different channel, leaving an appropriate gap between channels according to the wireless standard and frequency band used. For example, when using IEEE 802.11ac (VHT80), leave a gap of 8 channels between access points.

List of Messages

Refer to this section if a message appears on the screen. The messages in this section appear in alphabetical order. Note that for some messages, an indication of the card involved ([SD Card A], [SD Card B] or [SD Card]) may appear above the message itself.

Media full

- The card is full. Replace the card or delete recordings (□ 150) to free some space on the card.
- Recording will not start because the card is full. Switch to the card in the other card slot to record.

Media is almost full

- Available space on one or both cards is insufficient as described below. Replace the relevant card(s) or delete recordings (□ 150) to free some space on the card.
 - During normal recording, the space available on the card being used for recording is low.
 - During relay recording, the combined space available on cards A and B is low.
 - During sub recording or double slot recording, the space available on card A or B (the fullest one) is low.
 - During proxy recording, the space available on card A (primary clips) is low. Otherwise, when recording only on card B (proxy clips), the space available on card B is low.
 - During continuous recording, the space available on card B (continuous) is low.

Accessing <...> Do not remove

- You opened the card compartment cover while the camera was recording on the card. Be sure to stop the recording before removing the card.

Currently, the accessory cannot be used

- A communication error occurred between the camera and an accessory attached to the multi-function shoe. Turn the camera off and then back on again.

Currently, the accessory cannot be used

Please check the accessory power status

- Battery level is low on the accessory attached to the multi-function shoe. Replace the battery.

The following settings were changed.

- The settings displayed on the screen were changed automatically due to a change in one of the [⚙️ Recording/Media Setup] settings. Check the settings before you continue recording.

Memory card is write-protected

- The LOCK switch on the SD card is set to prevent accidental erasure. Change the position of the LOCK switch.

Check the memory card

- Cannot access the card. If the card is correctly inserted, remove it. Check it has no defects or other problems and then reinsert it.
- A card error occurred and recording/playback is not possible. Try removing and reinserting the card or replace it.
- You inserted a MultiMedia Card (MMC) into the camera. Use a recommended SD card (□ 35).
- If after the message disappears, **A** or **B** appears in red, perform the following: Turn off the camera and remove and reinsert the card. If **A** or **B** turns back to green you can resume recording/playback. If the problem persists, save your recordings and initialize the card (□ 37).

A (**B**) The management file's version is different.

Recommend full backup and initializing.

- Cannot record/playback because the management file's version is different. Back up the content in the card, then initialize the card (□ 37).

No photos

- There are no photos on the SD card.

Cover is open

- The card compartment cover is open. Insert a card and close the card compartment cover.

Camera ↔ Lens communication error. Clean the lens's contacts and reattach the lens.

- The camera cannot correctly communicate with the lens due to dirty lens contacts. After the message disappears, the **LENS** icon appears on the screen. Clean the lens contacts with a soft cloth and reattach the lens.

Management file error

- Cannot record because the camera cannot write to the file control information. This may occur if the files on the card were accessed using another device. Save your recordings and initialize the card (□ 37).

Recording was stopped.

- The file control information is corrupted or there was an encoder error. Turn the camera off and then on again. Then, remove the card being used and reinsert it. Alternatively, replace the card. If this does not solve the problem, consult a Canon Service Center.
- * Corrupted file control information cannot be recovered. Cards or XF-AVC clips with corrupted file control information cannot be read by the software (Canon XF Utility or plugins for NLE applications).

No clips

- There are no clips of the selected video format on the selected card.

Number of clips already at maximum

- The card selected for recording already contains the maximum number of clips (999 clips). Replace the card or use the card in the other card slot.
- Because both cards reached the maximum number of clips, double slot recording is not available.

The memory card is not compatible with the current recording settings.

- One of the following recording settings was used with a card with a video speed class lower than V90. Change to a V90 card.
 - Slow & fast motion recording mode is activated and the frame rate selected is for slow recording.
 - The recording format was set to [XF-AVC YCC422 10 bit] / [XF-AVC S YCC422 10 bit] and the resolution to [4096x2160 Intra-frame] / [3840x2160 Intra-frame].
- One of the following recording settings was used with a card with a video speed class lower than V60. Change to a V60 or V90 card.
 - The recording format was set to [XF-AVC YCC422 10 bit] / [XF-AVC S YCC422 10 bit] with an [Intra-frame] resolution.
 - The recording format was set to [XF-AVC YCC422 10 bit] / [XF-AVC S YCC422 10 bit] with a resolution of [4096x2160 Long GOP] / [3840x2160 Long GOP].
 - The recording format was set to [XF-HEVC S YCC422 10 bit] with a resolution of [4096x2160] / [3840x2160].
- The recording format was changed to RAW when an SD/SDHC memory card was inserted. Insert an SDXC memory card instead.

With the current [Gamma/Color Space] settings, setting the main recording format to one of the 10 bit options is recommended.

- The main recording format is set to one of the options using 8 bit depth but the color space component of the [Gamma/Color Space] setting in the custom picture file is set to [C.Gamut] or [BT.2020]. Using a 10 bit depth is recommended to fully realize the characteristics of the selected color space.

May not be possible to record clips on this media

- The card used does not meet the camera's requirements. Use a recommended card (35).

If you change this setting, you will not be able to use the current Look File.

- The Look File's adjustments to the image quality cannot be applied because the [Gamma/Color Space], [HLG Color], [White Level 100%], [Over 100%] settings in the custom picture file are different from those registered with the Look File. Change these settings or register a different Look File.

This photo cannot be displayed

- You may not be able to display photos taken with other devices or image files created or edited on a computer.

Cannot play back

- The XF-AVC clip's file control information is corrupted or there was a decoder error. Turn the camera off and then on again. If this does not solve the problem, consult a Canon Service Center.
- * Corrupted file control information cannot be recovered. Cards or XF-AVC clips with corrupted file control information cannot be read by the software (Canon XF Utility or plugins for NLE applications).
- Playback was stopped because the card's read speed was too slow. Use a recommended card for recording/playback (35).

Some clips require data recovery

- The power may have been suddenly turned off or the card may have been removed while the camera was recording. As a result, one or more clips contain corrupted data. You can try to recover the clips (38).

Some audio files require data recovery.

- The power may have been suddenly turned off or the card may have been removed while the camera was recording. As a result, one or more audio files contain corrupted data. You can try to recover the files (38).

False color cannot be used when [Slow & Fast Frame Rate] exceeds 60 and [SDI Output Signal] is 3840x2160 or higher.

- False color cannot be used. Check the settings.

Peaking and zebra cannot be used at the same time when [Slow & Fast Frame Rate] exceeds 60 and [SDI Output Signal] is 3840x2160 or higher.

- Peaking and zebra cannot be used at the same time. Check the settings.

Invalid operation

- The following are not valid operations and cannot be performed.
 - In MEDIA mode, during playback, trying to add a shot mark to a frame that has one already.
 - Trying to add an  mark and a  mark to the same clip.
 - Pressing the REC button when no cards are inserted in the camera.

Recommended settings for attached lens:

Sensor Mode: Full Frame

Digital IS: Off

Main Resolution: 3840x2160 or higher

- Adjust the menu settings as indicated in the message.

Attached lens accessory not supported by the camera. It may not work properly.

- The attached lens accessory is not supported. Some functions may not work correctly.

Attached lens's firmware must be updated for the lens to work properly with this camera.

- For details about available firmware updates for the lens used, visit your local Canon website.

With the current combination of lens and mount adapter, some functions' performance may not be precise. Visit your local Canon web site for details.

- With the current combination of lens and mount adapter used, the focal length and aperture value displayed by the camera may not be accurate and should be considered only as a reference. Additionally, some functions may not work as precisely.

Attached lens not supported by the camera. It may not work properly.

- The attached lens is not supported. Some functions may not work correctly.

Recommend checking the data and initializing

- The card cannot be used for any of the following reasons. Save your recordings and initialize the card ( 37).
 - A problem has occurred with the card.
 - The camera cannot read the data on the card.
 - The card was initialized using a computer.
 - The card is partitioned.

Unable to recover data

- Could not recover the selected recording (clip or audio file). Back up your recordings and delete the recordings that could not be recovered ( 150).
- The camera may not be able to recover files when there is not enough space on the card. Delete recordings ( 150) to free some space.

Low Power Warning Check the power supply.

- The input power supplied to the camera (DC IN terminal) has reached the level set for the power level warning ( 211). Check the power source.
- The message appears every time you press the REC button when the power supply is too low (as described above).

Battery communication error. Does this battery display the Canon logo?

- You attached a battery pack that is not recommended by Canon for use with this camera.
- If you are using a battery pack recommended by Canon for use with this camera, there may be a problem with the battery pack or camera. Consult a Canon Service Center.

Battery internal temperature is rising. Power supply from the battery may stop. Do not disconnect the AC adapter.

- Power supply from the battery may stop automatically if the internal temperature rises. Do not unplug the AC adapter

Buffer overflow. Recording was stopped.

- Recording was stopped because the card's write speed was too slow. Use a recommended card ( 35).
- Save your recordings and initialize the card ( 37).

Power Zoom Adapter Temperature too high. Cannot perform task.

- The power zoom adapter cannot be operated because its temperature is too high. Stop using the power zoom adapter and let it cool down before using it again.

Power Zoom Adapter Check the power supply.

- The power zoom adapter's remaining battery charge is low. Replace the power zoom adapter's batteries.

File name error

- Clip/photo numbers have reached their maximum value. Save your recordings and initialize the card ([37]) or delete all the recordings ([150]).

Fan error

- The cooling fan may not be working properly. The camera will turn off automatically after a few minutes. Consult a Canon Service Center.

Lens error Turn the camera off, then on again.

- There was a communication error between the camera and the lens. Turn the camera off and then on again.

Set the lens to the shooting position.

- The collapsible lens attached to the camera is not set to the shooting position (with the barrel extended and locked). Set the lens to the shooting position.

Set with switch on lens side

- If you select **MENU** > [Camera Setup] > [Focus Mode], attach a lens with a focus mode switch to switch AF/MF.
- If you select **MENU** > [Camera Setup] > [Lens Optical IS], attach a lens with an optical IS on/off switch to switch it.

Recorded at 24.00 Hz/50.00 Hz/59.94 Hz Recommend checking the data and initializing

- The card contains clips that were recorded using a system frequency different from the one currently used by the camera. To record on this card, save your recordings and initialize the card with the camera ([37]). To play back the XF-AVC clips recorded on the card, change the camera's system frequency ([61]) to match the recordings on the card.

60 minutes have elapsed. Audio (WAV) recording will stop.

- Recording of the audio file will stop after 60 minutes but video recording will continue unaffected.

Lens firmware update Firmware update failed. Try updating again.

- The lens's firmware could not be correctly updated. Try updating the firmware again.

Mount Adapter firmware update Firmware update failed. Try updating again.

- The mount adapter's firmware could not be correctly updated. Try updating the firmware again.

Power zoom adapter firmware update Firmware update failed. Try updating again.

- The power zoom adapter's firmware could not be correctly updated. Try updating the firmware again.

[Gamma/Color Space] ([HLG Color], [Over 100%] or [White Level 100%])

Look File not available because these settings are different from those registered with the Look File.

- A Look File is disabled if the [Gamma/Color Space], [HLG Color], [Over 100%] or [White Level 100%] settings are changed after registering it. Restore the setting or register the Look file again.

The number of ND filters used has changed. Check the focus.

- When using ND filter settings in the extended range (from 8 to 10 stops when [ND Display Units] is set to [Stop]), the number of ND filters used changes and this may result in a shift in focus. Check the focus before resuming shooting.

Noise levels will rise on the image of the sub recording and on video outputs not in RAW.

- The main recording format is set to RAW and the gamma curve component of the [Gamma/Color Space] setting in the custom picture file is set to an option other than [Canon Log 2]/[Canon Log 3]. Under such conditions, there may be more noise on the recorded proxy clips (SD card) and on video output from the various terminals.

SD Card A→SD Card B / SD Card B→SD Card A Switched

- This message appears when you use the SLOT SELECT button to switch the card slot in use or recording continued from one card to the other.

SD Card A→SD Card B / SD Card B→SD Card A Will switch in a moment

- The card is almost full so recording will continue on the other card in approximately 1 minute.

Cannot switch SD card slots

- The SLOT SELECT button was pressed while the camera is recording. Wait until recording is finished to change the selected card slot.

Number of Shot Marks at maximum

- The shot mark could not be added because the clip already contains 100 shot marks.

When [Slow & Fast Frame Rate] is set higher than 60 (fps), the Magnification function cannot be used.

- You attempted to use the magnification function with slow & fast motion recording activated with a shooting frame rate higher than 60. Change the sensor mode or set a shooting frame rate of 60 or lower.

Network Functions

Along with this list, refer also to the instruction manuals of the access point or other external devices you are using.

No response from access point.

- Check that the access point is working properly.
- Refer to *Precautions Regarding Wi-Fi Networks* (□ 229) and check if there are applicable steps you can take.

Unable to connect to access point.

- The camera's encryption method is different from that of the access point. Change the settings on the camera to match the access point.

Unable to connect to access point. Retry from the beginning.

- To configure a new network connection using the WPS function (push button method), refer to the access point's instruction manual and check how to activate the WPS function on the wireless router.

No Wi-Fi network found with the selected SSID.

- Check the access point's SSID (network name) and make sure the same name is used in the camera's settings.
- Check that the access point is working properly and try again.

Error code returned from the FTP server for the data session.

- The FTP server terminated the connection. Restart the FTP server.
- Change the file access permission settings on the FTP server to allow reading, writing and accessing logs.
- Allow access permissions to the selected destination folder on the FTP server.
- Check that the FTP server is turned on and working properly.
- Check that there is enough available space on the storage device (hard disk drive, etc.)

Security of server connection cannot be verified. To always trust this server and connect, set [Trust Destination Server] to [Enable].

- Check that the necessary certificate is correctly configured.
- To trust and use this server even without the proper certificate, set [Trust Destination Server] to [Enable].

Another device with the same IP address already connected to the network.

- Another device on the same network has the same IP address as the camera. Change the IP address of the conflicting device or the camera.
- When using a network with a DHCP server, if the camera's IP address assignment is set to [Manual Setting], change it to [Automatic Setting] (□ 176).

Multiple access points detected. Unable to connect. Retry from the beginning.

- Other Wi-Fi devices are using the WPS function (push button method) to connect. Try the operation again or use other methods to configure the network (□ 174).

Another device has set the same IP address.

- Another device on the same network has the same IP address as the camera. Change the IP address of the conflicting device or the camera.

A streaming error occurred.

- CV protocol data could not be sent to the receiver. Check the receiver's [Destination Server] and [Dest. Port No.] settings on the camera.

Firmware download failed.

File is write-protected.

- A file with the same name on the SD card is write-protected. Delete the corresponding file.

Invalid root certificate.

- The root certificate has expired. Load a root certificate from **MENU** > [ Network Settings] > [Frame.io] > [Root Certificate] > [Read Root Certificate].

A user with the same login name is already accessing the camera.

- This message appears on the screen of the connected device. Another device connected to the network is already operating the camera. To use this device, first end the connection on the device accessing the camera.

No address assigned by the DHCP server.

- The camera is set to automatic IP address assignment. If the selected network does not use a DHCP server, change the camera's IP address assignment to [Manual Setting] and configure the IP address (📖 176).
- Check the DNS server.
 - Check that the DHCP server is turned on and working properly.
 - Make sure the DHCP server has enough IP addresses to assign.
- Check the network.
 - Check if a router with an active gateway function is not being used on the network you are trying to connect to.
 - Set the correct gateway address on the camera and on all the devices connected to the same network.
 - Contact the network's administrator and obtain the correct gateway address. Enter the same address in the camera's network settings.

No response from DNS server.

- The camera is set to automatic IP address assignment. If the selected network does not use a DNS server, change the camera's DNS address to [Disable] and configure the IP address (📖 176).
- Enter the same IP address of the DNS server used in the camera's network settings.
- Check the DNS server.
 - Check that the DNS server is turned on and working properly.
 - On the DNS server, set the correct IP address and the name corresponding to the same address.
- Check the network.
 - Check if a router with an active gateway function is not being used on the network you are trying to connect to.
 - Contact the network's administrator and obtain the correct gateway address. Enter the same address in the camera's network settings.
 - Set the correct gateway address on the camera and on all the devices connected to the same network.

Pairing with Frame.io is disabled. Re-pair.

- The pairing has expired or was canceled from the menu settings. Select **MENU** > [🔌 Network Settings] > [Frame.io] > [Pair] to re-pair.

Communication with Frame.io failed.

- Check if there are any issues with the network connection or Frame.io.

File access error occurred during Frame.io upload.

- Check the SD card:
 - The memory card cover may be open.
 - A compatible card must be used (📖 35).
 - Initialize the card (📖 37) when you use it with the camera for the first time.
 - The LOCK switch on the SD card is set to prevent accidental erasure. Change the position of the LOCK switch.
 - The card is full. Replace the card or delete recordings (📖 150) to free some space on the card.

Connection refused by FTP server.

- The FTP server is set to allow connections only with specific IP addresses. Check the camera's IP address (📖 178), and add it to the FTP server's permission list settings.

Unable to disconnect from FTP server. Error code returned.

- The camera could not disconnect from the FTP server for an unknown reason. Turn the camera and FTP server off and then on again.

File transfer completion was not confirmed by FTP server.

- The camera did not receive a transfer completion notification from the FTP server for an unknown reason. Turn the camera and FTP server off and then on again and try the file transfer again.

Unable to connect to FTP server.

- Enter the correct address for the FTP server in the camera's network settings.
- The authentication method is set to [Open System] but the encryption key is incorrect. Check uppercase/lowercase letters and other characters and make sure to enter the correct encryption key.
- The default port number is 21 (or 22 for SFTP transfers). Check the FTP server's port number and enter the same port number in the camera's network settings.
- Check that the server name of the selected FTP server is correctly configured on the DNS server and that the same name is used also in the camera's network settings.
- Check the FTP server.
 - Check that the FTP server is turned on and working properly.
 - Check that the correct IP address assigned to the FTP server is the same as the FTP server's IP address in the camera's network settings.
 - Access to the FTP server may be protected by a firewall due to security software or broadband routers. Change the firewall's settings to allow connection to the FTP server.
 - You may be able to access the FTP server by setting the camera's passive mode to [Enable] (📖 169).
 - Contact the network's administrator and obtain the correct IP address and port number for the FTP server. Enter the same information in the camera's network settings.
- Check the network.
 - Check if a router with an active gateway function is not being used on the network you are trying to connect to.
 - Contact the network's administrator and obtain the correct gateway address. Enter the same address in the camera's network settings.
 - Set the correct gateway address on the camera and on all the devices connected to the same network.

Unable to connect to FTP server. Error code returned.

- The maximum number allowed of connections to the FTP server was reached. Reduce the number of network devices connected to the FTP server or increase the number of connections allowed.

Unable to log in to FTP server. Error code returned.

- Check the FTP server's [User Name] and [Password] in the camera's network settings.
- Change the file access permission settings on the FTP server to allow reading, writing and accessing logs.
- Change the destination folder so the path includes only ASCII characters.

Wi-Fi error. Incorrect encryption method.

- Make sure the camera and access point are using the same authentication/encryption method.

Wi-Fi connection lost.

- The camera could not connect to the access point or network device.
- The wireless signal may be affected by nearby cordless telephones, microwave ovens, refrigerators or other devices. Operate the camera in a place more distant from such interference.

Wi-Fi authentication unsuccessful

- The camera's authentication mode and/or encryption key are different from those of the access point. Change the settings on the camera to match the access point.

Incorrect Wi-Fi password.

- Set the correct encryption key on the camera and the access point.

Access Log

When security-related settings are changed or when device authentication/user authentication fails consecutively, the information is saved as an access log in the camera. From a security perspective, it is recommended to regularly check the access logs. (📖 212)

Access Log List

Access Log	Description
Change PIN code	The PIN code was changed.
Update PIN code request setting	The PIN code request setting was enabled/disabled.
Update Browser Remote settings	The browser remote user name/password was changed, or HTTP/HTTPS were switched.
Update Function settings	The RTSP user name/password was changed.
Update XC Protocol settings	The XC Protocol authentication method/port number/user name/password was changed, or HTTP/HTTPS were switched.
Update Communication settings	The Camera Access Point password or Wi-Fi connection parameters were changed.
Update Connection settings	The network connection settings (SET) were changed.
Update FTP root certificate	The root certificate for FTP transfer was changed or deleted.
Update 802.1X authentication	The root certificate for 802.1X authentication was changed or deleted.
Update Frame.io root certificate	The root certificate for Frame.io upload was changed or deleted.
Save Camera settings on camera	Menu/Custom Picture settings were saved to the camera.
Save Camera settings on card	Menu/Custom Picture settings were saved to the SD card.
Load Camera settings from camera	Menu/Custom Picture settings were loaded from the camera.
Load Camera settings from card	Menu/Custom Picture settings were loaded from the SD card.
Reset all settings	The camera's settings were reset or the firmware was updated.
Maximum PIN code attempts exceeded	An incorrect PIN code was entered consecutively.
Browser Remote Login Fail	Failed to log in consecutively with Browser Remote.
IP Streaming Login Fail	Failed to log in consecutively with IP Streaming.
XC Protocol Login Fail	Failed to log in consecutively with XC Protocol.

NOTES

- The access log is cleared when you reset the camera's settings.
- When the number of access logs exceeds 100, the oldest ones will be deleted.


Handling Precautions

238

Camera

Be sure to observe the following precautions to ensure maximum performance.

- Do not use or store the camera in dusty or sandy places. The camera is not waterproof – avoid also water, mud or salt. If any of the above should get into the camera it may damage the camera and/or the lens. Consult a Canon Service Center as soon as possible.
- Be careful to avoid dust and dirt particles accumulating on the lens or entering the camera. When you finish using the camera, make sure to attach the body cap to the lens mount and the lens cap and dust cap to the lens.
- Do not use the camera near strong electromagnetic fields such as near powerful magnets and motors, MRI machines or high-voltage power lines. Using the camera in such places may cause anomalies in the video, or audio/video noise.
- Do not point the camera toward an intense light source, such as the sun on a sunny day or an intense artificial light source. Doing so may damage the image sensor or the camera's internal components. Be especially careful when using a tripod or shoulder strap. When you are not using the camera, make sure to attach the lens cap to the lens.
- Do not touch the lens contacts on the lens mount. Dirty contacts may cause a poor contact between the camera and the lens resulting in incorrect operation of the camera. After removing the lens, make sure to attach the body cap to the lens mount and the lens cap and dust cap to the lens.
- Do not carry the camera by the LCD monitor or store the camera in a forced position, without returning the LCD monitor to its correct position. This may damage to the monitor's joints.
- Do not apply excessive force when touching the screen. This may cause irregularities in the display quality or damage to the monitor's joints.
- Do not apply protective film to the touch screen. The camera features a capacitive touch screen that may stop working correctly with a protective overlay.
- **About cables connected to the SDI OUT terminal (📖 154)**
Connect the power supply or the battery to the camera (and devices connected to the camera) before connecting cables. Also, be sure to disconnect the cables before removing the power supply or the battery.



Long-term storage

If you do not intend to use the camera for a long time, store it in a place free of dust, in low humidity, and at temperatures not higher than 30 °C (86 °F).


Battery Pack

DANGER!

Treat the battery pack with care.

- Keep it away from fire (or it might explode).
- Do not expose the battery pack to temperature higher than 60 °C (140 °F). Do not leave it near a heater or inside a car in hot weather.
- Do not try to disassemble or modify it.
- Do not drop it or subject it to shocks.
- Do not get it wet.

- Dirty terminals may cause a poor contact between the battery pack and the camera. Wipe the terminals with a soft dry cloth.
- Be sure to attach the terminal cover (Figure 1) to transport or store the battery pack. Do not allow any metal objects to touch the terminals (Figure 2), as this can cause a short circuit and damage the battery pack.
- The correct remaining battery time may not be displayed if a fully charged battery pack is used continuously in high temperatures or is left unused for long periods of time. Also, the correct remaining time may not be displayed, depending on the battery life. Use the time shown on the screen as an approximation.
- The battery terminal cover has a []-shaped hole. This is useful when you wish to differentiate between charged and uncharged battery packs.
- You can use the battery charger and AC adapter to charge battery packs in any country/region with power supply between 100 and 240 V AC, 50/60 Hz. Consult a Canon Service Center for information on plug adapters for overseas use.



Long-term storage

- Store battery packs in a dry place at temperatures no higher than 30 °C (86 °F).
- Before storing battery packs, charge them until two lamps (on the indicator on top of the battery) illuminate (21).
- Charge all your battery packs fully at least once every six months.

Recording Media

- Periodically backing up recordings from the cards used to a computer is recommended. Data may be corrupted or lost due to defects or exposure to static electricity. Canon shall not be liable for lost or corrupted data.
- Do not touch or expose the terminals to dust or dirt.
- Do not use cards in places subject to strong magnetic fields.
- Do not leave cards in places subject to high humidity and high temperature.
- Do not attach any labels or stickers on the cards.
- Do not disassemble, bend, drop, or subject cards to shocks and do not expose them to water.

Disposal

When you delete data on a card, only the file allocation table is altered and stored data is not physically erased. Take the necessary precautions when you dispose of the card, for example by physically damaging it to prevent the leakage of private data.

If giving the card to another person, initialize it. Fill it up with unimportant recordings, and then initialize it again. This makes recovering the original recordings very difficult.

Built-in Backup Battery

The camera has a built-in rechargeable lithium battery to keep the date/time and other settings. The built-in backup battery is recharged while you use the camera; however, it will be depleted completely if you do not use the camera for about 3 months.

To recharge the built-in backup battery: Turn off the camera and attach a power source (sufficiently charged battery or DC IN terminal). The built-in backup battery will be fully charged in approx. 24 hours.

Maintenance/Others

Condensation

Moving the camera rapidly between hot and cold temperatures may cause condensation (water droplets) to form on its internal surfaces. Stop using the camera if condensation is detected. Continued use may damage the camera. Condensation may form in the following cases:

- When the camera is moved quickly from cold to warm places
- When the camera is left in a humid room
- When a cold room is heated rapidly

When condensation is detected

Disconnect the battery or AC adapter. The precise time required for water droplets to evaporate will vary depending on the location and weather conditions. As a general rule, wait for 2 hours before resuming use of the camera.

To avoid condensation

Remove the battery pack and any cards. Then, place the camera in an airtight plastic bag and let it adjust gradually to temperature changes before removing it from the bag.

Cleaning

Camera body

- Use a soft dry cloth to clean the camera's body. Never use chemically treated cloths or volatile solvents such as paint thinner.

Lens

- Remove any dust or dirt particles using a non-aerosol type blower.
- Use a clean, soft lens-cleaning cloth to gently wipe the lens. Never use tissue paper.


LCD screen

- Clean the LCD screen using a clean, soft lens-cleaning cloth and commercially available cleaning fluid for eyeglasses.
- Condensation may form on the surface of the screen when the temperature changes suddenly. Wipe it with a soft dry cloth.


Optional Accessories

The following optional accessories are compatible with this camera. The availability differs from area to area. For details on using the optional accessories and on their specifications, refer also to the **Cinema EOS System Expansion User Guide** (PDF file), available from your local Canon website.


241




BP-A30, BP-A60
Battery Pack¹




BP-A30N, BP-A60N
Battery Pack¹




CA-CP200 L
Compact Power Adapter



CA-CP300 B
Compact Power Adapter




CG-A10 Battery Charger




CG-A20 Battery Charger and
CA-CP300 B Compact
Power Adapter



PL-RF Mount Adapter




RC-V100
Remote Controller




RC-IP100
Remote Camera Controller²




RC-IP1000
Remote Camera Controller²



DM-E1D Multi-Function Shoe
Directional Stereo Microphone



OC-E4A
Off-Camera Shoe Cord



IFC-100U / IFC-400U
Interface Cable

¹ These battery packs are compatible with Intelligent System. The camera can communicate with the battery pack and display a more accurate approximate remaining usage time (in minutes).

² This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

For our customers in the USA: Call or visit your local retailer/dealer for genuine Canon video accessories. You can also obtain genuine accessories for your Canon camera by calling: 1-800-828-4040, Canon U.S.A. Information Center.

 IMPORTANT

- **Use of genuine Canon accessories is recommended.**

The message [Battery communication error] is displayed if you use a non-genuine Canon battery pack, and user response is required. Note that Canon shall not be liable for any damages resulting from accidents, such as malfunction or fire, that occur due to use of non-genuine Canon battery packs.



This mark identifies genuine Canon video accessories. When you use Canon video equipment, we recommend Canon-brand accessories or products bearing the same mark.

Specifications

C80

System

243

• Recording System

Clips:

RAW

Video format:	Cinema RAW Light
Audio format:	Linear PCM, 24 bit, 48 kHz, 4 channels
File format:	CRM (Canon RAW Movie; Canon proprietary file format)

XF-AVC

Video compression:	MPEG-4 AVC / H.264
Audio format:	Linear PCM, 24 bit, 48 kHz, 4 channels
File format:	MXF

XF-HEVC S / XF-AVC S

Video compression:	XF- HEVC S HEVC / H.265, XF-AVC S MPEG-4 AVC / H.264
Audio format:	Linear PCM, 24 bit, 48 kHz, 2 channels MPEG-2 AAC-LC, 16 bit, 48 kHz, 2 channels
File format:	MP4

WAV

Audio format:	Audio files for slow & fast motion recording: Linear PCM, 24 bit, 48 kHz, 4 channels Audio files for the second card recording function: Linear PCM, 16 bit, 8 kHz, 1 channel
File format:	BWF

Photos: DCF (Design rule for Camera File system), compatible with Exif Ver. 2.31, JPEG compression

• Video Configuration (recording/playback)

Primary clips:

RAW

Bit rate:	678 Mbps, 639 Mbps, 611 Mbps, 576 Mbps, 563 Mbps, 553 Mbps, 552 Mbps, 470 Mbps, 451 Mbps, 366 Mbps, 306 Mbps, 293 Mbps
Resolution:	6000x3164, 4368x2304
Color bit depth:	12 bit
Frame rate:	59.94P, 50.00P, 29.97P, 25.00P, 24.00P, 23.98P

XF-AVC

Bit rate:	600 Mbps, 500 Mbps, 480 Mbps, 450 Mbps, 375 Mbps, 360 Mbps, 300 Mbps, 250 Mbps, 240 Mbps, 150 Mbps, 125 Mbps, 120 Mbps / Intra-frame, 250 Mbps, 150 Mbps, 50 Mbps, 25 Mbps / Long GOP
Resolution:	4096x2160, 3840x2160, 2048x1080, 1920x1080
Color sampling:	YCbCr 4:2:2, 10 bit
Frame rate:	59.94P, 59.94i, 50.00P, 50.00i, 29.97P, 25.00P, 24.00P, 23.98P

XF-HEVC S / XF-AVC S

Bit rate:	XF-HEVC S: 225 Mbps, 150 Mbps, 135 Mbps, 100 Mbps, 50 Mbps, 35 Mbps / Long GOP XF-AVC S: 600 Mbps, 500 Mbps, 480 Mbps, 450 Mbps, 375 Mbps, 360 Mbps, 300 Mbps, 250 Mbps, 240 Mbps, 150 Mbps, 125 Mbps, 120 Mbps / Intra-frame 250 Mbps, 150 Mbps, 100 Mbps, 50 Mbps, 35 Mbps / Long GOP
Resolution:	4096x2160, 3840x2160, 2048x1080, 1920x1080

Color sampling:	XF-HEVC S: 4:2:2 10 bit, 4:2:0 10 bit XF-AVC S: 4:2:2 10 bit, 4:2:0 8 bit
Frame rate:	59.94P, 50.00P, 29.97P, 25.00P, 24.00P, 23.98P

Sub recording clips:

XF-AVC

Bit rate:	600 Mbps, 500 Mbps, 480 Mbps, 450 Mbps, 375 Mbps, 360 Mbps, 300 Mbps, 250 Mbps, 240 Mbps, 150 Mbps, 125 Mbps, 120 Mbps / Intra-frame, 250 Mbps, 150 Mbps, 50 Mbps, 25 Mbps / Long GOP
Resolution:	4096x2160, 3840x2160, 2048x1080, 1920x1080
Color sampling:	YCbCr 4:2:2, 10 bit
Frame rate:	59.94P, 59.94i, 50.00P, 50.00i, 29.97P, 25.00P, 24.00P, 23.98P

XF-HEVC S / XF-AVC S

Bit rate:	XF-HEVC S: 225 Mbps, 150 Mbps, 135 Mbps, 100 Mbps, 50 Mbps, 35 Mbps / Long GOP XF-AVC S: 600 Mbps, 500 Mbps, 480 Mbps, 450 Mbps, 375 Mbps, 360 Mbps, 300 Mbps, 250 Mbps, 240 Mbps, 150 Mbps, 125 Mbps, 120 Mbps / Intra-frame 250 Mbps, 150 Mbps, 100 Mbps, 50 Mbps, 35 Mbps / Long GOP
Resolution:	4096x2160, 3840x2160, 2048x1080, 1920x1080
Color sampling:	XF-HEVC S: 4:2:2 10 bit, 4:2:0 10 bit XF-AVC S: 4:2:2 10 bit, 4:2:0 8 bit
Frame rate:	59.94P, 50.00P, 29.97P, 25.00P, 24.00P, 23.98P

Proxy clips:

XF-AVC

Bit rate:	35 Mbps / Long GOP
Resolution:	2048x1080, 1920x1080
Color sampling:	YCbCr 4:2:0, 8 bit
Frame rate:	59.94P, 59.94i, 50.00P, 50.00i, 29.97P, 25.00P, 24.00P, 23.98P

XF-HEVC S / XF-AVC S

Bit rate:	16 Mbps, 9 Mbps, 6 Mbps / Long GOP
Resolution:	2048x1080, 1920x1080, 1280x720
Color sampling:	XF-HEVC S: 4:2:0 10 bit, 4:2:0 8 bit XF-AVC S: 4:2:0 8 bit
Frame rate:	59.94P, 50.00P, 29.97P, 23.98P, 25.00P, 24.00P

- **Recording Media (not included)**

SD, SDHC (SD High Capacity) or SDXC (SD eXtended Capacity) cards

- **Image Sensor**

Full frame back-illuminated stacked CMOS sensor

Total number of pixels¹ (approximate): 26,700,000 pixels

Effective camera pixels¹ (approximate): 19,000,000 pixels

¹ Rounded to the nearest 10,000.

- **LCD Touch Screen**

8.8 cm (3.5 in.) color LCD, approx. 2,760,000 dots, 100% coverage, capacitive touch screen operation

- View assistance functions can be applied (Gamma: CMT 709 equivalent, Canon 709 equivalent, original / Color space: BT.709 equivalent) and assistance displays can be output (onscreen displays, peaking, zebra pattern, magnification, B&W image, video scope, false color, anamorphic desqueeze).

- **Lens Mount**

Canon RF lens mount compatible with Canon RF/EF/PL lenses¹

¹ RF lenses include RF-S lenses and RF Cinema lenses. One of the available Canon EF-EOS R Mount Adapters is required for using EF lenses (including EF-S and EF Cinema lenses). PL lenses can be used when a PL-RF Mount Adapter is attached.

- **Approximate lens multiplication factor (for 35mm equivalent focal length)**

[Full Frame] sensor mode:

Actual focal length¹ x 1.06² (when the horizontal resolution is 6000/4096/2048)

Actual focal length¹ x 1.12² (when the horizontal resolution is 3840/1920)

[Super 35mm (Cropped)] sensor mode:

Actual focal length¹ x 1.46² (when the horizontal resolution is 4368/4096/2048)

Actual focal length¹ x 1.54² (when the horizontal resolution is 3840/1920)

¹ Lens focal length

² Conversion factor

- **Lens Correction**

Peripheral illumination/chromatic aberration/diffraction correction is available for Canon RF, EF and RF/EF Cinema lenses²

Distortion aberration correction is available only for Canon RF and RF Cinema lenses

² Some lenses are not compatible with in-camera correction.

- **Shutter Speed**

Speed (1/3-stop increments, 1/4-stop increments), angle, clear scan, slow, off

- **Iris**

Manual (1/2-stop increments, 1/3-stop increments, fine adjustment available), push auto iris, automatic aperture

- **ISO Speed/Gain**

Manual, automatic adjustment

ISO speed ([1 stop] and [1/3 stop] settings): ISO 100 to ISO 102400

Gain ([Normal] and [Fine] settings): -6 dB to 54 dB

- **ND Filter**

Built-in (Off, 2, 4, 6, 8⁴ or 10⁴ stops), motor operated

⁴ With extended ND range.

- **Exposure**

AE shift, light metering modes (standard, spotlight, backlight)

- **White Balance**

Custom white balance (two sets, A and B); two preset settings (daylight, 5,600 K⁵ and tungsten lamp, 3,200 K⁵); color temperature setting (2,000 K to 15,000 K); automatic white balance (AWB)

Color temperature and color compensation (CC) adjustment available for all settings except custom white balance and AWB.

⁵ Color temperatures are approximate and given only as a reference.

- **Focus**

Manual focus, autofocus (one-shot AF, continuous AF, subject detection AF); subject tracking available
AF type: Dual Pixel CMOS AF

- **Sensor Sensitivity (ISO 800, 2000 lux, 89.9% reflection)**

59.94 Hz: F10 (at 59.94P), F14 (at 29.97P)

50.00 Hz: F11 (at 50.00P), F16 (at 25.00P)

- **Wi-Fi**

Wireless standard: IEEE 802.11b/g/n (2.4 GHz band), IEEE 802.11a/n/ac (5 GHz band)
 Connection methods: Infrastructure (Wi-Fi Protected Setup (WPS), search for access points, manual), Camera Access Point
 Authentication methods: Open, shared key, WPA/WPA2/WPA3-Personal, WPA/WPA2/WPA3-Enterprise
 Encryption methods: WEP-64, WEP-128, TKIP, AES

- **Microphone**

Electret condenser microphone (monaural)

- **Size of Photos**

4096x2160, 3840x2160

Terminals

- **SDI OUT Terminal**

BNC jack

Video: HD: SMPTE 292
 3G: SMPTE 424, SMPTE 425
 6G: SMPTE ST 2081
 12G: SMPTE ST 2082
 Audio: SMPTE ST 299-1, SMPTE ST 299-2
 Output signal level: 0.8 Vp-p
 Output impedance: 75 Ω

- **HDMI OUT Terminal**

HDMI connector, output only
 The time code signal can be output (proprietary standard)
 Video/audio output: Conforming to HDMI specifications.

- **INPUT Terminals (INPUT 1 and INPUT 2)**

Mini XLR 3-pin jack (pin1: shield, pin2: hot, pin3: cold), 2 sets, balanced
 Sensitivity:
 MIC setting: -60 dBu (volume center, full scale -18 dB) / microphone attenuator: 20 dB
 LINE setting: 4 dBu (volume center, full scale -18 dB)

- **MIC Terminal**

$\varnothing$ 3.5 mm stereo mini-jack
 Sensitivity:
 [MIC (with Power Supply)] setting:
 -72 dBV (volume center, full scale -18 dB) / microphone attenuator: 20 dB
 Plug-in power supply: 2.4 V DC
 [LINE] setting: -12 dBV (volume center, full scale -18 dB)

- **🎧 (Headphone) Terminal**

$\varnothing$ 3.5 mm stereo mini-jack, -17 dBV (32 Ω load, Max volume)

- **TIME CODE Terminal**

BNC jack, input/output
 Input setting: 0.5 Vp-p to 18 Vp-p / 100 k Ω ; Output setting: 1.3 Vp-p / 50 Ω or less

- **USB Terminal**

USB Type-C™ equivalent to SuperSpeed USB (USB 3.1 Gen 1)

- **REMOTE Terminal**

$\varnothing$ 2.5 mm stereo sub-mini jack

- **Ethernet Terminal**

RJ45 connector (1000BASE-T supported)

- **Multi-Function Shoe Terminal**
Proprietary Canon connector

Power/Others

- **Power Supply (rated)**
14.4 V DC (battery pack), 24 V DC (DC IN)
- **Power Consumption / Continuous Recording Time (with a BP-A30N) / Continuous Recording Time (with a BP-A60N)**
The values were measured using normal recording (second card recording function turned off) with an RF50mm F1.8 STM lens attached, LCD luminance set to [Normal], and using the SDI OUT terminal (3G-SDI).
RAW
Approx. 14.5 W / 170 min. / 355 min. ([Full Frame] sensor, RAW LT, 6000x3164 at 29.97P)
Approx. 13.7 W / 180 min. / 380 min. ([Full Frame] sensor, RAW LT, 6000x3164 at 25.00P)
Approx. 18.2 W / 135 min. / 280 min. ([Super 35mm (Cropped)] sensor, RAW LT, 4368x2304 at 59.94P)
Approx. 16.8 W / 145 min. / 305 min. ([Super 35mm (Cropped)] sensor, RAW LT, 4368x2304 at 50.00P)
XF-AVC
Approx. 19.6 W / 125 min. / 255 min. ([Full Frame] sensor, 3840x2160 at 59.94P)
Approx. 17.9 W / 140 min. / 290 min. ([Full Frame] sensor, 3840x2160 at 50.00P)
Approx. 17.9 W / 140 min. / 290 min. ([Super 35mm (Cropped)] sensor, 2048x1080 at 59.94P)
Approx. 16.5 W / 150 min. / 320 min. ([Super 35mm (Cropped)] sensor, 2048x1080 at 50.00P)
- **Operating Temperature**
0 – 40 °C (32 – 104 °F)
- **Dimensions (W x H x D)⁶**
Camera body only: 160 x 138 x 116 mm (6.3 x 5.4 x 4.6 in.)
Camera with handle unit, microphone holder: 160 x 276 x 173 mm (6.3 x 10.9 x 6.8 in.)
- **Weight⁶ (including tape measure hook and grip belt)**
Camera body: 1,310 g (2.9 lb.)
Camera with BP-A30N battery, 2 cards: 1,545 g (3.4 lb.)
Camera with handle unit, microphone holder, BP-A30N battery, 2 cards: 1,750 g (3.9 lb.)

Accessories

CG-A20 Battery Charger

- **Rated Input:** 24 V DC, 1.8 A
- **Rated Output:** 16.7 V DC, 1.5 A
- **Operating Temperature:** 0 – 40 °C (32 – 104 °F)
- **Dimensions⁶ (W x H x D):** 100 x 24 x 100 mm (3.9 x 0.9 x 3.9 in.)
- **Weight⁶:** 145 g (5.1 oz.)

CA-CP300 B Compact Power Adapter

- **Rated Input:** 100 – 240 V AC, 50/60 Hz, 0.88 A (100 V) – 0.43 A (240 V)
- **Rated Output:** 24 V DC, 1.8 A
- **Operating Temperature:** 0 – 40 °C (32 – 104 °F)
- **Dimensions⁶ (W x H x D):** 52.0 x 31.5 x 128.0 mm (2.0 x 1.2 x 5.0 in.)
- **Weight⁶:** 219 g (7.7 oz.)

BP-A30N Battery Pack

- **Battery Type:** Rechargeable lithium ion battery, compatible with Intelligent System
- **Rated Voltage:** 14.4 V DC
- **Rated Battery Capacity:** 3,200 mAh / 47 Wh
- **Operating Temperature:** 0 – 40 °C (32 – 104 °F)
- **Dimensions⁶ (W x H x D):** 41.5 x 45.1 x 69.7 mm (1.6 x 1.8 x 2.7 in.)
- **Weight⁶:** 243 g (8.6 oz.)

⁶ All dimensions and weights are approximate.

Compatible Lenses and Functions

Following is a list of lenses compatible with this camera and the various functions that can be used depending on the lens. Depending on the lens's purchase date, you may need to update the lens's firmware to use these functions. For details, visit your local Canon website or consult a Canon Service Center.

PL mount lenses can only be used after attaching the optional PL-RF Mount Adapter. In addition, connection to an external power source is required for lenses equipped with a drive unit.

Lens	Iris control from the camera			Zoom control from the camera
	Manual	Push auto iris	Automatic	
RF lenses	● ²	● ²	● ²	● ⁵
EF lenses ¹	●	●	—	● ³
EF lenses compatible with auto iris	●	●	●	—
RF / EF ¹ Cinema lenses / PL ¹ lenses				
CN7x17 KAS S/E1 ⁴ CN10x25 IAS S/E1 ⁴ CN20x50 IAS H/E1 ⁴ CN8x15 IAS S/E1 ⁴	●	●	●	●
CN-E18-80mm T4.4 L IS KAS S CN-E70-200mm T4.4 L IS KAS S CN7x17 KAS T/R1	●	●	●	●
CN7x17 KAS S/P1 ⁴ CN20x50 IAS H/P1 ⁴ CN10x25 IAS S/P1 ⁴ CN8x15 IAS S/P1 ⁴ CN7x17 KAS T/P1 ⁴	—	—	—	—
Manual focus lenses compatible with focus guide	—	—	—	—
CN-E15.5-47mm T2.8 L S				
CN-E15.5-47mm T2.8 L SP				
CN-E30-105mm T2.8 L S CN-E30-105mm T2.8 L SP				

¹ A mount adapter is required.

² Except for the RF600mm F11 IS STM, RF800mm F11 IS STM.

³ Only lenses with the PZ-E1 Power Zoom Adapter attached.

⁴ The AE response setting (□ 200) is not supported (not applicable).

⁵ Only lenses with the PZ-E2 / PZ-E2B Power Zoom Adapter attached.

- EF lenses compatible with auto iris:

EF85mm F1.4L IS USM

EF400mm F2.8L IS III USM

EF70-200mm F4L IS II USM

EF600mm F4L IS III USM

Lens	Focus control from the camera					Focus guide
	Manual	One-shot AF	Continuous AF	Subject detection AF	Tracking	
RF / EF ¹ lenses	● ²	● ²	● ²	● ²	● ²	●
RF / EF ¹ Cinema lenses, PL ¹ lenses						
CN7x17 KAS S/E1 CN7x17 KAS T/R1 CN8x15 IAS S/E1 CN10x25 IAS S/E1	●	●	●	●	●	●
CN20x50 IAS H/E1	●	—	—	—	—	—
CN7x17 KAS S/P1 CN20x50 IAS H/P1 CN10x25 IAS S/P1 CN8x15 IAS S/P1 CN7x17 KAS T/P1	—	—	—	—	—	—
CN-E18-80mm T4.4 L IS KAS S, CN-E70-200mm T4.4 L IS KAS S	●	●	●	●	●	●
Manual focus lenses compatible with focus guide	—	—	—	—	—	●

¹ A mount adapter is required.

² Except for the RF5.2mm F2.8 L Dual Fisheye lens.

• Manual focus lenses compatible with focus guide:

CN-E14mm T3.1 L F	CN-E50mm T1.3 L F
CN-E20mm T1.5 L F	CN-E85mm T1.3 L F
CN-E24mm T1.5 L F	CN-E135mm T2.2 L F
CN-E35mm T1.5 L F	CN-E20-50mm T2.4 L F
CN-E14-35mm T1.7 L S	CN-E45-135mm T2.4 L F
CN-E31.5-95mm T1.7 L S	CN-R24mm T1.5 L F
CN-R35mm T1.5 L F	CN-R50mm T1.3 L F
CN-R85mm T1.3 L F	CN-R14mm T3.1 L F
CN-R20mm T1.5 L F	CN-R135mm T2.2 L F

• Lenses compatible with automatic retraction when the camera is turned off (📖 212).

RF35mm F1.8 MACRO IS STM	EF50mm F1.8 STM
EF40mm F2.8 STM	EF-S24mm F2.8 STM
RF85mm F2 MACRO IS STM	RF50mm F1.8 STM
RF24mm F1.8 MACRO IS STM	RF16mm F2.8 STM

Reference Tables

Approximate Recording Time on a Card

Approximate times, for reference only, based on a single recording that continues until the card is full.

Recording format	Bit rate	128 GB	512 GB	Recording format	Bit rate	128 GB	512 GB
RAW	678 Mbps	23 min.	92 min.	XF-HEVC S	225 Mbps	70 min.	282 min.
	639 Mbps	24 min.	99 min.		150 Mbps	105 min.	422 min.
	563 Mbps	28 min.	112 min.		135 Mbps	117 min.	471 min.
	552 Mbps	28 min.	114 min.		100 Mbps	158 min.	635 min.
	451 Mbps	34 min.	139 min.		50 Mbps	309 min.	1237 min.
	366 Mbps	42 min.	171 min.		35 Mbps	435 min.	1740 min.
	293 Mbps	53 min.	213 min.	XF-AVC S	600 Mbps	26 min.	106 min.
XF-AVC	600 Mbps	26 min.	105 min.		480 Mbps	33 min.	133 min.
	480 Mbps	32 min.	131 min.		450 Mbps	35 min.	142 min.
	450 Mbps	35 min.	140 min.		360 Mbps	44 min.	177 min.
	360 Mbps	43 min.	174 min.		300 Mbps	53 min.	212 min.
	300 Mbps	51 min.	206 min.		250 Mbps	63 min.	254 min.
	250 Mbps	61 min.	245 min.		240 Mbps	66 min.	266 min.
	240 Mbps	64 min.	259 min.		150 Mbps	105 min.	422 min.
	150 Mbps	101 min.	406 min.		120 Mbps	132 min.	531 min.
	120 Mbps	125 min.	502 min.		100 Mbps	158 min.	635 min.
	50 Mbps	261 min.	1044 min.		50 Mbps	309 min.	1237 min.
	25 Mbps	485 min.	1943 min.		35 Mbps	435 min.	1740 min.

Charging Times

Charging times are approximate and vary according to charging conditions, ambient temperature and initial charge of the battery pack.

Battery pack	BP-A30N	BP-A60N
Charging time using the supplied CG-A20 Battery Charger	175 min.	310 min.


Appendix: Camera Dimensions

Unless indicated with the " (inch) mark, all units are in mm. ∇ represents the depth of a hole or socket.


252

Front


Lens
attachment plane




Top




Left




Bottom




Rear




Right



Camera with handle unit, microphone holder and BP-A30N battery pack



Handle unit



🎧 (headphones) terminal106, 146
802.1X Authentication177

A

ABB (automatic black balance)45
Abroad, using the camera239
Access log237
Access point165, 166
Accessories10, 241
AE shift75
Air vents12, 13, 44
Anamorphic lenses and desqueeze121
Aperture73
 Automatic aperture (auto iris)75
 Push auto iris74
Assignable buttons125
Audio
 Audio level103
 Bit depth100
 Format101
 Output channels160
 Peak limiter104
 Recording100
Audio files (for slow & fast motion clips)114
Audio reference signal107
Authentication175, 177
AWB (auto white balance)79
AWB lock79

B

Base ISO68
Bit rate62
Browser Remote187
Built-in backup battery239
Button connection mode (WPS)167, 169

C

Camera Access Point174
Camera dimensions252
CAMERA mode15
Camera nickname178
Canon App172, 195
Canon Log 2, Canon Log 3
 (gamma curves)134
Canon XF Utility (download)161

Card volume label 37
Check marks (☑) 110, 149
Cinema EOS System Expansion
 User Guide 241
Cinema RAW Development 162
Clips
 Adding OK marks/☑ marks 110, 149
 Adding shot marks 110, 149
 Clip information 148
 Clip name format 42
 Clip numbering 42, 43
 Deleting 150
 Playback 142
 Proxy clips 64
 Recording 47
 Recovering 38
Color bars 107
Color bit depth 62
Color compensation (CC) value 77
Color sampling 62
Color space 134, 158
Computer 161
Condensation 240
Connection to external devices 154
Content Transfer Professional 162, 163, 195
Continuous recording 118
Control dials 68, 73
Control ring (RF lens) 210
Custom displays 49, 204
Custom picture 129
 Detailed custom picture settings 134
 Look File 131
 Preset settings 129
CV Protocol 173

D

Data entry / keyboard screen 28
Date and time 25
DC IN terminal 21, 247
Deleting recordings 150
Desqueeze 121
Detection of access points 175
Digital IS 88
Digital tele-converter 90
Direct setting mode 57

Direct touch control	56
Double slot recording	39
Drop frame (time code)	96

E

EF Cinema lenses	29, 249
Encryption	174, 175
Exposure bar	76
Exposure compensation	75

F

False color	94
Fan	44
FEC error correction	170
File menu	147
File names	42
File numbering	43
File operations	147
Flicker reduction	67
Focus	80
AF lock	85
AF speed	83
Continuous AF	83
Focus assistance functions	81
Manual focus	80
One-shot AF	83
Subject detection AF	86
Tracking	87
Focus guide	81
Focus ring (lens)	80
Frame rate	62
Frame recording	119
Frame.io	196
Free-run (time code)	95
FTP transfer	184
Full range/Video range (level mapping)	156
FUNC button	57

G

Gain	68
Gamma curve	134, 158
GPS information	111, 150
GPS receiver (optional)	50, 211

H

Handle unit	32
HDMI OUT terminal	151, 155
HDMI RAW	155
HDR (high dynamic range)	134, 158, 159
Headphones	106, 146
HLG (hybrid log gamma)	134, 158
Hour meter	212
HTTPS	182

I

Image stabilizer	88
Importing files to a computer/smartphone	161
INDEX button	142
Index screens	141
Infrastructure	167
Initializing a card	37
INPUT terminals	100, 102
Interval recording	119
IP address (IPv4 settings)	176
IP streaming	185
IPv6 settings	180
Iris	73
ISO speed	68

J

Joystick	26, 90
----------	--------

K

Key lock	15
----------	----

L

Language	25
LCD monitor	23
Lens	29, 249
Lens correction (chromatic aberration/ peripheral illumination/diffraction/ distortion aberration)	31
Lens firmware	31
Lens mount	29, 245
Level	33
Light metering mode	76
Look File	131

M

Magnification	82
Main recording (primary clips)	39, 62
Main recording format	62
Maintenance	240
Manual network configuration	175
MEDIA button	15
MEDIA mode	15
Menu settings	139, 199
Message list	230
Metadata	111
MIC terminal	100, 102
Microphone	
External	102
Monaural	100
Sensitivity / Attenuator / Low cut filter	105
Microphone holder	33, 102
MP4 Join Tool (download)	161
Multi-Camera Control	194
Multi-function shoe	34
MXF (file format)	243
My Menu	27

N

ND filter	72
Network	
Communication setting (NW)	168, 179
Configuration	168
Connection setting (SET)	168, 178
Connection status	183
Function setting (MODE)	168, 179
Network functions	165
Network connection	
Wi-Fi	166
Wired (Ethernet)	167
News Metadata	112
Non-drop frame (time code)	96

O

OK marks (OK)	110, 149
Onscreen displays	49, 144
Display level	53
Opacity/transparency	157
Output	157
Peripheral border display	54

Onscreen markers	91
Output range	156

P

Peaking	82
Phantom power (microphone)	102
Photos	
Photo numbering	43
Recording	48
Viewing	142
PIN code	24
PIN code connection mode (WPS)	175
Playback	141
Plug-in power (microphone)	103
Portrait orientation (vertical video)	55
Power indicator	13
Power supply	19
AC adapter (DC IN)	21, 247
Canon battery packs	19
Checking power levels/remaining	
battery charge	21, 51
Power level warnings	211
POWER switch	15
Pre-recording	117
Progress bar (playback)	144
Proxy recording	64

R

RAW	59, 141, 151
RC-IP100/RC-IP1000	193
RC-V100	123
Real-time streaming (RTSP)	170
REC button	47
Rec run (time code)	95
Recording	
Photos	48
Primary clips	47
Proxy clips (simultaneous recording)	64
Sub recording clips	
(simultaneous recording)	63
Recording command	155
Recording media	35, 239
Reference tables (charging, usage and	
recording times)	251
Relay recording	39
Remote Camera Control Application	193

Remote Camera Controller	193
Remote controller	123
Remote operation	123, 187
REMOTE terminal	123
Resetting all camera settings	210
Resolution (frame size)	62
Reviewing a clip	55
Root certificate (FTPS)	177
Router	166
Running mode (time code)	95

S

Safe area	91
SD card	
Compatible cards	35
Initializing	37
Inserting/Removing	36
Recording method	39
Switching card slots	38, 142
SDI OUT terminal	154
Second card recording functions	39
Secure FTP (SFTP, FTPS)	169
Sensor mode	62
Setup menus	26, 199
Shooting frame rate	114
Shot marks	110, 149
Shutter speed	66
Slow & fast motion recording	114
Smartphone	161
Speaker	12, 146
Special recording modes	114
Specifications	243
SSID	175
Status screens	213
Sub recording	63, 214
Subject detection	86
Synchronization	98
System frequency	61

T

Tally lamp	47
Tally OSD	54
Time code	95
Time code synchronization	98
TIME CODE terminal	98

Tracking	87
Tripod	12, 15
Troubleshooting	224
Turning the camera on/off	11

U

USB terminal	13
User bit	96
User memo	111

V

Vectorscope	109
Video configuration	59
Video format	62
Video output configuration	151
Video recording method	39
Video scopes	108
Volume	146
Volume label	37

W

WAV audio files	114
Waveform monitor	108
White balance	77
Wide DR	134, 158
WPS (Wi-Fi Protected Setup)	167, 169, 175

X

XC Protocol	193
XF-AVC	62
XF-HEVC S / XF-AVC S	62

Z

Zebra pattern	93
Zoom	90

Trademark Acknowledgements

- SD, SDHC and SDXC Logos are trademarks of SD-3C, LLC.
- Microsoft and Windows are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries.
- Apple, macOS, App Store are trademarks of Apple Inc., registered in the U.S. and other countries.
- Adobe, Camera to Cloud, Frame.io, and the Frame.io logo are either registered trademarks or trademarks of Adobe in the United States and/or other countries.
- Avid and Media Composer are trademarks or registered trademarks of Avid Technology, Inc. or its subsidiaries in the United States and/or other countries.
- Wi-Fi is a registered trademark of the Wi-Fi Alliance.
- Wi-Fi Certified, WPA, WPA2, WPA3 and the Wi-Fi Certified logo are trademarks of the Wi-Fi Alliance.
- WPS as used on the camera's settings, onscreen displays and in this manual signifies Wi-Fi Protected Setup.
- JavaScript is a trademark or registered trademark of Oracle Corporation, its affiliates or subsidiaries in the United States and other countries.
- The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.
- USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum.
- DaVinci Resolve™ is the trademark of Blackmagic Design Pty. Ltd.
- Other names and products not mentioned above may be trademarks or registered trademarks of their respective companies.



Licensing Information

- This device incorporates exFAT technology licensed from Microsoft.
- This product is licensed under AT&T patents for the MPEG-4 standard and may be used for encoding MPEG-4 compliant video and/or decoding MPEG-4 compliant video that was encoded only (1) for a personal and noncommercial purpose or (2) by a video provider licensed under the AT&T patents to provide MPEG-4 compliant video. No license is granted or implied for any other use for MPEG-4 standard.
- THIS PRODUCT IS LICENSED UNDER THE AVC PATENT PORTFOLIO LICENSE FOR THE PERSONAL USE OF A CONSUMER OR OTHER USES IN WHICH IT DOES NOT RECEIVE REMUNERATION TO (i) ENCODE VIDEO IN COMPLIANCE WITH THE AVC STANDARD ("AVC VIDEO") AND/OR (ii) DECODE AVC VIDEO THAT WAS ENCODED BY A CONSUMER ENGAGED IN A PERSONAL ACTIVITY AND/OR WAS OBTAINED FROM A VIDEO PROVIDER LICENSED TO PROVIDE AVC VIDEO. NO LICENSE IS GRANTED OR SHALL BE IMPLIED FOR ANY OTHER USE. ADDITIONAL INFORMATION MAY BE OBTAINED FROM MPEG LA, L.L.C. SEE [HTTP://WWW.MPEGLA.COM](http://www.mpegla.com)

Third Party Software

For details regarding third party software, refer to *Software Used in This Product* (PDF) available on the download page of the Instruction Manual.

CANON CINEMA EOS LIMITED WARRANTY FOR PRODUCTS PURCHASED IN THE UNITED STATES

The limited warranty set forth below is given by Canon U.S.A., Inc. ("Canon USA") with respect to (a) the Canon Cinema EOS Product, and (b) the accessories for the Canon Cinema EOS Product (if any), packaged with this limited warranty (collectively the "Products")* and purchased in the United States. This limited warranty is only effective upon presentation of your Bill of Sale or other proof of purchase. The Products are warranted to the original end-user purchaser, when delivered in new condition in its original container, under normal use against defective materials or workmanship as follows: Parts: At Canon USA's option, defective parts will be exchanged for new parts or comparable rebuilt parts for a period of ONE YEAR from the date of original purchase. Labor: For a period of ONE YEAR from the date of original purchase, labor will be provided free of charge by Canon USA's factory service centers or designated service facilities located in the United States. When returning Products under this warranty, you must pre-pay the shipping charges, and you must enclose a copy of the Bill of Sale or other proof of purchase with a complete explanation of the problem. During the ONE-YEAR warranty period, repairs will be made and the Products will be return-shipped to you free of charge. For repairs after the warranty period is over, you will be given an estimate of the cost of repair and an opportunity to approve or disapprove of the repair expense before it is incurred. If you approve, repairs will be made and the Products will be returned to you at your risk and expense. If you disapprove, we will return-ship the Products to you at no charge to you to an address within the United States.

This limited warranty only applies if the Products are used in conjunction with compatible computer equipment and compatible software, as to which items Canon USA will have no responsibility. Canon USA shall have no responsibility under this limited warranty for use of the Products in conjunction with incompatible peripheral equipment and/or incompatible software. Non-Canon brand peripheral equipment and software which may be distributed with, or factory loaded on, the Products, are sold 'AS IS' without warranty of any kind by Canon USA, including any implied warranty regarding merchantability or fitness for a particular purpose. The sole warranty with respect to such non-Canon brand items is given by the manufacturer or producer thereof.

* Except for the battery pack packaged with the Products, which carries a separate ninety (90) day limited warranty.

In order to obtain warranty service, please contact the authorized Canon retail dealer from whom you purchased the Products or contact the CANON INFORMATION CENTER AT **855-CINE-EOS** (855-246-3367) or on the internet at pro.usa.canon.com/support. You will be directed to the nearest service facility for your Products.

This Limited Warranty covers all defects encountered in normal use of the Products and does not apply in the following cases:

- A. Loss or damage to the Products due to abuse, mishandling, accident, improper maintenance, use of non-Canon accessories or failure to follow operating, maintenance or environmental instructions prescribed in Canon USA's user's manual;
- B. If the Products are defective as a result of leaking batteries, sand, dirt or water damage;
- C. If defects or damages are caused by the use of parts or supplies (other than those sold by Canon USA) that cause damage to the Products or that cause abnormally frequent service calls or service problems;
- D. If defects or damages are caused by service other than Canon USA's factory service centers or authorized service facilities;
- E. Any internal modification to product hardware or firmware;
- F. Any applicable fee for Maintenance of the Products;
- G. If the Product has had its serial number or dating altered or removed.

This Limited Warranty does not apply to Products purchased outside the United States. This Limited Warranty does not apply to accessories or consumables not originally packaged with the Product. Please retain this warranty card and your Bill of Sale as a permanent record of your purchase. This card ensures that you are contacted promptly should there be a safety inspection, modification or Product recall under applicable laws or regulations.

NO IMPLIED WARRANTY, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE APPLIES TO THE PRODUCTS AFTER THE APPLICABLE PERIOD OF EXPRESS WARRANTY OR GUARANTY (EXCEPT AS MENTIONED ABOVE) GIVEN BY ANY PERSON, FIRM OR CORPORATION WITH RESPECT TO THE PRODUCTS SHALL BIND CANON USA (SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU). CANON USA SHALL NOT BE LIABLE FOR LOSS OF REVENUES OR PROFITS, EXPENSE FOR SUBSTITUTE PRODUCTS OR SERVICE, STORAGE CHARGES, LOSS OR CORRUPTION OF DATA, INCLUDING WITHOUT LIMITATION, LOSS OR CORRUPTION OF DATA STORED ON THE PRODUCTS' HARD DRIVE, OR ANY OTHER SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES CAUSED BY THE USE, MISUSE OR INABILITY TO USE THE PRODUCTS, REGARDLESS OF THE LEGAL THEORY ON WHICH THE CLAIM IS BASED, AND EVEN IF CANON USA HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. NOR SHALL RECOVERY OF ANY KIND AGAINST CANON USA BE GREATER THAN THE PURCHASE PRICE OF THE PRODUCTS SOLD BY CANON USA AND CAUSING THE ALLEGED DAMAGE. WITHOUT LIMITING THE FOREGOING, YOU ASSUME ALL RISK AND LIABILITY FOR LOSS, DAMAGE OR INJURY TO YOU AND YOUR PROPERTY AND TO OTHERS AND THEIR PROPERTY ARISING OUT OF USE, MISUSE OR INABILITY TO USE THE PRODUCTS NOT CAUSED DIRECTLY BY THE NEGLIGENCE OF CANON USA (SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU). THIS LIMITED WARRANTY SHALL NOT EXTEND TO ANYONE OTHER THAN THE ORIGINAL PURCHASER OF THE PRODUCTS OR THE PERSON FOR WHOM IT WAS PURCHASED AS A GIFT.

This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

CANON U.S.A., INC

CANON CINEMA EOS LIMITED WARRANTY FOR PRODUCTS PURCHASED IN CANADA

The limited warranty set forth below is given by Canon Canada Inc. ("Canon Canada") with respect to (a) the Canon Cinema EOS product, and (b) the accessories for the Canon Cinema EOS Product (if any), packaged with this limited warranty (collectively the "Products") and purchased in Canada. This limited warranty is only effective upon presentation of your Bill of Sale or other proof of purchase. The Products are warranted to the original end-user purchaser, when delivered in new condition in its original container, under normal use against defective materials or workmanship as follows: Parts: At Canon Canada's option, defective parts will be exchanged for new parts or comparable rebuilt parts for a period of ONE YEAR from the date of original purchase. Labor: For a period of ONE YEAR from the date of original purchase, labor will be provided free of charge by Canon Canada's factory service center or designated service facilities located in Canada. When returning Products under this warranty, you must pre-pay the shipping charges, and you must enclose a copy of the Bill of Sale or other proof of purchase with a complete explanation of the problem. During the ONE-YEAR warranty period, repairs will be made and the Products will be return-shipped to you free of charge. For repairs after the warranty period is over, you will be given an estimate of the cost of repair and an opportunity to approve or disapprove of the repair expense before it is incurred. If you approve, repairs will be made and the Products will be returned to you at your risk and expense. If you disapprove, we will return-ship the Products to you at no charge to you to an address within Canada.

This limited warranty only applies if the Products are used in conjunction with compatible computer equipment and compatible software, as to which items Canon Canada will have no responsibility. Canon Canada shall have no responsibility under this limited warranty for use of the Products in conjunction with incompatible peripheral equipment and/or incompatible software. Non-Canon brand peripheral equipment and software which may be distributed with, or factory loaded on, the Products, are sold 'AS IS' without warranty of any kind by Canon Canada, including any implied warranty or condition regarding merchantability or fitness for a particular purpose. The sole warranty with respect to such non-Canon brand items is given by the manufacturer or producer thereof.

* Except for the battery pack packaged with the Products, which carries a separate ninety (90) day limited warranty.

In order to obtain warranty service, please contact the authorized Canon retail dealer from whom you purchased the Products or contact the CANON PROFESSIONAL SERVICE CENTRE 1-800-667-2666 or on the internet at www.canon.ca/pro. You will be directed to the nearest service facility for your Products.

This Limited Warranty covers all defects encountered in normal use of the Products and does not apply in the following cases:

- A. Loss or damage to the Products due to abuse, mishandling, accident, improper maintenance, use of non-Canon accessories or failure to follow operating, maintenance or environmental instructions prescribed in Canon Canada's user's manual;
- B. If the Products are defective as a result of leaking batteries, sand, dirt or water damage;
- C. If defects or damages are caused by the use of parts or supplies (other than those sold by Canon Canada) that cause damage to the Products or that cause abnormally frequent service calls or service problems;
- D. If defects or damages are caused by service other than Canon Canada's factory service centers or authorized service facilities;
- E. Any internal modification to product hardware or firmware;
- F. Any applicable fee for Maintenance of the Products;
- G. If the Product has had its serial number or dating altered or removed.

This Limited Warranty does not apply to Products purchased outside Canada. This Limited Warranty does not apply to accessories or consumables not originally packaged with the Product. Please retain this warranty card and your Bill of Sale as a permanent record of your purchase. This card ensures that you are contacted promptly should there be a safety inspection, modification or Product recall under applicable laws or regulations.

NO IMPLIED WARRANTY OR CONDITION, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE APPLIES TO THE PRODUCTS AFTER THE APPLICABLE PERIOD OF EXPRESS WARRANTY OR GUARANTY (EXCEPT AS MENTIONED ABOVE) GIVEN BY ANY PERSON, FIRM OR CORPORATION WITH RESPECT TO THE PRODUCTS SHALL BIND CANON CANADA (SOME PROVINCES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY OR CONDITION LASTS, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU). CANON CANADA SHALL NOT BE LIABLE FOR LOSS OF REVENUES OR PROFITS, EXPENSE FOR SUBSTITUTE PRODUCTS OR SERVICE, STORAGE CHARGES, LOSS OR CORRUPTION OF DATA, INCLUDING WITHOUT LIMITATION, LOSS OR CORRUPTION OF DATA STORED ON THE PRODUCTS' HARD DRIVE, OR ANY OTHER SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES CAUSED BY THE USE, MISUSE OR INABILITY TO USE THE PRODUCTS, REGARDLESS OF THE LEGAL THEORY ON WHICH THE CLAIM IS BASED, AND EVEN IF CANON CANADA HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. NOR SHALL RECOVERY OF ANY KIND AGAINST CANON CANADA BE GREATER THAN THE PURCHASE PRICE OF THE PRODUCTS SOLD BY CANON CANADA AND CAUSING THE ALLEGED DAMAGE. WITHOUT LIMITING THE FOREGOING, YOU ASSUME ALL RISK AND LIABILITY FOR LOSS, DAMAGE OR INJURY TO YOU AND YOUR PROPERTY AND TO OTHERS AND THEIR PROPERTY ARISING OUT OF USE, MISUSE OR INABILITY TO USE THE PRODUCTS NOT CAUSED DIRECTLY BY THE NEGLIGENCE OF CANON CANADA (SOME PROVINCES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU). THIS LIMITED WARRANTY SHALL NOT EXTEND TO ANYONE OTHER THAN THE ORIGINAL PURCHASER OF THE PRODUCTS OR THE PERSON FOR WHOM IT WAS PURCHASED AS A GIFT.

This warranty gives you specific legal rights, and you may also have other rights which vary from province to province.

CANON CANADA INC.



Canon Inc. 30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo 146-8501, Japan
Canon Europa N.V. Bovenkerkerweg 59, 1185 XB Amstelveen, The Netherlands <http://www.canon-europe.com>

The information in this document is verified as of July 2025. Subject to change without notice.
Visit your local Canon website to download the latest version.